

Advanced EC2 Worker Node Monitoring Dashboard Guide (Updated)

This updated version now includes the complete index.j2 dashboard template code.

monitor.yml

```
---
- name: Worker Node Monitoring
  hosts: localhost
  gather_facts: yes

  tasks:

    - name: Get EC2 instance info
      amazon.aws.ec2_instance_info:
        region: ap-south-1
        register: ec2_info

    - name: Generate monitoring webpage
      become: yes
      template:
        src: templates/index.j2
        dest: /usr/share/nginx/html/index.html
```

Complete index.j2 Template

```
<!DOCTYPE html>
<html>

<head>

<title>EC2 Worker Node Dashboard</title>

<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">

<style>

body {
  margin: 0;
  padding: 20px;
  background: #081028;
  color: white;
  font-family: Arial, sans-serif;
}

h1 {
  color: #38bdf8;
  margin-bottom: 20px;
}

.top-section {
  display: flex;
  gap: 20px;
  margin-bottom: 25px;
  flex-wrap: wrap;
}

.card {
  background: #111c44;
  padding: 20px;
  border-radius: 12px;
}

.controls {
  display: flex;
  gap: 15px;
```

```

        margin-bottom: 20px;
        flex-wrap: wrap;
    }

    input, select {
        padding: 12px;
        border-radius: 8px;
        border: none;
        background: #111c44;
        color: white;
    }

    table {
        width: 100%;
        border-collapse: collapse;
        background: #0f172a;
    }

    th {
        background: #1e293b;
        padding: 14px;
    }

    td {
        padding: 14px;
        text-align: center;
        border-bottom: 1px solid #1e293b;
    }

    .running {
        background: #14532d;
        color: #4ade80;
        padding: 6px 12px;
        border-radius: 20px;
    }

    .stopped {
        background: #450a0a;
        color: #f87171;
        padding: 6px 12px;
        border-radius: 20px;
    }
</style>

</head>

<body>

<h1>■ EC2 Worker Node Dashboard</h1>

<div class="top-section">

<div class="card">
<h2>Total Instances</h2>
<p>{{ ec2_info.instances | length }}</p>
</div>

<div class="card">
<h2>Running Instances</h2>
<p>
{{
ec2_info.instances
| selectattr('state.name', 'equalto', 'running')
| list
| length
}}
</p>
</div>

<div class="card">
<h2>Stopped Instances</h2>
<p>
{{
ec2_info.instances
| selectattr('state.name', 'equalto', 'stopped')
| list
| length
}}
</p>

```

```

</div>

</div>

<div class="controls">

<input type="text" id="searchInput" placeholder="Search instance...">

<select id="statusFilter">
<option value="all">All Nodes</option>
<option value="running">Running</option>
<option value="stopped">Stopped</option>
</select>

</div>

<table id="instanceTable">

<thead>

<tr>
<th>Name</th>
<th>Status</th>
<th>Private IP</th>
<th>Public IP</th>
<th>Instance Type</th>
<th>Availability Zone</th>
<th>Active Since</th>
</tr>

</thead>

<tbody>

{% for reservation in ec2_info.instances %}

<tr>

<td>
{{ reservation.tags.Name | default('No-Name') }}
</td>

<td>
<span class="{{ reservation.state.name }}">
{{ reservation.state.name }}
</span>
</td>

<td>
{{ reservation.private_ip_address | default('N/A') }}
</td>

<td>
{{ reservation.public_ip_address | default('N/A') }}
</td>

<td>
{{ reservation.instance_type }}
</td>

<td>
{{ reservation.placement.availability_zone }}
</td>

<td>

{% if reservation.state.name == "running" %}
■ Active Since<br>
{{ reservation.launch_time[:16] }}

{% else %}
■ Instance Stopped

{% endif %}

</td>

</tr>

```

```

{% endfor %}

</tbody>

</table>

<script>

const searchInput = document.getElementById("searchInput");
const statusFilter = document.getElementById("statusFilter");
const table = document.getElementById("instanceTable");

function filterTable() {

const search = searchInput.value.toLowerCase();
const status = statusFilter.value;

const rows = table.getElementsByTagName("tr");

for (let i = 1; i < rows.length; i++) {

const row = rows[i];

const text = row.innerText.toLowerCase();

const rowStatus = row.cells[1].innerText.trim().toLowerCase();

const matchesSearch = text.includes(search);

const matchesStatus =
status === "all" || rowStatus === status;

if (matchesSearch && matchesStatus) {
row.style.display = "";
} else {
row.style.display = "none";
}
}
}

searchInput.addEventListener("keyup", filterTable);

statusFilter.addEventListener("change", filterTable);

setTimeout(() => {
location.reload();
}, 60000);

</script>

</body>

</html>

```