



Networkforyou

Subscribe to our
You **Tube** Channel



Networkforyou



**Welcome
To
Network for you
OSPF Path Selection**



Networkforyou

Email us:
networkforyou4@gmail.com

1 of 8

WhatsApp Us : +918143809578



L3-ADVENTERPRISEK9-M-15.2-M5.3.bin

Use this image for this lab in eve ng:

R1 Configuration:	R2 Configuration:
<pre>en config t hostname R1 int e0/0 ip add 192.168.15.1 255.255.255.0 no sh int lo0 ip add 8.8.8.8 255.255.255.255 router ospf 1 router-id 1.1.1.1 int e0/0 ip ospf 1 area 0 int lo0 ip ospf 1 area 0</pre>	<pre>en config t hostname R2 int e0/0 ip add 192.168.25.1 255.255.255.0 no sh int lo0 ip add 8.8.8.8 255.255.255.255 router ospf 1 router-id 2.2.2.2 int e0/0 ip ospf 1 area 0 exit router ospf 1 redistribute connected subnets metric-type 1</pre>
R3 Configuration:	R4 Configuration:
<pre>en config t hostname R3 int e0/0 ip add 192.168.35.1 255.255.255.0 no sh int lo0 ip add 8.8.8.8 255.255.255.255 router ospf 1 router-id 3.3.3.3 int e0/0 ip ospf 1 area 0</pre>	<pre>en config t hostname R4 int e0/0 ip add 192.168.45.1 255.255.255.0 no sh int lo0 ip add 8.8.8.8 255.255.255.255 router ospf 1 router-id 4.4.4.4 int e0/0 ip ospf 1 area 0 exit</pre>

Email us:
networkforyou4@gmail.com

3 of 8

WhatsApp Us : +918143809578



int lo0 ip ospf 1 area 2	router ospf 1 redistribute connected subnets metric-type 2
R5 Configuration:	R6 Configuration:
en conf t hostname R5 int e0/0 ip add 192.168.15.2 255.255.255.0 no sh int e0/1 ip add 192.168.25.2 255.255.255.0 no sh int e0/2 ip add 192.168.35.2 255.255.255.0 no sh int e0/3 ip add 192.168.45.2 255.255.255.0 no sh int e1/0 ip add 192.168.56.1 255.255.255.0 no sh int e1/1 ip add 192.168.57.1 255.255.255.0 no sh router ospf 1 router-id 5.5.5.5 int e0/0 ip ospf 1 area 0 int e0/1 ip ospf 1 area 0 int e0/2 ip ospf 1 area 0 int e0/3 ip ospf 1 area 0 int e1/0 ip ospf 1 area 1 int e1/1 ip ospf 1 area 1 exit router ospf 1	en conf t hostname R6 int e0/0 ip add 192.168.56.2 255.255.255.0 no sh router ospf 1 int e0/0 ip ospf 1 area 1 exit router ospf 1 redistribute connected subnets metric-type 2 area 1 nssa



area 1 nssa	
R7Configuration:	
en config t hostname R7 int e0/0 ip add 192.168.57.2 255.255.255.0 no sh router ospf 1 int e0/0 ip ospf 1 area 1 exit router ospf 1 redistribute connected subnets metric-type 1 area 1 nssa	

```
R5#sh ip route ospf
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
        E1 - OSPF external type 1, E2 - OSPF external type 2
        i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
        ia - IS-IS inter area, * - candidate default, U - per-user static route
        o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
        a - application route
        + - replicated route, % - next hop override

Gateway of last resort is not set

0      8.0.0.0/32 is subnetted, 1 subnets
0      8.8.8.8 [110/11] via 192.168.15.1, 00:02:35, Ethernet0/0
```

R1 Loopback Shutdown
Interface loopback 0 shutdown



```
R5#sh ip route ospf
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override
```

Gateway of last resort is not set

```
      8.0.0.0/32 is subnetted, 1 subnets
O IA    8.8.8.8 [110/11] via 192.168.35.1, 00:00:06, Ethernet0/2
```

R3 Loopback Shutdown

Interface loopback 0
shutdown

```
R5#sh ip route ospf
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override
```

Gateway of last resort is not set

```
      8.0.0.0/32 is subnetted, 1 subnets
O_N1    8.8.8.8 [110/30] via 192.168.57.2, 00:00:16, Ethernet1/1
```

R7 Loopback Shutdown

Interface loopback 0
shutdown



```
R5#sh ip route ospf
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override
```

Gateway of last resort is **not** set

```
      8.0.0.0/32 is subnetted, 1 subnets
O E1    8.8.8.8 [110/30] via 192.168.25.1, 00:00:13, Ethernet0/1
```

R2 Loopback Shutdown

Interface loopback 0
shutdown

```
R5#sh ip route ospf
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override
```

Gateway of last resort is **not** set

```
      8.0.0.0/32 is subnetted, 1 subnets
O N2    8.8.8.8 [110/20] via 192.168.56.2, 00:00:38, Ethernet1/0
```

R6 Loopback Shutdown

Interface loopback 0
shutdown



```
R5#sh ip route ospf
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override
```

Gateway of last resort is not set

```
8.0.0.0/32 is subnetted, 1 subnets
O_E2    8.8.8.8 [110/20] via 192.168.45.1, 00:00:09, Ethernet0/3
```

Networkforyou