

Agents

Так что же ты такой, агент?

Определение

Определение агента

Определение агента

Агент – нечто, что взаимодействует с некоторой **средой**, пользуясь действиями из доступного **инструментария**

Определение агента



Агент – нечто, что взаимодействует с некоторой **средой**, пользуясь действиями из доступного **инструментария**

Агент – система, которая **независимо** выполняет вашу работу

Определение агента


Агент – нечто, что взаимодействует с некоторой **средой**, пользуясь действиями из доступного **инструментария**

Агент – система, которая **независимо** выполняет вашу работу




Агент – система, независимо от человека выполняющая работу, **итеративно** взаимодействуя с некоторой средой при помощи доступного инструментария

Агент, пользуясь инструментами, размышляя о выполнении задачи, может выполнять ее автономно




Multi-Agent Systems. Control and context flow

Workflow Agent



LLM Agent



Main building blocks:

Workflow Agent: Fixed order of agent invocations

LLM Agent: Model decides whether to use another agent or not


Control flow types:

Handoff - Full control and context transfer to another agent


Agent-as-tool - Call the agent and return his response back immediately. Usually no context is passed

MAS Example


High-level Architecture of Advanced Research



Multi-agent System Process Diagram



Agents Collaboration. Voting and debate



Voting or Consensus?
Decision-Making in Multi-Agent
Debate. Kaesberg et. al.

Tooling. How tools are provided?

1. Python API interface:

```
from openai import OpenAI
import json
```

```
client = OpenAI()
```

1. Define a list of callable tools for the model

```
tools = [
    {
        "type": "function",
        "name": "get_horoscope",
        "description": "Get today's horoscope for an astrological sign.",
        "parameters": {
            "type": "object",
            "properties": {
                "sign": {
                    "type": "string",
                    "description": "An astrological sign like Taurus or Aquarius",
                },
            },
            "required": ["sign"],
        },
    },
]
```

```
def get_horoscope(sign):
    return f"{sign}: Next Tuesday you will befriend a baby otter."
```

Create a running input list we will add to over time

```
input_list = [
    {"role": "user", "content": "What is my horoscope? I am an Aquarius."}
]
```

2. Prompt the model with tools defined

```
response = client.responses.create(
    model="gpt-5",
    tools=tools,
    input=input_list,
)
```

Save function call outputs for subsequent requests

```
input_list += response.output
```

```
for item in response.output:
```

```
    if item.type == "function_call":
```

```
        if item.name == "get_horoscope":
```

3. Execute the function logic for

```
get_horoscope
```

```
    horoscope =
```

```
get_horoscope(json.loads(item.arguments))
```

4. Provide function call results to the

```
model
```

```
input_list.append({
    "type": "function_call_output",
    "call_id": item.call_id,
    "output": json.dumps({
        "horoscope": horoscope
    })
})
```

```
print("Final input:")
print(input_list)
```

```
response = client.responses.create(
    model="gpt-5",
    instructions="Respond only with a horoscope generated by a tool.",
    tools=tools,
    input=input_list,
)
```

5. The model should be able to give a response!

```
print("Final output:")
print(response.model_dump_json(indent=2))
print("\n" + response.output_text)
```

Tooling. How tools are provided?

2. OpenAI API interface:

```
{
  "model": "gwen3-32b",
  "instructions": "Respond only with a horoscope
generated by a tool.",
  "tools": [
    {
      "type": "function",
      "name": "get_horoscope",
      "description": "Get today's horoscope for an
astrological sign.",
      "parameters": {
        "type": "object",
        "properties": {
          "sign": {
            "type": "string",
            "description": "An astrological sign
like Taurus or Aquarius"
          }
        },
        "required": ["sign"]
      }
    }
  ],
}
```

```
"input": [
  {
    "role": "user",
    "content": "What is my horoscope? I am an
Aquarius."
  },
  {
    "role": "assistant",
    "content": [
      {
        "type": "function_call",
        "name": "get_horoscope",
        "arguments": "{\"sign\": \"Aquarius\"}",
        "call_id": "call_12345"
      }
    ]
  },
  {
    "type": "function_call_output",
    "call_id": "call_12345",
    "output": "{\"horoscope\": \"Aquarius: Next
Tuesday you will befriend a baby otter.\"}"
  }
]
```

Tooling. How tools are provided?

3. LLM Chat template:

```
➤ <|im_start|>system
# Tools

You may call one or more functions to assist with
the user query.

You are provided with function signatures within
➤ <tools></tools> XML tags:
<tools>
{
  "type": "function",
  "name": "get_horoscope",
  "description": "Get today's horoscope for an
astrological sign.",
  "parameters": {
    "type": "object",
    "properties": {
      "sign": {
        "type": "string",
        "description": "An astrological sign like
Taurus or Aquarius"
      }
    },
    "required": ["sign"]
  }
}
</tools>
```

For each function call, return a json object with function name and arguments within <tool_call></tool_call> XML tags:

```
<tool_call>
{"name": <function-name>, "arguments":
<args-json-object>}
</tool_call>
➤ <|im_end|>
➤ <|im_start|>user
What is my horoscope? I am an Aquarius.
<|im_end|>
➤ <|im_start|>assistant
<tool_call>
{"name": "get_horoscope", "arguments": {"sign":
"Aquarius"}}
</tool_call>
<|im_end|>
<|im_start|>user
<tool_response>
{"call_id": "call_12345", "output": {"horoscope":
"Aquarius: Next Tuesday you will befriend a baby
otter."}}
</tool_response>
<|im_end|>
<|im_start|>system
Respond only with a horoscope generated by a tool.
<|im_end|>
<|im_start|>assistant
Aquarius: Next Tuesday you will befriend a baby
otter.
```

Можно выделить три широких типа инструментов, доступных агенту

1. Дополнение информации агента

- Выход в интернет
- Парсинг нетекстовых типов данных (звука, изображений)
- Доступ к почте (чтение)
- Хожение по API
- Retrieval Augmented Generation (RAG)*
- etc.

2. Расширение возможностей агента

- Переводчики (в широком смысле) e.g. языков, единиц измерения
- Доступ к геолокации, времени
- Интерпретаторы и компиляторы языков программирования
- Калькулятор
- etc.

3. Возможность агента действовать


- Управление роботами (в т.ч. автомобилями)
- Исполнение написанного агентом кода и запросов
- Доступ к почте (с возможностью писать)
- etc.

Tooling. Common Tools

Commonly Used Tools:

- **Web Search:** For accessing real-time, up-to-date information.
 - Google API
 - Serp
 - Yandex
 - → Tavily: Designed specifically for LLMs
- **Code Interpreter:** For executing code (Python, etc.) to perform calculations, data analysis, or file manipulation.
 - Python sandbox
 - Bash
 - JS
 - e.t.c
- **Database Query:** To retrieve structured information from SQL or NoSQL databases.
 - → Postgres
 - Clickhouse
 - e.t.c
- **External APIs:** To interact with any service (GitHub, Spotify, corporate systems).
- **Retrieval:** To search over a private knowledge base (e.g., using a vector database).
 - Confluence/Wiki
 - Vector DB over documents

Retrieval-Augmented Generation (RAG) тоже может быть одним из инструментов



Agentic RAG. Single Agent RAG




Figure 16: An Overview of Single Agentic RAG

Agentic RAG. Multi-Agent RAG




Figure 17: An Overview of Multi-Agent Agentic RAG Systems

Adaptive Agentic RAG.




Figure 20: An Overview of Adaptive Agentic RAG


Multi-step agents. ReAct

ReAct: Synergizing Reasoning and Acting in Language Models:

Mostly prompting and response processing technique.

Main idea:

Let LLM reason first, perform some actions and then observe the outcome



ReAct example. Turn 1

```
{
  ↪ "messages": [
    {
      ↪ "role": "system",
      ↪ "content": 'Answer the following questions as best you can. You have access to the following tools:\n\nSearch: A search engine. Useful
for when you need to answer questions about current events. Input should be a search query.\n\nCalculator: Useful for when you need to answer
questions about math.\n\nThe way you use the tools is by specifying a json blob.\nSpecifically, this json should have a action key (with the name
of the tool to use) and a action_input key (with the input to the tool going here).\n\nThe only values that should be in the "action" field are:
Search, Calculator\n\nThe $JSON_BLOB should only contain a SINGLE action, do NOT return a list of multiple actions. Here is an example of a valid
$JSON_BLOB:\n\n```\n  "action": $TOOL_NAME,\n  "action_input": $INPUT\n```\n\nALWAYS use the following format:\n\nQuestion: the input question
you must answer\nThought: you should always think about what to do\nAction:\n```\n$JSON_BLOB\n```\nObservation: the result of the action\n... (this
Thought/Action/Observation can repeat N times)\nThought: I now know the final answer\nFinal Answer: the final answer to the original input
question\n\nBegin! Reminder to always use the exact characters Final Answer when responding.',
    },
    {
      ↪ "role": "user",
      ↪ "content": "Who is Olivia Wilde's boyfriend? What is his current age raised to the 0.23 power?\n\n",
    },
  ],
  "model": "gpt-3.5-turbo",
  "request_timeout": 60,
  "max_tokens": None,
  "stream": False,
  "n": 1,
  "temperature": 0.0,
  "stop": ["Observation:"],
}
```

ReAct example. Turn 2

Who is Olivia Wilde's boyfriend? What is his current age raised to the 0.23 power?

This was your previous work (but I haven't seen any of it! I only see what you return as final answer):

→ Thought: I need to use a search engine to find Olivia Wilde's boyfriend and a calculator to raise his age to the 0.23 power.

→ Action:

```
{  
  → "action": "Search",  
  → "action_input": "Olivia Wilde boyfriend"  
}
```

→ Observation: Sudeikis and Wilde's relationship ended in November 2020. Wilde was publicly served with court documents regarding child custody while she was presenting Don't Worry Darling at CinemaCon 2022. In January 2021, Wilde began dating singer Harry Styles after meeting during the filming of Don't Worry Darling.

Thought:

ReAct example. Turn 3

Who is Olivia Wilde's boyfriend? What is his current age raised to the 0.23 power?

This was your previous work (but I haven't seen any of it! I only see what you return as final answer):

Thought: I need to use a search engine to find Olivia Wilde's boyfriend and a calculator to raise his age to the 0.23 power.

Action:

```
{  
  "action": "Search",  
  "action_input": "Olivia Wilde boyfriend"  
}
```

Observation: Sudeikis and Wilde's relationship ended in November 2020. Wilde was publicly served with court documents regarding child custody while she was presenting Don't Worry Darling at CinemaCon 2022. In January 2021, Wilde began dating singer Harry Styles after meeting during the filming of Don't Worry Darling.

Thought: I need to use a search engine to find Harry Styles' current age.

Action:

```
→ {  
  "action": "Search",  
  "action_input": "Harry Styles age"  
}
```

→ Observation: 29 years

Thought:

ReAct example. Final turn

Who is Olivia Wilde's boyfriend? What is his current age raised to the 0.23 power?

This was your previous work (but I haven't seen any of it! I only see what you return as final answer):

Thought: I need to use a search engine to find Olivia Wilde's boyfriend and a calculator to raise his age to the 0.23 power.

Action:

```
{  
  "action": "Search",  
  "action_input": "Olivia Wilde boyfriend"  
}
```

Observation: Sudeikis and Wilde's relationship ended in November 2020. Wilde was publicly served with court documents regarding child custody while she was presenting Don't Worry Darling at CinemaCon 2022. In January 2021, Wilde began dating singer Harry Styles after meeting during the filming of Don't Worry Darling.

Thought: I need to use a search engine to find Harry Styles' current age.

Action:

```
{  
  "action": "Search",  
  "action_input": "Harry Styles age"  
}
```

Observation: 29 years

Thought: Now I need to calculate 29 raised to the 0.23 power.

Action:

```
{  
  "action": "Calculator",  
  "action_input": "29^0.23"  
}
```

Observation: Answer: 2.169459462491557


Thought:

LLM Response:


I now know the final answer.

Final Answer: 2.169459462491557

Архитектура агента на основе генеративной модели



В наиболее критических узлах системы мы ставим т.н. ограждения (guardrails)



Критический навык – умение оценить, можно ли доверять сервису



Greg Brockman ✓
@gdb



evals are surprisingly often all you need

6:24 PM · Dec 9, 2023 · **343.8K** Views



67



121



1.2K



136



Мы как разработчик/заказчик выставляем требование на желаемые характеристики сервиса

Evals

input

o.

Response	Concise?	Polite?	Helpful?
	✓	✓	✓
	✓	✓	✗
	✓	✓	✗
	✓	✓	✓


tools

-J

? *?* *?*



В наиболее критических узлах системы мы ставим т.н. ограждения (guardrails)



СПАСИБО ЗА ВНИМАНИЕ