HEP C^{++} course

D.Chamont, B. Gruber, S. Hageboeck, S. Ponce
sebastien.ponce@cern.ch

CERN

March 9, 2025

Foreword

What this course is not

- It is not for absolute beginners
- It is not for experts
- It is not complete at all (would need 3 weeks...)
  - although it is already too long for the time we have
  - 253 slides, 346 pages, 13 exercises...

How I see it

Adaptative pick what you want

Interactive tell me what to skip/insist on

Practical let's spend time on real code

Where to find latest version ?

- full sources at github.com/hsf-training/cpluspluscourse
- latest pdf on GitHub

More courses

The HSF Software Training Center

A set of course modules on more software engineering aspects prepared from within the HEP community

- Unix shell
- Python
- Version control (git, gitlab, github)
- ...

https://hepsoftwarefoundation.org/training/curriculum.html

Outline

1. History and goals
2. Language basics
3. Object orientation (OO)
4. Core modern C++
5. Useful tools

Detailed outline

1. History and goals
   - History
   - Why we use it?
2. Language basics
   - Core syntax and types
   - Arrays and Pointers
   - Scopes / namespaces
   - Class and enum types
   - References
   - Functions
   - Operators
   - Control structures
   - Headers and interfaces
   - Auto keyword
3. Object orientation (OO)
   - Objects and Classes
   - Inheritance
   - Constructors/destructors
   - Static members
   - Allocating objects
   - Advanced OO
   - Operator overloading
   - Function objects
4. Core modern C++
   - Constness
   - Exceptions
   - Templates
   - Lambdas
   - The STL
   - RAII and smart pointers
5. Useful tools
   - C++ editor
   - Version control
   - Code formatting
   - The Compiling Chain
   - Web tools
   - Debugging

History and goals

1. History and goals
   - History
   - Why we use it?
2. Language basics
3. Object orientation (OO)
4. Core modern C++
5. Useful tools

History

1. History and goals
   - History
   - Why we use it?

C/C++ origins



C inventor
Dennis M. Ritchie

C++ inventor
Bjarne Stroustrup

- Both C and C++ are born in Bell Labs
- C++ *almost* embeds C
- C and C++ are still under development
- We will discuss all C++ specs up to C++ 20 (only partially)
- Each slide will be marked with first spec introducing the feature

C^{++} 11, C^{++} 14, C^{++} 17, C^{++} 20, C^{++} 23, C^{++} 26...

Status

- A new C^{++} specification every 3 years
  - C^{++} 23 complete since 11th of Feb. 2023
  - work on C^{++} 26 is ongoing
- Bringing each time a lot of goodies

C++ 11, C++ 14, C++ 17, C++ 20, C++ 23, C++ 26...

Status

- A new C++ specification every 3 years
  - C++ 23 complete since 11th of Feb. 2023
  - work on C++ 26 is ongoing
- Bringing each time a lot of goodies

How to use C++ XX features

- Use a compatible compiler
- add `-std=c++xx` to compilation flags
- e.g. `-std=c++17`

C++	gcc	clang
11	≥4.8	≥3.3
14	≥4.9	≥3.4
17	≥7.3	≥5
20	≥11, 14	≥19
23	>15	>20

Table: Minimum versions of gcc and clang for a given C++ version

Why we use it?

1 History and goals
- History
- Why we use it?

Why is C++ our language of choice?

Adapted to large projects

- statically and strongly typed
- object oriented
- widely used (and taught)
- many available libraries

Why is C++ our language of choice?

Adapted to large projects

- statically and strongly typed
- object oriented
- widely used (and taught)
- many available libraries

Fast

- compiled to native machine code
  - unlike Java, C#, Python, ...
- allows to go close to hardware when needed

Why is C++ our language of choice?

Adapted to large projects

- statically and strongly typed
- object oriented
- widely used (and taught)
- many available libraries

Fast

- compiled to native machine code
  - unlike Java, C#, Python, ...
- allows to go close to hardware when needed

What we get

- the most powerful language
- the most complicated one
- the most error prone?

Language basics

1. History and goals
2. Language basics
   - Core syntax and types
   - Arrays and Pointers
   - Scopes / namespaces
   - Class and enum types
   - References
   - Functions
   - Operators
   - Control structures
   - Headers and interfaces
   - Auto keyword
3. Object orientation (OO)
4. Core modern C++
5. Useful tools

Core syntax and types

2 Language basics
- Core syntax and types
- Arrays and Pointers
- Scopes / namespaces
- Class and enum types
- References
- Functions
- Operators
- Control structures
- Headers and interfaces
- Auto keyword

Hello World


```
1  #include <iostream>
2
3  // This is a function
4  void print(int i) {
5    std::cout << "Hello, world " << i << std::endl;
6  }
7
8  int main(int argc, char** argv) {
9    int n = 3;
10   for (int i = 0; i < n; i++) {
11     print(i);
12   }
13   return 0;
14 }
```

Comments


```
// simple comment until end of line
int i;

/* multiline comment
 * in case we need to say more
 */
double /* or something in between */ d;

/**
 * Best choice : doxygen compatible comments
 * \brief checks whether i is odd
 * \param i input
 * \return true if i is odd, otherwise false
 * \see https://www.doxygen.nl/manual/docblocks.html
 */
bool isOdd(int i);
```

Basic types(1)


```
bool b = true;                  // boolean, true or false

char c = 'a';                   // min 8 bit integer
                                // may be signed or not
                                // can store an ASCII character
signed char c = 4;              // min 8 bit signed integer
unsigned char c = 4;            // min 8 bit unsigned integer

char* s = "a C string";         // array of chars ended by \0
string t = "a C++ string";// class provided by the STL

short int s = -444;             // min 16 bit signed integer
unsigned short s = 444;         // min 16 bit unsigned integer
short s = -444;                 // int is optional
```

Basic types(2)


```
int i = -123456;              // min 16, usually 32 bit
unsigned int i = 1234567; // min 16, usually 32 bit

long l = 0L                   // min 32 bit
unsigned long l = 0UL;        // min 32 bit

long long ll = 0LL;              // min 64 bit
unsigned long long l = 0ULL; // min 64 bit

float f = 1.23f;              // 32 (1+8+23) bit float
double d = 1.23E34;           // 64 (1+11+52) bit float
long double ld = 1.23E34L // min 64 bit float
```

Portable numeric types


```
#include <cstdint> // defines the following:

std::int8_t c = -3;      // 8 bit signed integer
std::uint8_t c = 4;      // 8 bit unsigned integer

std::int16_t s = -444;   // 16 bit signed integer
std::uint16_t s = 444;   // 16 bit unsigned integer

std::int32_t s = -674;   // 32 bit signed integer
std::uint32_t s = 674;   // 32 bit unsigned integer

std::int64_t s = -1635; // 64 bit signed integer
std::uint64_t s = 1635; // 64 bit unsigned int
```

Integer literals


```
int i = 1234;              // decimal     (base 10)
int i = 02322;             // octal       (base  8)
int i = 0x4d2;             // hexadecimal (base 16)
int i = 0X4D2;             // hexadecimal (base 16)
int i = 0b10011010010;     // binary      (base  2) C++14

int i = 123'456'789;       // digit separators, C++14
int i = 0b100'1101'0010;   // digit separators, C++14

42            // int
42u,   42U    // unsigned int
42l,   42L    // long
42ul,  42UL   // unsigned long
42ll,  42LL   // long long
42ull, 42ULL  // unsigned long long
```

Floating-point literals


```
double d = 12.34;
double d = 12.;
double d = .34;
double d = 12e34;            // 12 * 10^34
double d = 12E34;            // 12 * 10^34
double d = 12e-34;           // 12 * 10^-34
double d = 12.34e34;         // 12.34 * 10^34

double d = 123'456.789'101; // digit separators, C++14

double d = 0x4d2.4p3;    // hexfloat, 0x4d2.4 * 2^3
                         // = 1234.25 * 2^3 = 9874

3.14f, 3.14F,  // float
3.14,  3.14,   // double
3.14l, 3.14L,  // long double
```

Arrays and Pointers

2 Language basics
- Core syntax and types
- Arrays and Pointers
- Scopes / namespaces
- Class and enum types
- References
- Functions
- Operators
- Control structures
- Headers and interfaces
- Auto keyword

Static arrays


```
int ai[4] = {1,2,3,4};
int ai[] = {1,2,3,4};  // identical

char ac[3] = {'a','b','c'};   // char array
char ac[4] = "abc";           // valid C string
char ac[4] = {'a','b','c',0}; // same valid string

int i = ai[2];  // i = 3
char c = ac[8]; // at best garbage, may segfault
int i = ai[4];  // also garbage !
```

Pointers


```
int i = 4;
int *pi = &i;
int j = *pi + 1;

int ai[] = {1,2,3};
int *pai = ai; // decay to ptr
int *paj = pai + 1;
int k = *paj + 1;

// compile error
int *pak = k;

// seg fault !
int *pak = (int*)k;
int l = *pak;
```

Pointers


```
int i = 4;
int *pi = &i;
int j = *pi + 1;

int ai[] = {1,2,3};
int *pai = ai; // decay to ptr
int *paj = pai + 1;
int k = *paj + 1;

// compile error
int *pak = k;

// seg fault !
int *pak = (int*)k;
int l = *pak;
```

Memory layout



Pointers


```
int i = 4;
int *pi = &i;
int j = *pi + 1;

int ai[] = {1,2,3};
int *pai = ai; // decay to ptr
int *paj = pai + 1;
int k = *paj + 1;

// compile error
int *pak = k;

// seg fault !
int *pak = (int*)k;
int l = *pak;
```



Pointers


```
int i = 4;
int *pi = &i;
int j = *pi + 1;

int ai[] = {1,2,3};
int *pai = ai; // decay to ptr
int *paj = pai + 1;
int k = *paj + 1;

// compile error
int *pak = k;

// seg fault !
int *pak = (int*)k;
int l = *pak;
```



Pointers


```
int i = 4;
int *pi = &i;
int j = *pi + 1;

int ai[] = {1,2,3};
int *pai = ai; // decay to ptr
int *paj = pai + 1;
int k = *paj + 1;

// compile error
int *pak = k;

// seg fault !
int *pak = (int*)k;
int l = *pak;
```



Pointers


```
int i = 4;
int *pi = &i;
int j = *pi + 1;

int ai[] = {1,2,3};
int *pai = ai; // decay to ptr
int *paj = pai + 1;
int k = *paj + 1;

// compile error
int *pak = k;

// seg fault !
int *pak = (int*)k;
int l = *pak;
```



Pointers


```
int i = 4;
int *pi = &i;
int j = *pi + 1;

int ai[] = {1,2,3};
int *pai = ai; // decay to ptr
int *paj = pai + 1;
int k = *paj + 1;

// compile error
int *pak = k;

// seg fault !
int *pak = (int*)k;
int l = *pak;
```



Pointers


```
int i = 4;
int *pi = &i;
int j = *pi + 1;

int ai[] = {1,2,3};
int *pai = ai; // decay to ptr
int *paj = pai + 1;
int k = *paj + 1;

// compile error
int *pak = k;

// seg fault !
int *pak = (int*)k;
int l = *pak;
```



Pointers


```
int i = 4;
int *pi = &i;
int j = *pi + 1;

int ai[] = {1,2,3};
int *pai = ai; // decay to ptr
int *paj = pai + 1;
int k = *paj + 1;

// compile error
int *pak = k;

// seg fault !
int *pak = (int*)k;
int l = *pak;
```



nullptr

A pointer to nothing

- if a pointer doesn't point to anything, set it to `nullptr`
  - useful to e.g. mark the end of a linked data structure
  - or absence of an optional function argument (pointer)
- same as setting it to 0 or `NULL` (before C++ 11)
- triggers compilation error when assigned to integer

nullptr

A pointer to nothing

- if a pointer doesn't point to anything, set it to **nullptr**
  - useful to e.g. mark the end of a linked data structure
  - or absence of an optional function argument (pointer)
- same as setting it to 0 or NULL (before C++ 11)
- triggers compilation error when assigned to integer

Example code

```
int* ip = nullptr;
int i = NULL;        // compiles, bug?
int i = nullptr;     // ERROR
```

Dynamic arrays using C


```
#include <cstdlib>
#include <cstring>

int *bad;            // pointer to random address
int *ai = nullptr; // better, deterministic, testable

// allocate array of 10 ints (uninitialized)
ai = (int*) malloc(10*sizeof(int));
memset(ai, 0, 10*sizeof(int)); // and set them to 0

ai = (int*) calloc(10, sizeof(int)); // both in one go

free(ai); // release memory
```

Good practice: Don't use C's memory management

Use `std::vector` and friends or smart pointers

Manual dynamic arrays using C++


```
#include <cstdlib>
#include <cstring>

// allocate array of 10 ints
int* ai = new int[10];    // uninitialized
int* ai = new int[10]{}; // zero-initialized

delete[] ai; // release array memory

// allocate a single int
int* pi = new int;
int* pi = new int{};
delete pi; // release scalar memory
```

Good practice: Don't use manual memory management

Use `std::vector` and friends or smart pointers

Scopes / namespaces

2 Language basics

- Core syntax and types
- Arrays and Pointers
- Scopes / namespaces
- Class and enum types
- References
- Functions
- Operators
- Control structures
- Headers and interfaces
- Auto keyword

Scope

Definition

Portion of the source code where a given name is valid

Typically :

- simple block of code, within {}
- function, class, namespace
- the global scope, i.e. translation unit (.cpp file + all includes)

Example

```
1 { int a;
2   { int b;
3   } // end of b scope
4 } // end of a scope
```

Scope and lifetime of variables

Variable life time

- Variables are (statically) allocated when defined
- Variables are freed at the end of a scope

Good practice: Initialisation

- Initialise variables when allocating them!
- This prevents bugs reading uninitialised memory

```
int a = 1;
{
  int b[4];
  b[0] = a;
}
// Doesn't compile here:
// b[1] = a + 1;
```

Memory layout



Scope and lifetime of variables

Variable life time

- Variables are (statically) allocated when defined
- Variables are freed at the end of a scope

Good practice: Initialisation

- Initialise variables when allocating them!
- This prevents bugs reading uninitialised memory

```
1  int a = 1;
2  {
3    int b[4];
4    b[0] = a;
5  }
6  // Doesn't compile here:
7  // b[1] = a + 1;
```

Memory layout

b[3] = ?	0x3010
b[2] = ?	0x300C
b[1] = ?	0x3008
b[0] = ?	0x3004
a = 1	0x3000

Scope and lifetime of variables

Variable life time

- Variables are (statically) allocated when defined
- Variables are freed at the end of a scope

Good practice: Initialisation

- Initialise variables when allocating them!
- This prevents bugs reading uninitialised memory

```
int a = 1;
{
  int b[4];
  b[0] = a;
}
// Doesn't compile here:
// b[1] = a + 1;
```

Memory layout

b[3] = ?	0x3010
b[2] = ?	0x300C
b[1] = ?	0x3008
b[0] = 1	0x3004
a = 1	0x3000

Scope and lifetime of variables

Variable life time

- Variables are (statically) allocated when defined
- Variables are freed at the end of a scope

Good practice: Initialisation

- Initialise variables when allocating them!
- This prevents bugs reading uninitialised memory

```
int a = 1;
{
  int b[4];
  b[0] = a;
}
// Doesn't compile here:
// b[1] = a + 1;
```

Memory layout

?	0x3010
?	0x300C
?	0x3008
1	0x3004
a = 1	0x3000

Namespaces

- Namespaces allow to segment your code to avoid name clashes
- They can be embedded to create hierarchies (separator is '::')

```
int a;
namespace n {
  int a;   // no clash
}
namespace p {
  int a;   // no clash
  namespace inner {
    int a; // no clash
  }
}
void f() {
  n::a = 3;
}
namespace p { // reopen p
  void f() {
    p::a = 6;
    a = 6;  //same as above
    ::a = 1;
    p::inner::a = 8;
    inner::a = 8;
    n::a = 3;
  }
}
using namespace p::inner;
void g() {
  a = -1; // err: ambiguous
}
```

Nested namespaces

C++ 98: Old way to declare nested namespaces

```
namespace A {
  namespace B {
    namespace C {
      //...
    }
  }
}
```

C++ 17: Nested declaration

```
namespace A::B::C {
  //...
}
```

C++ 17: Namespace alias

```
namespace ABC = A::B::C;
```

Class and enum types

2 Language basics
- Core syntax and types
- Arrays and Pointers
- Scopes / namespaces
- Class and enum types
- References
- Functions
- Operators
- Control structures
- Headers and interfaces
- Auto keyword

struct

"members" grouped together under one name

```
struct Individual {
  unsigned char age;
  float weight;
};

Individual student;
student.age = 25;
student.weight = 78.5f;

Individual teacher = {
  45, 67.0f
};
```

```
Individual *ptr = &student;
ptr->age = 25;
// same as: (*ptr).age = 25;
```

struct

"members" grouped together under one name

```
struct Individual {
  unsigned char age;
  float weight;
};

Individual student;
student.age = 25;
student.weight = 78.5f;

Individual teacher = {
  45, 67.0f
};
```

```
Individual *ptr = &student;
ptr->age = 25;
// same as: (*ptr).age = 25;
```

Memory layout



struct

"members" grouped together under one name

```
struct Individual {
  unsigned char age;
  float weight;
};

Individual student;
student.age = 25;
student.weight = 78.5f;

Individual teacher = {
  45, 67.0f
};
```

```
Individual *ptr = &student;
ptr->age = 25;
// same as: (*ptr).age = 25;
```

Memory layout



struct

"members" grouped together under one name

```
struct Individual {
  unsigned char age;
  float weight;
};

Individual student;
student.age = 25;
student.weight = 78.5f;

Individual teacher = {
  45, 67.0f
};
```

```
Individual *ptr = &student;
ptr->age = 25;
// same as: (*ptr).age = 25;
```

Memory layout



struct

"members" grouped together under one name

```
struct Individual {
  unsigned char age;
  float weight;
};

Individual student;
student.age = 25;
student.weight = 78.5f;

Individual teacher = {
  45, 67.0f
};
```

```
Individual *ptr = &student;
ptr->age = 25;
// same as: (*ptr).age = 25;
```

Memory layout



union

"members" packed together at same memory location

```
union Duration {
  int seconds;
  short hours;
  char days;
};
Duration d1, d2, d3;
d1.seconds = 259200;
d2.hours = 72;
d3.days = 3;
d1.days = 3; // d1.seconds overwritten
int a = d1.seconds; // d1.seconds is garbage
```

union

"members" packed together at same memory location

```
union Duration {
  int seconds;
  short hours;
  char days;
};
Duration d1, d2, d3;
d1.seconds = 259200;
d2.hours = 72;
d3.days = 3;
d1.days = 3; // d1.seconds overwritten
int a = d1.seconds; // d1.seconds is garbage
```

Memory layout



union

"members" packed together at same memory location

```
union Duration {
  int seconds;
  short hours;
  char days;
};
Duration d1, d2, d3;
d1.seconds = 259200;
d2.hours = 72;
d3.days = 3;
d1.days = 3; // d1.seconds overwritten
int a = d1.seconds; // d1.seconds is garbage
```

Memory layout



union

"members" packed together at same memory location

```
union Duration {
  int seconds;
  short hours;
  char days;
};
Duration d1, d2, d3;
d1.seconds = 259200;
d2.hours = 72;
d3.days = 3;
d1.days = 3; // d1.seconds overwritten
int a = d1.seconds; // d1.seconds is garbage
```

Memory layout

				0x300C
				0x3008
← d2	72 →	?	?	0x3004
←	d1 259200		→	0x3000

union

"members" packed together at same memory location

```
union Duration {
  int seconds;
  short hours;
  char days;
};
Duration d1, d2, d3;
d1.seconds = 259200;
d2.hours = 72;
d3.days = 3;
d1.days = 3; // d1.seconds overwritten
int a = d1.seconds; // d1.seconds is garbage
```

Memory layout

				0x300C
d3 3	?	?	?	0x3008
← d2 72 →		?	?	0x3004
← d1 259200 →				0x3000

union

"members" packed together at same memory location

```
union Duration {
  int seconds;
  short hours;
  char days;
};
Duration d1, d2, d3;
d1.seconds = 259200;
d2.hours = 72;
d3.days = 3;
d1.days = 3; // d1.seconds overwritten
int a = d1.seconds; // d1.seconds is garbage
```

Memory layout

				0x300C
d3 3	?	?	?	0x3008
← d2	72 →	?	?	0x3004
d1 3	?	?	?	0x3000

union

"members" packed together at same memory location

```
union Duration {
  int seconds;
  short hours;
  char days;
};
Duration d1, d2, d3;
d1.seconds = 259200;
d2.hours = 72;
d3.days = 3;
d1.days = 3; // d1.seconds overwritten
int a = d1.seconds; // d1.seconds is garbage
```

Memory layout

				0x300C
d3 3	?	?	?	0x3008
← d2	72 →	?	?	0x3004
d1 3	?	?	?	0x3000

Good practice: Avoid unions

- Starting with C++ 17: prefer `std::variant`

Enums

- use to declare a list of related constants (enumerators)
- has an underlying integral type
- enumerator names leak into enclosing scope

```
enum VehicleType {

  BIKE,   // 0
  CAR,    // 1
  BUS,    // 2
};
VehicleType t = CAR;
```

```
enum VehicleType
  : int { // C++11
  BIKE = 3,
  CAR = 5,
  BUS = 7,
};
VehicleType t2 = BUS;
```

Scoped enumeration, aka enum class

Same syntax as enum, with scope

```
enum class VehicleType { Bus, Car };
VehicleType t = VehicleType::Car;
```

Scoped enumeration, aka enum class

C++ 11

Same syntax as enum, with scope

```
enum class VehicleType { Bus, Car };
VehicleType t = VehicleType::Car;
```

Only advantages

- scopes enumerator names, avoids name clashes
- strong typing, no automatic conversion to int

```
enum VType { Bus, Car }; enum Color { Red, Blue };
VType t = Bus;
if (t == Red) { /* We do enter */ }
int a = 5 * Car; // Ok, a = 5

enum class VT { Bus, Car }; enum class Col { Red, Blue };
VT t = VT::Bus;
if (t == Col::Red) { /* Compiler error */ }
int a = t * 5;        // Compiler error
```

More sensible example


```
enum class ShapeType {
  Circle,
  Rectangle
};

struct Rectangle {
  float width;
  float height;
};
```

More sensible example


```
enum class ShapeType {
  Circle,
  Rectangle
};

struct Rectangle {
  float width;
  float height;
};
```

```
struct Shape {
  ShapeType type;
  union {
    float radius;
    Rectangle rect;
  };
};
```

More sensible example


```
enum class ShapeType {
  Circle,
  Rectangle
};

struct Rectangle {
  float width;
  float height;
};
```

```
struct Shape {
  ShapeType type;
  union {
    float radius;
    Rectangle rect;
  };
};
```

```
Shape s;
s.type =
  ShapeType::Circle;
s.radius = 3.4;

```

```
Shape t;
t.type =
  Shapetype::Rectangle;
t.rect.width = 3;
t.rect.height = 4;
```

typedef and using

C++ 98 / C++ 11

Used to create type aliases

C++ 98

```
typedef std::uint64_t myint;
myint count = 17;
typedef float position[3];
```

C++ 11

```
using myint = std::uint64_t;
myint count = 17;
using position = float[3];

template <typename T> using myvec = std::vector<T>;
myvec<int> myintvec;
```

References

2 Language basics
- Core syntax and types
- Arrays and Pointers
- Scopes / namespaces
- Class and enum types
- References
- Functions
- Operators
- Control structures
- Headers and interfaces
- Auto keyword

References

References

- References allow for direct access to another object
- They can be used as shortcuts / better readability
- They can be declared `const` to allow only read access

Example:

```
int i = 2;
int &iref = i; // access to i
iref = 3;      // i is now 3

// const reference to a member:
struct A { int x; int y; } a;
const int &x = a.x; // direct read access to A's x
x = 4;              // doesn't compile
a.x = 4;            // fine
```

Pointers vs References

Specificities of reference

- Natural syntax
- Cannot be `nullptr`
- Must be assigned when defined, cannot be reassigned
- References to temporary objects must be `const`

Advantages of pointers

- Can be `nullptr`
- Can be initialized after declaration, can be reassigned

Pointers vs References

Specificities of reference

- Natural syntax
- Cannot be `nullptr`
- Must be assigned when defined, cannot be reassigned
- References to temporary objects must be `const`

Advantages of pointers

- Can be `nullptr`
- Can be initialized after declaration, can be reassigned

Good practice: References

- Prefer using references instead of pointers
- Mark references `const` to prevent modification

Functions

2 Language basics
- Core syntax and types
- Arrays and Pointers
- Scopes / namespaces
- Class and enum types
- References
- Functions
- Operators
- Control structures
- Headers and interfaces
- Auto keyword

Functions


```
// with return type
int square(int a) {
  return a * a;
}

// multiple parameters
int mult(int a,
         int b) {
  return a * b;
}
```

```
// no return
void log(char* msg) {
  std::cout << msg;
}

// no parameter
void hello() {
  std::cout << "Hello World";
}
```

Functions


```
// with return type
int square(int a) {
  return a * a;
}

// multiple parameters
int mult(int a,
         int b) {
  return a * b;
}
```

```
// no return
void log(char* msg) {
  std::cout << msg;
}

// no parameter
void hello() {
  std::cout << "Hello World";
}
```

Functions and references to returned values

```
int result = square(2);
int & temp = square(2);          // Not allowed
int const & temp2 = square(2); // OK
```

Function default arguments


```
// must be the trailing
// argument
int add(int a,
        int b = 2) {
  return a + b;
}
// add(1) == 3
// add(3,4) == 7

// multiple default
// arguments are possible
int add(int a = 2,
        int b = 2) {
  return a + b;
}
// add() == 4
// add(3) == 5
```

Functions: parameters are passed by value


```
1  struct BigStruct {...};
2  BigStruct s;
3
4  // parameter by value
5  void printVal(BigStruct p) {
6     ...
7  }
8  printVal(s); // copy
9
10 // parameter by reference
11 void printRef(BigStruct &q) {
12    ...
13 }
14 printRef(s); // no copy
```

Memory layout



Functions: parameters are passed by value


```
struct BigStruct {...};
BigStruct s;

// parameter by value
void printVal(BigStruct p) {
   ...
}
printVal(s); // copy

// parameter by reference
void printRef(BigStruct &q) {
   ...
}
printRef(s); // no copy
```



Functions: parameters are passed by value


```
struct BigStruct {...};
BigStruct s;

// parameter by value
void printVal(BigStruct p) {
   ...
}
printVal(s); // copy

// parameter by reference
void printRef(BigStruct &q) {
   ...
}
printRef(s); // no copy
```



Functions: parameters are passed by value


```
struct BigStruct {...};
BigStruct s;

// parameter by value
void printVal(BigStruct p) {
   ...
}
printVal(s); // copy

// parameter by reference
void printRef(BigStruct &q) {
   ...
}
printRef(s); // no copy
```



Functions: pass by value or reference?


```
struct SmallStruct {int a;};
SmallStruct s = {1};

void changeVal(SmallStruct p) {
  p.a = 2;
}
changeVal(s);
// s.a == 1

void changeRef(SmallStruct &q) {
  q.a = 2;
}
changeRef(s);
// s.a == 2
```

Memory layout



Functions: pass by value or reference?


```
1  struct SmallStruct {int a;};
2  SmallStruct s = {1};
3
4  void changeVal(SmallStruct p) {
5    p.a = 2;
6  }
7  changeVal(s);
8  // s.a == 1
9
10 void changeRef(SmallStruct &q) {
11   q.a = 2;
12 }
13 changeRef(s);
14 // s.a == 2
```

Memory layout

	0x3008
	0x3004
s.a = 1	0x3000

Functions: pass by value or reference?


```
struct SmallStruct {int a;};
SmallStruct s = {1};

void changeVal(SmallStruct p) {
  p.a = 2;
}
changeVal(s);
// s.a == 1

void changeRef(SmallStruct &q) {
  q.a = 2;
}
changeRef(s);
// s.a == 2
```

Memory layout

	0x3008
p.a = 1	0x3004
s.a = 1	0x3000

Functions: pass by value or reference?


```
1  struct SmallStruct {int a;};
2  SmallStruct s = {1};
3
4  void changeVal(SmallStruct p) {
5    p.a = 2;
6  }
7  changeVal(s);
8  // s.a == 1
9
10 void changeRef(SmallStruct &q) {
11   q.a = 2;
12 }
13 changeRef(s);
14 // s.a == 2
```

Memory layout

	0x3008
p.a = 2	0x3004
s.a = 1	0x3000

Functions: pass by value or reference?


```
struct SmallStruct {int a;};
SmallStruct s = {1};

void changeVal(SmallStruct p) {
  p.a = 2;
}
changeVal(s);
// s.a == 1

void changeRef(SmallStruct &q) {
  q.a = 2;
}
changeRef(s);
// s.a == 2
```

Memory layout

	0x3008
	0x3004
s.a = 1	0x3000

Functions: pass by value or reference?


```
1  struct SmallStruct {int a;};
2  SmallStruct s = {1};
3
4  void changeVal(SmallStruct p) {
5    p.a = 2;
6  }
7  changeVal(s);
8  // s.a == 1
9
10 void changeRef(SmallStruct &q) {
11   q.a = 2;
12 }
13 changeRef(s);
14 // s.a == 2
```

Memory layout



Functions: pass by value or reference?


```
1  struct SmallStruct {int a;};
2  SmallStruct s = {1};
3
4  void changeVal(SmallStruct p) {
5    p.a = 2;
6  }
7  changeVal(s);
8  // s.a == 1
9
10 void changeRef(SmallStruct &q) {
11   q.a = 2;
12 }
13 changeRef(s);
14 // s.a == 2
```



Functions: pass by value or reference?


```
struct SmallStruct {int a;};
SmallStruct s = {1};

void changeVal(SmallStruct p) {
  p.a = 2;
}
changeVal(s);
// s.a == 1

void changeRef(SmallStruct &q) {
  q.a = 2;
}
changeRef(s);
// s.a == 2
```

Memory layout

	0x3008
	0x3004
s.a = 2	0x3000

Pass by value, reference or pointer

Different ways to pass arguments to a function

- By default, arguments are passed by value (= copy)
  good for small types, e.g. numbers
- Use references for parameters to avoid copies
  good for large types, e.g. objects
- Use `const` for safety and readability whenever possible

Pass by value, reference or pointer

Different ways to pass arguments to a function

- By default, arguments are passed by value (= copy)
  good for small types, e.g. numbers
- Use references for parameters to avoid copies
  good for large types, e.g. objects
- Use `const` for safety and readability whenever possible

Syntax

```
struct T {...}; T a;
void fVal(T value);          fVal(a);    // by value
void fRef(const T &value);   fRef(a);    // by reference
void fPtr(const T *value);   fPtr(&a);   // by pointer
void fWrite(T &value);       fWrite(a);  // non-const ref
```

Overloading

Overloading

- We can have multiple functions with the same name
  - Must have different parameter lists
  - A different return type alone is not allowed
  - Form a so-called "overload set"
- Default arguments can cause ambiguities

```
int sum(int b);                  // 1
int sum(int b, int c);           // 2, ok, overload
// float sum(int b, int c); // disallowed
sum(42); // calls 1
sum(42, 43); // calls 2
int sum(int b, int c, int d = 4); // 3, overload
sum(42, 43, 44); // calls 3
sum(42, 43);      // error: ambiguous, 2 or 3
```

Functions

Exercise: Functions

Familiarise yourself with pass by value / pass by reference.

- Go to `exercises/functions`
- Look at `functions.cpp`
- Compile it (`make`) and run the program (`./functions`)
- Work on the tasks that you find in `functions.cpp`

Functions: good practices

Good practice: Write readable functions

- Keep functions short
- Do one logical thing (single-responsibility principle)
- Use expressive names
- Document non-trivial functions

Example: Good

```
/// Count number of dilepton events in data.
/// \param d Dataset to search.
unsigned int countDileptons(Data &d) {
  selectEventsWithMuons(d);
  selectEventsWithElectrons(d);
  return d.size();
}
```

Functions: good practices

Example: don't! Everything in one long function

```
unsigned int runJob() {
  // Step 1: data
  Data data;
  data.resize(123456);
  data.fill(...);

  // Step 2: muons
  for (....) {
    if (...) {
      data.erase(...);
    }
  }
  // Step 3: electrons
  for (....) {
    if (...) {
      data.erase(...);
    }
  }

  // Step 4: dileptons
  int counter = 0;
  for (....) {
    if (...) {
      counter++;
    }
  }

  return counter;
}
```

Operators

2 Language basics

- Core syntax and types
- Arrays and Pointers
- Scopes / namespaces
- Class and enum types
- References
- Functions
- Operators
- Control structures
- Headers and interfaces
- Auto keyword

Operators(1)

Binary and Assignment Operators

```
int i = 1 + 4 - 2;   // 3
i *= 3;              // 9, short for: i = i * 3;
i /= 2;              // 4
i = 23 % i;          // modulo => 3
```

Operators(1)

Binary and Assignment Operators

```
int i = 1 + 4 - 2;   // 3
i *= 3;              // 9, short for: i = i * 3;
i /= 2;              // 4
i = 23 % i;          // modulo => 3
```

Increment / Decrement Operators

```
int i = 0; i++; // i = 1
int j = ++i;    // i = 2, j = 2
int k = i++;    // i = 3, k = 2
int l = --i;    // i = 2, l = 2
int m = i--;    // i = 1, m = 2
```

Operators(1)

Binary and Assignment Operators

```
int i = 1 + 4 - 2;   // 3
i *= 3;              // 9, short for: i = i * 3;
i /= 2;              // 4
i = 23 % i;          // modulo => 3
```

Increment / Decrement Operators

Use wisely

```
int i = 0; i++; // i = 1
int j = ++i;    // i = 2, j = 2
int k = i++;    // i = 3, k = 2
int l = --i;    // i = 2, l = 2
int m = i--;    // i = 1, m = 2
```

Operators(2)

Bitwise and Assignment Operators

```
unsigned i = 0xee & 0x55;   // 0x44
i |= 0xee;                  // 0xee
i ^= 0x55;                  // 0xbb
unsigned j = ~0xee;         // 0xffffff11
unsigned k = 0x1f << 3;     // 0xf8
unsigned l = 0x1f >> 2;     // 0x7
```

Operators(2)

Bitwise and Assignment Operators

```
unsigned i = 0xee & 0x55;   // 0x44
i |= 0xee;                  // 0xee
i ^= 0x55;                  // 0xbb
unsigned j = ~0xee;         // 0xffffff11
unsigned k = 0x1f << 3;     // 0xf8
unsigned l = 0x1f >> 2;     // 0x7
```

Logical Operators

```
bool a = true;
bool b = false;
bool c = a && b;     // false
bool d = a || b;     // true
bool e = !d;         // false
```

Operators(3)

Comparison Operators

```
bool a = (3 == 3);  // true
bool b = (3 != 3);  // false
bool c = (4 <  4);  // false
bool d = (4 <= 4);  // true
bool e = (4 >  4);  // false
bool f = (4 >= 4);  // true
auto g = (5 <=> 5); // C++20 (later)
```

Operators(3)

Comparison Operators

```
bool a = (3 == 3);  // true
bool b = (3 != 3);  // false
bool c = (4 <  4);  // false
bool d = (4 <= 4);  // true
bool e = (4 >  4);  // false
bool f = (4 >= 4);  // true
auto g = (5 <=> 5); // C++20 (later)
```

Precedences

```
c &= 1+(++b)|(a--)*4%5^7; // ???
```

Details can be found on cppreference

Operators(3)

Comparison Operators

```
bool a = (3 == 3);  // true
bool b = (3 != 3);  // false
bool c = (4 <  4);  // false
bool d = (4 <= 4);  // true
bool e = (4 >  4);  // false
bool f = (4 >= 4);  // true
auto g = (5 <=> 5); // C++20 (later)
```

Precedences **Avoid**

```
c &= 1+(++b)|(a--)*4%5^7; // ???
```

Details can be found on cppreference

Operators(3)

Comparison Operators

```
bool a = (3 == 3);  // true
bool b = (3 != 3);  // false
bool c = (4 <  4);  // false
bool d = (4 <= 4);  // true
bool e = (4 >  4);  // false
bool f = (4 >= 4);  // true
auto g = (5 <=> 5); // C++20 (later)
```

Precedences

Avoid - use parentheses

```
c &= 1+(++b)|(a--)*4%5^7; // ???
```

Details can be found on cppreference

Control structures

2 Language basics

- Core syntax and types
- Arrays and Pointers
- Scopes / namespaces
- Class and enum types
- References
- Functions
- Operators
- Control structures
- Headers and interfaces
- Auto keyword

Control structures: if

if syntax

```
if (condition1) {
  Statement1; Statement2;
} else if (condition2)
  OnlyOneStatement;
else {
  Statement3;
  Statement4;
}
```

- The `else` and `else if` clauses are optional
- The `else if` clause can be repeated
- Braces are optional if there is a single statement

Control structures: if

Practical example

```
int collatz(int a) {
  if (a <= 0) {
    std::cout << "not supported\n";
    return 0;
  } else if (a == 1) {
    return 1;
  } else if (a%2 == 0) {
    return collatz(a/2);
  } else {
    return collatz(3*a+1);
  }
}
```

Control structures: conditional operator

Syntax

```
test ? expression1 : expression2;
```

- If test is `true` `expression1` is returned
- Else, `expression2` is returned

Control structures: conditional operator

Syntax

```
test ? expression1 : expression2;
```

- If test is `true` `expression1` is returned
- Else, `expression2` is returned

Practical example

```
const int charge = isLepton ? -1 : 0;
```

Control structures: conditional operator

Syntax

```
test ? expression1 : expression2;
```

- If test is `true` `expression1` is returned
- Else, `expression2` is returned

Practical example

```
const int charge = isLepton ? -1 : 0;
```

Do not abuse it

```
int collatz(int a) {
  return a==1 ? 1 : collatz(a%2==0 ? a/2 : 3*a+1);
}
```

- Explicit `if`s are generally easier to read
- Use the ternary operator with short conditions and expressions
- Avoid nesting

Control structures: switch

Syntax

```
switch(identifier) {
  case c1 : statements1; break;
  case c2 : statements2; break;
  case c3 : statements3; break;
  ...
  default : statementsn; break;
}
```

- The `break` statement is not mandatory but...
- Cases are entry points, not independent pieces
- Execution "falls through" to the next case without a `break`!
- The `default` case may be omitted

Control structures: switch

Syntax

```
switch(identifier) {
  case c1 : statements1; break;
  case c2 : statements2; break;
  case c3 : statements3; break;
  ...
  default : statementsn; break;
}
```

- The `break` statement is not mandatory but...
- Cases are entry points, not independent pieces
- Execution "falls through" to the next case without a `break`!
- The `default` case may be omitted

Use break

Avoid `switch` statements with fall-through cases

Control structures: switch

Practical example

```
enum class Lang { French, German, English, Other };
Lang language = ...;
switch (language) {
  case Lang::French:
    std::cout << "Bonjour";
    break;
  case Lang::German:
    std::cout << "Guten Tag";
    break;
  case Lang::English:
    std::cout << "Good morning";
    break;
  default:
    std::cout << "I do not speak your language";
}
```

[[fallthrough]] attribute

C++ 17

New compiler warning

Since C++ 17, compilers are encouraged to warn on fall-through

C++ 17

```
switch (c) {
  case 'a':
    f();     // Warning emitted
  case 'b': // Warning probably suppressed
  case 'c':
    g();
    [[fallthrough]]; // Warning suppressed
  case 'd':
    h();
}
```

Init-statements for if and switch

C++ 17

Purpose

Allows to limit variable scope in **if** and **switch** statements

C++ 17

```
if (Value val = GetValue(); condition(val)) {
  f(val); // ok
} else
  g(val); // ok
h(val);   // error, no `val` in scope here
```

Init-statements for if and switch

C++ 17

Purpose

Allows to limit variable scope in **if** and **switch** statements

C++ 17

```
if (Value val = GetValue(); condition(val)) {
  f(val); // ok
} else
  g(val); // ok
h(val);   // error, no `val` in scope here
```

C++ 98

Don't confuse with a variable declaration as condition:

```
if (Value* val = GetValuePtr())
  f(*val);
```

Control structures: for loop

for loop syntax

```
for(initializations; condition; increments) {
  statements;
}
```

- Multiple initializations / increments are comma separated
- Initializations can contain declarations
- Braces are optional if loop body is a single statement

Control structures: for loop

for loop syntax

```
for(initializations; condition; increments) {
  statements;
}
```

- Multiple initializations / increments are comma separated
- Initializations can contain declarations
- Braces are optional if loop body is a single statement

Practical example

```
for(int i = 0, j = 0 ; i < 10 ; i++, j = i*i) {
  std::cout << i << "^2 is " << j << '\n';
}
```

Control structures: for loop

for loop syntax

```
for(initializations; condition; increments) {
  statements;
}
```

- Multiple initializations / increments are comma separated
- Initializations can contain declarations
- Braces are optional if loop body is a single statement

Practical example

```
for(int i = 0, j = 0 ; i < 10 ; i++, j = i*i) {
  std::cout << i << "^2 is " << j << '\n';
}
```

Good practice: Don't abuse the `for` syntax

- The `for` loop head should fit in 1-3 lines

Range-based loops

Reason of being

- Simplifies loops over "ranges" tremendously
- Especially with STL containers and ranges

Syntax

```
for ( type iteration_variable : range ) {
  // body using iteration_variable
}
```

Example code

```
int v[4] = {1,2,3,4};
int sum = 0;
for (int a : v) { sum += a; }
```

Init-statements for range-based loops

C++ 20

Purpose

Allows to limit variable scope in range-based loops

C++ 17

```
std::array data = {"hello", ",", "world"};
std::size_t i = 0;
for (auto& d : data) {
  std::cout << i++ << ' ' << d << '\n';
}
```

C++ 20

```
for (std::size_t i = 0; auto const & d : data) {
  std::cout << i++ << ' ' << d << '\n';
}
```

Control structures: while loop

while loop syntax

```
while(condition) {
  statements;
}

do {
  statements;
} while(condition);
```

- Braces are optional if the body is a single statement

Control structures: while loop

while loop syntax

```
while(condition) {
  statements;
}

do {
  statements;
} while(condition);
```

- Braces are optional if the body is a single statement

Bad example

```
while (n != 1)
  if (0 == n%2) n /= 2;
  else n = 3 * n + 1;
```

Control structures: jump statements

break	Exits the loop and continues after it
continue	Goes immediately to next loop iteration
return	Exits the current function
goto	Can jump anywhere inside a function, avoid!

Control structures: jump statements

break	Exits the loop and continues after it
continue	Goes immediately to next loop iteration
return	Exits the current function
goto	Can jump anywhere inside a function, avoid!

Bad example

```
while (1) {
  if (n == 1) break;
  if (0 == n%2) {
    std::cout << n << '\n';
    n /= 2;
    continue;
  }
  n = 3 * n + 1;
}
```

Control structures

Exercise: Control structures

Familiarise yourself with different kinds of control structures.
Re-implement them in different ways.

- Go to `exercises/control`
- Look at `control.cpp`
- Compile it (`make`) and run the program (`./control`)
- Work on the tasks that you find in `README.md`

Headers and interfaces

2 Language basics
- Core syntax and types
- Arrays and Pointers
- Scopes / namespaces
- Class and enum types
- References
- Functions
- Operators
- Control structures
- Headers and interfaces
- Auto keyword

Headers and interfaces

Interface

Set of declarations defining some functionality

- Put in a so-called "header file"
- The implementation exists somewhere else

Header: hello.hpp

```
void printHello();
```

Usage: myfile.cpp

```
#include "hello.hpp"
int main() {
  printHello();
}
```

Preprocessor


```
// file inclusion
#include "hello.hpp"
// macro constants and function-style macros
#define MY_GOLDEN_NUMBER 1746
#define CHECK_GOLDEN(x) if ((x) != MY_GOLDEN_NUMBER) \
  std::cerr << #x " was not the golden number\n";
// compile time or platform specific configuration
#if defined(USE64BITS) || defined(__GNUG__)
  using myint = std::uint64_t;
#elif
  using myint = std::uint32_t;
#endif
```

Preprocessor


```
// file inclusion
#include "hello.hpp"
// macro constants and function-style macros
#define MY_GOLDEN_NUMBER 1746
#define CHECK_GOLDEN(x) if ((x) != MY_GOLDEN_NUMBER) \
  std::cerr << #x " was not the golden number\n";
// compile time or platform specific configuration
#if defined(USE64BITS) || defined(__GNUG__)
  using myint = std::uint64_t;
#elif
  using myint = std::uint32_t;
#endif
```

Good practice: Use preprocessor only in very restricted cases

- Conditional inclusion of headers
- Customization for specific compilers/platforms

Header include guards

Problem: redefinition by accident

- Headers may define new names (e.g. types)
- Multiple (transitive) inclusions of a header would define those names multiple times, which is a compile error
- Solution: guard the content of your headers!

Include guards

```
#ifndef MY_HEADER_INCLUDED
#define MY_HEADER_INCLUDED
... // header file content
#endif
```

Pragma once (non-standard)

```
#pragma once
... // header file content
```

Header / source separation

Good practice: Headers and source files

- Headers should contain declarations of functions / classes
  - Only create them if interface is used somewhere else
- Might be included/compiled many times
- Good to keep them short
- Minimise `#include` statements
- Put long code in implementation files. Exceptions:
  - Short functions
  - Templates and constexpr functions

Auto keyword

2 Language basics
- Core syntax and types
- Arrays and Pointers
- Scopes / namespaces
- Class and enum types
- References
- Functions
- Operators
- Control structures
- Headers and interfaces
- Auto keyword

Auto keyword

Reason of being

- Many type declarations are redundant
- They are often a source for compiler warnings and errors
- Using auto prevents unwanted/unnecessary type conversions

```
std::vector<int> v;
float a = v[3];     // conversion intended?
int b = v.size();   // bug? unsigned to signed
```

Auto keyword

Reason of being

- Many type declarations are redundant
- They are often a source for compiler warnings and errors
- Using auto prevents unwanted/unnecessary type conversions

```
std::vector<int> v;
float a = v[3];     // conversion intended?
int b = v.size();   // bug? unsigned to signed
```

Practical usage

```
std::vector<int> v;
auto a = v[3];
const auto b = v.size(); // std::size_t
int sum{0};
for (auto n : v) { sum += n; }
```

Loops, references, auto

Exercise: Loops, references, auto

Familiarise yourself with range-based for loops and references

- Go to `exercises/loopsRefsAuto`
- Look at `loopsRefsAuto.cpp`
- Compile it (`make`) and run the program (`./loopsRefsAuto`)
- Work on the tasks that you find in `loopsRefsAuto.cpp`

Object orientation (OO)

1. History and goals
2. Language basics
3. Object orientation (OO)
   - Objects and Classes
   - Inheritance
   - Constructors/destructors
   - Static members
   - Allocating objects
   - Advanced OO
   - Operator overloading
   - Function objects
4. Core modern C++
5. Useful tools

Objects and Classes

3 Object orientation (OO)

- Objects and Classes
- Inheritance
- Constructors/destructors
- Static members
- Allocating objects
- Advanced OO
- Operator overloading
- Function objects

What are classes and objects

Classes (or "user-defined types")

C structs on steroids

- with inheritance
- with access control
- including methods (aka. member functions)

Objects

- instances of classes

A class encapsulates state and behavior of "something"

- shows an interface
- provides its implementation
  - status, properties
  - possible interactions
  - construction and destruction

My first class


```
1  struct MyFirstClass {
2    int a;
3    void squareA() {
4      a *= a;
5    }
6    int sum(int b) {
7      return a + b;
8    }
9  };
10
11 MyFirstClass myObj;
12 myObj.a = 2;
13
14 // let's square a
15 myObj.squareA();
```

MyFirstClass

int a;
void squareA();
int sum(int b);

Separating the interface

Header: MyClass.hpp

```
#pragma once
struct MyClass {
  int a;
  void squareA();
};
```

User 1: main.cpp

```
#include "MyClass.hpp"
int main() {
  MyClass mc;
  ...
}
```

Implementation: MyClass.cpp

```
#include "MyClass.hpp"
void MyClass::squareA() {
  a *= a;
}
```

User 2: fun.cpp

```
#include "MyClass.hpp"
void f(MyClass& mc) {
  mc.squareA();
}
```

Implementing methods

Good practice: Implementing methods

- usually in .cpp, outside of class declaration
- using the class name as "namespace"
- short member functions can be in the header
- some functions (templates, `constexpr`) must be in the header

```
#include "MyFirstClass.hpp"

void MyFirstClass::squareA() {
  a *= a;
}
int MyFirstClass::sum(int b) {
  return a + b;
}
```

Method overloading

The rules in C++

- overloading is authorized and welcome
- signature is part of the method identity
- but not the return type

```
struct MyFirstClass {
  int a;
  int sum(int b);
  int sum(int b, int c);
};

int MyFirstClass::sum(int b) { return a + b; }

int MyFirstClass::sum(int b, int c) {
  return a + b + c;
}
```

Inheritance

3 Object orientation (OO)
- Objects and Classes
- Inheritance
- Constructors/destructors
- Static members
- Allocating objects
- Advanced OO
- Operator overloading
- Function objects

First inheritance


```
struct MyFirstClass {
  int a;
  void squareA() { a *= a; }
};
struct MySecondClass :
  MyFirstClass {
  int b;
  int sum() { return a + b; }
};

MySecondClass myObj2;
myObj2.a = 2;
myObj2.b = 5;
myObj2.squareA();
int i = myObj2.sum(); // i = 9
```



First inheritance


```
struct MyFirstClass {
  int a;
  void squareA() { a *= a; }
};
struct MySecondClass :
  MyFirstClass {
  int b;
  int sum() { return a + b; }
};

MySecondClass myObj2;
myObj2.a = 2;
myObj2.b = 5;
myObj2.squareA();
int i = myObj2.sum(); // i = 9
```

Memory layout



Managing access to class members

public / private keywords

`private` allows access only within the class

`public` allows access from anywhere

- The default for `class` is `private`
- The default for `struct` is `public`

```
class MyFirstClass {
public:
  void setA(int x);
  int getA();
  void squareA();
private:
  int a;
};
```

```
MyFirstClass obj;
obj.a = 5;    // error !
obj.setA(5); // ok
obj.squareA();
int b = obj.getA();
```

Managing access to class members

public / private keywords

`private` allows access only within the class

`public` allows access from anywhere

- The default for `class` is `private`
- The default for `struct` is `public`

```
class MyFirstClass {
public:
  void setA(int x);
  int getA();
  void squareA();
private:
  int a;
};
```

```
MyFirstClass obj;
obj.a = 5;    // error !
obj.setA(5); // ok
obj.squareA();
int b = obj.getA();
```

This breaks MySecondClass !

Managing access to class members(2)

Solution is protected keyword

Gives access to classes inheriting from base class

```
class MyFirstClass {
public:
  void setA(int a);
  int getA();
  void squareA();
protected:
  int a;
};
```

```
class MySecondClass :
  public MyFirstClass {
public:
  int sum() {
    return a + b;
  }
private:
  int b;
};
```

Managing inheritance privacy

Inheritance can be public, protected or private

It influences the privacy of inherited members for external code.
The code of the class itself is not affected

`public`	privacy of inherited members remains unchanged
`protected`	inherited public members are seen as protected
`private`	all inherited members are seen as private this is the default for classes if nothing is specified

Managing inheritance privacy

Inheritance can be public, protected or private

It influences the privacy of inherited members for external code. The code of the class itself is not affected

`public`	privacy of inherited members remains unchanged
`protected`	inherited public members are seen as protected
`private`	all inherited members are seen as private this is the default for classes if nothing is specified

Net result for external code

- only public members of public inheritance are accessible

Net result for code in derived classes

- only public and protected members of public and protected parents are accessible

Managing inheritance privacy - public




```
1  void funcSecond() {
2    int a = priv;    // Error
3    int b = prot;    // OK
4    int c = pub;     // OK
5  }
6  void funcThird() {
7    int a = priv;    // Error
8    int b = prot;    // OK
9    int c = pub;     // OK
10 }
11 void extFunc(MyThirdClass t) {
12   int a = t.priv; // Error
13   int b = t.prot; // Error
14   int c = t.pub;  // OK
15 }
```

Managing inheritance privacy - protected




```
1  void funcSecond() {
2    int a = priv;    // Error
3    int b = prot;    // OK
4    int c = pub;     // OK
5  }
6  void funcThird() {
7    int a = priv;    // Error
8    int b = prot;    // OK
9    int c = pub;     // OK
10 }
11 void extFunc(MyThirdClass t) {
12   int a = t.priv; // Error
13   int b = t.prot; // Error
14   int c = t.pub;  // Error
15 }
```

Managing inheritance privacy - private




```
1  void funcSecond() {
2    int a = priv;    // Error
3    int b = prot;    // OK
4    int c = pub;     // OK
5  }
6  void funcThird() {
7    int a = priv;    // Error
8    int b = prot;    // Error
9    int c = pub;     // Error
10 }
11 void extFunc(MyThirdClass t) {
12   int a = t.priv; // Error
13   int b = t.prot; // Error
14   int c = t.pub;  // Error
15 }
```

Constructors/destructors

3 Object orientation (OO)
- Objects and Classes
- Inheritance
- Constructors/destructors
- Static members
- Allocating objects
- Advanced OO
- Operator overloading
- Function objects

Class constructors and destructors

Concept

- special functions called when building/destroying an object
- a class can have several constructors, but only one destructor
- the constructors have the same name as the class
- same for the destructor with a leading ~

```
class C {
public:
  C();
  C(int a);
  ~C();
  ...
protected:
  int a;
};
```

```
// note: special notation for
// initialization of members
C::C() : a(0) {}

C::C(int a) : a(a) {}

C::~C() {}
```

Class constructors and destructors


```
class Vector {
public:
  Vector(int n);
  ~Vector();
  void setN(int n, int value);
  int getN(int n);
private:
  int len;
  int* data;
};
Vector::Vector(int n) : len(n) {
  data = new int[n];
}
Vector::~Vector() {
  delete[] data;
}
```

Constructors and inheritance


```
1  struct First {
2    int a;
3    First() {} // leaves a uninitialized
4    First(int a) : a(a) {}
5  };
6  struct Second : First {
7    int b;
8    Second();
9    Second(int b);
10   Second(int a, int b);
11 };
12 Second::Second() : First(), b(0) {}
13 Second::Second(int b) : b(b) {} // First() implicitly
14 Second::Second(int a, int b) : First(a), b(b) {}
```

Copy constructor

Concept

- special constructor called for replicating an object
- takes a single parameter of type `const &` to class
- provided by the compiler if not declared by the user
- in order to forbid copy, use `= delete` (see next slides)
  - or private copy constructor with no implementation in C++ 98

Copy constructor

Concept

- special constructor called for replicating an object
- takes a single parameter of type `const &` to class
- provided by the compiler if not declared by the user
- in order to forbid copy, use `= delete` (see next slides)
  - or private copy constructor with no implementation in C++ 98

```
struct C {
  C();
  C(const C &other);
};
```

Copy constructor

Concept

- special constructor called for replicating an object
- takes a single parameter of type `const &` to class
- provided by the compiler if not declared by the user
- in order to forbid copy, use `= delete` (see next slides)
  - or private copy constructor with no implementation in C++ 98

```
struct C {
  C();
  C(const C &other);
};
```

Good practice: The rule of 3/5 (C++ 98/11) - cppreference

if a class needs a custom destructor, a copy/move constructor or a copy/move assignment operator, it should have all three/five.

Class Constructors and Destructors


```
class Vector {
public:
  Vector(int n);
  Vector(const Vector &other);
  ~Vector();
private:
  int len; int* data;
};
Vector::Vector(int n) : len(n) {
  data = new int[n];
}
Vector::Vector(const Vector &other) : len(other.len) {
  data = new int[len];
  std::copy(other.data, other.data + len, data);
}
Vector::~Vector() { delete[] data; }
```

Explicit unary constructor

Concept

- A constructor with a single non-default parameter can be used by the compiler for an implicit conversion.

Example - godbolt

```
void print(const Vector & v) {
  std::cout << "printing v elements...\n";
}

int main {
  // calls Vector::Vector(int n) to construct a Vector
  // then calls print with that Vector
  print(3);
};
```

Explicit unary constructor

Concept

- The keyword **explicit** forbids such implicit conversions.
- It is recommended to use it systematically, except in special cases.

```
class Vector {
public:
  explicit Vector(int n);
  Vector(const Vector &other);
  ~Vector();
  ...
};
```

Defaulted Constructor

Idea

- avoid empty default constructors like `ClassName() {}`
- declare them as `= default`

Details

- without a user-defined constructor, a default one is provided
- any user-defined constructor disables the default one
- but the default one can be requested explicitly
- rule can be more subtle depending on data members

Practically

```
Class() = default; // provide default if possible
Class() = delete;  // disable default constructor
```

Delegating constructor

Idea

- avoid replication of code in several constructors
- by delegating to another constructor, in the initialization list

Practically

```
struct Delegate {
  int m_i;
  Delegate(int i) : m_i(i) {
    ... complex initialization ...
  }
  Delegate() : Delegate(42) {}
};
```

Constructor inheritance

Idea

- avoid having to redeclare parent's constructors
- by stating that we inherit all parent constructors
- derived class can add more constructors

Practically

```
struct Base {
  Base(int a);              // ctor 1
};
struct Derived : Base {
  using Base::Base;
  Derived(int a, int b); // ctor 2
};
Derived d{5};     // calls ctor 1
Derived d{5, 6}; // calls ctor 2
```

Member initialization

Idea

- avoid redefining same default value for members n times
- by defining it once at member declaration time

Practically

```
struct Base {
  int a{5}; // also possible: int a = 5;
  Base() = default;
  Base(int _a) : a(_a) {}
};
struct Derived : Base {
  int b{6};
  using Base::Base;
};
Derived d1;     // a = 5, b = 6
Derived d2{7}; // a = 7, b = 6
```

Calling constructors

After object declaration, arguments within {}

```
struct A {
  int a;
  float b;
  A();
  A(int);
  A(int, int);
};

A a{1,2};     // A::A(int, int)
A a{1};       // A::A(int)
A a{};        // A::A()
A a;          // A::A()
A a = {1,2}; // A::A(int, int)
```

Calling constructors the old way

Arguments are given within (), aka C++ 98 nightmare

```
struct A {
  int a;
  float b;
  A();
  A(int);
  A(int, int);
};

A a(1,2);     // A::A(int, int)
A a(1);       // A::A(int)
A a();        // declaration of a function!
A a;          // A::A()
A a = (1,2); // A::A(int), comma operator!
A a = {1,2}; // not allowed
```

Constructing arrays and vectors

List of items given within {}

```
int ip[3]{1,2,3};
int* ip = new int[3]{1,2,3}; // not allowed in C++98
std::vector<int> v{1,2,3};   // same
```

Static members

3 Object orientation (OO)
- Objects and Classes
- Inheritance
- Constructors/destructors
- Static members
- Allocating objects
- Advanced OO
- Operator overloading
- Function objects

Static members

Concept

- members attached to a class rather than to an object
- usable with or without an instance of the class
- identified by the `static` keyword

Static.hpp

```
class Text {
public:
  static std::string upper(std::string);
private:
  static int callsToUpper; // add `inline` in C++17
};
```

Static members

Concept

- members attached to a class rather than to an object
- usable with or without an instance of the class
- identified by the `static` keyword

Static.cpp

```
#include "Static.hpp"
int Text::callsToUpper = 0; // required before C++17

std::string Text::upper(std::string lower) {
  callsToUpper++;
  // convert lower to upper case
  // return ...;
}
std::string uppers = Text::upper("my text");
// now Text::callsToUpper is 1
```

Allocating objects

3 Object orientation (OO)
- Objects and Classes
- Inheritance
- Constructors/destructors
- Static members
- Allocating objects
- Advanced OO
- Operator overloading
- Function objects

Process memory organization

4 main areas

the code segment for the machine code of the executable

the data segment for global variables

the heap for dynamically allocated variables

the stack for parameters of functions and local variables

Memory layout



The Stack

Main characteristics

- allocation on the stack stays valid for the duration of the current scope. It is destroyed when it is popped off the stack.
- memory allocated on the stack is known at compile time and can thus be accessed through a variable.
- the stack is relatively small, it is not a good idea to allocate large arrays, structures or classes
- each thread in a process has its own stack
  - allocations on the stack are thus "thread private"
  - and do not introduce any thread safety issues

Object allocation on the stack

On the stack

- objects are created on variable definition (constructor called)
- objects are destructed when out of scope (destructor is called)

```
int f() {
  MyFirstClass a{3}; // constructor called
  ...
} // destructor called

int g() {
  MyFirstClass a; // default constructor called
  ...
}  // destructor called
```

The Heap

Main characteristics

- Allocated memory stays allocated until it is specifically deallocated
  - beware memory leaks
- Dynamically allocated memory must be accessed through pointers
- large arrays, structures, or classes should be allocated here
- there is a single, shared heap per process
  - allows to share data between threads
  - introduces race conditions and thread safety issues!

Object allocation on the heap

On the heap

- objects are created by calling **new** (constructor is called)
- objects are destructed by calling **delete** (destructor is called)

```
int f() {
  // default constructor called
  MyFirstClass *a = new MyFirstClass;
  delete a; // destructor is called
}
int g() {
  // constructor called
  MyFirstClass *a = new MyFirstClass{3};
} // memory leak !!!
```

Good practice: Prefer smart pointers over new/delete

Prefer smart pointers to manage objects (discussed later)

Array allocation on the heap

Arrays on the heap

- arrays of objects are created by calling `new[]`
  default constructor is called for each object of the array
- arrays of object are destructed by calling `delete[]`
  destructor is called for each object of the array

```
int f() {
  // default constructor called 10 times
  MyFirstClass *a = new MyFirstClass[10];
  ...
  delete[] a; // destructor called 10 times
}
```

Good practice: Prefer containers over new-ed arrays

Prefer containers to manage collections of objects (discussed later)

Advanced OO

3 Object orientation (OO)

- Objects and Classes
- Inheritance
- Constructors/destructors
- Static members
- Allocating objects
- Advanced OO
- Operator overloading
- Function objects

this keyword

How to know an object's address?

- Sometimes we need the address of the current object
- Or we need to pass our address / a reference to a different entity (for example to implement operators, see later)
- All class methods can use the keyword **this**
  - It returns the address of the current object
  - Its type is T* in the methods of a class T

```
struct S {
  int a,b;
  // these two are the same:
  int getB() { return b; }          // 5
  int getB() { return this->b; } // 5
  void testAddress() {
    S* addr = this; // 0x3000
  }
} s{2,5};
```

Memory layout



Polymorphism

the concept

- objects actually have multiple types simultaneously
- and can be used as any of them

```
Polygon p;

int f(Drawable & d) {...}
f(p);  //ok

try {
  throw p;
} catch (Shape & e) {
  // will be caught
}
```



Polymorphism

the concept

- objects actually have multiple types simultaneously
- and can be used as any of them

```
Polygon p;

int f(Drawable & d) {...}
f(p);  //ok

try {
  throw p;
} catch (Shape & e) {
  // will be caught
}
```

Memory layout



Polymorphism

the concept

- objects actually have multiple types simultaneously
- and can be used as any of them

```
Polygon p;

int f(Drawable & d) {...}
f(p);  //ok

try {
  throw p;
} catch (Shape & e) {
  // will be caught
}
```

Memory layout



Polymorphism

the concept

- objects actually have multiple types simultaneously
- and can be used as any of them

```
Polygon p;

int f(Drawable & d) {...}
f(p);  //ok

try {
  throw p;
} catch (Shape & e) {
  // will be caught
}
```

Memory layout



Inheritance privacy and polymorphism

Only public base classes are visible to outside code

- private and protected bases are not
- this may restrict usage of polymorphism

```
Polygon p;

int f(Drawable & d) {...}
f(p);  // Not ok anymore

try {
  throw p;
} catch (Shape & e) {
  // ok, will be caught
}
```



Method overriding

the idea

- a method of the parent class can be replaced in a derived class
- but which one is called?

```
Polygon p;
p.draw(); // ?

Shape & s = p;
s.draw(); // ?
```



Virtual methods

the concept

- methods can be declared `virtual`
- for these, the most derived object's implementation is used (i.e. the dynamic type behind a pointer/reference)
- for non-virtual methods, the static type of the variable decides

Virtual methods

the concept

- methods can be declared `virtual`
- for these, the most derived object's implementation is used (i.e. the dynamic type behind a pointer/reference)
- for non-virtual methods, the static type of the variable decides

```
Polygon p;
p.draw(); // Polygon.draw

Shape & s = p;
s.draw(); // Drawable.draw
```



Virtual methods

the concept

- methods can be declared `virtual`
- for these, the most derived object's implementation is used (i.e. the dynamic type behind a pointer/reference)
- for non-virtual methods, the static type of the variable decides

```
Polygon p;
p.draw(); // Polygon.draw

Shape & s = p;
s.draw(); // Polygon.draw
```



Virtual methods - implications

Mechanics

- virtual methods are dispatched at run time
  - while non-virtual methods are bound at compile time
- they also imply extra storage and an extra indirection
  - practically, the object stores a pointer to the correct method
  - in a so-called "virtual table" ("vtable")

Consequences

- virtual methods are "slower" than standard ones
- and they can rarely be inlined
- templates are an alternative for performance-critical cases

override keyword

Principle

- when overriding a virtual method
- the `override` keyword should be used
- the `virtual` keyword is then optional

Practically

```
struct Base {
  virtual void some_func(float);
};
struct Derived : Base {
  void some_func(float) override;
};
```

Why was override keyword introduced?

To detect the mistake in the following code :

Without override (C++ 98)

```
struct Base {
  virtual void some_func(float);
};
struct Derived : Base {
  void some_func(double); // oops !
};
```

- with `override`, you would get a compiler error
- if you forget `override` when you should have it, you get a compiler warning

Pure Virtual methods

Concept

- unimplemented methods that must be overridden
- marked by = 0 in the declaration
- makes their class abstract
- only non-abstract classes can be instantiated

Pure Virtual methods

Concept

- unimplemented methods that must be overridden
- marked by = 0 in the declaration
- makes their class abstract
- only non-abstract classes can be instantiated

```
// Error : abstract class
Shape s;

// ok, draw has been implemented
Polygon p;

// Shape type still usable
Shape & s = p;
s.draw();
```



Polymorphism and destruction

Owning base pointers

We sometimes need to maintain owning pointers to base classes:

```
struct Drawable {
    virtual void draw() = 0;
};
Drawable* getImpl();

Drawable* p = getImpl();
p->draw();
delete p;
```

- What happens when `p` is deleted?
- What if a class deriving from `Drawable` has a destructor?

Polymorphism and destruction

Owning base pointers

We sometimes need to maintain owning pointers to base classes:

```
struct Drawable {
    virtual void draw() = 0;
};
std::unique_ptr<Drawable> getImpl(); // better API

auto p = getImpl();
p->draw();
```

- What happens when p is deleted?
- What if a class deriving from Drawable has a destructor?

Polymorphism and destruction

Virtual destructors

- We can mark a destructor as `virtual`
- This selects the right destructor based on the runtime type

```
struct Drawable {
    virtual ~Drawable() = default;
    virtual void draw() = 0;
};
Drawable* p = getImpl(); // returns derived obj.
p->draw();
delete p; // dynamic dispatch to right destructor
```

Good practice: Virtual destructors

If you expect users to inherit from your class and override methods (i.e. use your class polymorphically), declare its destructor `virtual`

Pure Abstract Class aka Interface

Definition of pure abstract class

- a class that has
  - no data members
  - all its methods pure virtual
  - a `virtual` destructor
- the equivalent of an Interface in Java

```
struct Drawable {
  virtual ~Drawable()
                  = default;
  virtual void draw() = 0;
}
```

Drawable
virtual void draw() = 0;

Overriding overloaded methods

Concept

- overriding an overloaded method will hide the others
- unless you inherit them using **using**

```
struct BaseClass {
  virtual int foo(std::string);
  virtual int foo(int);
};
struct DerivedClass : BaseClass {
  using BaseClass::foo;
  int foo(std::string) override;
};
DerivedClass dc;
dc.foo(4);      // error if no using
```

Polymorphism

Exercise: Polymorphism

- go to `exercises/polymorphism`
- look at the code
- open trypoly.cpp
- create a Pentagon, call its perimeter method
- create a Hexagon, call its perimeter method
- create a Hexagon, call its parent's perimeter method
- retry with virtual methods

Multiple Inheritance

Concept

- one class can inherit from multiple parents




```
class TextBox :
  public Rectangle, Text {
  // inherits from both
  // publicly from Rectangle
  // privately from Text
}
```

The diamond shape

Definition

- situation when one class inherits several times from a given grand parent

Problem

- are the members of the grand parent replicated?



Virtual inheritance

Solution

- inheritance can be `virtual` or not
  - `virtual` inheritance will "share" parents
  - standard inheritance will replicate them
- most derived class will call the virtual base class's constructor

```
class Text : public virtual Drawable {...};
class Rectangle : public virtual Drawable {...};
```





Multiple inheritance advice

Good practice: Avoid multiple inheritance

- Except for inheriting from interfaces (=no data members)
- And for rare special cases

Absolutely avoid diamond-shape inheritance

- This is a sign that your architecture is not correct
- In case you are tempted, think twice and change your mind

Virtual inheritance

Exercise: Virtual inheritance

- go to `exercisescode/virtual_inheritance`
- look at the code
- open trymultiherit.cpp
- create a TextBox and call draw
- Fix the code to call both draws by using types
- retry with virtual inheritance

Operator overloading

3 Object orientation (OO)
- Objects and Classes
- Inheritance
- Constructors/destructors
- Static members
- Allocating objects
- Advanced OO
- Operator overloading
- Function objects

Operator overloading example


```
struct Complex {
  float m_real, m_imaginary;
  Complex(float real, float imaginary);
  Complex operator+(const Complex& other) {
    return Complex(m_real + other.m_real,
                   m_imaginary + other.m_imaginary);
  }
};

Complex c1{2, 3}, c2{4, 5};
Complex c3 = c1 + c2; // (6, 8)
```

Operator overloading

Defining operators for a class

- implemented as a regular method
  - either inside the class, as a member function
  - or outside the class (not all)
- with a special name (replace @ by operators from below)

Expression	As member	As non-member
@a	(a).operator@()	operator@(a)
a@b	(a).operator@(b)	operator@(a,b)
a=b	(a).operator=(b)	cannot be non-member
a(b...)	(a).operator()(b...)	cannot be non-member
a[b]	(a).operator[](b)	cannot be non-member
a->	(a).operator->()	cannot be non-member
a@	(a).operator@(0)	operator@(a,0)

```
possible operators: + - * / % ^ & | ~ ! = < >
    += -= *= /= %= ^= &= |= << >> >>= <<=
    == != <= >= <=> && || ++ -- , ->* -> () []
```

Why have non-member operators?

Symmetry

```
struct Complex {
  float m_real, m_imaginary;
  Complex operator+(float other) {
    return Complex(m_real + other, m_imaginary);
  }
};
Complex c1{2.f, 3.f};
Complex c2 = c1 + 4.f;  // ok
Complex c3 = 4.f + c1;  // not ok !!
```

Why have non-member operators?

Symmetry

```
struct Complex {
  float m_real, m_imaginary;
  Complex operator+(float other) {
    return Complex(m_real + other, m_imaginary);
  }
};
Complex c1{2.f, 3.f};
Complex c2 = c1 + 4.f;  // ok
Complex c3 = 4.f + c1;  // not ok !!
Complex operator+(float a, const Complex& obj) {
  return Complex(a + obj.m_real, obj.m_imaginary);
}
```

Other reason to have non-member operators?

Extending existing classes

```
struct Complex {
  float m_real, m_imaginary;
  Complex(float real, float imaginary);
};

std::ostream& operator<<(std::ostream& os,
                         const Complex& obj) {
  os << "(" << obj.m_real << ", "
             << obj.m_imaginary << ")";
  return os;
}
Complex c1{2.f, 3.f};
std::cout << c1 << std::endl; // Prints '(2, 3)'
```

Friend declarations

Concept

- Functions/classes can be declared **friend** within a class scope
- They gain access to all private/protected members
- Useful for operators such as a + b
- Don't abuse friends to go around a wrongly designed interface
- Avoid unexpected modifications of class state in a friend

operator+ as a friend

```
class Complex {
  float m_r, m_i;
  friend Complex operator+(Complex const & a, Complex const & b);
public:
  Complex ( float r, float i ) : m_r(r), m_i(i) {}
};
Complex operator+(Complex const & a, Complex const & b) {
  return Complex{ a.m_r+b.m_r, a.m_i+b.m_i };
}
```

Operators

Exercise: Operators

Write a simple class representing a fraction and pass all tests

- go to `exercises/operators`
- look at `operators.cpp`
- inspect `main` and complete the implementation of `class Fraction` step by step
- you can comment out parts of `main` to test in between

Function objects

3 Object orientation (OO)
- Objects and Classes
- Inheritance
- Constructors/destructors
- Static members
- Allocating objects
- Advanced OO
- Operator overloading
- Function objects

Function objects

Concept

- also known as functors (no relation to functors in math)
- a class that implements `operator()`
- allows to use objects in place of functions
- with constructors and data members

```
struct Adder {
  int m_increment;
  Adder(int increment) : m_increment(increment) {}
  int operator()(int a) { return a + m_increment; }
};
Adder inc1{1}, inc10{10};
int i = 3;
int j = inc1(i);  // 4
int k = inc10(i); // 13
int l = Adder{25}(i); // 28
```

Function objects

Function objects as function arguments - godbolt

```
int count_if(const auto& range, auto predicate) {
  int count = 0;                    // ↑ template (later)
  for (const auto& e : range)
    if (predicate(e)) count++;
  return count;
}
struct IsBetween {
  int lower, upper;
  bool operator()(int value) const {
    return lower < value && value < upper;
  }
};
int arr[]{1, 2, 3, 4, 5, 6, 7};
std::cout << count_if(arr, IsBetween{2, 6}); // 3
// prefer: std::ranges::count_if
```

Core modern C++

1 History and goals

2 Language basics

3 Object orientation (OO)

4 Core modern C++

- Constness
- Exceptions
- Templates
- Lambdas
- The STL
- RAII and smart pointers

5 Useful tools

Constness

4 Core modern C++
- Constness
- Exceptions
- Templates
- Lambdas
- The STL
- RAII and smart pointers

Constness

The const keyword

- indicates that the element to the left is constant
  - when nothing on the left, applies to the right
- this element won't be modifiable in the future
- this is all checked at compile time

```
int const i = 6;
const int i = 6; // equivalent

// error: i is constant
i = 5;

auto const j = i; // works with auto
```

Constness and pointers


```
int a = 1, b = 2;

int const *i = &a; // pointer to const int
*i = 5; // error, int is const
i = &b; // ok, pointer is not const

int * const j = &a; // const pointer to int
*j = 5; // ok, value can be changed
j = &b; // error, pointer is const

int const * const k = &a; // const pointer to const int
*k = 5; // error, value is const
k = &b; // error, pointer is const

int const & l = a; // reference to const int
l = b; // error, reference is const

int const & const l = a; // compile error
```

Member function constness

The const keyword for member functions

- indicates that the function does not modify the object
- in other words, **this** is a pointer to a constant object

```
struct Example {
  void foo() const {
    // type of 'this' is 'Example const*'
    data = 0; // Error: member function is const
  }
  void foo() { // ok, overload
    data = 1;  // ok, 'this' is 'Example*'
  }
  int data;
};
Example const e1; e1.foo(); // calls     const foo
Example       e2; e2.foo(); // calls non-const foo
```

Member function constness

Constness is part of the type

- T const and T are different types
- but: T is automatically converted to T const when needed

```
void change(int & a);
void read(int const & a);

int a = 0;
int const b = 0;

change(a); // ok
change(b); // error
read(a);   // ok
read(b);   // ok
```

constness

Exercise: Constness

- go to `exercises/constness`
- open constplay.cpp
- try to find out which lines won't compile
- check your guesses by compiling for real

Exceptions

4 Core modern C++

- Constness
- Exceptions
- Templates
- Lambdas
- The STL
- RAII and smart pointers

Exceptions

Purpose

- to handle *exceptional* events that happen rarely
- and cleanly jump to a place where the error can be handled

In practice

- add an exception handling block with **try** ... **catch**
  - when exceptions are possible *and can be handled*
- throw an exception using **throw**
  - when a function cannot proceed or recover internally

```
try {
  process_data(f);
} catch (const
  std::out_of_range& e) {
  std::cerr << e.what();
}
```

```
void process_data(file &f) {
  ...
  if (i >= buffer.size())
    throw std::out_of_range{
      "buf overflow"};
}
```

Exceptions

Throwing exceptions

- objects of any type can be thrown (even e.g. `int`)

Good practice: Throwing exceptions

- prefer throwing standard exception classes
- throw objects by value

```
#include <stdexcept>
void process_data(file& f) {
  if (!f.open())
    throw std::invalid_argument{"stream is not open"};
  auto header = read_line(f); // may throw an IO error
  if (!header.starts_with("BEGIN"))
    throw std::runtime_error{"invalid file content"};
  std::string body(f.size()); // may throw std::bad_alloc
  ...
}
```

Exceptions

Standard exceptions

- `std::exception`, defined in header `<exception>`
  - Base class of all standard exceptions
  - Get error message: `virtual const char* what() const;`
  - Please derive your own exception classes from this one
- From `<stdexcept>`:
  - `std::runtime_error`, `std::logic_error`, `std::out_of_range`, `std::invalid_argument`, ...
  - Store a string: `throw std::runtime_error{"msg"}`
  - You should use these the most
- `std::bad_alloc`, defined in header `<new>`
  - Thrown by standard allocation functions (e.g. `new`)
  - Signals failure to allocate
  - Carries no message
- ...

Exceptions

Catching exceptions

- a catch clause catches exceptions of the same or derived type
- multiple catch clauses will be matched in order
- if no catch clause matches, the exception propagates
- if the exception is never caught, `std::terminate` is called

```
try {
  process_data(f);
} catch (const std::invalid_argument& e) {
  bad_files.push_back(f);
} catch (const std::exception& e) {
  std::cerr << "Failed to process file: " << e.what();
}
```

Good practice: Catching exceptions

- Catch exceptions by const reference

Exceptions

Rethrowing exceptions

- a caught exception can be rethrown inside the catch handler
- useful when we want to act on an error, but cannot handle and want to propagate it

```
try {
  process_data(f);
} catch (const std::bad_alloc& e) {
  std::cerr << "Insufficient memory for " << f.name();
  throw; // rethrow
}
```

Exceptions

Catching everything

- sometimes we need to catch all possible exceptions
- e.g. in `main`, a thread, a destructor, interfacing with C, ...

```
1
2  try {
3    callUnknownFramework();
4  } catch(const std::exception& e) {
5    // catches std::exception and all derived types
6    std::cerr << "Exception: " << e.what() << std::endl;
7  } catch(...) {
8    // catches everything else
9    std::cerr << "Unknown exception type" << std::endl;
10 }
```

Exceptions

Stack unwinding

- all objects on the stack between a **throw** and the matching **catch** are destructed automatically
- this should cleanly release intermediate resources
- make sure you are using the RAII idiom for your own classes

```
class C { ... };
void f() {
  C c1;
  throw exception{};
    // start unwinding
  C c2; // not run
}
void g() {
  C c3; f();
}
int main() {
  try {
    C c4;
    g();
    cout << "done"; // not run
  } catch(const exception&) {
    // c1, c3 and c4 have been
    // destructed
  }
}
```

Exceptions

Good practice: Exceptions

- use exceptions for *unlikely* runtime errors outside the program's control
  - bad inputs, files unexpectedly not found, DB connection, ...
- *don't* use exceptions for logic errors in your code
  - use `assert` and tests
- *don't* use exceptions to provide alternative/skip return values
  - you can use `std::optional`, `std::variant` or `std::expected` (C++ 23)
  - avoid using the global C-style `errno`
- never throw in destructors
- see also the C++ core guidelines and the ISO C++ FAQ

Exceptions

A more illustrative example

- exceptions are very powerful when there is much code between the error and where the error is handled
- they can also rather cleanly handle different types of errors
- `try`/`catch` statements can also be nested

```
try {
  for (File const &f : files) {
    try {
      process_file(f);
    }
    catch (bad_file const & e) {
      ... // loop continues
    }
  }
} catch (bad_db const & e) {
  ... // loop aborted
}
```

```
void process_file(File const & file) {
  ...
  if (handle = open_file(file))
    throw bad_file(file.status());
  while (!handle) {
    line = read_line(handle);
    database.insert(line); // can throw
                           // bad_db
  }
}
```

Exceptions

Cost

- exceptions have little cost if no exception is thrown
  - they are recommended to report *exceptional* errors
- for performance, when error raising and handling are close, or errors occur often, prefer error codes or a dedicated class
- when in doubt about which error strategy is better, profile!

Avoid

```
for (string const &num: nums) {
  try {
    int i = convert(num); // can
                          // throw
    process(i);
  } catch (not_an_int const &e) {
    ... // log and continue
  }
}
```

Prefer

```
for (string const &num: nums) {
  optional<int> i = convert(num);
  if (i) {
    process(*i);
  } else {
    ... // log and continue
  }
}
```

noexcept specifier

noexcept

- a function with the `noexcept` specifier states that it guarantees to not throw an exception

```
int f() noexcept;
```

  - either no exceptions is thrown or they are handled internally
  - checked at compile time
  - allows the compiler to optimize around that knowledge
- a function with `noexcept(expression)` is only `noexcept` when `expression` evaluates to `true` at compile-time

```
int safe_if_8B() noexcept(sizeof(long)==8);
```

Good practice: noexcept

- Use `noexcept` on leaf functions where you know the behavior
- C++11 destructors are `noexcept` - never throw from them

Templates

4 Core modern C++

- Constness
- Exceptions
- Templates
- Lambdas
- The STL
- RAII and smart pointers

Templates

Concept

- The C++ way to write reusable code
  - like macros, but fully integrated into the type system
- Applicable to functions, classes and variables

```
template<typename T>
const T & max(const T &a, const T &b) {
  return b < a ? a : b;
}
template<typename T>
struct Vector {
  int m_len;
  T* m_data;
};
template <typename T>
std::size_t size = sizeof(T);
```

Templates

Warning

- they are compiled for each instantiation
- they need to be defined before used
  - so all template code must typically be in headers
  - or declared to be available externally (`extern template`)
- this may lead to longer compilation times and bigger binaries

```
1 template<typename T>
2 T func(T a) {
3   return a;
4 }
```

func(3) →

```
int func(int a) {
  return a;
}
```

func(5.2) →

```
double func(double a) {
  return a;
}
```

Templates

Template parameters

- can be types, values or other templates
- you can have several
- default values allowed starting at the last parameter

```
template<typename KeyType=int, typename ValueType=KeyType>
struct Map {
  void set(const KeyType &key, ValueType value);
  ValueType get(const KeyType &key);
  ...
};

Map<std::string, int> m1;
Map<float> m2;    // Map<float, float>
Map<> m3;         // Map<int, int>
Map m4;           // Map<int, int>, C++17
```

Template parameters

typename vs. class keyword

- for declaring a template type parameter, the **typename** and **class** keyword are semantically equivalent
- template template parameters require C++ 17 for **typename**

```
template<typename T>
T func(T a); // equivalent to:
template<class T>
T func(T a);

template<template<class> class C>
C<int> func(C<int> a); // equivalent to:
template<template<typename> class C>
C<int> func(C<int> a); // equivalent to:
template<template<typename> typename C> // C++17
C<int> func(C<int> a);
```

Template implementation


```
template<typename KeyType=int, typename ValueType=KeyType>
struct Map {
  // declaration and inline definition
  void set(const KeyType &key, ValueType value) {
    ...
  }
  // just declaration
  ValueType get(const KeyType &key);
};

// out-of-line definition
template<typename KeyType, typename ValueType>
ValueType Map<KeyType, ValueType>::get
   (const KeyType &key) {
  ...
}
```

Non-type template parameter C++ 98 / C++ 17 / C++ 20

template parameters can also be values

- integral types, pointer, enums in C++ 98
- auto in C++ 17
- literal types (includes floating points) in C++ 20

```
template<unsigned int N>
struct Polygon {
  float perimeter() {
    return 2 * N * std::sin(PI / N) * radius;
  }
  float radius;
};

Polygon<19> nonadecagon{3.3f};
```

Template specialization

Specialization

Templates can be specialized for given values of their parameter

```
template<typename F, unsigned int N>
struct Polygon { ... }; // primary template

template<typename F> // partial specialization
struct Polygon<F, 6> {
  F perimeter() { return 6 * radius; }
  F radius;
};
template<>           // full specialization
struct Polygon<int, 6> {
  int perimeter() { return 6 * radius; }
  int radius;
};
```

The full power of templates

Exercise: Templates

- go to `exercises/templates`
- look at the OrderedVector code
- compile and run playwithsort.cpp. See the ordering
- modify playwithsort.cpp and reuse OrderedVector with Complex
- improve OrderedVector to template the ordering
- test reverse ordering of strings (from the last letter)
- test order based on Manhattan distance with complex type
- check the implementation of Complex
- try ordering complex of complex

Lambdas

4 Core modern C++

- Constness
- Exceptions
- Templates
- Lambdas
- The STL
- RAII and smart pointers

Lambda expressions

Definition

A lambda expression is a function with no name

Lambda expressions

Definition

A lambda expression is a function with no name

Python example

```
data = [1,9,3,8,3,7,4,6,5]

# without lambdas
def isOdd(n):
  return n%2 == 1
print(filter(isOdd, data))

# with lambdas
print(filter(lambda n:n%2==1, data))
```

C++ Lambdas

Simplified syntax

```
auto f = [] (arguments) -> return_type {
  statements;
};
```

- The return type specification is optional
- f is an instance of a functor type, generated by the compiler

Usage example

```
int data[]{1,2,3,4,5};
auto f = [](int i) {
  std::cout << i << " squared is " << i*i << '\n';
};
for (int i : data) f(i);
```

Trailing function return type

An alternate way to specify a function's return type

```
int f(float a);                    // classic
auto f(float a) -> int;            // trailing
auto f(float a) { return 42; } // deduced, C++14
```

Trailing function return type

An alternate way to specify a function's return type

```
int f(float a);                    // classic
auto f(float a) -> int;            // trailing
auto f(float a) { return 42; } // deduced, C++14
```

When to use trailing return type

- Only way to specify return type for lambdas
- Allows to simplify inner type definition

```
class Equation {
  using ResultType = double;
  ResultType evaluate();
}
Equation::ResultType Equation::evaluate() {...}
auto Equation::evaluate() -> ResultType {...}
```

Capturing variables

Adaptable lambdas

- Adapt lambda's behaviour by accessing variables outside of it
- This is called "capture"

Capturing variables

Adaptable lambdas

- Adapt lambda's behaviour by accessing variables outside of it
- This is called "capture"

First attempt in C++

```
int increment = 3;
int data[]{1,9,3,8,3,7,4,6,5};
auto f = [](int x) { return x+increment; };
for(int& i : data) i = f(i);
```

Capturing variables

Adaptable lambdas

- Adapt lambda's behaviour by accessing variables outside of it
- This is called "capture"

First attempt in C++

```
int increment = 3;
int data[]{1,9,3,8,3,7,4,6,5};
auto f = [](int x) { return x+increment; };
for(int& i : data) i = f(i);
```

Error

```
error: 'increment' is not captured
  [](int x) { return x+increment; });
                                 ^
```

Capturing variables

The capture list

- local variables outside the lambda must be explicitly captured
  - unlike in Python, Java, C#, Rust, ...
- captured variables are listed within initial []

Capturing variables

The capture list

- local variables outside the lambda must be explicitly captured
  - unlike in Python, Java, C#, Rust, ...
- captured variables are listed within initial []

Example

```
int increment = 3;
int data[]{1,9,3,8,3,7,4,6,5};
auto f = [increment](int x) { return x+increment; };
for(int& i : data) i = f(i);
```

Default capture is by value

Code example

```
int sum = 0;
int data[]{1,9,3,8,3,7,4,6,5};
auto f = [sum](int x) { sum += x; };
for (int i : data) f(i);
```

Default capture is by value

Code example

```
int sum = 0;
int data[]{1,9,3,8,3,7,4,6,5};
auto f = [sum](int x) { sum += x; };
for (int i : data) f(i);
```

Error

```
error: assignment of read-only variable 'sum'
          [sum](int x) { sum += x; });
```

Default capture is by value

Code example

```
int sum = 0;
int data[]{1,9,3,8,3,7,4,6,5};
auto f = [sum](int x) { sum += x; };
for (int i : data) f(i);
```

Error

```
error: assignment of read-only variable 'sum'
                [sum](int x) { sum += x; });
```

Explanation

- By default, variables are captured by value
- The lambda's `operator()` is `const inline`

Capture by reference

Simple example

In order to capture by reference, add '&' before the variable

```
int sum = 0;
int data[]{1,9,3,8,3,7,4,6,5};
auto f = [&sum](int x) { sum += x; };
for (int i : data) f(i);
```

Capture by reference

Simple example

In order to capture by reference, add '&' before the variable

```
int sum = 0;
int data[]{1,9,3,8,3,7,4,6,5};
auto f = [&sum](int x) { sum += x; };
for (int i : data) f(i);
```

Mixed case

One can of course mix values and references

```
int sum = 0, off = 1;
int data[]{1,9,3,8,3,7,4,6,5};
auto f = [&sum, off](int x) { sum += x + off; };
for (int i : data) f(i);
```

Anatomy of a lambda

Lambdas are pure syntactic sugar - cppinsight

- They are replaced by a functor during compilation

```
int sum = 0, off = 1;
auto l =
[&sum, off]



(int x) {
  sum += x + off;
};


l(42);
```

```
int sum = 0, off = 1;
struct __lambda4 {
  int& sum; int off;
  __lambda4(int& s, int o)
  : sum(s), off(o) {}

  auto operator()(int x) const {
    sum += x + off;
  }
};
auto l = __lambda4{sum, off};
l(42);
```

Some nice consequence

- Lambda expressions create ordinary objects
- They can be copied, moved, or inherited from

Capture list

all by value

```
[=](...) { ... };
```

Capture list

all by value

```
[=](...) { ... };
```

all by reference

```
[&](...) { ... };
```

Capture list

all by value

```
[=](...) { ... };
```

all by reference

```
[&](...) { ... };
```

mix

```
[&,  b](...) { ... };
[=, &b](...) { ... };
```

The STL

4 Core modern C++

- Constness
- Exceptions
- Templates
- Lambdas
- The STL
- RAII and smart pointers

The Standard Template Library

What it is

- A library of standard templates
- Has almost everything you need
  - strings, containers, iterators
  - algorithms, functions, sorters
  - functors, allocators
  - ...
- Portable
- Reusable
- Efficient

The Standard Template Library

What it is

- A library of standard templates
- Has almost everything you need
  - strings, containers, iterators
  - algorithms, functions, sorters
  - functors, allocators
  - ...
- Portable
- Reusable
- Efficient

Use it

and adapt it to your needs, thanks to templates

STL in practice

STL example - godbolt

```
#include <vector>
#include <algorithm>
#include <functional>      // `import std;` in C++23
#include <iterator>
#include <iostream>

std::vector<int> in{5, 3, 4};     // initializer list
std::vector<int> out(3);  // constructor taking size
std::transform(in.begin(), in.end(),  // input range
               out.begin(),           // start result
               std::negate{});        // function obj
std::copy(out.begin(), out.end(),     // -5 -3 -4
  std::ostream_iterator<int>{std::cout, " "});
```

STL's concepts

containers

- data structures for managing a range of elements, irrespective of:
  - the data itself (templated)
  - the memory allocation of the structure (templated)
  - the algorithms that may use the structure (iterators)

Examples (→ string and container library on cppreference)

- string, string_view (C++ 17)
- list, forward_list (C++ 11), vector, deque, array (C++ 11)
- [multi]map, [multi]set (C++ 23: flat_[multi]map, flat_[multi]set)
- unordered_[multi]map (C++ 11), unordered_[multi]set (C++ 11)
- stack, queue, priority_queue
- span (C++ 20)
- non-containers: bitset, pair, tuple (C++ 11), optional (C++ 17), variant (C++ 17), any (C++ 17), expected (C++ 23)

Containers: std::vector


```
#include <vector>
std::vector<T> v{5, 3, 4}; // 3 Ts, 5, 3, 4
std::vector<T> v(100);     // 100 default constr. Ts
std::vector<T> v(100, 42); // 100 Ts with value 42
std::vector<T> v2 = v;             // copy
std::vector<T> v2 = std::move(v); // move, v is empty

std::size_t s = v.size();
bool empty = v.empty();

v[2] = 17;          // write element 2
T& t = v[1000];     // access element 1000, bug!
T& t = v.at(1000); // throws std::out_of_range
T& f = v.front();  // access first element
v.back() = 0;       // write to last element
T* p = v.data();    // pointer to underlying storage
```

Containers: std::vector


```
std::vector<T> v = ...;
auto b = v.begin(); // iterator to first element
auto e = v.end();   // iterator to one past last element
// all following operations, except reserve, invalidate
// all iterators (b and e) and references to elements

v.resize(100); // size changes, grows: new T{}s appended
               //                shrinks: Ts at end destroyed
v.reserve(1000); // size remains, memory increased
for (T i = 0; i < 900; i++)
  v.push_back(i); // add to the end
v.insert(v.begin()+3, T{}); // insert after 3rd position

v.pop_back();          // removes last element
v.erase(v.end() - 3); // removes 3rd-last element
v.clear();             // removes all elements
```

Containers: std::unordered_map

C++ 11

Conceptually a container of std::pair<Key const, Value>

```
#include <unordered_map>
std::unordered_map<std::string, int> m;
m["hello"] = 1;  // inserts new key, def. constr. value
m["hello"] = 2;  // finds existing key
auto [it, isNewKey] = m.insert({"hello", 0}); // no effect
int val = m["world"];     // inserts new key (val == 0)
int val = m.at("monde"); // throws std::out_of_range

if (auto it = m.find("hello"); it != m.end()) // C++17
    m.erase(it);        // remove by iterator (fast)
if (m.contains("hello")) // C++20
    m.erase("hello"); // remove by key, 2. lookup, bad
for (auto const& [k, v] : m) // iterate k/v pairs (C++17)
    std::cout << k << ": " << v << '\n';
```

std::hash

- The standard utility to create hash codes
- Used by std::unordered_map and others
- Can be customized for your types via template specialization

```
#include <functional>
std::hash<std::string> h;
std::cout << h("hello"); // 2762169579135187400
std::cout << h("world"); // 8751027807033337960

class MyClass { int a, b; ... };
template<> struct std::hash<MyClass> {
  std::size_t operator()(MyClass const& c) {
    std::hash<int> h;
    return h(c.a) ^ h(c.b); // xor to combine hashes
  }
};
```

STL's concepts

iterators

- generalization of pointers
- allow iteration over some data, irrespective of:
  - the container used (templated)
  - the data itself (container is templated)
  - the consumer of the data (templated algorithm)
- examples
  - `std::reverse_iterator`, `std::back_insert_iterator`, ...

Iterator example - godbolt

```
std::vector<int> const v = {1,2,3,4,5,6,7,8,9};
auto const end = v.rend() - 3; // arithmetic
for (auto it = v.rbegin();
     it != end;      // compare positions
     it += 2)        // jump 2 positions
  std::cout << *it; // dereference, prints: 975
```

STL's concepts

algorithms

- implementation of an algorithm working on data
- with a well defined behavior (defined complexity)
- irrespective of
  - the data handled
  - the container where the data live
  - the iterator used to go through data (almost)
- examples
  - for_each, find, find_if, count, count_if, search
  - copy, swap, transform, replace, fill, generate
  - remove, remove_if
  - unique, reverse, rotate, shuffle, partition
  - sort, partial_sort, merge, make_heap, min, max
  - lexicographical_compare, iota, reduce, partial_sum
- see also 105 STL Algorithms in Less Than an Hour and the algorithms library on cppreference

STL's concepts

functors / function objects

- generic utility functions
- as structs with `operator()`
- mostly useful to be passed to STL algorithms
- implemented independently of
  - the data handled (templated)
  - the context (algorithm) calling it
- examples
  - plus, minus, multiplies, divides, modulus, negate
  - equal_to, less, greater, less_equal, ...
  - logical_and, logical_or, logical_not
  - bit_and, bit_or, bit_xor, bit_not
  - identity, not_fn
  - bind, bind_front
- see also documentation on cppreference

Functors / function objects

Example

```
struct Incrementer {
  int m_inc;
  Incrementer(int inc) : m_inc(inc) {}

  int operator()(int value) const {
    return value + m_inc;
  }
};
std::vector<int> v{1, 2, 3};
const auto inc = 42;
std::transform(v.begin(), v.end(), v.begin(),
               Incrementer{inc});
```

Prefer lambdas over functors

With lambdas

```
std::vector<int> v{1, 2, 3};
const auto inc = 42;
std::transform(begin(v), end(v), begin(v),
               [inc](int value) {
                 return value + inc;
               });
```

Prefer lambdas over functors

With lambdas

```
std::vector<int> v{1, 2, 3};
const auto inc = 42;
std::transform(begin(v), end(v), begin(v),
               [inc](int value) {
                 return value + inc;
               });
```

Good practice: Use STL algorithms with lambdas

- Prefer lambdas over functors when using the STL
- Avoid binders like `std::bind2nd`, `std::ptr_fun`, etc.

Range-based for loops with STL containers

C++ 11

Iterator-based loop (since C++ 98)

```
std::vector<int> v = ...;
int sum = 0;
for (std::vector<int>::iterator it = v.begin();
     it != v.end(); it++)
  sum += *it;
```

Range-based for loops with STL containers

C++ 11

Iterator-based loop (since C++ 98)

```
std::vector<int> v = ...;
int sum = 0;
for (std::vector<int>::iterator it = v.begin();
     it != v.end(); it++)
  sum += *it;
```

Range-based for loop (since C++ 11)

```
std::vector<int> v = ...;
int sum = 0;
for (auto a : v) { sum += a; }
```

Range-based for loops with STL containers

C++ 11

Iterator-based loop (since C++ 98)

```
std::vector<int> v = ...;
int sum = 0;
for (std::vector<int>::iterator it = v.begin();
     it != v.end(); it++)
  sum += *it;
```

Range-based for loop (since C++ 11)

```
std::vector<int> v = ...;
int sum = 0;
for (auto a : v) { sum += a; }
```

STL way (since C++ 98)

```
std::vector<int> v = ...;
int sum = std::accumulate(v.begin(), v.end(), 0);
// std::reduce(v.begin(), v.end()); // C++17
```

More examples


```
std::list<int> l = ...;

// Finds the first element in a list between 1 and 10.
const auto it = std::find_if(l.begin(), l.end(),
    [](int i) { return i >= 1 && i <= 10; });
if (it != l.end()) {
  int element = *it; ...
}

// Computes sin(x)/(x + DBL_MIN) for elements of a range.
std::vector<double> r(l.size());
std::transform(l.begin(), l.end(), r.begin(),
  [](auto x) { return std::sin(x)/(x + DBL_MIN); });

// reduce/fold (using addition)
const auto sum = std::reduce(v.begin(), v.end());
```

More examples


```
std::vector<int> v = ...;

// remove duplicates
std::sort(v.begin(), v.end());
auto newEndIt = std::unique(v.begin(), v.end());
v.erase(newEndIt, v.end());

// remove by predicate
auto p = [](int i) { return i > 42; };
auto newEndIt = std::remove_if(v.begin(), v.end(), p);
v.erase(newEndIt, v.end());

// remove by predicate (C++20)
std::erase_if(v, p);
```

Welcome to lego programming!

Using the STL

Exercise: STL

- go to `exercises/stl`
- look at the non STL code in randomize.nostl.cpp
  - it creates a vector of ints at regular intervals
  - it randomizes them
  - it computes differences between consecutive ints
  - and the mean and variance of it
- open randomize.cpp and complete the "translation" to STL
- see how easy it is to reuse the code with complex numbers

Using the STL

Be brave and persistent!

- you may find the STL quite difficult to use
- template syntax is really tough
- it is hard to get right, compilers spit out long error novels
  - but, compilers are getting better with error messages
- C++ 20 will help with concepts and ranges
- the STL is extremely powerful and flexible
- it will be worth your time!

RAII and smart pointers

4 Core modern C++

- Constness
- Exceptions
- Templates
- Lambdas
- The STL
- RAII and smart pointers

Pointers: why are they error prone?

They need initialization

```
1 char *s;
2 try {
3   foo(); // may throw
4   s = new char[100];
5   read_line(s);
6 } catch (...) { ... }
7 process_line(s);
```

Pointers: why are they error prone?

They need initialization — Seg Fault

```
char *s;
try {
  foo(); // may throw
  s = new char[100];
  read_line(s);
} catch (...) { ... }
process_line(s);
```

Pointers: why are they error prone?

They need initialization — Seg Fault

```
1  char *s;
2  try {
3    foo(); // may throw
4    s = new char[100];
```

They need to be released

```
1  char *s = new char[100];
2  read_line(s);
3  if (s[0] == '#') return;
4  process_line(s);
5  delete[] s;
```

Pointers: why are they error prone?

They need initialization — Seg Fault

```
1  char *s;
2  try {
3    foo(); // may throw
4    s = new char[100];
```

They need to be released — Memory leak

```
1  char *s = new char[100];
2  read_line(s);
3  if (s[0] == '#') return;
4  process_line(s);
5  delete[] s;
```

Pointers: why are they error prone?

They need initialization — Seg Fault

```
char *s;
try {
  foo(); // may throw
  s = new char[100];
```

They need to be released — Memory leak

```
char *s = new char[100];
read_line(s);
```

They need clear ownership

```
char *s = new char[100];
read_line(s);
vec.push_back(s);
set.add(s);
std::thread t1{func1, vec};
std::thread t2{func2, set};
```

Pointers: why are they error prone?

They need initialization — Seg Fault

```
1 char *s;
2 try {
3   foo(); // may throw
4   s = new char[100];
```

They need to be released — Memory leak

```
1 char *s = new char[100];
2 read_line(s);
```

They need clear ownership — Who should release ?

```
1 char *s = new char[100];
2 read_line(s);
3 vec.push_back(s);
4 set.add(s);
5 std::thread t1{func1, vec};
6 std::thread t2{func2, set};
```

This problem exists for any resource

For example with a file

```
std::FILE *handle = std::fopen(path, "w+");
if (nullptr == handle) { throw ... }
std::vector v(100, 42);
write(handle, v);
if (std::fputs("end", handle) == EOF) {
  return;
}
std::fclose(handle);
```

Which problems do you spot in the above snippet?

Resource Acquisition Is Initialization (RAII)

Practically

Use variable construction/destruction and scope semantics:

- wrap the resource inside a class
- acquire resource in constructor
- release resource in destructor
- create an instance on the stack
  - automatically destructed when leaving the scope
  - including in case of exception
- use move semantics to pass the resource around

RAII in practice

An RAII File class

```
class File {
public:
  // constructor: acquire resource
  File(const char* filename)
    : m_handle(std::fopen(filename, "w+")) {
    // abort constructor on error
    if (m_handle == nullptr) { throw ... }
  }
  // destructor: release resource
  ~File() { std::fclose(m_handle); }
  void write (const char* str) {
    ...
  }
private:
  std::FILE* m_handle; // wrapped resource
};
```

RAII usage

Usage of File class

```
void log_function() {
  // file opening, aka resource acquisition
  File logfile("logfile.txt");

  // file usage
  logfile.write("hello logfile!"); // may throw

  // file is automatically closed by the call to
  // its destructor, even in case of exception!
}
```

Good practice: Use `std::fstream` for file handling

The standard library provides `std::fstream` to handle files, use it!

std::unique_ptr

A RAII pointer

- wraps and behaves like a regular pointer
- get underlying pointer using `get()`
- when destroyed, deletes the object pointed to
- has move-only semantic
  - the pointer has unique ownership
  - copying will result in a compile error

std::unique_ptr

A RAII pointer

- wraps and behaves like a regular pointer
- get underlying pointer using get()
- when destroyed, deletes the object pointed to
- has move-only semantic
  - the pointer has unique ownership
  - copying will result in a compile error

```
#include <memory>
void f(std::unique_ptr<Foo> ptr) {
  ptr->bar();
} // deallocation when f exits

std::unique_ptr<Foo> p{ new Foo{} }; // allocation
f(std::move(p)); // transfer ownership
assert(p.get() == nullptr);
```

Quiz

What do you expect?

```
void f(std::unique_ptr<Foo> ptr);
std::unique_ptr<Foo> uptr(new Foo{});
f(uptr); // transfer of ownership
```

Quiz

What do you expect?

```
void f(std::unique_ptr<Foo> ptr);
std::unique_ptr<Foo> uptr(new Foo{});
f(uptr); // transfer of ownership
```

Compilation Error - godbolt

```
test.cpp:15:5: error: call to deleted constructor
of 'std::unique_ptr<Foo>'
  f(uptr);
    ^~~~
/usr/include/c++/4.9/bits/unique_ptr.h:356:7: note:
 'unique_ptr' has been explicitly marked deleted here
 unique_ptr(const unique_ptr&) = delete;
 ^
```

std::make_unique

std::make_unique

- allocates and constructs an object with arguments and wraps it with `std::unique_ptr` in one step
- no `new` or `delete` calls anymore!
- no memory leaks if used consistently

std::make_unique

std::make_unique

- allocates and constructs an object with arguments and wraps it with `std::unique_ptr` in one step
- no **new** or **delete** calls anymore!
- no memory leaks if used consistently

std::make_unique usage

```
{
  // calls new File("logfile.txt") internally
  auto f = std::make_unique<File>("logfile.txt");
  f->write("hello logfile!");
} // deallocation at end of scope
```

RAII or raw pointers

When to use what?

- Always use RAII for resources, in particular allocations
  - You thus never have to release / deallocate yourself
- Use raw pointers as non-owning, re-bindable observers
- Remember that `std::unique_ptr` is move only

RAII or raw pointers

When to use what?

- Always use RAII for resources, in particular allocations
  - You thus never have to release / deallocate yourself
- Use raw pointers as non-owning, re-bindable observers
- Remember that `std::unique_ptr` is move only

A question of ownership

```
std::unique_ptr<T> produce();
void observe(const T&);
void modifyRef(T&);
void modifyPtr(T*);
void consume(std::unique_ptr<T>);
std::unique_ptr<T> pt{produce()}; // Receive ownership
observe(*pt);                     // Keep ownership
modifyRef(*pt);                   // Keep ownership
modifyPtr(pt.get());              // Keep ownership
consume(std::move(pt));           // Transfer ownership
```

std::unique_ptr usage summary

Good practice: std::unique_ptr

- std::unique_ptr is about lifetime management
  - use it to tie the lifetime of an object to a unique RAII owner
  - use raw pointers/references to refer to another object without owning it or managing its lifetime
- use std::make_unique for creation
- strive for having no new/delete in your code
- for dynamic arrays, std::vector may be more useful

std::shared_ptr

std::shared_ptr : a reference counting pointer

- wraps a regular pointer similar to unique_ptr
- has move and copy semantic
- uses reference counting internally
  - "Would the last person out, please turn off the lights?"
- reference counting is thread-safe, therefore a bit costly

std::make_shared : creates a std::shared_ptr

```
{
  auto sp = std::make_shared<Foo>(); // #ref = 1
  vector.push_back(sp);              // #ref = 2
  set.insert(sp);                    // #ref = 3
} // #ref 2
```

Quiz: std::shared_ptr in use

What is the output of this code? - godbolt

```
auto shared = std::make_shared<int>(100);
auto print = [shared](){
  std::cout << "Use: " << shared.use_count() << " "
            << "value: " << *shared << "\n";
};
print();
{
  auto ptr{ shared };
  (*ptr)++;
  print();
}
print();
```

Quiz: std::shared_ptr in use

What is the output of this code? - godbolt

```
auto shared = std::make_shared<int>(100);
auto print = [shared](){
  std::cout << "Use: " << shared.use_count() << " "
            << "value: " << *shared << "\n";
};
print();
{
  auto ptr{ shared };
  (*ptr)++;
  print();
}
print();
```

```
Use: 2 value: 100
Use: 3 value: 101
Use: 2 value: 101
```

Quiz: std::shared_ptr in use

What is the output of this code?

```
auto shared = std::make_shared<int>(100);
auto print = [&shared](){
  std::cout << "Use: " << shared.use_count() << " "
            << "value: " << *shared << "\n";
};
print();
{
  auto ptr{ shared };
  (*ptr)++;
  print();
}
print();
```

```
Use: 1 value: 100
Use: 2 value: 101
Use: 1 value: 101
```

Rule of zero

Good practice: Single responsibility principle (SRP)

Every class should have only one responsibility.

Good practice: Rule of zero

- If your class has any special member functions (except ctor.)
  - Your class probably deals with a resource, use RAII
  - Your class should only deal with this resource (SRP)
  - Apply rule of 3/5: write/default/delete all special members
- Otherwise: do not declare any special members (rule of zero)
  - A constructor is fine, if you need some setup
  - If your class holds a resource as data member:
    wrap it in a smart pointer, container, or any other RAII class

smart pointers

Exercise: Smart pointers

- go to `exercises/smartPointers`
- compile and run the program. It doesn't generate any output.
- Run with valgrind if possible to check for leaks

```
$ valgrind --leak-check=full --track-origins=yes ./smartPointers
```

- In the *essentials course*, go through `problem1()` and `problem2()` and fix the leaks using smart pointers.
- In the *advanced course*, go through `problem1()` to `problem4()` and fix the leaks using smart pointers.
- `problem4()` is the most difficult. Skip if not enough time.

Useful tools

1. History and goals
2. Language basics
3. Object orientation (OO)
4. Core modern C++
5. Useful tools
   - C++ editor
   - Version control
   - Code formatting
   - The Compiling Chain
   - Web tools
   - Debugging

C++ editor

5 Useful tools
- C++ editor
- Version control
- Code formatting
- The Compiling Chain
- Web tools
- Debugging

C++ editors and IDEs

Can dramatically improve your efficiency by

- Coloring the code for you to "see" the structure
- Helping with indenting and formatting properly
- Allowing you to easily navigate in the source tree
- Helping with compilation/debugging, profiling, static analysis
- Showing you errors and suggestions while typing

Visual Studio Heavy, fully fledged IDE for Windows

Visual Studio Code Editor, open source, portable, many plugins

Eclipse IDE, open source, portable

Emacs **Vim** Editors for experts, extremely powerful.
They are to IDEs what latex is to PowerPoint

CLion, Code::Blocks, Atom, NetBeans, Sublime Text, ...

Choosing one is mostly a matter of taste

Version control

5 Useful tools

- C++ editor
- Version control
- Code formatting
- The Compiling Chain
- Web tools
- Debugging

Version control

Please use one!

- Even locally
- Even on a single file
- Even if you are the only committer

It will soon save your day

A few tools

- git — THE mainstream choice. Fast, light, easy to use
- mercurial — The alternative to git
- Bazaar — Another alternative
- Subversion — Historical, not distributed - don't use
- CVS — Archeological, not distributed - don't use

Git crash course

```
$ git init myProject
Initialized empty Git repository in myProject/.git/

$ vim file.cpp; vim file2.cpp
$ git add file.cpp file2.cpp
$ git commit -m "Committing first 2 files"
[master (root-commit) c481716] Committing first 2 files
...

$ git log --oneline
d725f2e Better STL test
f24a6ce Reworked examples + added stl one
bb54d15 implemented template part
...

$ git diff f24a6ce bb54d15
```

Code formatting

5 Useful tools

- C++ editor
- Version control
- Code formatting
- The Compiling Chain
- Web tools
- Debugging

clang-format

.clang-format

- File describing your formatting preferences
- Should be checked-in at the repository root (project wide)
- `clang-format -style=LLVM -dump-config > .clang-format`
- Adapt style options with help from: https://clang.llvm.org/docs/ClangFormatStyleOptions.html

Run clang-format

- `clang-format --style=LLVM -i <file.cpp>`
- `clang-format -i <file.cpp>` (looks for .clang-format file)
- `git clang-format` (formats local changes)
- `git clang-format <ref>` (formats changes since git <ref>)
- Most editors/IDEs can find a .clang-format file and adapt

clang-format

Exercise: clang-format

- Go to any example
- Format code with:
  `clang-format --style=GNU -i <file.cpp>`
- Inspect changes, try `git diff .`
- Revert changes using `git checkout -- <file.cpp>` or `git checkout .`
- Go to `exercises` directory and create a .clang-format file
  `clang-format -style=LLVM -dump-config > .clang-format`
- Run `clang-format -i <any_exercise>/*.cpp`
- Revert changes using `git checkout <any_exercise>`

The Compiling Chain

5 Useful tools

- C++ editor
- Version control
- Code formatting
- The Compiling Chain
- Web tools
- Debugging

The compiling chain



The steps

cpp the preprocessor
handles the # directives (macros, includes)
creates "complete" source code (ie. translation unit)

g++ the compiler
creates machine code from C++ code

ld the linker
links several binary files into libraries and executables

Compilers

Available tools

- gcc — the most common and most used
  free and open source
- clang — drop-in replacement of gcc
  slightly better error reporting
  free and open source, based on LLVM
- icc, icx — Intel's compilers, proprietary but now free
  optimized for Intel hardware
  icc being replaced by icx, based on LLVM
- Visual C++ / MSVC — Microsoft's C++ compiler on Windows

My preferred choice today

- gcc as the de facto standard in HEP
- clang in parallel to catch more bugs

Useful compiler options (gcc/clang)

Get more warnings

-Wall -Wextra get all warnings

-Werror force yourself to look at warnings

Optimization

-g add debug symbols (also: -g3 or -ggdb)

-Ox 0 = no opt., 1-2 = opt., 3 = highly opt. (maybe larger binary), g = opt. for debugging

Compilation environment

-I <path> where to find header files

-L <path> where to find libraries

-l <name> link with libname.so

-E / -c stop after preprocessing / compilation

How to inspect object files?

Listing symbols : nm

- gives list of symbols in a file
  - these are functions and constants
  - with their internal (mangled/encoded) naming
- also gives type and location in the file for each symbol
  - 'U' type means undefined
    - so a function used but not defined
    - linking will be needed to resolve it
- use -C option to demangle on the fly

```
> nm -C Struct.o
                 U strlen
                 U _Unwind_Resume
000000000000008a T SlowToCopy::SlowToCopy(SlowToCopy const&)
0000000000000000 T SlowToCopy::SlowToCopy()
0000000000000064 T SlowToCopy::SlowToCopy(std::__cxx11::basic_st
```

How to inspect libraries/executables?

Listing dependencies : ldd

- gives (recursive) list of libraries required by the given argument
  - and if/where they are found in the current context
- use -r to list missing symbols (mangled)

```
> ldd -r trypoly
    linux-vdso.so.1 (0x00007f3938085000)
    libpoly.so => not found
    libstdc++.so.6 => /lib/x86_64-linux-gnu/libstdc++.so.6 (0x00
    [...]
    undefined symbol: _ZNK7Hexagon16computePerimeterEv    (./try
    undefined symbol: _ZNK7Polygon16computePerimeterEv    (./try
    undefined symbol: _ZN7HexagonC1Ef    (./trypoly.sol)
    undefined symbol: _ZN8PentagonC1Ef    (./trypoly.sol)
```

Makefiles

Why to use them

- an organized way of describing building steps
- avoids a lot of typing

Several implementations

- raw Makefiles: suitable for small projects
- cmake: portable, the current best choice
- automake: GNU project solution

```
test : test.cpp libpoly.so
    $(CXX) -Wall -Wextra -o $@ $^
libpoly.so: Polygons.cpp
    $(CXX) -Wall -Wextra -shared -fPIC -o $@ $^
clean:
    rm -f *o *so *~ test test.sol
```

CMake

- a cross-platform meta build system
- generates platform-specific build systems
- see also this basic and detailed talks

Example CMakeLists.txt

```
cmake_minimum_required(VERSION 3.18)
project(hello CXX)

find_package(ZLIB REQUIRED) # for external libs

add_executable(hello main.cpp util.h util.cpp)
target_compile_features(hello PUBLIC cxx_std_17)
target_link_libraries(hello PUBLIC ZLIB::ZLIB)
```

CMake - Building

Building a CMake-based project

Start in the directory with the top-level `CMakeLists.txt`:

```
mkdir build # will contain all build-related files
cd build
cmake ..     # configures and generates a build system
cmake -DCMAKE_BUILD_TYPE=Release .. # pass arguments
ccmake .     # change configuration using terminal GUI
cmake-gui . # change configuration using Qt GUI
cmake --build . -j8     # build project with 8 jobs
cmake --build . --target hello  # build only hello
sudo cmake --install . # install project into system
cd ..
rm -r build # clean everything
```

Compiler chain

Exercise: Compiler chain

- go to `exercises/polymorphism`
- preprocess Polygons.cpp (g++ -E -o output)
- compile Polygons.o and trypoly.o (g++ -c -o output)
- use nm to check symbols in .o files
- look at the Makefile
- try make clean; make
- see linking stage of the final program using g++ -v
  - just add a -v in the Makefile command for trypoly target
  - run make clean; make
  - look at the collect 2 line, from the end up to "-o trypoly"
- see library dependencies of 'trypoly' using 'ldd'

Web tools

5 Useful tools

- C++ editor
- Version control
- Code formatting
- The Compiling Chain
- Web tools
- Debugging

Godbolt / Compiler Explorer

Concept

An online generic compiler with immediate feedback. Allows:

- trying various compilers in the browser
- inspecting the assembly generated
- use of external libraries (over 50 available !)
- running the produced code
- sharing small pieces of code via permanent short links

Typical usage

- check small pieces of code on different compilers
- check some new C^{++} functionality and its support
- optimize small pieces of code
- NOT relevant for large codes

Godbolt by example

Check effect of optimization flags

https://godbolt.org/z/Pb8WsWjEx

- Check generated code with -O0, -O1, -O2, -O3
- See how it gets shorter and simpler

COMPILER EXPLORER | Add... | More | Templates | Share | Policies | Other

C++ source #1 — C++

```cpp
#include <iostream>

constexpr int fact(int a) {
  int n = 1;
  for (int i = 1; i <=a; i++) {
      n *= i;
  }
  return n;
}

int main() {
  for (int i = 4; i < 8; i++) {
    std::cout << fact(i);
  }
}
```

x86-64 gcc 12.1 (C++, Editor #1, Compiler #1) — x86-64 gcc 12.1 — -O0

```asm
fact(int):
  push rbp
  mov rbp, rsp
  mov DWORD PTR [rbp-20], edi
  mov DWORD PTR [rbp-4], 1
  mov DWORD PTR [rbp-8], 1
  jmp .L2
.L3:
  mov eax, DWORD PTR [rbp-4]
  imul eax, DWORD PTR [rbp-8]
  mov DWORD PTR [rbp-4], eax
  add DWORD PTR [rbp-8], 1
.L2:
  mov eax, DWORD PTR [rbp-8]
  cmp eax, DWORD PTR [rbp-20]
  jle .L3
  mov eax, DWORD PTR [rbp-4]
  pop rbp
  ret
main:
  push rbp
  mov rbp, rsp
  sub rsp, 16
  mov DWORD PTR [rbp-4], 4
  jmp .L6
.L7:
  mov eax, DWORD PTR [rbp-4]
  mov edi, eax
  call fact(int)
  mov esi, eax
  mov edi, OFFSET FLAT:_ZSt4cout
  call std::basic_ostream<char, std::char_tra
```

Output (0/0) x86-64 gcc 12.1 - 467ms (94457B) ~6653 lines filtered

x86-64 gcc 12.1 (C++, Editor #1, Compiler #3) — x86-64 gcc 12.1 — -O3

```asm
main:
        sub     rsp, 8
        mov     esi, 24
        mov     edi, OFFSET FLAT:_ZSt4cout
        call    std::basic_ostream<char, std::
        mov     esi, 120
        mov     edi, OFFSET FLAT:_ZSt4cout
        call    std::basic_ostream<char, std::
        mov     esi, 720
        mov     edi, OFFSET FLAT:_ZSt4cout
        call    std::basic_ostream<char, std::
        mov     esi, 5040
        mov     edi, OFFSET FLAT:_ZSt4cout
        call    std::basic_ostream<char, std::
        xor     eax, eax
        add     rsp, 8
        ret
_GLOBAL__sub_I_main:
        sub     rsp, 8
        mov     edi, OFFSET FLAT:_ZStL8__ioin
        call    std::ios_base::Init::Init() [
        mov     edx, OFFSET FLAT:__dso_handle
        mov     esi, OFFSET FLAT:_ZStL8__ioin
```

Output (0/0) x86-64 gcc 12.1 - 596ms (96817B) ~6874 lines filtered

Output of x86-64 gcc 12.1 (Compiler #3) — Wrap lines | Select all

```
ASM generation compiler returned: 0
Execution build compiler returned: 0
Program returned: 0
 241207205040
```

cppinsights

Concept

Reveals the actual code behind C++ syntactic sugar

- lambdas
- range-based loops
- templates
- initializations
- auto
- ...

Typical usage

- understand how things work behind the C++ syntax
- debug some non working pieces of code

cppinsights by example

Check how range-based loop work

https://cppinsights.io/s/b886aa76

- See how they map to regular iterators
- And how operators are converted to function calls

[C++ Standard: C++ 20] Def... More

Made by Andreas Fertig
Powered by Flask and CodeMirror

Source:

```
1 #include <array>
2 #include <iostream>
3
4 int main() {
5     std::array<int, 5> arr{2,4,6,8,10};
6     for(auto const & c : arr) {
7       std::cout << "c=" << c << "\n";
8     }
9 }
```

Insight:

```
1 #include <array>
2 #include <iostream>
3
4 int main()
5 {
6   std::array<int, 5> arr = {{2, 4, 6, 8, 10}};
7   {
8     std::array<int, 5> & __range1 = arr;
9     int * __begin1 = __range1.begin();
10    int * __end1 = __range1.end();
11    for(; __begin1 != __end1; ++__begin1) {
12      const std::array<int, 5>::value_type & c = *__begin1;
13      std::operator<<(std::operator<<(std::cout, "c=").operator<<(c), "\n");
14    }
15
16  }
17  return 0;
18 }
19
```

Console:

```
Insights exited with result code: 0
```

Debugging

5 Useful tools

- C++ editor
- Version control
- Code formatting
- The Compiling Chain
- Web tools
- Debugging

Debugging

The problem

- everything compiles fine (no warning)
- but crashes at run time
- no error message, no clue

Debugging

The problem

- everything compiles fine (no warning)
- but crashes at run time
- no error message, no clue

The solution: debuggers

- dedicated program able to stop execution at any time
- and show you where you are and what you have

Debugging

The problem

- everything compiles fine (no warning)
- but crashes at run time
- no error message, no clue

The solution: debuggers

- dedicated program able to stop execution at any time
- and show you where you are and what you have

Existing tools

- gdb — THE main player
- lldb — the debugger coming with clang/LLVM
- gdb-oneapi — the Intel OneAPI debugger

gdb crash course

start gdb

- gdb <program>
- gdb <program><core file>
- gdb --args <program><program arguments>

inspect state

bt	prints a backtrace
print <var>	prints current content of the variable
list	show code around current point
up/down	go up or down in call stack

breakpoints

break <function>	puts a breakpoint on function entry
break <file>:<line>	puts a breakpoint on that line

gdb

Exercise: gdb

- go to `exercises/debug`
- compile, run, see the crash
- run it in gdb (or lldb on newer MacOS)
- inspect backtrace, variables
- find problem and fix bug
- try stepping, breakpoints

Debugging UIs

User interfaces for debuggers

- offer convenience on top of command line
- windows for variables, breakpoints, call stack, active threads, watch variables in-code, disassembly, run to cursor ...

Native gdb Try "tui enable" for a simple built-in UI

- VSCode Built-in support for gdb
- CodeLLDB VS Code plugin for LLDB
- GDB dashboard Poplar terminal UI for gdb
- GEF Modern terminal UI for gdb

- some editors and most IDEs have good debugger integration

This is the end

Questions ?

https://github.com/hsf-training/cpluspluscourse/raw/download/talk/C++Course_full.pdf
https://github.com/hsf-training/cpluspluscourse

Index of Good Practices

1. C's memory management 25
2. Manual memory management 26
3. Initialisation 29
4. Avoid unions 34
5. References 41
6. Write readable functions 50
7. `for` syntax 63
8. preprocessor 71
9. Header / source 73
10. Implementing methods 82
11. Rule of 3/5 96
12. Prefer smart pointer 114
13. Prefer containers 115
14. Virtual destructors 127
15. Avoid multiple inheritance 134
16. Throwing exceptions 155
17. Catching exceptions 157
18. Exceptions 161
19. `noexcept` 164
20. STL and lambdas 196
21. Use `std::fstream` 208
22. `std::unique_ptr` 213
23. Single responsibility principle 217
24. Rule of zero 217

Index of Exercises

1. Functions 49
2. Control structs 68
3. Loops, refs, auto 76
4. Polymorphism 130
5. Virtual OO 135
6. Operators 142
7. Constness 152
8. Templates 173
9. STL 201
10. Smart pointers 218
11. clang-format 227
12. Compiler chain 237
13. gdb 246

Index of Godbolt code examples

1. Unary constructor - godbolt 98
2. function objects - godbolt 145
3. STL - godbolt 186
4. Iterator example - godbolt 192
5. `unique_ptr` copy - godbolt 210
6. `shared_ptr` quiz - godbolt 215

Books

A Tour of C++, Third Edition
Bjarne Stroustrup, Addison-Wesley, Sep 2022
ISBN-13: 978-0136816485

Effective Modern C++
Scott Meyers, O'Reilly Media, Nov 2014
ISBN-13: 978-1-491-90399-5

C++ Templates - The Complete Guide, 2nd Edition
David Vandevoorde, Nicolai M. Josuttis, and Douglas Gregor
ISBN-13: 978-0-321-71412-1

C++ Best Practices, 2nd Edition
Jason Turner
https://leanpub.com/cppbestpractices

Clean Architecture
Robert C. Martin, Pearson, Sep 2017
ISBN-13: 978-0-13-449416-6

The Art of UNIX Programming
Eric S. Raymond, Addison-Wesley, Sep 2002
ISBN-13: 978-0131429017

Introduction to Algorithms, 4th Edition
T. H. Cormen, C. E. Leiserson, R. L. Rivest, C. Stein, Apr 2022
ISBN-13: 978-0262046305

Conferences

- CppCon — cppcon.org — CppCon
- C++ Now — cppnow.org — BoostCon
- Code::Dive — codedive.pl — codediveconference
- ACCU Conference — accu.org — ACCUConf
- Meeting C++ — meetingcpp.com — MeetingCPP
- See link below for more information
  https://isocpp.org/wiki/faq/conferences-worldwide