



# Forecasting

**Jeffrey Leek, Assistant Professor of Biostatistics  
Johns Hopkins Bloomberg School of Public Health**

# Time series data

Finance

Google Inc (NASDAQ:GOOG)

Add to portfolio

More results

Company

Summary

News

Option chain

Related companies

Historical prices

Financials

Markets

News

Portfolios

Stock screener

Google Domestic Trends

Recent Quotes (Turn on)

You have no recent quotes

1,120.71  
+11.25 (1.01%)

Dec 31 - Close  
NASDAQ real-time data - Disclaimer  
Currency in USD

Range 1,106.26 - 1,121.00  
52 week 695.52 - 1,121.00  
Open 1,112.24  
Vol / Avg. 1.36M/1.54M  
Mkt cap 374.42B  
P/E 32.19  
Div/yield -  
EPS 34.81  
Shares 334.09M  
Beta 0.87  
Inst. own 72%

8+1 9.4k

Dow Jones 16,576.66 0.44%  
Nasdaq 4,176.59 0.00%  
Technology 0.70%  
GOOG 1,120.71 1.01%




<https://www.google.com/finance>

# What is different?

- Data are dependent over time
- Specific pattern types
  - Trends - long term increase or decrease
  - Seasonal patterns - patterns related to time of week, month, year, etc.
  - Cycles - patterns that rise and fall periodically
- Subsampling into training/test is more complicated
- Similar issues arise in spatial data
  - Dependency between nearby observations
  - Location specific effects
- Typically goal is to predict one or more observations into the future.
- All standard predictions can be used (with caution!)

# Beware spurious correlations!


User uploaded activity for Google stock price and US Web Search activity for **solitaire network** ( $r=0.8312$ )



<http://www.google.com/trends/correlate>

<http://www.newscientist.com/blogs/onepercent/2011/05/google-correlate-passes-our-we.html>


# Also common in geographic analyses



PET PEEVE #208:  
GEOGRAPHIC PROFILE MAPS WHICH ARE  
BASICALLY JUST POPULATION MAPS

<http://xkcd.com/1138/>

# Beware extrapolation!



<http://www.nature.com/nature/journal/v431/n7008/full/431525a.html>

# Google data

```
library(quantmod)
from.dat <- as.Date("01/01/08", format="%m/%d/%y")
to.dat <- as.Date("12/31/13", format="%m/%d/%y")
getSymbols("GOOG", src="google", from = from.dat, to = to.dat)
```

```
[1] "GOOG"
```

```
head(GOOG)
```

	GOOG.Open	GOOG.High	GOOG.Low	GOOG.Close	GOOG.Volume
2008-01-02	692.9	697.4	677.7	685.2	4306848
2008-01-03	685.3	686.9	676.5	685.3	3252846
2008-01-04	679.7	681.0	655.0	657.0	5359834
2008-01-07	653.9	662.3	637.4	649.2	6404945
2008-01-08	653.0	660.0	631.0	631.7	5341949
2008-01-09	630.0	653.3	622.5	653.2	6744242

# Summarize monthly and store as time series

```
mGoog <- to.monthly(GOOG)
googOpen <- Op(mGoog)
ts1 <- ts(googOpen,frequency=12)
plot(ts1,xlab="Years+1", ylab="GOOG")
```



# Example time series decomposition


- **Trend** - Consistently increasing pattern over time
- **Seasonal** - When there is a pattern over a fixed period of time that recurs.
- **Cyclic** - When data rises and falls over non fixed periods

<https://www.otexts.org/fpp/6/1>

# Decompose a time series into parts

```
plot(decompose(tsl),xlab="Years+1")
```

**Decomposition of additive time series**



# Training and test sets

```
ts1Train <- window(ts1,start=1,end=5)
ts1Test <- window(ts1,start=5,end=(7-0.01))
ts1Train
```

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1	692.9	528.7	471.5	447.7	578.3	582.5	519.6	472.5	476.8	412.1	357.6	286.7
2	308.6	334.3	333.3	343.8	395.0	418.7	424.2	448.7	459.7	493.0	537.1	588.1
3	627.0	534.6	529.2	571.4	526.5	480.4	445.3	489.0	455.0	530.0	615.7	563.0
4	596.5	604.5	617.8	588.8	545.7	528.0	506.7	611.2	540.8	509.9	580.1	600.0
5	652.9											

# Simple moving average

$$Y_t = \frac{1}{2 * k + 1} \sum_{j=-k}^k y_{t+j}$$

```
plot(tslTrain)  
lines(ma(tslTrain,order=3),col="red")
```

# Exponential smoothing

## Example - simple exponential smoothing

$$\hat{y}_{t+1} = \alpha y_t + (1 - \alpha)\hat{y}_{t-1}$$


	Seasonal Component		
Trend Component	N (None)	A (Additive)	M (Multiplicative)
N (None)	(N,N)	(N,A)	(N,M)
A (Additive)	(A,N)	(A,A)	(A,M)
A <sub>d</sub> (Additive damped)	(A <sub>d</sub> ,N)	(A <sub>d</sub> ,A)	(A <sub>d</sub> ,M)
M (Multiplicative)	(M,N)	(M,A)	(M,M)
M <sub>d</sub> (Multiplicative damped)	(M <sub>d</sub> ,N)	(M <sub>d</sub> ,A)	(M <sub>d</sub> ,M)

<https://www.otexts.org/fpp/7/6>

# Exponential smoothing

```
ets1 <- ets(tslTrain,model="MMM")  
fcast <- forecast(ets1)  
plot(fcast); lines(tslTest,col="red")
```

Forecasts from ETS(M,Md,M)



# Get the accuracy

```
accuracy(fcast,tslTest)
```

	ME	RMSE	MAE	MPE	MAPE	MASE	ACF1	Theil's U
Training set	0.9464	48.78	39.35	-0.3297	7.932	0.3733	0.07298	NA
Test set	156.1890	205.76	160.78	18.1819	18.971	1.5254	0.77025	3.745

# Notes and further resources

- [Forecasting and timeseries prediction](#) is an entire field
- Rob Hyndman's [Forecasting: principles and practice](#) is a good place to start
- Cautions
  - Be wary of spurious correlations
  - Be careful how far you predict (extrapolation)
  - Be wary of dependencies over time
- See [quantmod](#) or [quandl](#) packages for finance-related problems.