

Bayesian Symbol-Refined Tree Substitution Grammars for Syntactic Parsing

Hiroyuki Shindo
NTT CS Labs.

Yusuke Miyao
NII


Akinori Fujino
NTT CS Labs.

Masaaki Nagata
NTT CS Labs.


July 10
ACL 2012

Task: Statistical Constituent Parsing

Training



Testing



F-score: ?

Previous Work


- Naive CFG-based parser does **NOT** perform well...
 - Coarse symbol annotations
 - Strong independence assumption

Previous approaches:

- a) CFG with automatic symbol refinement
[Matsuzaki et al. 05, Petrov et al. 06]
- b) Tree substitution grammars (TSG)
[Cohn et al. 09, Post et al. 09]

a) CFG with automatic symbol refinement

- Idea: split symbols into subcategories (based on the likelihood)
- Inference: EM algorithm




a) CFG with automatic symbol refinement

- Idea: split symbols into subcategories (based on the likelihood)
- Inference: EM algorithm


Refined PCFG rules:

S-0	→	NP-1 VP-2	p_0
NP-1	→	PRP-0	p_1
PRP-0	→	“I”	p_2
VP-2	→	VBP-0 NP-1	p_3



b) Tree Substitution Grammars (TSG)

- Idea: Allow arbitrarily large tree fragments
- Inference: MCMC sampling



Motivation

Two approaches are complementary

[Cohn et al. 09, Bansal & Klein 10]


- Clustering context
- Learning structure

Proposal:


Symbol-Refined TSG (SR-TSG)

SR-TSG

TSG




SR-TSG



SR-TSG

- Latent variables of SR-TSG:




Search space is huge !

Challenge:

Fully automatic learning

↔ TSG + refinement
[Bansal & Klein 10]



Probabilistic model

Inference



Probabilistic Model of SR-TSG



Overview of Probabilistic Model

What we need:

1. Probability distribution over refined tree fragments

Pitman-Yor process

[Pitman & Yor 96]

2. Framework for back-off smoothing

Large \rightarrow small tree fragments

3-level hierarchy



3-Level Hierarchy

complex ←————→ simple



Pitman-Yor process

Sparse!



1. SR-TSG



2. SR-CFG




3. RU-CFG



Pitman-Yor Process (PYP)

- A prior for non-parametric Bayesian model
- Useful for modeling data with [power-law](#) distribution
- Closely related to [Chinese Restaurant Process \(CRP\)](#)

Pitman-Yor Process (PYP)



Eq. $p(A) = \alpha \cdot \text{count}(A) + \beta \cdot \underline{P_0(A)}$ Base distr.

“Rich get richer” effect


Chinese Restaurant Process

$\propto p'(A1) \times p'(A2)$

smoothing


Chinese Restaurant Process

PYP (d, θ, P_0)





1

$\times P_0(A)$





Chinese Restaurant Process

PYP (d, θ, P_0)




Chinese Restaurant Process

PYP (d, θ, P_0)




- Prob. of choosing a table $\propto \begin{cases} \text{count}(k) - d & \text{occupied} \\ \theta + \# \text{ tables} \cdot d & \text{new table} \end{cases}$
- “Rich get richer” effect

Chinese Restaurant Process





- Prob. of choosing a table $\propto \begin{cases} \text{count}(k) - d & \text{occupied} \\ \theta + \# \text{ tables} \cdot d & \text{new table} \end{cases}$
- “Rich get richer” effect

Chinese Restaurant Process




- Prob. of choosing a table $\propto \begin{cases} \text{count}(k) - d & \text{occupied} \\ \theta + \# \text{ tables} \cdot d & \text{new table} \end{cases}$
- “Rich get richer” effect

Chinese Restaurant Process



Effect of back-off smoothing



Summary of Probabilistic Model

- Probability distribution over SR-TSG fragments
 - Pitman-Yor process as a prior
- 3-level hierarchy for back-off smoothing
 - SR-TSG \leftarrow SR-CFG \leftarrow RU-CFG
- Parsing accuracy(f-score): 91.1% on English PTB




Inference




Overview of Inference

What we want:



Overview of Inference


- MAP estimation: $\operatorname{argmax}_{\mathbf{Z}} p(\mathbf{Z} | \mathbf{T})$
- MCMC sampling for inference




Stepwise training:

1. Fix Train
2. Train Almost fixed


Overview of MCMC Sampling




Overview of MCMC Sampling




Overview of MCMC Sampling




Overview of MCMC Sampling




Overview of MCMC Sampling




Overview of MCMC Sampling




Overview of MCMC Sampling




Overview of MCMC Sampling




Overview of MCMC Sampling




Overview of MCMC Sampling



Overview of MCMC Sampling




Overview of MCMC Sampling



Inference of Symbol Refinement

Problem:

- Gibbs sampler is inefficient
Update only one variable at a time



Inference of Symbol Refinement

Proposal:

- 3 types of blocked samplers to find better solution

For each MCMC iteration...


- a) Run sentence sampler
- b) Run subtree sampler
- c) Run restaurant sampler

a) Sentence Sampler

- Metropolis-Hastings (MH) algorithm [Johnson et al. 07]







For each sentence...

1. Run inside algorithm
2. Sample a derivation
3. Accept or reject the sample



a) Sentence Sampler

- Update a sentence at a time









b) Subtree Sampler

- Update the same type of subtree simultaneously







b) Subtree Sampler

- Update the same type of subtree simultaneously









b) Subtree Sampler

- Update the same type of subtree simultaneously









b) Subtree Sampler

- Update the same type of subtree simultaneously









b) Subtree Sampler

- Update the same type of subtree simultaneously



b) Subtree Sampler

- Update the same type of subtree simultaneously




c) Restaurant Sampler

- Update # of tables

c) Restaurant Sampler

- Update # of tables




For each table label ...

- Keep count
- Remove all
- Add one by one

count = 6

Helpful for optimizing # of tables

Effect of MCMC Samplers



Summary of Inference


- MCMC sampling
- Stepwise training for the induction of latent variables
- 3 types of blocked samplers
 - Effective for finding better solution




Experiment



Parsing Accuracy



Final Result



- System combination [Zhang et al. 09]
- Self-training [Huang et al. 10]

are better than SR-TSG.

Conclusion

Approach:

SR-TSG = TSG + symbol refinement
- Fully automatic learning

Probabilistic Model:

Pitman-Yor process + 3-level hierarchy

Inference:

3 types of MCMC samplers for efficient training

Result:

State-of-the-art




Thank you.




Internal Subcategory Marginalization

- Encourage the model to find large tree fragments

S-0 count = 5



count = 8



S-0 count = 3

