## BLUETOOTH 4.1 VERSION SENSORS

| ITEM | PRODUCT | PICTURE | MODEL NO. | FEATURES | UNIT PRICE | |
|---|---|---|---|---|---|---|
| | | | | | 1000PCS | SAMPLE |
| 1 | Wall-mounted PIR Detector |  | QP-IX30_BLE | • 2.4G frequency, support BLE 4.1 version, backward compatible<br>• 3V 2PCS AA 1.5V battery, up to 2 years working life<br>• Current 15uA (standby), Alarm 5mA, 100m distance;<br>• 12m x 12m detection range, 110 degree,<br>• Imported dual passive IR; low noise structure<br>• Super Anti-false alarm ability<br><br>• Dimension: 110*62*47mm;   Packing Size: 138*70*60mm<br>• N.W: 0.135KG ;    G.W: 0.16KG | $9.80 | $12.50 |
| 2 | Ceiling PIR Detector |  | QP-IX32_BLE | • 2.4G frequency, support BLE 4.1 version, backward compatible<br>• 3V 2PCS AA 1.5V battery, up to 2 years working life<br>• Current 15uA (standby), Alarm 18mA, 100m distance;<br>• 12m x 12m detection range, 360 degree<br>•  Imported dibit passive IR; low noise structure<br>• Super Anti-false alarm ability<br><br>• Dimension: 100*100*33.5mm;   Packing Size: 110*123*44mm<br>• N.W: 0.14KG ;    G.W: 0.165KG | $9.60 | $12.00 |
| 3 | PIR Detector |  | QP-IX34_BLE | • 2.4G frequency, support BLE 4.1 version, backward compatible<br>• CR2450 battery, up to 2 years working life<br>• Current 15uA (standby), Alarm 18mA, 100m distance;<br>•  Imported dibit passive IR; low noise structure<br>• Super Anti-false alarm ability<br>• Dimension: 53*38*59mm (L*W*H) | $10.20 | $12.00 |
| 4 | Door Contact |  | QP-IM20_BLE | • 2.4G frequency, support BLE 4.1 version, backward compatible<br>• 3V 1PCS Lithium button battery, 2-3 years working life<br>• Current 15uA (standby), Alarm 5mA, 80m distance;<br>•  Anti-tamper alarm, self-check once in one hour<br>•  Imported reed switch, digital sending circuit<br>• Up to 16 million unduplicated encoding<br>• Low battery real-time detection<br><br>• Dimension: 78*49*19mm;   Packing Size: 102*57*27mm<br>• N.W: 0.08KG;     G.W: 0.09KG | $6.30 | $8.00 |
| 5 | Mini Door Contact |  | QP-IM21_BLE | • 2.4G frequency, support BLE 4.1 version, backward compatible<br>• Current 5uA (standby), Alarm 6mA, 80m distance;<br>•  Up to 16 million unduplicated encoding<br>• 3V 1PCS CR 2032 button battery, 2-3 years working life<br>• Real-time battery level checking<br><br>•  Dimension: 50*32*13mm | $5.30 | $7.00 |
| 6 | Door Contact |  | IM24_BLE | • 2.4G frequency, support BLE 4.1 version, backward compatible<br>• Current 5uA (standby), Alarm 6mA, 80m distance;<br>•  Up to 16 million unduplicated encoding<br>• 3V 1PCS CR 2032 button battery, 2-3 years working life<br>• Real-time battery level checking<br><br>•  Dimension:52*40*18mm | $5.30 | $6.00 |
| 7 | Smoke Detector |  | QP-ES61_BLE | • 2.4G frequency, support BLE 4.1 version, backward compatible<br>• Built-in alarm siren ≥85dB @ 1m<br>• Sensitivity: 1%~3 FT (0.14-0.43dB/m)<br>• Standby current ≤50uA, operating current ≤150mA<br>• With battery level monitoring, anti-tamper<br><br>• Dimension: 130*130*35mm;   Packing Size: 140*164*42mm<br>• N.W: 0.26KG;    G.W: 0.305KG | $12.50 | $15.00 |
| 8 | Gas detector |  | EN61_BLE | • 2.4G frequency, support BLE 4.1 version<br>• Built-in alarm siren ≥85dB @ 1m<br>• Alarm concentration 10%LEL+ 3%LEL<br>• 100~240V 50~60Hz AC power supply<br>• With anti-tamper alarm, 3 years working life<br>• Dimension: 130*130*35mm;   Packing Size: 140*164*42mm<br>• N.W: 0.265KG;    G.W: 0.31KG | $13.50 | $14.00 |
| 9 | Remote control |  | RC10_BLE | • 2.4G frequency, support BLE 4.1 version<br>• 4 buttons: away arm, disarm, home arm, SOS<br>• 3V 1PCS CR 2032 lithium button battery, 2-3 years battery life<br>• Standby current ≤1uA, operating current ≤15mA<br>• Dimension: 58*31*10mm; Packing Size: 66*34*17mm<br>• N.W: 0.03KG ; G.W: 0.035KG | $5.30 | $6.50 |
| 10 | Doorbell Button |  | RB50_BLE | • 2.4G frequency, support BLE 4.1 version<br>• DC3V, 1PCS CR2450 button battery, 3 years battery life<br>• Static current ≤1uA, working current ≤ 20mA<br><br>• Dimension: 69*43*17mm; | $5.30 | $7.50 |
| 11 | Water Leakage Sensor |  | QP-EW70_BLE | • 2.4G frequency, support BLE 4.1 version, backward compatible<br>• Working Voltage 3VDC (1PCS CR2450 button battery)<br>• Communication Distance 100m (open area)<br>• Static current t≤15uA<br>• transmit current ≤20mA（433/315M）≤35mA（868M）<br>• trigger report ,tamper report, battery level status report, heartbeat report<br>• Dimension 60*15mm(Dia*H) | $6.25 | $8.00 |
| 12 | Temperature& Humidity Sensor |  | QP-ET90_BLE | • 2.4G frequency, support BLE 4.1 version, backward compatible<br>• Working Voltage 3VDC (1PCS CR2032 button battery)<br>• Communication Distance 50m (open area)<br>• Static current t≤5uA<br>• transmit current ≤10mA<br>• trigger report ,tamper report, battery level status report, heartbeat report<br>• Dimension 36*36mm(Dia*H) | $7.81 | $9.00 |

**NOTES**

- Support OEM & ODM;
- Delivery: 12-18 working day after payment confirmed for sample order;
- Payment term: **EXW**, 50% deposit, 50% balance payment before shipment;
- Warranty: 1 year guarantee with maintenance and technical support;
- Quotation exclude VAT and shipping cost;
- The quotation sheet is valid in 1 month.