

The Hamiltonian Brain: Efficient Probabilistic Inference with Excitatory-Inhibitory Neural Circuit Dynamics¹

—
Modeling in neuroscience - and elsewhere

Hugo Simon

22/03/2022

école —
normale —
supérieure —
paris — saclay —

université
PARIS-SACLAY

¹Laurence Aitchison et al. (2016). "The Hamiltonian Brain: Efficient Probabilistic Inference with Excitatory-Inhibitory Neural Circuit Dynamics". In: *PLOS Computational Biology*.

① Introduction

- Reasoning under uncertainty
- How to implement Bayesian inference ?

② Methods

- MCMC framework
- Hamiltonian approach
- The Gaussian Scale Mixture model
- Implementing HMC

③ Results

- Face-like features
- Stimulus definition
- Stimulus vs. no-stimulus response
- Stimulus reconstruction
- Stimulus onset and stimulus offset
- Balanced EI network

④ Conclusion and perspectives

- Our brain operates in the face of substantial uncertainty due to ambiguity in the inputs, and inherent unpredictability in the environment.
- In such condition, reasoning under uncertainty is crucial for survival.
- The optimal way to do so is not making single-best point estimates but rather considering a whole weighted range of explanations, namely Bayesian inference.
- Some human behaviours are known to be consistent with Bayesian inference in many sensory, motor and cognitive tasks.



Figure 1: Principle of Bayesian inference

Current limitations are that

- traditional models of neural computation neglect uncertainty in favor of circuit dynamics that seek for the single best explanation of their inputs.
- they don't capture the rich dynamics of cortical responses. Neural activities in the cortex show **prominent intrinsic oscillations**, and **large transient changes** in response to stimulus onset.
- they typically violate Dales's law by having neurons with both excitatory and inhibitory outputs.

① Introduction

Reasoning under uncertainty
How to implement Bayesian inference ?

② Methods

MCMC framework
Hamiltonian approach
The Gaussian Scale Mixture model
Implementing HMC

③ Results

Face-like features
Stimulus definition
Stimulus vs. no-stimulus response
Stimulus reconstruction
Stimulus onset and stimulus offset
Balanced EI network

④ Conclusion and perspectives

- Markov Chain Monte Carlo (MCMC) methods are a class of methods for sampling from probability distributions.
- based on sequentially sampling new point from previous one such that the actual dynamic follows a Markov chains that have the target distribution as stationary laws.
- The higher the mixing rate, the faster the inference.




Figure 2: MCMC as Metropolis-Hastings.

- Idea: Introduce a latent space \mathbf{q} as momentum and treat the whole as an Hamiltonian system².

$$\dot{\mathbf{q}} = \frac{\partial \mathcal{H}}{\partial \mathbf{p}}, \quad \dot{\mathbf{p}} = -\frac{\partial \mathcal{H}}{\partial \mathbf{q}}$$

with for instance

$$\mathcal{H}(\mathbf{q}, \mathbf{p}) = -\ln f(\mathbf{q}) + \frac{1}{2} \|\mathbf{p}\|_M^2,$$

- Hamiltonian dynamic proposes moves to distant states which maintain high acceptance probability due to approximate energy conserving property.




Figure 3: HMC yields higher mixing rate and acceptance ratio than MH.

Generative model defined as




Figure 4: A. GSM graphical model. B. edge-like features \mathbf{A} .

$$\begin{aligned} \mathbf{u} &\sim \mathcal{N}(0, C) \quad \text{where} \quad C = (1 - \sigma_{\mathbf{x}}^2)(\mathbf{A}^\top \mathbf{A})^{-1} \\ z &\sim |\mathcal{N}(0, 1)| \\ \mathbf{x} \mid \mathbf{u}, z &\sim \mathcal{N}(z\mathbf{A}\mathbf{u}, \sigma_{\mathbf{x}}^2 \mathbf{I}) \end{aligned}$$

- widely used statistical model of natural images³.
- latent variable \mathbf{u} known to account for *stationary* responses of V1 neurons.
- latent variable z known to account for complex-cell activations.

³Martin J Wainwright et al. (1999). "Scale Mixtures of Gaussians and the Statistics of Natural Images". In: *Advances in Neural Information Processing Systems*. Vol. 12. MIT Press.

Defining the Excitatory-Inhibitory network

$$\dot{\mathbf{u}} = \frac{1}{\tau} \left[\mathbf{W}_{uu} \mathbf{u} - \mathbf{W}_{uv} \mathbf{v} + \frac{1}{2} \tau \rho^2 \mathbf{I}_{\text{input}} \right] + \rho \boldsymbol{\eta}_{\mathbf{u}}$$

$$\dot{\mathbf{v}} = \frac{1}{\tau} [\mathbf{W}_{vu} \mathbf{u} - \mathbf{W}_{vv} \mathbf{v} - \mathbf{I}_{\text{input}}] + \rho \boldsymbol{\eta}_{\mathbf{v}}$$

where

$$\mathbf{I}_{\text{input}} = \frac{z}{\sigma_{\mathbf{x}}^2} \mathbf{A}^T (\mathbf{x} - z \mathbf{A} \mathbf{u}) - \mathbf{C}^{-1} \mathbf{u}$$




Figure 5: EI Hamiltonian network architecture.

This implements noised HMC for the GSM posterior distribution !

1 Introduction

- Reasoning under uncertainty
- How to implement Bayesian inference ?

2 Methods

- MCMC framework
- Hamiltonian approach
- The Gaussian Scale Mixture model
- Implementing HMC

3 Results

- Face-like features
- Stimulus definition
- Stimulus vs. no-stimulus response
- Stimulus reconstruction
- Stimulus onset and stimulus offset
- Balanced EI network

4 Conclusion and perspectives

- GSM with edge-like features (Gabor filters) capture statistics of natural image but not very realist looking.
- We factorize face dataset with Multiplicative Update (MU) algorithm to get face-like features.




Figure 6: Face-like features obtained from NNMF of a face dataset.

- Recall

$$\mathbf{u} \sim \mathcal{N}(0, C)$$


$$z \sim |\mathcal{N}(0, 1)|$$

$$\mathbf{x} \mid \mathbf{u}, z \sim \mathcal{N}(z\mathbf{A}\mathbf{u}, \sigma_{\mathbf{x}}^2\mathbf{I})$$

- Stimulus is when z is large, no-stimulus is when z is close to zero,



(a) Stimulus



(b) No-stimulus

Stimulus vs. no-stimulus response





Figure 8: EI HMC and EI Langevin ($W=0$) behaviours under no-stimulus and stimulus.

What does reconstructed observation from inferred variables looks like ?



(a) Stimulus reconstruction among sampling.



(b) No-stimulus reconstruction among sampling.

In practice, decision is made from not a single but a distribution of samples across time, i.e. frequency estimates posterior probability.






Figure 10: EI HMC and EI Langevin ($\mathbf{W}=0$) behaviours under stimulus onset and offset.

- $\mathbf{W}_{uu}\mathbf{u} - \mathbf{W}_{uv}\mathbf{v}$ and $\mathbf{W}_{vu}\mathbf{u} - \mathbf{W}_{vv}\mathbf{v}$ are respectively activation of excitatory cells and inhibitory cells.
- For stable sampling from the posterior, excitation and inhibition should be balanced.
 - For EI Langevin, \mathbf{W} always 0.
 - For EI HMC, net excitation and net inhibition can be momentarily imbalanced to perform better.



(a) excitatory and inhibitory inputs among sampling.



(b) excitatory inputs vs. inhibitory inputs.

- Note transient increases in firing rates upon stimulus onset and offset.

① Introduction

- Reasoning under uncertainty
- How to implement Bayesian inference ?

② Methods

- MCMC framework
- Hamiltonian approach
- The Gaussian Scale Mixture model
- Implementing HMC

③ Results

- Face-like features
- Stimulus definition
- Stimulus vs. no-stimulus response
- Stimulus reconstruction
- Stimulus onset and stimulus offset
- Balanced EI network

④ Conclusion and perspectives

Conclusion

- Relatively simple and highly efficient Bayesian inference ☒
- Dales's principle compliant ☒
- Prominent intrinsic and **functionally explainable** cortical oscillations ☒
- Transient increase in firing rates upon stimulus onset and offset ☒

Perspectives

- EI HMC architecture rely on GMS model, but even with face-like features, GMS does not capture natural images notions such as object and obstruction.
- How local learning rules may be able to set up weights needed for implementing EI HMC ?

- Aitchison, Laurence et al. (2016). "The Hamiltonian Brain: Efficient Probabilistic Inference with Excitatory-Inhibitory Neural Circuit Dynamics". In: *PLOS Computational Biology*.
- Duane, Simon et al. (1987). "Hybrid Monte Carlo". In: *Physics Letters B* 195.2, pp. 216–222.
- Wainwright, Martin J et al. (1999). "Scale Mixtures of Gaussians and the Statistics of Natural Images". In: *Advances in Neural Information Processing Systems*. Vol. 12. MIT Press.

Thank you!