

Data challenge: link predictions in a graph of citations with abstracts and co-authors.

Hugo SIMON, Enguerrand CHARY, Samuel GRUFFAZ

Presentation

Tuesday, 15 February 2022

Source of informations:

- Citations between papers, $G = (V, E)$ (undirected graph).
- Abstract associated to each paper.
- coauthors relations.
- Surprisingly, we don't have time information ! It forces us to be agnostic of the underlying time process.

In real life, two types of reasons for citing a paper:

- We cite a paper because it treats the topic where we work.
(information coming from the abstract)
- We cite a paper because it is the paper of a friend.
(information coming from the authors network)




Figure: Summary scheme of our pipeline, mettre notre score final

Pre-processing:

- SciBERT is a BERT Architecture retrained on a corpus of scientific paper (with a big part of computer science paper). We load it 2 from hugging face. Each abstracts i was embedded with a vector f_t of dimension 768.
- For the co-authorship graph, there is an edge between author i and j if they have written a paper together.

The principle of TADW is a matrix factorization:

$$\operatorname{argmin}_{W,H} \|M - W^T H T\|_{frob}^2 + \lambda(\|W\|_{frob}^2 + \|H\|_{frob}^2), \quad \lambda > 0$$

where:

- $M = \frac{1}{2}(\bar{A} + \bar{A}^2)$, \bar{A} the normalized adjacency matrix of $G = (V, E)$.
- $T \in \mathbb{R}^{n_v \times 768}$, the abstracts features.
- $W \in \mathbb{R}^{n_v \times k}$, the structure features, k an hyper-parameter.
- $H \in \mathbb{R}^{k \times d}$ a transformation to create an interaction between W and T .




Figure: Matrix factorization.

We used Node2Vec to have a numerical representation of authors proximity.

- 2nd Order random Walk
- applies a bias factor α to reweigh the edge weights depending on the previous state.
- α is a function that takes as inputs the current node and the potential next node.
- gives a good and homogeneous exploration of information

Putting together

Finally, we put all together.

- Article author features are made by concatenating average author embeddings and the embeddings of the 2 closest authors for each pair of articles. The idea is that the likelihood of citation between 2 articles depends on the proximity of its closest authors.
- Article final features are made by concatenating article TADW features and article author features.



Training set (x_i, y_i) for a classification task:

- All existing edges are added with label $y = 1$.
- We sample the same number of non-existing edges with label $y = 0$.
- We concatenate the article features associated to the two nodes of an edge to get the final features (x_i) . We double the size of our dataset by permuting nodes features in the concatenation to enforce the invariance due to undirected edges.

The classifier:

- MLP classifier with 5 hidden dense layers, LeakyReLU activation function, and 0.3 dropout rate.




Figure: Loss plot of our final training

We reach a validation loss of 0.1434 but only score 0.1613 submitting prediction to the challenge, which means our dataset is not exactly representative of the scoring set.

Interpretation of some phenomenons:

- When we add the features related to co-authorship, we decrease the loss by 0.04. There is a real source of information in the relations information.
- Little improvement between $k = 150$ and $k = 300$, we can reduce the dimension of text features !

If we want to do better:

- Adding features in the co-authorship graph with topic modeling and process it with TADW or something else.
- Work differently with pluridisciplinary papers and cross-domain collaboration [1].
- Using a directed graph to compute fisher information metrics related to citations.



Jie Tang, Sen Wu, Jimeng Sun, and Hang Su.

Cross-domain collaboration recommendation.

In Proceedings of the 18th ACM SIGKDD international conference on Knowledge discovery and data mining, pages 1285–1293, 2012.



David Liben-Nowell and Jon Kleinberg.

The link-prediction problem for social networks.

Journal of the American society for information science and technology, 58(7):1019–1031, 2007.



Robin Brochier, Adrien Guille, and Julien Velcin.

Link prediction with mutual attention for text-attributed networks.

In Companion Proceedings of The 2019 World Wide Web Conference, pages 283–284, 2019.



Cheng Yang, Zhiyuan Liu, Deli Zhao, Maosong Sun, and Edward Chang.

Network representation learning with rich text information.

In *Twenty-fourth international joint conference on artificial intelligence*, 2015.



Peng Wang, BaoWen Xu, YuRong Wu, and XiaoYu Zhou.
Link prediction in social networks: the state-of-the-art.
Science China Information Sciences, 58(1):1–38, 2015.



Iz Beltagy, Kyle Lo, and Arman Cohan.
Scibert: A pretrained language model for scientific text.
In *EMNLP*. Association for Computational Linguistics, 2019.



Hsiang-Fu Yu, Prateek Jain, Purushottam Kar, and Inderjit Dhillon.
Large-scale multi-label learning with missing labels.
In *International conference on machine learning*, pages 593–601. PMLR, 2014.