

## 7.1 — Compound statements (blocks)

 **ALEX**  **SEPTEMBER 11, 2023**

A **compound statement** (also called a **block**, or **block statement**) is a group of zero or more statements that is treated by the compiler as if it were a single statement.

Blocks begin with a `{` symbol, end with a `}` symbol, with the statements to be executed being placed in between. Blocks can be used anywhere a single statement is allowed. No semicolon is needed at the end of a block.

You have already seen an example of blocks when writing functions, as the function body is a block:

```
int add(int x, int y)
{ // start block
    return x + y;
} // end block (no semicolon)

int main()
{ // start block

    // multiple statements
    int value {}; // this is initialization, not a block
    add(3, 4);

    return 0;

} // end block (no semicolon)
```

### Blocks inside other blocks

Although functions can't be nested inside other functions, blocks can be nested inside other blocks:

```
int add(int x, int y)
{ // block
    return x + y;
} // end block

int main()
{ // outer block

    // multiple statements
    int value {};

    { // inner/nested block
        add(3, 4);
    } // end inner/nested block

    return 0;

} // end outer block
```

When blocks are nested, the enclosing block is typically called the **outer block** and the enclosed block is called the **inner block** or **nested block**.

---

## Using blocks to execute multiple statements conditionally

One of the most common use cases for blocks is in conjunction with `if statements`. By default, an `if statement` executes a single statement if the condition evaluates to `true`. However, we can replace this single statement with a block of statements if we want multiple statements to execute when the condition evaluates to `true`.

For example:

```
#include <iostream>

int main()
{ // start of outer block
    std::cout << "Enter an integer: ";
    int value {};
    std::cin >> value;

    if (value >= 0)
    { // start of nested block
        std::cout << value << " is a positive integer (or zero)\n";
        std::cout << "Double this number is " << value * 2 << '\n';
    } // end of nested block
    else
    { // start of another nested block
        std::cout << value << " is a negative integer\n";
        std::cout << "The positive of this number is " << -value << '\n';
    } // end of another nested block

    return 0;
} // end of outer block
```

If the user enters the number 3, this program prints:

```
Enter an integer: 3
3 is a positive integer (or zero)
Double this number is 6
```

If the user enters the number -4, this program prints:

```
Enter an integer: -4
-4 is a negative integer
The positive of this number is 4
```

---

## Block nesting levels

It is even possible to put blocks inside of blocks inside of blocks:

```
#include <iostream>

int main()
{ // block 1, nesting level 1
  std::cout << "Enter an integer: ";
  int value {};
  std::cin >> value;

  if (value > 0)
  { // block 2, nesting level 2
    if ((value % 2) == 0)
    { // block 3, nesting level 3
      std::cout << value << " is positive and even\n";
    }
    else
    { // block 4, also nesting level 3
      std::cout << value << " is positive and odd\n";
    }
  }

  return 0;
}
```

The **nesting level** (also called the **nesting depth**) of a function is the maximum number of nested blocks you can be inside at any point in the function (including the outer block). In the above function, there are 4 blocks, but the nesting level is 3 since in this program you can never be inside more than 3 blocks at any point.

The C++ standard says that C++ compilers should support 256 levels of nesting -- however not all do (e.g. as of the time of writing, Visual Studio supports less).

It's a good idea to keep your nesting level to 3 or less. Just as overly-long functions are good candidates for refactoring (breaking into smaller functions), overly-nested blocks are hard to read and are good candidates for refactoring (with the most-nested blocks becoming separate functions).

### Best practice

Keep the nesting level of your functions to 3 or less. If your function has a need for more nested levels, consider refactoring your function into sub-functions.



### [Next lesson](#)

**7.2** [User-defined namespaces and the scope resolution operator](#)



### [Back to table of contents](#)



### [Previous lesson](#)

**0.4** [Converting integers between binary and decimal representation](#)

Leave a comment...

Name\*

@ Email\*

?

Notify me about replies:



POST COMMENT

Find a mistake? Leave a comment above!

Avatars from <https://gravatar.com/> are connected to your provided email address.

114 COMMENTS

Newest ▾

We and our partners share information on your use of this website to help improve your experience.

Do not sell my info: ☐

OKAY

