

## Supplementary Notes

### Supplementary Note 1: Distance metric for clustering algorithm

Assume there are 2 Poisson distributions  $P_1$  and  $P_2$  with density functions

$$p_1(x, \lambda_1) = \frac{e^{-\lambda_1} \lambda_1^x}{\Gamma(x+1)}$$

and

$$p_2(x, \lambda_2) = \frac{e^{-\lambda_2} \lambda_2^x}{\Gamma(x+1)}$$

The Kullback-Leibner divergence from  $P_2$  to  $P_1$  is defined as:

$$D_{KL}(P_1||P_2) = \int_{-\infty}^{\infty} p_1(x) \log \frac{p_1(x)}{p_2(x)} dx$$

or in other words, it is the expectation of the logarithmic difference between the probabilities  $P_1$  and  $P_2$ , where the expectation is taken with regard to  $P_1$ .

The log ratio of the density functions is

$$\log \frac{p_1(x)}{p_2(x)} = x \log \frac{\lambda_1}{\lambda_2} + \lambda_2 - \lambda_1$$

take expectation of this expression with regard to  $P_1$  with mean  $\lambda_1$  we have

$$D_{KL}(P_1||P_2) = \lambda_1 \log \frac{\lambda_1}{\lambda_2} + \lambda_2 - \lambda_1$$

The metric we used is the distance defined as

$$D(P_1, P_2) = \frac{D_{KL}(P_1||P_2) + D_{KL}(P_2||P_1)}{2} = \frac{1}{2}(\lambda_1 - \lambda_2)(\log \lambda_1 - \log \lambda_2)$$

### Supplementary Note 2: Coverage re-estimation

The re-estimation is basically carried out by following two steps.

1. From nodes coverage, estimate edges' value by quadratic unconstrained optimization of the least-square function:

$$\frac{1}{2} \sum_i l_i ((\sum e_i^+ - c_i)^2 + (\sum e_i^- - c_i)^2)$$

where  $l_i$  and  $c_i$  is the length and coverage of a node  $i$  in the graph;

$\sum e_i^+$  and  $\sum e_i^-$  indicates sum of the values of incoming and outgoing edges from  $i$  respectively. The above function can be rewritten as:

$$f(x) = \frac{1}{2} x^T Q x + b^T x + r$$

and then being minimized by using gradient-based method.


2. Update nodes' coverage based on itself and its neighbor edges' measures.

The calibration is iterative until no further improvements are made or a threshold loop count is reached.

### Supplementary Note 3: Constructing bridges in real-time

A bridge has 4 levels of completion, ranging from 1 to 4 depends on how close to finish it is. When a new bridge is built with only one unique ending, it has level 1. If both endings are identified, its completion level is 2. Only then, a path finding algorithm is applied to find candidate paths of this bridge. When potential paths (more than 1) are listed successfully, the completion level is increased to 3. Finally, when the only path solution is determined out of all candidates, the bridge is assigned as completely built with level 4.

In the early stages (level 1 or 2), a bridge is constructed progressively by alignments from long reads that spanning its corresponding anchor(s).



Supplementary Figure 1: Bridge merging progressively in real-time. Long reads generate alignments to the contigs where new bridges are created respectively. Bridges sharing same anchors can be merged together to form the ultimate, more comprehensive bridge (with more spans and better approximation about distances between them).

---

**Algorithm 1:** Pseudo-code for finding paths connecting a bridge with 2 ends.

---

**Data:** Assembly graph  $G\{V, E\}$   
**Input:** Bridge  $B = (\vec{v}_1, \vec{v}_2)$  with two ending unique bidirected nodes  $\vec{v}_1, \vec{v}_2$   
**Output:** Set of candidate paths  $P$  connecting  $B$

```

1 begin
2    $d := B.length()$                                      // length of the bridge or the distance between 2 ending nodes
3    $M := shortestTree(\vec{v}_2, d)$                            // build shortest tree from  $\vec{v}_2$  with range  $d$ 
4   if  $M.contains(\vec{v}_1)$  then
5      $S := new Stack()$                                      // stack of sets of edges to traverse
6      $edgesSet := getEdges(\vec{v}_1)$                          // get all bidirected edges going from  $\vec{v}_1$ 
7      $S.push(edgesSet)$ 
8      $p := new Path(\vec{v}_1)$                                // init a path that has  $\vec{v}_1$  as root
9     while true do
10       $edgesSet := S.peek()$ 
11      if  $edgesSet.isEmpty()$  then
12        if  $p.size() \leq 1$  then
13          break                                           // stop the loop when there is no more edge to discover
14         $S.pop()$ 
15         $d += p.peekNode.length() + p.popEdge().length()$ 
16      else
17         $curEdge := edgesSet.remove()$ 
18         $\vec{v} := curEdge.getOpposite(p.peekNode())$ 
19         $S.push(getEdges(\vec{v}).includedIn(M))$ 
20         $p.add(curEdge)$ 
21        if reach  $\vec{v}_2$  with reasonable  $d$  then
22           $P.add(p)$ 
23           $d = \vec{v}.length() + curEdge.length()$ 
24   return  $P$ 

```

---

## Supplementary Note 4: Path finding algorithm

Algorithm 1 demonstrates the path finding module in general. In which, function

$\text{shortestTree}(\text{vertex}, \text{distance}) : (V, Z) \rightarrow V^n$

from line 3 of the algorithm's pseudo code builds a shortest tree rooted from  $\vec{v}$ , following its direction until a distance of approximately  $d$  (with a tolerance regarding nanopore read error rate) is reached. This task is implemented based on Dijkstra algorithm. This tree is used on line 4 and in function *includedIn()* on line 19 to filter out any node or edge with ending nodes that do not belong to the tree.


Basically, the algorithm keeps track of a stack that contains sets of candidate edges to discover. During the traversal, a variable  $d$  is updated as an estimation for the distance to the target. A hit is reported if the target node is reached with a reasonable distance *i.e.* close to zero, within a given tolerance (line 21). A threshold for the traversing depth is set (150) to ignore too complicated and time-consuming path searching.

It is worth to mention that the *length()* functions for node and edge are totally different. While the former returns the length of the sequence represented by the node, *i.e.* contig from short-read assembly, the latter is usually negative because an edge models a link between two nodes, which is normally an overlap (except for composite edges). For example, in a  $k$ -mers SPAdes assembly graph, the value of an edge is  $-k + 1$ .

On the other hand, if external binning algorithm is employed, the resulting output must be converted into a text file that specifies the corresponding bin of every contigs. By that, each line of the file would be: `< contig_ID > < bin.ID >` where `bin.ID = 0` indicates unspecified binned contigs.

## Supplementary Note 5: Graph decomposing for output report

A path  $p = \{v_0, e_1, v_1, \dots, v_{k-1}, e_k, v_k\}$  of size  $k$  is considered as straight if every edge along the path,  $e_i, \forall i = 1, \dots, k$ , must be the only option to traverse from either  $v_{i-1}$  or  $v_i$  following the transition rule. To decompose the graph, we can just simply mask out all incoming/outgoing edges rooted from any node with in/out degree greater than 1 as demonstrated in Figure 2. These edges are defined as branching edges which stop straight paths from further extending.



Supplementary Figure 2: Example of graph decomposition into longest straight paths. Branching edges are masked out (shaded) leaving only straight paths (bold colored) to report. There would be 3 contigs extracted by traversing along the straight paths here.

The decomposed graph is only used to report the contigs that can be extracted from an assembly graph at certain time point. For that reason, the branching edges are only masked but not removed from the original graph as they would be used for further bridging.

## Supplementary Figures and Tables

Supplementary Table 1: Benchmarking npGraph against npScarf versions, hybridSPAdes and Unicycler hybrid assembler with the synthetic data set.

Method	Assembly size (bp)	#Contigs	N50 (bp)	Mis-assemblies	Mismatch (per 100Kbp)	Indel (per 100Kbp)
random sequences no repeats						
npScarf	4110000	3	4000000	0	0.00	0.00
npScarf_wag	4109516	3	4000000	0	0.00	0.00
npGraph-bwa	4110000	3	4000000	0	0.00	0.00
npGraph-mm2	4110000	3	4000000	0	0.00	0.00
hybridSPAdes	4110231	3	4000077	0	0.00	0.07
Unicycler	4110000	3	4000000	0	0.00	0.00
random sequences some repeats						
npScarf	4110940	3	4002715	0	0.00	0.66
npScarf_wag	4437094	7	2795129	0	0.00	1.07
npGraph-bwa	4110000	3	4000000	0	0.00	0.00
npGraph-mm2	4110000	3	4000000	0	0.00	0.00
hybridSPAdes	4107566	3	3999364	0	0.02	0.02
Unicycler	4110000	3	4000000	0	0.00	0.00
random sequences many repeats						
npScarf	4316934	8	3963485	24	11.55	34.54
npScarf_wag	5215965	16	1515563	37	0.32	7.22
npGraph-bwa	4110000	3	4000000	0	0.32	0.15
npGraph-mm2	4110000	3	4000000	0	0.32	0.15
hybridSPAdes	4108190	3	3999621	0	0.68	0.15
Unicycler	4110000	3	4000000	0	0.32	0.15
<i>Acinetobacter</i> A1						
npScarf	3912299	3	3870269	4	4.74	13.02
npScarf_wag	3945166	3	3906368	1	7.00	14.02
npGraph-bwa	3918374	2	3909643	0	16.34	0.61
npGraph-mm2	3885898	2	3877167	1	18.05	1.03
hybridSPAdes	3929948	53	3353679	0	35.48	3.22
Unicycler	3917745	2	3909014	0	2.50	0.13
<i>Acinetobacter</i> AB30						
npScarf	4512464	7	4304628	35	57.95	72.87
npScarf_wag	5315235	13	1267710	136	73.55	8.15
npGraph-bwa	4335342	2	4148952	1	16.93	1.45
npGraph-mm2	4335790	1	4335790	0	6.97	0.25
hybridSPAdes	4337369	3	2701005	0	12.80	1.39
Unicycler	4333041	1	4333041	1	6.42	0.53
<i>E. coli</i> K12 MG1655						
npScarf	4649902	2	4641702	4	14.94	34.35
npScarf_wag	4687952	3	4641732	0	6.55	1.96
npGraph-bwa	4641743	1	4641743	0	4.50	0.43
npGraph-mm2	4641820	1	4641820	0	3.88	0.26
hybridSPAdes	4644555	1	4641036	0	0.62	0.09
Unicycler	4641650	1	4641650	0	3.43	0.26
<i>E. coli</i> O25b H4-ST131						
npScarf	5245913	3	5095571	7	7.05	18.81
npScarf_wag	5292700	3	3469617	9	9.03	1.55
npGraph-bwa	5237821	7	4049493	1	3.38	0.31
npGraph-mm2	5249799	3	5110117	0	2.40	0.15
hybridSPAdes	5252762	8	4258948	2	5.43	0.57
Unicycler	5249442	3	5109760	0	4.02	0.27


Continued on next page

Supplementary Table 1 – Continued from previous page


Method	Assembly size (bp)	#Contigs	N50 (bp)	Mis- assemblies	Mismatch (per 100Kbp)	Indel (per 100Kbp)
<i>Klebsiella</i> 30660 NJST258 1						
npScarf	5559772	7	5259053	4	17.18	13.48
npScarf_wag	5613780	7	5268535	6	1.59	1.92
npGraph-bwa	5534843	8	5263229	0	3.15	0.76
npGraph-mm2	5534878	8	5263264	0	2.75	0.74
hybridSPAdes	5545668	8	5545668	2	4.95	0.09
Unicycler	5537860	9	5263196	0	1.34	0.51
<i>Klebsiella</i> MGH 78578						
npScarf	5729304	5	5316429	12	14.90	20.27
npScarf_wag	5754443	5	3026286	16	8.17	2.56
npGraph-bwa	5695801	7	5311745	1	12.65	1.25
npGraph-mm2	5696302	6	5315267	0	6.06	0.44
hybridSPAdes	5706470	11	5315273	1	3.82	0.67
Unicycler	5694231	14	5315096	0	5.38	0.21
<i>Klebsiella</i> NTUH-K2044						
npScarf	5471696	2	5249198	6	4.82	8.55
npScarf_wag	5530559	3	5249369	2	2.25	1.35
npGraph-bwa	5472629	2	5248476	0	2.52	0.31
npGraph-mm2	5472655	2	5248503	0	1.21	0.26
hybridSPAdes	5473572	2	5248894	0	0.44	0.15
Unicycler	5472697	2	5248545	0	2.41	0.35
<i>Mycobacterium tuberculosis</i> H37Rv						
npScarf	4498245	4	4402238	8	5.15	2.68
npScarf_wag	4506056	4	4410942	3	6.81	2.59
npGraph-bwa	4411406	1	4411406	0	1.88	0.43
npGraph-mm2	4411532	1	4411532	0	0.68	0.00
hybridSPAdes	4413942	1	4410519	0	0.75	0.11
Unicycler	4411538	1	4411538	0	2.22	0.34
<i>Saccharomyces cerevisiae</i> S288c						
npScarf	11986800	24	796769	51	62.12	21.46
npScarf_wag	12003203	21	917017	21	69.14	5.47
npGraph-bwa	11921736	40	913090	3	38.04	1.94
npGraph-mm2	11920984	38	913198	2	20.66	0.95
hybridSPAdes	12027533	45	770543	5	32.58	1.94
Unicycler	11847655	72	909114	0	21.81	1.04
<i>Shigella dysenteriae</i> Sd197						
npScarf	4586075	173	36560	55	120.14	111.59
npScarf_wag	5462918	92	98791	105	147.48	79.28
npGraph-bwa	4564058	6	4369264	5	80.64	11.16
npGraph-mm2	4558920	6	4364264	7	75.51	10.98
hybridSPAdes	4519131	23	821249	96	9.57	1.42
Unicycler	4560901	3	4369231	0	11.88	1.05
<i>Shigella sonnei</i> 53G						
npScarf	6441461	20	1953896	82	164.02	219.52
npScarf_wag	-	-	-	-	-	-
npGraph-bwa	5211544	4	4988532	0	14.53	0.31
npGraph-mm2	5211527	4	4988519	0	8.56	0.17
hybridSPAdes	5223875	8	2195455	2	41.92	0.06
Unicycler	5220517	5	4988548	0	7.39	0.52
<i>Streptococcus suis</i> BM407						
npScarf	2183951	3	2146594	0	21.51	9.17
npScarf_wag	2289880	3	1493189	1	3.17	1.96
npGraph-bwa	2154623	6	2131479	1	5.25	0.28
npGraph-mm2	2149876	6	2146774	0	1.44	0.28
hybridSPAdes	2172703	2	2146237	0	6.82	0.09
Unicycler	2170829	2	2146250	0	2.67	0.32



(a) *Citrobacter freundii* CAV1374




(b) *Klebsiella oxytoca* CAV1015




(c) *Enterobacter cloacae* CAV1411

Supplementary Figure 1: Dotplot generated by MUMmer for assembly results of **Unicycler** versus **npGraph**. Structural agreements between two methods were found in (a) *C.frendii* and (b) *K.oxytoca* assembly contigs. On the other hand, for (c) *E.cloacae* sample, there was a disagreement detected between 2 largest contigs given by two assembly algorithms. This case is investigated more thoroughly by using a reference from a same bacterial strain in Figure 2.



(a) *E. cloacae* Unicycler assembly versus reference genome



(b) *E. cloacae* npGraph assembly versus reference genome

Supplementary Figure 2: Alignments of an *Enterobacter cloacae* reference genome to assembly sequences generated by (a) Unicycler and (b) npGraph. While the former presents a structural variant, the latter is virtually an 1-to-1 mapping.