

A Declarative Semantics for SNOMED CT Expression Constraints

January 26, 2015

Contents

1	Axiomatic Data Types	2
1.1	Atomic Data Types	2
1.2	Composite Data Types	3
2	The Substrate	3
2.1	Substrate Components	4
2.2	Substrate	4
3	Result	6
4	Interpretation of Intermediate Constructs	6
4.1	expressionConstraint	7
4.1.1	Interpretation	7
4.1.2	unrefinedExpressionConstraint	7
4.1.3	refinedExpressionConstraint	8
4.2	simpleExpressionConstraint	8
4.3	compoundExpressionConstraint	8
4.4	conjunctionExpressionConstraint	9
4.5	disjunctionExpressionConstraint	10
4.6	exclusionExpressionConstraint	10
4.7	subExpressionConstraint	10
4.8	refinement	11
4.9	expressionConstraintValue	12
4.10	Attributes and Attribute Groups	13
4.11	AttributeName and AttributeSubject	13
4.12	Attribute	13
4.13	AttributeSet and AttributeGroup	15
4.14	Compound attribute evaluation	16
4.15	Group Cardinality	17
4.16	Cardinality	18

5	Substrate Interpretations	19
5.1	AttributeExpressionConstraint	19
5.2	ConcreteAttributeConstraint	20
5.3	ConstraintOperator	21
5.4	FocusConcept	21
5.4.1	memberOf	22
5.5	ConceptReference	22
6	Glue and Helper Functions	22
6.1	Types	23
6.2	Result transformations	23
7	Appendix 1	25

1 Axiomatic Data Types

1.1 Atomic Data Types

This section identifies the atomic data types that are assumed for the rest of this specification, specifically:

- **SCTID** – a SNOMED CT identifier
- **TERM** – a fully specified name, preferred term or synonym for a SNOMED CT Concept
- **REAL** – a real number
- **STRING** – a string literal
- **GROUP** – a role group identifier
- \mathbb{N} – a non-negative integer
- \mathbb{Z} – an integer

We also introduce several synonyms for *SCTID*: **TODO:** change SUBJECT to SOURCE

- **SUBJECT** – a *SCTID* that appears in the *sourceId* position of a relationship.
- **ATTRIBUTE** – a *SCTID* that appears in the *typeId* position of a relationship.
- **REFSETID** – a *SCTID* that identifies a reference set

[*SCTID*, *TERM*, *REAL*, *STRING*, *GROUP*]

SUBJECT == *SCTID*

ATTRIBUTE == *SCTID*

REFSETID == *SCTID*

1.2 Composite Data Types

While we can't fully specify the behavior of the concrete data types portion of the specification at this point, it is still useful to spell out the anticipated behavior on an abstract level.

- **CONCRETEVALUE** – a string, integer or real literal
- **TARGET** – the target of a relationship that is either an SCTID or a CONCRETEVALUE

$$\begin{aligned} \text{CONCRETEVALUE} &::= \text{string}\langle\langle\text{STRING}\rangle\rangle \mid \text{integer}\langle\langle\mathbb{Z}\rangle\rangle \mid \text{real}\langle\langle\text{REAL}\rangle\rangle \\ \text{TARGET} &::= \text{object}\langle\langle\text{SCTID}\rangle\rangle \mid \text{concrete}\langle\langle\text{CONCRETEVALUE}\rangle\rangle \end{aligned}$$

2 The Substrate

A substrate represents the context of an interpretation. A substrate consists of:

- **c** The set of *SCTIDs* (concepts) that are considered valid in the context of the substrate. **References to any *SCTID* that is not a member of this set MUST be treated as an error.**
- **a** The set of *SCTIDs* that are considered to be valid attributes in the context of the substrate. **Reference to any *ATTRIBUTE* that is not a member of this set MUST be treated as an error.**
- **r** A set of relationship quads (subject, attribute, target, group)
- **descs** The subsumption (ISA) closure from general to specific (descendants)
- **ancs** The subsumption (ISA) closure from specific to general (ancestors)
- **refset** The reference sets within the context of the substrate whose members are members are concept identifiers (i.e. are in *c*). While not formally spelled out in this specification, it is assumed that the typical reference set function would be returning a subset of the *refsetId/referencedComponentId* tuples represented in one or more RF2 Refset Distribution tables.

Issue: this is currently the simplest possible kind of Substrate; it represents the DNF form of SNOMED CT with concepts only (i.e., *Expressions* and *Expression Libraries* are not supported).

Issue: this is a *flat* representation (fixed to 1 level of nesting corresponding to role grouping) and does not properly handle Concrete Domains (which almost always involve additional nesting)

Open questions: While the Core will not contain cycles, and probably NRC Extensions will not, arbitrary extensions (e.g. as a result of handling Expression libraries) may involve cycles (or at least equivalent concepts).

- **Resolution:** A reflexive, symmetric equivalence relationship (*equiv*) was added to the substrate. How it is determined is left unspecified, but a rule

was added saying that an equivalent concept can not be a descendant of its equivalence.

- Is it correct to interpret the transitive closure directly against the substrate relationships (r) set or is there an implication of a reasoner being invoked somewhere, which could potentially render the transitive closure as logically derived from (r). **Answer:** If substrate includes postcoordinated expressions then subsumption would need to be calculated. **Followup:** How does one know whether it includes postcoordinated expressions? How do we express this decision formally?
- Do we want to assert that it is an error to use a non-attribute concept in a attribute position? If not, should we explicitly include a formal definition of the attribute set? **Answer:** Because the ECL doesn't declare this as an error condition, we shouldn't assert in the Z spec. **Resolution:** $a = \text{descs attribute_concept}$ assertion pulled from the substrate declaration.

2.1 Substrate Components

Quad Relationships in the substrate are represented a 4 element tuples or “Quads”, which consist of a subject, attribute, target and role group identifier.

<i>Quad</i>
$s : SUBJECT$
$a : ATTRIBUTE$
$t : TARGET$
$g : GROUP$

We will also need to recognize some ”well known” identifiers: the *is_a* attribute, the *zero_group* and *attribute_concept*, the parent of all attributes

$is_a : ATTRIBUTE$
$zero_group : GROUP$
$attribute_concept : SCTID$
$refset_concept : SCTID$

2.2 Substrate

The formal definition of substrate follows, where c and r are given and the remainder are derived. The expressions below assert that:

1. All subjects and attributes and targets of type *object* in r must be members of the set of concepts, c . All attributes are also members of a .
2. The *is_a* relation is irreflexive and can only occur in the zero group.
3. *childrenOf includes* the function from a concept in c to the set of concepts that are the source of c in an *is_a* relationship in the *zero_group*. Note

that substrates that include post-coordinated expressions may include additional entries in the *childrenOf* function that are not in the relationships table and, instead, are derived through the application of a DL reasoner.

4. *parentsOf includes* the function from a concept *c* to the set of concepts that are the target of *c* in an *is_a* relationship in the *zero_group*. Note that substrates that include post-coordinated expressions may include additional entries in the *parentsOf* function that are not in the relationships table and, instead, are derived through the application of a DL reasoner.
5. *parentsOf* and *childrenOf* are irreflexive.
6. The *equiv* relationship is symmetric and reflexive.
7. The ancestors function, *ancs*, is the *irreflexive* transitive closure of the *parentsOf* relationship.
8. The descendants function, *descs*, is the *irreflexive* transitive closure of the inverse of the *childrenOf* relationship.
9. The descendants relationship must not contain any concepts that are declared as equivalent to the root.
10. The reference set function is a function from *subset of c* to set of SCTID's in *c*. A SCTID that is not in the domain of *refset* cannot appear as the target of a *memberOf* function

$ \begin{array}{l} \textit{Substrate} \\ c : \mathbb{P} \textit{SCTID} \\ r : \mathbb{P} \textit{Quad} \\ a : \mathbb{P} \textit{SCTID} \\ \\ \textit{childrenOf} : \textit{SCTID} \rightarrow \mathbb{P} \textit{SCTID} \\ \textit{parentsOf} : \textit{SCTID} \rightarrow \mathbb{P} \textit{SCTID} \\ \\ \textit{descs} : \textit{SCTID} \rightarrow \mathbb{P} \textit{SCTID} \\ \textit{ancs} : \textit{SCTID} \rightarrow \mathbb{P} \textit{SCTID} \\ \textit{equiv} : \mathbb{P}(\textit{SCTID} \times \textit{SCTID}) \\ \textit{refset} : \textit{REFSETID} \rightarrow \mathbb{P} \textit{SCTID} \end{array} $
$ \begin{array}{l} a \subseteq c \\ \forall \textit{rel} : r \bullet \textit{rel}.s \in c \wedge \textit{rel}.a \in a \wedge (\textit{object} \sim \textit{rel}.t \in \textit{SCTID} \Rightarrow \textit{object} \sim \textit{rel}.t \in c) \\ \forall \textit{rel} : r \bullet q.a = \textit{is_a} \Rightarrow (q.s \neq \textit{object} \sim q.t \wedge q.g = \textit{zero_group}) \\ \\ \text{dom } \textit{childrenOf} = c \wedge \bigcup (\text{ran } \textit{childrenOf}) \subseteq c \\ \forall s : c \bullet \textit{parentsOf} s \subseteq \{q : r \mid q.s = s \wedge q.a = \textit{is_a} \bullet \textit{object} \sim q.t\} \\ \forall c1, c2 : c \bullet c1 \in \textit{parentsOf} c2 \Leftrightarrow c2 \in \textit{childrenOf} c1 \\ \\ \forall x : c \bullet (x \mapsto x) \in \textit{equiv} \\ \forall x1, x2 : c \bullet x1 \mapsto x2 \in \textit{equiv} \Rightarrow x2 \mapsto x1 \in \textit{equiv} \\ \\ \forall s : c \bullet \textit{descs} s = \textit{childrenOf} s \cup \bigcup \{t : \textit{childrenOf} s \bullet \textit{descs} t\} \\ \forall t : c \bullet \textit{ancs} t = \textit{parentsOf} t \cup \bigcup \{s : \textit{parentsOf} t \bullet \textit{ancs} s\} \\ \forall r : \textit{equiv} \bullet \textit{first} r \in \text{dom } \textit{descs} \Rightarrow \textit{second} r \notin (\textit{descs} (\textit{first} r)) \\ \\ \text{dom } \textit{refset} \subseteq c \wedge \bigcup (\text{ran } \textit{refset}) \subseteq c \end{array} $
$ \begin{array}{l} \textit{strict_substrate} \\ \textit{Substrate} \\ \\ \forall q : r \bullet q.a \in \textit{descs attribute_concept} \\ \text{dom } \textit{refset} \subseteq \textit{descs refset_concept} \end{array} $

3 Result

The result of applying a query against a substrate is either a (possibly empty) set of SCTID's or an *ERROR*. **TODO:** Where is `unknownAttribute` used?

$$\begin{array}{l}
\textit{ERROR} ::= \textit{unknownOperation} \mid \textit{unknownConceptReference} \mid \\
\hspace{10em} \textit{unknownAttribute} \mid \textit{unknownRefsetId} \\
\\
\textit{Result} ::= \textit{ok} \langle \mathbb{P} \textit{SCTID} \rangle \mid \textit{error} \langle \textit{ERROR} \rangle
\end{array}$$

4 Interpretation of Intermediate Constructs

This section carries the interpretation of the intermediate constructs – the various forms of expressions and their combinations.

4.1 expressionConstraint

```
expressionConstraint =
( refinedExpressionConstraint / unrefinedExpressionConstraint )
```

4.1.1 Interpretation

The interpretation of **expressionConstraint** the interpretation of the **refinedExpressionConstraint** or the **unrefinedExpressionConstraint**.

```
expressionConstraint ::=
    ecrec⟨⟨refinedExpressionConstraint⟩⟩ |
    ecurec⟨⟨unrefinedExpressionConstraint⟩⟩
```

```
i_expressionConstraint :
    Substrate → expressionConstraint → Result

∀ ss : Substrate; ec : expressionConstraint • i_expressionConstraint ss ec =
    if ecrec~ec ∈ refinedExpressionConstraint
    then i_refinedExpressionConstraint ss (ecrec~ec)
    else if ecurec~ec ∈ unrefinedExpressionConstraint
    then i_unrefinedExpressionConstraint ss (ecurec~ec)
    else error unknownOperation
```

4.1.2 unrefinedExpressionConstraint

An **unrefinedExpressionConstraint** is either a **compoundExpressionConstraint** or a **simpleExpressionConstraint**

```
unrefinedExpressionConstraint =
    compoundExpressionConstraint / simpleExpressionConstraint
```

```
unrefinedExpressionConstraint ::=
    ucec⟨⟨compoundExpressionConstraint⟩⟩ |
    usec⟨⟨simpleExpressionConstraint⟩⟩
```

$i_unrefinedExpressionConstraint :$ $Substrate \rightarrow unrefinedExpressionConstraint \rightarrow Result$
$\forall ss : Substrate; uec : unrefinedExpressionConstraint \bullet$ $i_unrefinedExpressionConstraint ss uec =$ $\text{if } uec \sim uec \in compoundExpressionConstraint$ $\quad \text{then } i_compoundExpressionConstraint ss (uec \sim uec)$ $\text{else if } usec \sim uec \in simpleExpressionConstraint$ $\quad \text{then } i_simpleExpressionConstraint ss (usec \sim uec)$ $\text{else } error\ unknownOperation$

4.1.3 refinedExpressionConstraint

```

refinedExpressionConstraint =
  unrefinedExpressionConstraint ":" refinement /
  "(" refinedExpressionConstraint ")"

```

The interpretation of **refinedExpressionConstraint** is the intersection of the interpretation of the **unrefinedExpressionConstraint** and the **refinement**, both of which return a set of SCTID's or an error.

The interpretation of the second option adds no value.

$$refinedExpressionConstraint == \\ unrefinedExpressionConstraint \times refinement$$

$i_refinedExpressionConstraint :$ $Substrate \rightarrow refinedExpressionConstraint \rightarrow Result$
$\forall ss : Substrate; rec : refinedExpressionConstraint \bullet$ $i_refinedExpressionConstraint ss rec =$ $intersect (i_unrefinedExpressionConstraint ss (first\ rec))(i_refinement ss (second\ rec))$

4.2 simpleExpressionConstraint

The interpretation of **simpleExpressionConstraint** is the application of an optional constraint operator to the interpretation of **focusConcept**, which returns a set of SCTID's or an error. The interpretation of an error is the error.

```

simpleExpressionConstraint =
  [constraintOperator ] focusConcept

```

$$constraintOperator ::= descendantOrSelfOf \mid descendantOf \mid \\ ancestorOrSelfOf \mid ancestorOf$$

$$simpleExpressionConstraint == constraintOperator[0..1] \times focusConcept$$

$i_simpleExpressionConstraint :$ $Substrate \rightarrow simpleExpressionConstraint \rightarrow Result$
$\forall ss : Substrate; sec : simpleExpressionConstraint \bullet$ $i_simpleExpressionConstraint ss sec =$ $i_constraintOperator ss (first sec) (i_focusConcept ss (second sec))$

4.3 compoundExpressionConstraint

The interpretation of a *compoundExpressionConstraint* is the interpretation of its corresponding component.

```
compoundExpressionConstraint = conjunctionExpressionConstraint |
disjunctionExpressionConstraint | exclusionExpressionConstraint |
"(" compoundExpressionConstraint ")"
```

```
compoundExpressionConstraint ::=
cecConj⟨⟨conjunctionExpressionConstraint⟩⟩ |
cecDisj⟨⟨disjunctionExpressionConstraint⟩⟩ |
cecExc⟨⟨exclusionExpressionConstraint⟩⟩
```

$i_compoundExpressionConstraint :$ $Substrate \rightarrow compoundExpressionConstraint \rightarrow Result$
$\forall ss : Substrate; cec : compoundExpressionConstraint \bullet$ $i_compoundExpressionConstraint ss cec =$ if $cecConj \sim cec \in conjunctionExpressionConstraint$ then $i_conjunctionExpressionConstraint ss (cecConj \sim cec)$ else if $cecDisj \sim cec \in disjunctionExpressionConstraint$ then $i_disjunctionExpressionConstraint ss (cecDisj \sim cec)$ else if $cecExc \sim cec \in exclusionExpressionConstraint$ then $i_exclusionExpressionConstraint ss (cecExc \sim cec)$ else $error\ unknownOperation$

$i_compoundExpressionConstraint' :$ $Substrate \rightarrow compoundExpressionConstraint \rightarrow Result$

4.4 conjunctionExpressionConstraint

conjunctionExpressionConstraint is interpreted the conjunction (intersection) of the interpretation of two or more *subExpressionConstraints*

```

conjunctionExpressionConstraint =
    subExpressionConstraint 1*(conjunction subExpressionConstraint)

```

conjunctionExpressionConstraint == *subExpressionConstraint* × seq₁(*subExpressionConstraint*)

$i_conjunctionExpressionConstraint :$ $Substrate \rightarrow conjunctionExpressionConstraint \rightarrow Result$
$\forall ss : Substrate; cecr : conjunctionExpressionConstraint \bullet$ $i_conjunctionExpressionConstraint ss cecr =$ $\text{if } tail(second\ cecr) = \langle \rangle \text{ then}$ $intersect\ (i_subExpressionConstraint\ ss\ (first\ cecr))(i_subExpressionConstraint\ ss\ (head\ (second\ cecr)))$ else $intersect\ (i_subExpressionConstraint\ ss\ (first\ cecr))(i_conjunctionExpressionConstraint\ ss\ ((head\ (second\ cecr))\ cecr))$

4.5 disjunctionExpressionConstraint

disjunctionExpressionConstraint is interpreted the disjunction (union) of the interpretation of two or more *subExpressionConstraints*

```

disjunctionExpressionConstraint =
    subExpressionConstraint 1*(disjunction subExpressionConstraint)

```

disjunctionExpressionConstraint ==
subExpressionConstraint × seq₁(*subExpressionConstraint*)

$i_disjunctionExpressionConstraint :$ $Substrate \rightarrow disjunctionExpressionConstraint \rightarrow Result$
$\forall ss : Substrate; cecr : disjunctionExpressionConstraint \bullet$ $i_disjunctionExpressionConstraint ss cecr =$ $\text{if } tail(second\ cecr) = \langle \rangle \text{ then}$ $union\ (i_subExpressionConstraint\ ss\ (first\ cecr))(i_subExpressionConstraint\ ss\ (head\ (second\ cecr)))$ else $union\ (i_subExpressionConstraint\ ss\ (first\ cecr))(i_disjunctionExpressionConstraint\ ss\ ((head\ (second\ cecr))\ cecr))$

4.6 exclusionExpressionConstraint

exclusionExpressionConstraint is interpreted the result of removing the members of the second *subExpressionConstraint* from the first

```

exclusionExpressionConstraint =
    subExpressionConstraint exclusion subExpressionConstraint

```

exclusionExpressionConstraint ==
subExpressionConstraint × *subExpressionConstraint*

<i>i_exclusionExpressionConstraint</i> : <i>Substrate</i> → <i>exclusionExpressionConstraint</i> → <i>Result</i>
$\forall ss : \text{Substrate}; ecr : \text{exclusionExpressionConstraint} \bullet$ <i>i_exclusionExpressionConstraint</i> <i>ss</i> <i>ecr</i> = <i>minus</i> (<i>i_subExpressionConstraint</i> <i>ss</i> (<i>first ecr</i>)) (<i>i_subExpressionConstraint</i> <i>ss</i> (<i>second ecr</i>))

4.7 subExpressionConstraint

subExpressionConstraint is interpreted as the interpretation of either a *simpleExpressionConstraint* or a *compoundExpressionConstraint*

subExpressionConstraint =
simpleExpressionConstraint | "(" *compoundExpressionConstraint* ")

subExpressionConstraint ::=
secSec⟨⟨*simpleExpressionConstraint*⟩⟩ |
secCec⟨⟨*compoundExpressionConstraint*⟩⟩

<i>i_subExpressionConstraint</i> : <i>Substrate</i> → <i>subExpressionConstraint</i> → <i>Result</i>
$\forall ss : \text{Substrate}; sec : \text{subExpressionConstraint} \bullet$ <i>i_subExpressionConstraint</i> <i>ss</i> <i>sec</i> = if (<i>secSec</i> ~ <i>sec</i>) ∈ <i>simpleExpressionConstraint</i> then <i>i_simpleExpressionConstraint</i> <i>ss</i> (<i>secSec</i> ~ <i>sec</i>) else if <i>secCec</i> ~ <i>sec</i> ∈ <i>compoundExpressionConstraint</i> then <i>i_compoundExpressionConstraint'</i> <i>ss</i> (<i>secCec</i> ~ <i>sec</i>) else <i>error unknownOperation</i>

4.8 refinement

refinement is the interpretation of one or more *attribute* or *attributeGroups* joined by *binaryOperators*

binaryOperator = *conjunction* / *disjunction* / *minus*
refinement = (*attribute* / *attributeGroup* / "(" *refinement* ")")
 [*binaryOperator* *refinement*]

refTarget ::= *att*⟨⟨*attribute*⟩⟩ | *attg*⟨⟨*attributeGroup*⟩⟩
refinement == *refTarget* × *seq*(*binaryOperator* × *refTarget*)

$i_refTarget : Substrate \rightarrow refTarget \rightarrow Result$ $i_refinement : Substrate \rightarrow refinement \rightarrow Result$
$\forall ss : Substrate; rt : refTarget \bullet i_refTarget\ ss\ rt =$ if $att \sim rt \in attribute$ then $i_attribute\ ss\ (att \sim rt)$ else if $attg \sim rt \in attributeGroup$ then $i_attributeGroup\ ss\ (attg \sim rt)$ else $error\ unknownOperation$
$\forall ss : Substrate; ref : refinement \bullet$ $i_refinement\ ss\ ref =$ $evalRefinement\ ss\ (i_refTarget\ ss\ (first\ ref))\ (second\ ref)$

$evalRefinement :$ $Substrate \rightarrow Result \rightarrow seq(binaryOperator \times refTarget) \rightarrow Result$
$\forall ss : Substrate; r : Result; opt : seq(binaryOperator \times refTarget) \bullet$ $evalRefinement\ ss\ r\ opt =$ if $opt = \langle \rangle$ then r else if $first\ (head\ opt) = conjunction$ then $evalRefinement\ ss\ (intersect\ r\ (i_refTarget'\ ss\ (second\ (head\ opt))))\ (tail\ opt)$ else if $first\ (head\ opt) = disjunction$ then $evalRefinement\ ss\ (union\ r\ (i_refTarget'\ ss\ (second\ (head\ opt))))\ (tail\ opt)$ else if $first\ (head\ opt) = exclusion$ then $evalRefinement\ ss\ (minus\ r\ (i_refTarget'\ ss\ (second\ (head\ opt))))\ (tail\ opt)$ else $error\ unknownOperation$

$i_refTarget' : Substrate \rightarrow refTarget \rightarrow Result$
--

4.9 expressionConstraintValue

```
expressionConstraintValue = simpleExpressionConstraint /
    "(" (refinedExpressionConstraint /
        compoundExpressionConstraint) ")"
```

```
expressionConstraintValue ::= ecvsec⟨⟨simpleExpressionConstraint⟩⟩ |
    ecvrec⟨⟨refinedExpressionConstraint'⟩⟩ |
    ecvcec⟨⟨compoundExpressionConstraint⟩⟩
[refinedExpressionConstraint']
```

$i_expressionConstraintValue : Substrate \rightarrow$ $expressionConstraintValue \rightarrow Result$
$\forall ss : Substrate; ecv : expressionConstraintValue \bullet$ $i_expressionConstraintValue ss ecv =$ if $ecvsec \sim ecv \in simpleExpressionConstraint$ then $i_simpleExpressionConstraint ss (ecvsec \sim ecv)$ else if $ecvrec \sim ecv \in refinedExpressionConstraint'$ then $i_refinedExpressionConstraint' ss (ecvrec \sim ecv)$ else if $ecvcec \sim ecv \in compoundExpressionConstraint$ then $i_compoundExpressionConstraint ss (ecvcec \sim ecv)$ else $error\ unknownOperation$
$i_refinedExpressionConstraint' :$ $Substrate \rightarrow refinedExpressionConstraint' \rightarrow Result$

4.10 Attributes and Attribute Groups

The interpretation of an attribute. `attributeOperator` and `attributeName` determines the set of possible attributes in the substrate relationship table. `reverseFlag` and `expressionConstraintValue` determine the set of candidate targets (if `reverseFlag` is absent) or `subjects` (if `reverseFlag` is present).

`cardinality` determines the minimum and maximum matches. In all cases, only a subset of the subjects (targets if `reverseFlag` is present) in the substrate relationship table will be returned in the interpretation.

```
attribute = [cardinality] [reverseFlag] [attributeOperator] attributeName
            (comparisonOperator concreteValue / "=" expressionConstraintValue )
attributeGroup = "{" attributeSet "}"
attributeSet = attribute [binaryOperator attributeSet] / "(" attributeSet ")"
cardinality = "[" nonNegativeIntegerValue to (nonNegativeIntegerValue / many) "]"
comparisonOperator = "=" / "!=" ws "=" /
                    ("n"/"N") ("o"/"O") ("t"/"T") ws "<=" / "<" / ">=" / ">"
```

4.11 AttributeName and AttributeSubject

`i_attributeName` verifies that `conceptReference` is a valid concept in the substrate and interprets it as a set of (exactly one) *ATTRIBUTE*

`i_attributeSubject` interprets the `constraintOperator`, if any in the context of the attribute name and interprets it as a set of *ATTRIBUTES*

Question: Should we add any additional validation checks?

```
attributeName == conceptReference
attributeOperator == {descendantOrSelfOf, descendantOf}
attributeSubject == attributeOperator[0..1] × attributeName
```

$i_attributeName : Substrate \rightarrow attributeName \rightarrow Result$ $i_attributeSubject : Substrate \rightarrow attributeSubject \rightarrow Result$
$\forall ss : Substrate; an : attributeName \bullet i_attributeName ss an =$ $i_conceptReference ss an$
$\forall ss : Substrate; as : attributeSubject \bullet i_attributeSubject ss as =$ $i_constraintOperator ss (first as) (i_attributeName ss (second as))$

4.12 Attribute

attribute consists of an optional **cardinality** and an **attributeConstraint**.

$unlimitedNat ::= num\langle\mathbb{N}\rangle \mid many$
 $cardinality == \mathbb{N} \times unlimitedNat$

$attribute$
$card : cardinality[0..1]$ $attw : attributeConstraint$

attributeConstraint is either an attribute expression constraint or a concrete value constraint.

$attributeConstraint ::= aec\langle\langle attributeExpressionConstraint \rangle\rangle \mid$
 $acvc\langle\langle attributeConcreteValueConstraint \rangle\rangle$

attributeExpressionEonstraint is a combination of a subject constraint (target if reverse flag is true) and an expression constraint value whose interpretation yields a set of SCTID's that filter the target (subject if reverse flag).

$[reverseFlag]$

$attributeExpressionConstraint$
$a : attributeSubject$ $rf : reverseFlag[0..1]$ $cs : expressionConstraintValue$

A concrete value constraint is the combination of a subject constraint and a comparison operator/concrete value whose interpretation yields a set of subject ids. The intersection of the subject and concrete value interpretation is the interpretation of **attributeConcreteValueConstraint**

$comparisonOperator ::= eq \mid neq \mid gt \mid ge \mid lt \mid le$

attributeConcreteValueConstraint

a : *attributeSubject*

op : *comparisonOperator*

v : *concreteValue*

The interpretation of an attribute is the interpretation of the cardinality applied against the underlying attribute constraint, producing a set of SCTID's or an error condition

The interpretation of an attribute constraint is the interpretation of either the attribute expression constraint or the concrete expression constraint that produces a set of Quads or an error condition.

The actual interpretations if attribute expression and concrete value are in Section 5

i_attribute :

Substrate \rightarrow *attribute* \rightarrow *Result*

i_attributeConstraint :

Substrate \rightarrow *attributeConstraint* \rightarrow *Quads*

i_attributeExpressionConstraint :

Substrate \rightarrow *attributeExpressionConstraint* \rightarrow *Quads*

i_attributeConcreteValueConstraint :

Substrate \rightarrow *attributeConcreteValueConstraint* \rightarrow *Quads*

$\forall ss : \text{Substrate}; a : \text{attribute} \bullet$

$i_attribute\ ss\ a = i_cardinality\ a.\text{card}\ (i_attributeConstraint\ ss\ a.\text{attw})$

$\forall ss : \text{Substrate}; aw : \text{attributeConstraint} \bullet i_attributeConstraint\ ss\ aw =$

if $aec \sim aw \in \text{attributeExpressionConstraint}$

then $i_attributeExpressionConstraint\ ss\ (aec \sim aw)$

else if $acvc \sim aw \in \text{attributeConcreteValueConstraint}$

then $i_attributeConcreteValueConstraint\ ss\ (acvc \sim aw)$

else $qerror\ unknownOperation$

$\forall ss : \text{Substrate}; aec : \text{attributeExpressionConstraint}; eca : \text{expressionConstraintArgs} \mid$

$eca.\text{atts} = i_attributeSubject\ ss\ aec.a \wedge$

$eca.\text{rf} = aec.\text{rf} \wedge$

$eca.\text{subjOrTarg} = i_expressionConstraintValue\ ss\ aec.cs \bullet$

$i_attributeExpressionConstraint\ ss\ aec = i_attributeExpression\ ss\ eca$

$\forall ss : \text{Substrate}; awc : \text{attributeConcreteValueConstraint}; aca : \text{concreteConstraintArgs} \mid$

$aca.\text{atts} = i_attributeSubject\ ss\ awc.a \wedge$

$aca.op = awc.op \wedge$

$aca.t = awc.v \bullet$

$i_attributeConcreteValueConstraint\ ss\ awc = i_concreteAttributeConstraint\ ss\ aca$

4.13 AttributeSet and AttributeGroup

An **attributeGroup** is an **attributeSet**. An **attributeSet** consists of a sequence of one or more attribute constraints joined by **binaryOperators**.

binaryOperator ::= *conjunction* | *disjunction* | *exclusion*
attributeGroup == *attributeSet*
attributeSet == *attribute* × seq(*binaryOperator* × *attribute*)

<i>i_attributeGroup</i> : <i>Substrate</i> → <i>attributeGroup</i> → <i>Result</i>
<i>i_attributeSet</i> : <i>Substrate</i> → <i>attributeSet</i> → <i>Result</i>
$\forall ss : \text{Substrate}; ag : \text{attributeGroup} \bullet i_attributeGroup\ ss\ ag =$ $i_attributeSet\ ss\ ag$
$\forall ss : \text{Substrate}; a : \text{attributeSet} \bullet i_attributeSet\ ss\ a =$ $result\ (evalCmpndAtt\ ss\ (i_groupedAttribute\ ss\ (first\ a))\ (second\ a))$

4.14 Compound attribute evaluation

The left-to-right evaluation of **attributeSet**. The interpretation takes a *lhs* as a function from *SCTID* to *GROUP* and a *rhs* which is sequence of operator/attribute tuples and recursively interprets the *lhs* and interpretation of the head of the *rhs*.

<pre> evalCmpndAtt : Substrate → IDGroups → seq(binaryOperator × attribute) → IDGroups gintersect, gunion, gminus, gfirstError : IDGroups → IDGroups → IDGroups </pre>
<pre> ∀ ss : Substrate; lhs : IDGroups; rhs : seq(binaryOperator × attribute) • evalCmpndAtt ss lhs rhs = if rhs = ⟨⟩ then lhs else if first(head rhs) = conjunction then evalCmpndAtt ss (gintersect lhs(i_groupedAttribute ss(second(head rhs))))(tail rhs) else if first(head rhs) = disjunction then evalCmpndAtt ss (gunion lhs(i_groupedAttribute ss(second(head rhs))))(tail rhs) else if first(head rhs) = exclusion then evalCmpndAtt ss (gminus lhs(i_groupedAttribute ss(second(head rhs))))(tail rhs) else gerror unknownOperation ∀ a, b, r : IDGroups r = if gerror~a ∈ ERROR ∨ gerror~b ∈ ERROR then gfirstError a b else gv (gv~a ∩ gv~b) • gintersect a b = r ∀ a, b, r : IDGroups r = if gerror~a ∈ ERROR ∨ gerror~b ∈ ERROR then gfirstError a b else gv (gv~a ∪ gv~b) • gunion a b = r ∀ a, b, r : IDGroups r = if gerror~a ∈ ERROR ∨ gerror~b ∈ ERROR then gfirstError a b else gv (gv~a \ gv~b) • gminus a b = r </pre>
<pre> i_groupedAttribute : Substrate → attribute → IDGroups </pre>
<pre> ∀ ss : Substrate; a : attribute • i_groupedAttribute ss a = i_groupCardinality (i_attributeConstraint ss a.attw) a.card </pre>

4.15 Group Cardinality

The interpretation of cardinality within a group impose additional constraints:

- $[0..n]$ – the set of all substrate concept codes that have at least one group (entry) in the substrate relationships and, at most n matching entries in the same group

- $[0..0]$ – the set of all substrate concept codes that have at least one group (entry) in the substrate relationships and *no* matching entries
- $[1..*]$ – (default) at least one matching entry in the substrate relationships
- $[m_1..n_1]op[m_2..n_2]...$ – set of substrate concept codes where there exists at least one group where all conditions are simultaneously true

The interpretation of a grouped cardinality is a function from a set of SCTID's to the groups in which they were qualified.

The algorithm below partitions the input set of Quads by group and validates the cardinality on a per-group basis. Groups that pass are returned

TODO: This assumes that *q.t* is always type object. It doesn't say what to do if it is concrete **TODO:** the *gresult* function seems to express what is described below more simply

```

i_groupCardinality :
  Quads → cardinality[0..1] → IDGroups

  ∀ quads : Quads; oc : cardinality[0..1]; uniqueGroups : ℙ GROUP;
    quadsByGroup : GROUP → ℙ Quad |
    uniqueGroups = {q : qids quads • q.g} ∧
    quadsByGroup = {g : uniqueGroups; q : ℙ Quad |
      q = {e : qids quads | e.g = g} • g ↦ (evalCardinality oc q)} •
  i_groupCardinality quads oc =
    gv {sctid : SCTID; groups : ℙ GROUP | sctid ∈ {q : ⋃(ran quadsByGroup) •
      if qidd quads = subjects then q.s else object~q.t} ∧
    groups = {g : dom quadsByGroup | (∃ q : quadsByGroup g •
      sctid = if qidd quads = subjects then q.s else object~q.t)} •
    sctid ↦ groups}

```

4.16 Cardinality

Interpretation: *cardinality* is tested against a set of quads with the following rules:

1. Errors are propagated
2. No cardinality or passing cardinality returns the subjects / targets of the set of quads
3. Otherwise return an empty set

```

i_cardinality :
  cardinality[0..1] → Quads → Result

  ∀ oc : cardinality[0..1]; qr : Quads •
  i_cardinality oc qr =
    if qerror~qr ∈ ERROR then result (gresult qr)
    else result (gresult (qv (evalCardinality oc (qids qr), qidd qr)))

```

evalCardinality Evaluate the cardinality of a set, returning the set if it meets the constraints, otherwise return the empty set.

<i>evalCardinality</i> : <i>cardinality</i> [0 .. 1] \rightarrow \mathbb{P} <i>Quad</i> \rightarrow \mathbb{P} <i>Quad</i>
$\forall oc : \text{cardinality}[0 \dots 1]; s : \mathbb{P} \text{Quad} \bullet \text{evalCardinality } oc \ s =$ if $\#oc = 0$ then s else if $(\#s \geq \text{first}(\text{head } oc)) \wedge$ $(\text{second}(\text{head } oc) = \text{many} \vee \text{num}^\sim(\text{second}(\text{head } oc)) \leq \#s)$ then s else \emptyset

5 Substrate Interpretations

This section defines the interpretations that are realized against the substrate.

5.1 AttributeExpressionConstraint

expressionConstraintArgs carries the arguments necessary to evaluate an attribute expression

- **rf** – If present, return subjects matching attribute/target subjects
- **subjOrTarg** – Set of subject or target SCTIDS (or error)
- **atts** – Set of attributes to evaluate

<i>expressionConstraintArgs</i>
<i>rf</i> : <i>reverseFlag</i> [0 .. 1]
<i>subjOrTarg</i> : <i>Result</i>
<i>atts</i> : <i>Result</i>

Evaluate an attribute expression, returning the set of quads in the substrate relationship table with the supplied subject / attribute if *rf* is absent and attribute / target if *rf* is present. The interpretation returns an error there is an error in either the subject/targets or attributes. **TODO:** We don't say what to do if the target (t) is concrete

$i_attributeExpression :$ $Substrate \rightarrow expressionConstraintArgs \rightarrow Quads$
$\forall ss : Substrate; args : expressionConstraintArgs;$ $sti : \mathbb{P} TARGET; atts : \mathbb{P} ATTRIBUTE \mid$ $sti = ok \sim args.subjectOrTarg \wedge atts = ok \sim args.atts \bullet$ $i_attributeExpression ss args =$ if $error \sim (bigunion\{args.subjectOrTarg, args.atts\}) \in ERROR$ then $qfirstError\{args.subjectOrTarg, args.atts\}$ else if $\neg (sti \cup atts) \subseteq ss.c$ then $qerror\ unknownConceptReference$ else if $\#args.rf = 0$ then $qv(\{s : SUBJECT; t : sti; a : atts; g : GROUP; re : ss.r \mid$ $re.t = t \wedge re.a = a \bullet re\}, subjects)$ else $qv(\{s : sti; a : atts; t : TARGET; g : GROUP; re : ss.r \mid$ $re.s = object \sim t \wedge re.a = a \bullet re\}, targets)$

5.2 ConcreteAttributeConstraint

```

concreteValue = QM stringValue QM / "#" numericValue
stringValue = 1*(anyNonEscapedChar / escapedChar)
numericValue = decimalValue / integerValue
integerValue = ( ["-"/"+"] digitNonZero *digit ) / zero

```

The mechanism for interpreting *concreteValue* is not fully specified at this point. Much of the rest of the machinery is focused around interpreting constraints in the context of quads - subject, attribute, target and group, so the function is currently defined as returning a *Quads*, but another type or interpretation may be in order.

$concreteValue ::= stringValue \mid integerValue \mid realValue$

concreteConstraintArgs The arguments to the concrete value function.

- **atts** – list of attributes to test
- **op** – operator
- **t** – value to test against

Note: *reverseFlag* has no meaning for concrete constraints.

$concreteConstraintArgs$
$atts : Result$ $op : comparisonOperator$ $t : concreteValue$

```

i_concreteAttributeConstraint :
  Substrate → concreteConstraintArgs → Quads

```

5.3 ConstraintOperator

```

constraintOperator =
  descendantOrSelfOf / descendantOf / ancestorOrSelfOf / ancestorOf

```

Interpretation: Apply the substrate descendants (*descs*) or ancestors (*ancs*) function to a set of SCTID's in the supplied *Result*. Error conditions are propagated.

```

i_constraintOperator :
  Substrate → constraintOperator[0 .. 1] → Result → Result

completeFun : (SCTID →  $\mathbb{P}$  SCTID) → SCTID →  $\mathbb{P}$  SCTID

 $\forall ss : \text{Substrate}; \text{oco} : \text{constraintOperator}[0 .. 1]; \text{refset} : \text{Result} \bullet$ 
i_constraintOperator ss oco refset =
  if error ~ refset  $\in$  ERROR  $\vee$  #oco = 0
  then refset
  else if head oco = descendantOrSelfOf
    then ok( $\bigcup \{id : ids \text{ refset} \bullet \text{completeFun ss.descs } id \cup \{id\}\}$ )
  else if head oco = descendantOf
    then ok( $\bigcup \{id : ids \text{ refset} \bullet \text{completeFun ss.descs } id \setminus \{id\}\}$ )
  else if head oco = ancestorOrSelfOf
    then ok( $\bigcup \{id : ids \text{ refset} \bullet \text{completeFun ss.ancs } id \cup \{id\}\}$ )
  else if head oco = ancestorOf
    then ok( $\bigcup \{id : ids \text{ refset} \bullet \text{completeFun ss.ancs } id \setminus \{id\}\}$ )
  else error unknownOperation

 $\forall f : (SCTID \rightarrow \mathbb{P} SCTID); id : SCTID \bullet \text{completeFun } f \text{ } id =$ 
  if  $id \in \text{dom } f$  then  $f \text{ } id$  else  $\emptyset$ 

```

5.4 FocusConcept

```

focusConcept = [memberOf] conceptReference

```

Interpretation: focusConcept is interpreted as the interpretation of conceptReference itself or, if memberOf is specified, the interpretation of the memberOf function applied to the conceptReference

$$\text{focusConcept} ::= \text{mo} \langle \langle \text{conceptReference} \rangle \rangle \mid \text{cr} \langle \langle \text{conceptReference} \rangle \rangle$$

$i_focusConcept : Substrate \rightarrow focusConcept \rightarrow Result$
$\forall ss : Substrate; fc : focusConcept \bullet$ $i_focusConcept ss fc =$ if $cr \sim fc \in conceptReference$ then $i_conceptReference ss (cr \sim fc)$ else if $mo \sim fc \in conceptReference$ then $i_memberOf ss (mo \sim fc)$ else $error unknownOperation$

5.4.1 memberOf

Interpretation: `memberOf` is interpreted as application *refset* function to the `conceptReference` SCTID or an error if the SCTID isn't in the domain of the *refset* function.

$i_memberOf : Substrate \rightarrow conceptReference \rightarrow Result$
$\forall ss : Substrate; cr : conceptReference \bullet$ $i_memberOf ss cr =$ (let $sctid == toSCTID cr \bullet$ if $sctid \notin \text{dom } ss.refset$ then $error unknownRefsetId$ else $ok (ss.refset sctid)$)

5.5 ConceptReference

`conceptReference` = `conceptId` ["|" Term "|"]
`conceptId` = `sctId`

Interpretation: `conceptReference` is interpreted as *SCTID* if it is a member the list of concepts, *c* in the substrate, otherwise as an *error*.

[*conceptReference*]

$toSCTID : conceptReference \rightarrow SCTID$
$i_conceptReference : Substrate \rightarrow conceptReference \rightarrow Result$
$\forall ss : Substrate; c : conceptReference \bullet i_conceptReference ss c =$ if $(toSCTID c) \in ss.c$ then $ok\{(toSCTID c)\}$ else $error unknownConceptReference$

6 Glue and Helper Functions

This section carries various type transformations and error checking functions

6.1 Types

- **direction** – an indicator whether a collection of quads was determined as subject to target (*subjects*) or target to subject (*targets*)
- **Quads** – a collection of *Quads* or an error condition. If it is a collection *Quads*, it also carries a direction indicator that determines whether it represents a set of subjects or targets.
- **IDGroups** – a map from *SCTIDs* to the *GROUP* they were in when they passed if successful, otherwise an error indication.

$direction ::= subjects \mid targets$

$Quads ::= qv\langle\mathbb{P} Quad \times direction\rangle \mid qerror\langle ERROR\rangle$

$IDGroups ::= gv\langle SCTID \rightarrow \mathbb{P} GROUP\rangle \mid gerror\langle ERROR\rangle$

6.2 Result transformations

- **ids** – return the set of *SCTIDs* in a result or the empty set if there is an error
- **qids** – return the set of *Quads* in a quads result or an empty set if there is an error
- **qidd** – return the direction of a *Quads* result. Undefined if error
- **gids** – return the *SCTID* to group map in an id group or an empty map if there is error
- **gresult** – convert a set of quads into a set of id groups
- **result** – convert a set of id groups into a simple result.

$ids : Result \rightarrow \mathbb{P} SCTID$ $qids : Quads \rightarrow \mathbb{P} Quad$ $qidd : Quads \rightarrow direction$ $gids : IDGroups \rightarrow SCTID \rightarrow \mathbb{P} GROUP$ $gresult : Quads \rightarrow IDGroups$ $result : IDGroups \rightarrow Result$
$\forall r : Result \bullet ids\ r =$ if $error \sim r \in ERROR$ then \emptyset else $ok \sim r$ $\forall q : Quads \bullet qids\ q =$ if $qerror \sim q \in ERROR$ then \emptyset else $first\ (qv \sim q)$ $\forall q : Quads \bullet qidd\ q =$ $second\ (qv \sim q)$ $\forall g : IDGroups \bullet gids\ g =$ if $gerror \sim g \in ERROR$ then \emptyset else $gv \sim g$ $\forall q : Quads \bullet gresult\ q =$ if $qerror \sim q \in ERROR$ then $gerror(qerror \sim q)$ else if $qidd\ q = subjects$ then $gv\ \{s : SCTID \mid (\exists qr : qids\ q \bullet s = qr.s) \bullet$ $s \mapsto \{qr : qids\ q \bullet qr.g\}\}$ else $gv\ \{t : SCTID \mid (\exists qr : qids\ q \bullet t = object \sim qr.t) \bullet$ $t \mapsto \{qr : qids\ q \bullet qr.g\}\}$ $\forall g : IDGroups \bullet result\ g =$ if $gerror \sim g \in ERROR$ then $error(gerror \sim g)$ else $ok(dom(gv \sim g))$

Definition of the various functions that are performed on the result type.

- **firstError** – take a set of *Results* with one or more errors and return an aggregation / summary as a *Result*. (Not fully defined)
- **qfirstError** – take a set of *Results* with one or more errors and return an aggregation / summary as a *Quads* instance. (not fully defined)
- **union** – return the union of two *Result SCTIDs* or *ERROR* if either of them have an error.
- **intersect** – return the intersection of two *Result SCTIDs* or *ERROR* if either of them have an error.

- **minus** – return the set of *SCTIDs* in the first set of results that are not in the second or *ERROR* if either of them have an error.
- **bigunion** – return the union of a set *Result SCTIDs* or *ERROR* if any of the results in the set have an error.
- **bigintersect** – return the intersection of a set *Result SCTIDs* or *ERROR* if any of the results in the set have an error.

firstError is not fully defined – it takes a set of results with one or more errors and returns an aggregation of all of the errors.

$union, intersect, minus : Result \rightarrow Result \rightarrow Result$ $bigunion, bigintersect : \mathbb{P} Result \rightarrow Result$ $firstError : \mathbb{P} Result \rightarrow Result$ $qfirstError : \mathbb{P} Result \rightarrow Quads$
$\forall x, y : Result \bullet union\ x\ y =$ if $error \sim x \in ERROR$ then x else if $error \sim y \in ERROR$ then y else $ok\ ((ok \sim x) \cup (ok \sim y))$ $\forall x, y : Result \bullet intersect\ x\ y =$ if $error \sim x \in ERROR$ then x else if $error \sim y \in ERROR$ then y else $ok\ ((ok \sim x) \cap (ok \sim y))$ $\forall x, y : Result \bullet minus\ x\ y =$ if $error \sim x \in ERROR$ then x else if $error \sim y \in ERROR$ then y else $ok\ ((ok \sim x) \setminus (ok \sim y))$ $\forall rs : \mathbb{P} Result \bullet bigunion\ rs =$ if $\exists r : rs \bullet error \sim r \in ERROR$ then $firstError\ rs$ else $ok\ (\bigcup \{r : rs \bullet ids\ r\})$ $\forall rs : \mathbb{P} Result \bullet bigintersect\ rs =$ if $\exists r : rs \bullet error \sim r \in ERROR$ then $firstError\ rs$ else $ok\ (\bigcap \{r : rs \bullet ids\ r\})$

7 Appendix 1

Representing optional elements of type T . Representing it as a sequence allows us to determine absence by $\#T = 0$ and the value by $head\ T$.

$$T[0..1] == \{s : seq\ T \mid \#s \leq 1\}$$