

■ VS CODE QUICK GUIDE

Launch Chrome for JS / jQuery Debugging (Future Reference)

🔗 WHAT THIS DEBUGGER DOES

- Launches **Chrome automatically**
 - Attaches VS Code debugger to that Chrome tab
 - Allows you to:
 - Set breakpoints in `.js` files
 - Debug jQuery events, AJAX, DOM logic
 - Use VARIABLES, WATCH, CALL STACK, Debug Console
-

□ REQUIRED PROJECT STRUCTURE (YOURS)

```
C:/xampp/htdocs/jaysan_12-08/  
├── sub_assembly.html  
├── js/  
│   ├── sub_assembly.js  
│   └── other.js  
├── php/  
│   └── get_bom_output.php  
├── .vscode/  
│   └── launch.json
```

✓ CORRECT DEBUG CONFIG (JS / jQuery)

```
{  
  "name": "Launch Chrome for JS/jQuery Debugging",  
  "type": "pwa-chrome",  
  "request": "launch",  
  "url": "http://localhost/jaysan_12-08/sub_assembly.html",  
  "webRoot": "C:/xampp/htdocs/jaysan_12-08",  
  "userDataDir": true,  
  "skipFiles": ["**/jquery*.js", "**/node_modules/**"]  
}
```

🔑 MOST IMPORTANT SETTINGS (MEMORIZE THIS)

◆ url

🔗 The exact page you want to debug

```
"url": "http://localhost/jaysan_12-08/sub_assembly.html"
```

- ✓ Must open in browser
- ✓ Must be the page that loads your JS
- ✓ Change this if you debug another HTML page

Examples:

```
"url": "http://localhost/jaysan_12-08/assembly.html"
"url": "http://localhost/jaysan_12-08/map.html"
```

◆ webRoot

📁 **Local folder that matches the browser URL**

```
"webRoot": "C:/xampp/htdocs/jaysan_12-08"
```

✓ This is **NOT** a URL

✓ This is your **project root folder**

✓ Must contain your HTML + js/ folder

✗ WRONG:

```
"${workspaceFolder}"
"${ 'C:\\xampp\\htdocs' }"
```

✓ RIGHT:

```
"C:/xampp/htdocs/jaysan_12-08"
```

□ HOW VS CODE MATCHES FILES (VERY IMPORTANT)

Browser loads	VS Code expects
/jaysan_12-08/js/sub_assembly.js	C:/xampp/htdocs/jaysan_12-08/js/sub_assembly.js
/jaysan_12-08/sub_assembly.html	C:/xampp/htdocs/jaysan_12-08/sub_assembly.html

If this mapping is correct → **breakpoints bind** ✓

If not → **breakpoints stay gray/unbound** ✗

► □ HOW TO USE (EVERY TIME)

1. **Close all Chrome windows**
2. Open VS Code
3. Ctrl + Shift + D → Run & Debug
4. Select **Launch Chrome for JS/jQuery Debugging**
5. Press **F5**
6. Chrome opens automatically
7. Put breakpoints in:
 - js/*.js
 - <script> inside HTML
8. Click / submit / trigger events → debugger stops

⚠ □ **DO NOT open Chrome manually**

❑ IF BREAKPOINT DOES NOT HIT (CHECKLIST)

✓ Did Chrome open by VS Code?

✓ Is webRoot correct?

✓ Is script loaded like this?

```
<script src="js/sub_assembly.js" defer></script>
```

✓ Hard reload page: Ctrl + Shift + R

✓ Try temporary:

```
debugger;
```

❑ USEFUL ADD-ONS (OPTIONAL)

Skip jQuery internals

```
"skipFiles": ["**/jquery*.js"]
```

Debug info (when confused)

```
"trace": true
```

Clean Chrome (no extensions)

```
"runtimeArgs": ["--disable-extensions"]
```

❑ GOLDEN RULE (REMEMBER THIS)

URL = what browser opens

webRoot = where that file exists on disk

If those two match → debugging works **100%**