482 半導體元件物理與製程——理論與實務

階梯覆蓋 (step coverage) 195, 253

順向偏壓 (forward bias) 38-39, 41, 46-52, 54-60

順序邏輯 (sequential logic) 294, 305-307, 311

十三劃

傳輸線 (transmission line) 452

微控制器 (Microcontroller; MCU) 386, 393, 401, 405-406

微粒 (particle) 103, 195, 223

微處理器 221, 318, 326, 329, 356, 386, 389-391, 393, 401, 406

微影 (photolithography) 104, 184, 189-191, 193, 195-196, 198-205, 208-211, 215, 226

感應放大器 (sense amplifiers) 318, 358-360, 366

損壞 (damage) 186-189, 198-200, 333

量狀植入(halo implant) 243

源/汲極工程 (Source/Drain engineering) 239-240, 246, 332

準中性近似 (quasi-neutral approximation) 45

硼渗透 (boron penetration) 201, 205

禁止能隙 (forbidden energy gap) 2,107

罩蓋層 (capping layer) 277

解離速率 (ionization rate) 64-66

資料選擇器 (data selector) 304

載子 (carrier) 2, 4-6, 8-11, 13-15, 17-18, 20, 22-23, 30-33, 41-42, 45-53, 57-58, 62-63, 65, 79, 81-82, 84, 94-95, 104, 108, 116, 124, 130-133, 136-137, 149-151, 153, 158-159, 161-163, 171, 173, 188, 202, 224, 228, 231-233, 236-240, 244, 258-259, 264-265, 267-269, 271-272, 279, 281-282, 286, 293, 295, 322-323, 332-333, 343-344, 347, 371, 415, 417, 421, 425, 456, 461

載子倍增 (carrier multiplication) 62-63

載子速度飽和(velocity saturation) 158

載子漂移 (carrier drift) 14

載子遷移率(carrier mobility) 137, 149, 153, 162-163, 224, 233, 267, 272, 279, 282, 293, 295

載子遷移率下降 (mobility degradation) 279, 282

載子擴散 (carrier diffusion) 18

過渡區 (transition region) 99, 104-105

鉀 (kalium) 102

閘矩陣 (gate array) 309-310, 314

閘極介電層 (gate dielectric) 123, 238, 275-277, 280, 467

閘極氧化層 103-104, 115, 117, 123, 126, 132, 147, 152-153, 159, 166, 179, 188, 196,