## 478 半導體元件物理與製程——理論與實務

閂鎖器 (latch) 305-306

倍增因數 (multiplication factor) 63,65

個人數位助理 (Personal Digital Assistant) 394, 404, 409

## 十割

原子層沉積 (atomic layer deposition, ALD) 253, 277, 277

差動放大器 (differential amp) 340, 358-359

差排 (dislocation) 226-227, 269, 366

庫倫散射 (Coulomb scattering) 230, 279

弱反轉 (weak inversion) 82, 84, 116, 140

時序邏輯 290, 305, 312

時脈 (clock) 290, 300, 307, 318, 326, 328-329, 343, 345, 356, 363

時間延遲(propagation delay time) 210, 251, 290-291, 293, 326, 358, 442, 448-449, 455, 466

氧化層陷阱電荷 (oxide trapped charge) 99, 104

氧化層電容 (oxide capacitance) 89, 91, 94-95, 110, 130, 152, 442

氧化層電荷 (oxide charge) 89, 91, 94-95, 110, 130, 152, 442

浮動閘 (floating gate) 353-355, 369, 371, 373-377

特殊用途 IC (Application Specific Integrated Circuit; ASIC) 386

真空能階(vacuum level) 77, 79, 97-98

窄通道效應 (narrow channel effect) 461

能帶圖 (energy band diagram) 2, 13, 24, 31-32, 38-39, 62, 70, 77-80, 83-84, 88, 90, 96, 98, 100, 111, 116-117, 153

能隙中心 (midgap) 7,107,108

能障高度 (barrier height) 79, 172-173, 423

記憶卡 (memory card) 370, 406

記憶體 (Memory) 275-276, 283, 294, 318, 329, 352-356, 358, 360, 362-364, 368-377, 379-380, 382-383, 386, 389, 391, 396, 401, 405-406

送回重作 (re-work) 192

逆向偏壓 (reverse bias) 38-42, 44, 46-50, 53-54, 56-58, 61-63, 65, 67, 70, 143-144, 170, 172, 175, 178, 292, 337

逆向飽和電流 (reverse saturation current) 53-56, 58

退後井 (retrograde well) 229

配線 (routing) 311-313

閃爍雜訊 (flicker noise, 1/f noise) 344, 456

高介電係數 (high-k) 123, 136, 215, 275-276

高介電係數閘極介電層 (high-k gate dielectric) 123, 276