

第三章

Getting started with Thresholding

1

Thresholding

影像處理

2

Global Local

處理類別

3

Thresholding

參數優化

同學,歡迎你參加本課程

- ☑ 請關閉你的FB、Line等溝通工具,以免影響你上課。
- ☑ 考量頻寬,請預設關閉麥克風、攝影機,若有需要再打開。
- ☑ 隨時準備好,老師會呼叫你的名字進行互動。
- ✓ 如果有緊急事情,你必需離開線上教室,請用聊天室私訊給老師, 以免老師癡癡呼喚你的名字。
- ☑ 先倒好水、上個洗手間,準備上課囉^^

課程檔案下載



ZOOM 學員操作說明





Thresholding

Partitioning an image into a foreground and background

By making it black and white

We do so by setting each pixel to:

- 255 (white) if pixel > thresh value
- 0 (black) if pixel < thresh value

Original



Thresholded





Thresholding

Simplest method of image segmentation

- Isolate objects
 - Object detection
 - Face detection
 - o Etc.

Original image




Thresholded image





Thresholding

Only from grayscale images





Apply it

```
# Obtain the optimal threshold value
thresh = 127

# Apply thresholding to the image
binary = image > thresh

# Show the original and thresholded
show_image(image, 'Original')
show_image(binary, 'Thresholded')
```

Original



Thresholded





Inverted thresholding

Original Image



Inverted Thresholded





Categories

- Global or histogram based: good for uniform backgrounds
- Local or adaptive: for uneven background illumination

Original

Region-based segmentation

background. These markers are pixels that we can label mambiguously as either object or background. Here, the markers are found at the two extreme parts of the histogram of grey values:

* farrage - marerus_1Dm(coine)

Global thresholding

n-based segmentation

determine markers of the coins and the proper markers are pixels that we can lot all the pixels that we can lot all the pixels that we can lot all the pixels are parts of the pixels are pixels.

Local thresholding

Region-based segmentation

Let us first determine markers of the coins and the background. These markers are pixels that we can label mambiguously as either object or background. Here, the markers are found at the two extreme parts of the listogram of grey values:

Per sqriber - up. seros_10m(entes)



Try more thresholding algorithms

```
from skimage.filters import try_all_threshold

# Obtain all the resulting images
fig, ax = try_all_threshold(image, verbose=False)

# Showing resulting plots
show_plot(fig, ax)
```



Global

Uniform background

```
# Import the otsu threshold function
from skimage.filters import threshold_otsu
# Obtain the optimal threshold value
thresh = threshold_otsu(image)

# Apply thresholding to the image
binary_global = image > thresh
```



Try more thresholding algorithms

Original

Region-based segmentation

is a firm determine mercers of the come and the element. These moreover are passed that we can used name place by an element object of backgrowed. First it measures are found at the extreme parts of the mercer and come values.

Manage - with the beauty

15

on-based segmentation

the determine markings of the color and the in Thise markers are places that we can shall before either object or background. For the 20 Spand at the two extreme purish life (Stopy Values):

Berta Silversia

Isodata

an-based segmentation

Systemsine mericus of the colour and the Down markets are please that the sail and the reference pleas, or hashy point. HOW, possess of the two betterne purision in possess.

AND PARTIES

Mean Named Segmentation

compline members of the colors and the streets are placed that we can add a get object or background. Fort, the two estperms puris of the

Minimum

egmentation

Tighters of the coint and the large place that we can lake tripid or background. Here, the two concerns parts of the

Triangle

signification.

to of the calor and the open to the state of the satisfactorial. Here we can be set to the satisfactorial of t

Otsu

n-based segmentation

Astermine merkers of the coins and the These markers are piece ever we can aird be either object or background, b.Ch., collect at the two extreme pures of the collection.

Con Chinester

Yen

Région-based segmentet an

The first determine marker; of the compared his specific and an action are placed that an act, and applicated as either object of lapping out in formalists and found at the two nations is a 15 m of prey values.

with the tapes, I bereichen:



Global

Uniform background


```
# Import the otsu threshold function
from skimage.filters import threshold_otsu
# Obtain the optimal threshold value
thresh = threshold_otsu(image)

# Apply thresholding to the image
binary_global = image > thresh
```



Global

```
# Show the original and binarized image
show_image(image, 'Original')
show_image(binary_global, 'Global thresholding')
```





Local

Uneven background

```
# Import the local threshold function
from skimage.filters import threshold_local

# Set the block size to 35
block_size = 35

# Obtain the optimal local thresholding
local_thresh = threshold_local(text_image, block_size, offset=10)

# Apply local thresholding and obtain the binary image
binary_local = text_image > local_thresh
```



Local

```
# Show the original and binarized image
show_image(image, 'Original')
show_image(binary_local, 'Local thresholding')
```

Original

Region-based segmentation

Let us first determine markers of the coins and the background. These markers are pixels that we can label trambiguously as either object or background. Here, the markers are found at the two extreme parts of the histogram of grey values:

Baranes - np. neros_like(coins)


Local thresholding

Region-based segmentation


Let us first determine markers of the coins and the background. These markers are pixels that we can label unambiguously as either object or background. Here, the markers are found at the two extreme parts of the histogram of grey values:

Non markets - ng. seros_like(coins)



















問卷

http://www.pcschoolonline.com.tw



