26F Stat TA Session W3

📢 Quiz 1 Information

- Time: **10/1 (Thu.) 15:30 - 16:20** (first hour of TA session)
- Quiz 1 will only cover Chapter 1 & 2 (no TA session material included)
- This is a closed-book quiz and only calculators are permitted
- The questions will be based on homework and in-class exercises
- Check syllabus for more quiz information


0. Preparation for TA session

- Please download the W3 example code and the attached dataset click here
  - This week we'll use the dataset `loan_full_schema` , which is a extended version of `loan50` (the W2 dataset)
- Import `loan_full_schema` and `county`

1. Miscellaneous things

Folder Organization

- Although it sounds simple, but it's important to have well-organized folders for your working project!
- Different types of files (code scripts, datasets, output, etc.) should be saved in different folders.



Coding Styles

- You can write your code in any ways as long as it works. But it's important to allow others to read your codes and understand what you're doing!
- Check the following website to learn more about readable codes

> Tidyverse style guide
>
> Good coding style is like correct punctuation: you can manage without it, butitsuremakesthingseasiertoread. This site describes the style used throughout the tidyverse. It was derived from Google's original R Style Guide - but Google's current guide is derived from the tidyverse style guide.
>
> https://style.tidyverse.org/

- **Naming:** Only use lowercase letters, numbers, and use `_` to replace any spaces
  - Make sure others are able to understand the meaning of your variable

```
# Good
lesson_one
lesson_1

# Not good
LessonOne
lessonone

# Total Disasters
LeSSoNone
one       # it's hard to be distinguished from the number 1
a <- 1    # "a" does not provide any meanings!
```

- **Spacing:**
  - Always put a space after a comma `,` and never put one before it
  - Do not put spaces inside or outside parentheses
  - You may put spaces before and after `=`

```
# Good
x[, 1]
mean(x, na.rm = TRUE)

# Bad
x[,1]
x[ ,1]
x[ , 1]
```

```r
mean (x, na.rm = TRUE)
mean( x, na.rm = TRUE )   # weird spacing
```

- **Function Indents:**
  - Indent the argument name with a single indent
    - Indents is mandatory for some programming language (e.g., `Python`), but not for `R`
  - Avoid putting `+` or `,` at the head of a new line!

```r
# Good
long_function_name <- function(
    a = "a long argument",
    b = "another argument",
    c = "another long argument"
) {
}

# an example from W2
ggplot(county, aes(x = multi_unit, y = homeownership)) +
        # then start a new line with indent
    geom_point(color = "steelblue",
               size = 1,
               shape = 5
               )

# Bad
long_function_name <- function(a = "a long argument",
b = "another argument",
c = "another long argument"
) {
}
long_function_name <- function(a = "a long argument", b = "another argumen
t", c = "another long argument"){}
```

Clean up the environment

- When dealing with multiple datasets at the same time, you may end up with too many variables in the environment. e.g., variables from previous analyses
- You can use `rm(list = ls())` to clean up the workspace, especially when you want to rerun the entire code
  - `ls()` returns a character vector of object names in the current environment

```r
x <- 1
y <- "hi"
ls()
# [1] "x" "y"

# rm = remove
rm(list = ls())
```

2. Summary Statistics

Create a contingency table `table()`

- A contingency table is a specialized table used to record the relation between two or more **categorical** variables
  - `table()` gives us numbers for each category

```r
# dnn = dimension names
A <- table(..., dnn = ...)

# example
loan <- read.csv("loans_full_schema.csv")

table <- table(loan$application_type,
                            loan$homeownership,
                            dnn = c("application type",  # create a vector c
() to name rows and cols                                          "home ow
nership"
                                                    )
                            )

# output
                    home ownership
application type MORTGAGE  OWN RENT
      individual     3839 1170 3496
      joint           950  183  362
```

- We can also count the total number for each category along using `addmargins`

```r
table_withsum <- addmargins(table)

# output
                 home ownership
application type MORTGAGE   OWN  RENT   Sum
```

```
      individual     3839  1170  3496  8505
      joint           950   183   362  1495
      Sum            4789  1353  3858 10000
```

- `addmargins()` adds marginal totals to the original table
  - We can also use other functions to extend the table

```
# example: minimal values
# FUN = the function (statistics) you want to compute
addmargins(table, FUN = list(list(MIN = min)))

# output
Margins computed over dimensions
in the following order:
1: application type
2: home ownership

                home ownership
application type MORTGAGE  OWN RENT  MIN
      individual     3839 1170 3496 1170
      joint           950  183  362  183
      MIN             950  183  362  183
```

3. More data visualization


Bar plot `geom_bar()`

```
ggplot(loan, aes(x = homeownership, fill = application_type)) +
  geom_bar(position = "dodge")   # the bars dodge each other
```



Figure: Bar plot of homeownership by application type

```r
# bar plot defaults to stack the catagory counts
ggplot(loan, aes(x = homeownership, fill = application_type)) +
  geom_bar()
```




- We can add title and axis labels to improve the readability of the figure

```r
your_plot +
    labs(x = ..., y = ..., title = ...) +            # labs = labels
    theme(plot.title = element_text(hjust = 0.5))

# example
bar_graph +
  labs(x = "Type of Homeownership",   # what is shown in x-axis
       y = "Number of People",        # what is shown in y-axis
```

```
       title = "The Bar Plot with Beautiful Labels",    # your plot title
       fill = "Application Type"      # fill in bars with different colors
      ) +
  theme(plot.title = element_text(hjust = 0.5))   # center the title
```




- Another trick is to adjust the scale of x and y-axes
  - Again we can relabel the scales!

```
your_plot +
    # breaks = where tick marks appear
    # labels = change the text for each ticks
    scale_x_continuous(breaks = ..., labels = ...) +
    scale_y_continuous(breaks = ..., labels = ...)

# example
# recall scatter plot we learned last week
scatter_plot <- ggplot(county, aes(x = multi_unit, y = homeownership)) +
  geom_point(color = "steelblue", shape = 5)

scatter_plot_scale <- scatter_plot +
  scale_x_continuous(
      breaks = c(0, 20, 40, 60, 80, 100),
      labels = c("0%", "20%", "40%", "60%", "80%", "100%")
    ) +

  scale_y_continuous(
      breaks = c(0, 50, 100),
      labels = c("0%", "50%", "100%")
    )
```




- `scale_x_continuous()` is used for numeric variables (continuous valued)
- For categorical variables (discrete), use `scale_x_discrete()` instead

▼ Q. What's the difference between a histogram and a bar plot?

Ans.

- A histogram shows the **distribution of a numeric variable**
- A bar plot compares the values or counts across **different categories of a categorical variable**





We summarize the subtle differences in the table below

- Think about what would happen if we use a histogram to show categorical variables!

	Histogram	Bar plot
What it shows?	the distribution	the density (count)
What's on the x-axis?	numeric values	categories of variables

 Always check if your data visualization strategy is valid and appropriate!

Exercises

W3 Exercises