

# Geometric Multigrid for Higher-order Discretizations

Hari Sundar

Georg Stadler, Omar Ghattas, George Biros

Institute for Computational Engineering & Sciences



Copper Mountain Multigrid 2013

# Motivation

Scalable solution of large-scale linear systems

asymptotically optimal parallel solvers for elliptic PDEs

# Motivation

Scalable solution of large-scale linear systems

asymptotically optimal parallel solvers for elliptic PDEs

variable coefficients

adaptive discretizations

arbitrary geometries

high-order discretizations

massively parallel

# Motivation

Scalable solution of large-scale linear systems

asymptotically optimal parallel solvers for elliptic PDEs

variable coefficients

adaptive discretizations

arbitrary geometries

high-order discretizations

massively parallel


## Parallel Geometric Multigrid

$$O\left(\frac{N}{p} + \log N\right) \text{ for elliptic PDEs with smooth coefficients}$$

# parallel multigrid

## challenges


- geometric multigrid for arbitrary meshes
  - graph based partitioning (ParMETIS SC'98, SC'00)
  - scalability is challenging



# parallel multigrid

## challenges


- geometric multigrid for arbitrary meshes
  - graph based partitioning (ParMETIS SC'98, SC'00)
  - scalability is challenging
- octrees
  - dendro (Sampath et al., SC'08)
  - limited to cubic domains



# parallel multigrid

## challenges


- geometric multigrid for arbitrary meshes
  - graph based partitioning (ParMETIS SC'98, SC'00)
  - scalability is challenging
- octrees
  - dendro (Sampath et al., SC'08)
  - limited to cubic domains
- two-tier meshes, macromesh + regular grid
  - HHG (Bergen et al., SC'05)
  - limited adaptivity



# parallel multigrid

## challenges


- geometric multigrid for arbitrary meshes
  - graph based partitioning (ParMETIS SC'98, SC'00)
  - scalability is challenging
- octrees
  - dendro (Sampath et al., SC'08)
  - limited to cubic domains
- two-tier meshes, macromesh + regular grid
  - HHG (Bergen et al., SC'05)
  - limited adaptivity
- algebraic multigrid
  - Adams et al., SC'04
  - Hypre(CHPC'10), trilinos::ML
  - graph based coarsening
  - need assembled matrix



# Parallel Multigrid

## Key Contributions


- GMG for complex geometries with adaptivity (macromesh + octrees)
- excellent strong and weak scalability
- low setup cost
- matrix-free implementation using non-blocking MPI calls
- 262K cores with single MPI process per core



# Parallel Multigrid


## Key Contributions

- GMG for complex geometries with adaptivity (macromesh + octrees)
- excellent strong and weak scalability
- low setup cost
- matrix-free implementation using non-blocking MPI calls
- $262K$  cores with single MPI process per core




# two-tier meshes

conforming macromesh of adaptive octrees



# two-tier meshes

conforming macromesh of adaptive octrees



# two-tier meshes

conforming macromesh of adaptive octrees


# two-tier meshes

conforming macromesh of adaptive octrees

forest of octrees


# two-tier meshes

conforming macromesh of adaptive octrees



# two-tier meshes

conforming macromesh of adaptive octrees




# multigrid setup

coarsening

for octrees:

if all siblings exist, replace with parent




# multigrid setup

coarsening

for octrees:

if all siblings exist, replace with parent




# multigrid setup

coarsening

for octrees:


preserve 2:1 balance at all grids



# multigrid setup


coarsening

for forests: cannot coarsen beyond  
first-tier macromesh




# Multigrid Setup

Partitioning & load balancing




# Multigrid Setup

Partitioning & load balancing




# Multigrid Setup

partitioning & load balancing



# Multigrid Setup

partitioning & load balancing



# Inter-grid transfer operators


Simultaneous traversal over coarse and fine meshes

- matrix-free implementation
- $P_{ij}$  - coarse grid shape function ( $\phi_j$ ) evaluated at the fine grid point ( $p_i$ )

# Multigrid Solve

Coarse grid solver


- smoothed aggregation algebraic multigrid (trilinos::ML)
- GMG-AMG approach matches our two-tier geometric decomposition of the domain
- AMG is used for small problem sizes on small process counts



# Multigrid Solve

Coarse grid solver

- smoothed aggregation algebraic multigrid (trilinos::ML)
- GMG-AMG approach matches our two-tier geometric decomposition of the domain
- AMG is used for small problem sizes on small process counts




# Results

Test problem

$$-\operatorname{div}(\mu(x)\nabla u(x)) = f(x) \quad \forall x \in \Omega, \quad u(x) = 0 \text{ on } \partial\Omega.$$


$$\mu(x) = 1 + 10^6(e^{-(x-x_1)^2/2\sigma_1^2} + e^{-(x-x_2)^2/2\sigma_2^2})$$

- 3D Poisson problem
- Dirichlet boundary conditions
- isotropic spatially varying coefficient
- forest of 24 Octrees




# Results

## Strong scaling




124M elements  
5 GMG levels  
AMG\* for Coarse solve  
1 MPI process per core  
Jaguar XK6




\* smoothed aggregation (ML)

# Results

## Weak scaling




215K elements per process  
AMG for Coarse solve  
1 MPI process per core  
Jaguar XK6



# Results

Weak scaling : Antarctica mesh



45K Octrees


400K elements per process

constant coefficient Poisson

Cores	64	512	4096	32768	262144
Setup	2.97	2.64	3.1	3.76	8.6
<b>Smoother</b>	<b>289.7</b>	<b>301.5</b>	<b>336.3</b>	<b>391.3</b>	<b>409.1</b>
Transfer	7.45	8.47	11.5	11.35	15.88
Coarse Setup	1.85	2.13	0.82	1.27	1.63
Coarse Solve	24.3	30.8	18.47	30.1	26.01
Total Time	326.3	345.5	370.2	437.8	461.2

# Results

Weak scaling : Antarctica mesh



45K Octrees

400K elements per process  
constant coefficient Poisson

Cores	64	512	4096	32768	262144
Setup	2.97	2.64	3.1	3.76	8.6
<b>Smoother</b>	<b>289.7</b>	<b>301.5</b>	<b>336.3</b>	<b>391.3</b>	<b>409.1</b>
Transfer	7.45	8.47	11.5	11.35	15.88
Coarse Setup	1.85	2.13	0.82	1.27	1.63
Coarse Solve	24.3	30.8	18.47	30.1	26.01
Total Time	326.3	345.5	370.2	437.8	461.2

100 Billion unknowns on 262K cores while sustaining 272 TFlops/sec.

# Motivation

Scalable solution of large-scale linear systems

asymptotically optimal parallel solvers for elliptic PDEs

variable coefficients

adaptive discretizations

arbitrary geometries

high-order discretizations

massively parallel


How to support high-order discretizations ?

# high-order discretizations

## challenges

- $p$ -multigrid


- coarse grid based on lower-order polynomials
- Use GMG once  $p = 1$  has been reached



# high-order discretizations

## challenges

- $p$ -multigrid
  - coarse grid based on lower-order polynomials
  - Use GMG once  $p = 1$  has been reached
- Schwarz-based methods
  - expensive local solves (deformed elements)
  - parallel scalability of coarse grid solve



Local Solve

- Dirichlet boundary node
- unknowns

# high-order discretizations


## challenges

- $p$ -multigrid

- coarse grid based on lower-order polynomials
- Use GMG once  $p = 1$  has been reached

- Schwarz-based methods

- expensive local solves (deformed elements)
- parallel scalability of coarse grid solve



Schwarz Solve



● Dirichlet boundary node

● unknowns

# high-order discretizations

## challenges



- $p$ -multigrid
  - coarse grid based on lower-order polynomials
  - Use GMG once  $p = 1$  has been reached
- Schwarz-based methods
  - expensive local solves (deformed elements)
  - parallel scalability of coarse grid solve
- precondition using lower-order operator
  - Spectrally equivalent
  - lower convergence at higher orders



# high-order discretizations

## challenges

- $p$ -multigrid
  - coarse grid based on lower-order polynomials
  - Use GMG once  $p = 1$  has been reached
- Schwarz-based methods
  - expensive local solves (deformed elements)
  - parallel scalability of coarse grid solve
- precondition using lower-order operator
  - Spectrally equivalent
  - lower convergence at higher orders
- $h$ -multigrid using high-order discretizations
  - Use AMG (Heys *et al.*)



# high-order discretizations

precondition using lower-order operator

Number of pCG iterations to converge to a relative tolerance of  $10^{-8}$

order	$8 \times 8$	$32 \times 32$	$128 \times 128$	$8 \times 8 \times 8$
1*	4	4	4	5
2	14	14	14	25
3	21	21	21	45
4	30	30	30	79
5	43	43	43	144
6	64	65	65	260
7	98	99	99	465
8	142	146	148	840

# high-order discretizations

$h$ -multigrid using high-order discretizations

- Coarsening, inter-grid operators & coarse-grid solvers are straightforward

# high-order discretizations

$h$ -multigrid using high-order discretizations

- Coarsening, inter-grid operators & coarse-grid solvers are straightforward
- Smoothers
  - Jacobi
  - chebyshev
  - Symmetric SOR

# high-order discretizations

$h$ -multigrid using high-order discretizations

- Coarsening, inter-grid operators & coarse-grid solvers are straightforward
- Smoothers
  - Jacobi
  - chebyshev
  - Symmetric SOR
- MG as a solver or with PCG

# high-order discretizations

$h$ -multigrid using high-order discretizations

Number of CG iterations/v-cycles to converge to a relative tolerance of  $10^{-8}$

order	Multigrid			MG pCG		
	Jacobi(3)	Chebyshev(3)	SSOR(2)	Jacobi(3)	Chebyshev(3)	SSOR(2)
1	5	6	4	4	4	4
2	6	10	4	5	6	4
3	8	24	5	6	11	4
4	-	54	8	-	16	6
5	-	178	13	-	28	8
6	-	-	24	-	51	12
7	-	-	70	-	105	19
8	-	-	270	-	204	36

# high-order discretizations

$h$ -multigrid using high-order discretizations


Number of CG iterations/v-cycles to converge to a relative tolerance of  $10^{-8}$

order	Multigrid			MG pCG			pCG	
	Jacobi(3)	Chebyshev(3)	SSOR(2)	Jacobi(3)	Chebyshev(3)	SSOR(2)	linear	nonlinear
1	5	6	4	4	4	4	4	4
2	6	10	4	5	6	4	4	14
3	8	24	5	6	11	4	4	21
4	-	54	8	-	16	6	6	30
5	-	178	13	-	28	8	8	43
6	-	-	24	-	51	12	12	65
7	-	-	70	-	105	19	19	99
8	-	-	270	-	204	36	36	148

# high-order discretizations

parallelizing SSOR - Octree Coloring


- block parallel SOR
- need coloring to define ordering
- Only boundary nodes need to be colored
- Coloring for balanced octree boundaries
  - Similar to Quadtree coloring
- Luby, LDF, SDL
- SDL → 5 balanced colors



# high-order discretizations

parallelizing SSOR - Octree Coloring


- block parallel SOR
- need coloring to define ordering
- Only boundary nodes need to be colored
- Coloring for balanced octree boundaries
  - Similar to Quadtree coloring
- Luby, LDF, SDL
- SDL → 5 balanced colors



# high-order discretizations

parallelizing SSOR - Octree Coloring

- block parallel SOR
- need coloring to define ordering
- Only boundary nodes need to be colored
- Coloring for balanced octree boundaries
  - Similar to Quadtree coloring
- Luby, LDF, SDL
- SDL → 5 balanced colors



# Summary

- parallel, matrix-free multigrid method on geometry-conforming unstructured forests of octrees
- pCG using SSOR as a smoother capable of supporting high-order discretizations
- demonstrated strong scalability from 512 to 131K cores
- demonstrated weak scalability up to 262K cores using one MPI process per core
- largest solve was on a mesh with 45K octrees with 100 billion unknowns on 262K cores sustaining 272 TFlops/s
- Ongoing work to parallelize support for high-order discretizations

Thank you !