Auto Flight Charts (S.O.O. 6221) – General Data

1. General

The charts given in this section relate to the various components associated with auto flight.

A. Cable Charts – Honeywell Autopilot (S.O.O. 6221)

Table 1 — Autopilot Servo Actuator Control – Cable Chart gives the Part No. end terminations, cable size, length, material and cable proof load figures for the autopilot servo actuator cables. When using the chart, refer to 91-00-00, Charts – General Data, Cable Charts.

Table 1 Autopilot Servo Actuator Control – Cable Chart

CABLE PART NO. & LOCATION	END TERMINATIONS		CABLE SIZE	LENGTH INCHES	MATERIAL & SPEC	PROOF LOAD LBS
	LEFT	RIGHT				
C6R1806–7 Aileron servo actuator cable.	MS20664C3 (Swaged)	MS20664C3 (Swaged)	3/32 inch 7 X 7	A9 to B11 20.50 ± 0.120	Carbon Steel MIL–W–83420 TY1 COB	550
C6R1806–9 Elevator servo actuator cable.	MS20664C3 (Swaged)	MS20664C2 (Swaged)	3/32 inch 7 X 7	A9 to B11 50.50 ± 0.120	Carbon Steel MIL–W–83420 TY1 COB	550
C6R1806–11 Rudder servo actuator cable.	MS20664C3 (Swaged)	MS20664C3 (Swaged)	3/32 inch 7 X 7	A9 to B11 49.75 ± 0.120	Carbon Steel MIL–W–83420 TY1 COB	550
C6R1807–9 Aileron servo actuator cable. (1) Rudder servo actuator cable. (2)	MS21260–53LH	MS20664C3 (Swaged)	3/32 inch 7 X 7	A1 to B11 4.80 ± 0.120	Carbon Steel MIL–W–83420 TY1 COB	550
C6R1807–11 Aileron servo actuator cable.	MS21260–53RH	MS20664C3 (Swaged)	3/32 inch 7 X 7	A1 to B12 26.50 ± 0.120	Carbon Steel MIL–W–83420 TY1 COB	550
C6R1807–13 Elevator servo actuator cable.	MS21260–53RH	MS20664C3 (Swaged)	3/32 inch 7 X 7	A1 to B12 34.50 ± 0.120	Carbon Steel MIL–W–83420 TY1 COB	550
C6R1807–15 Rudder servo actuator cable.	MS21260–53RH	MS20664C3 (Swaged)	3/32 inch 7 X 7	A1 to B12 34.75 ± 0.120	Carbon Steel MIL–W–83420 TY1 COB	550
C6R2042–1 Pitch Trim bridle cable.	MS20664C2 (Swaged) with sleeve VS100–S3 and sleeve spacer C6R2042–29	MS20664C2 (Swaged)	1/16 inch 7 X 7	A10 to B11 57.50 ± 0.030	Carbon Steel MIL–W–83420 TY1 COB	290
C6R2043–1 Pitch Trim bridle adjust cable.	MS20664C3 (Swaged)	MS20664C3 (Swaged) with crosspiece VS100–C3 and nut VS 100–N3	3/32 inch 7 X 19	A10 to B11 2.50 ± 0.030	Carbon Steel MIL–W–83420 TY1 COB	550