Recorders – General Data

1. General

The Recording System consists of two types of crash protected digital recording devices; the Cockpit Voice Recorder (CVR), and the Flight Data Recorder (FDR). These devices capture the cockpit communications and the flight data information for retrieval in the event of a crash.

For aircraft incorporating customer standard option Mod S.O.O. 6292, the Cockpit Voice Recorder (CVR) is removed from the aircraft and associated systems.

For aircraft incorporating customer standard option Mod S.O.O. 6299, the Flight Data Recorder (FDR) is removed from aircraft and associated systems.

An optional recorder is offered for Engine Condition Trend Monitoring (ECTM)/Flight Operations Quality Assurance (FOQA) Data Capture (S.O.O. 6288) system which consists of an IONode recording unit and a multi element GPS/WiFi antenna. The IONode continuously records data from the aircraft Flight Data Recorder, and its own internal sensors. Data is subsequently downloaded to a PC for analysis.

For aircraft incorporating Mod 6/2303, provisions have been made for 512 Word FDR outputs for Apex ARINC 717 output data stream only.

For aircraft with customer Standard Option Order S.O.O. 6388 installed, the Cockpit Voice Recorder (CVR) and the Flight Data Recorder (FDR) are not installed.

For aircraft with S.O.O. 6388 incorporated, the Cockpit Voice Recorder (CVR) and associated systems are installed by incorporating customer Standard Order Option S.O.O. 6384.

For aircraft with S.O.O. 6388 incorporated, the 512 Word Flight Data Recorder (FDR) and associated systems are installed by incorporating customer Standard Order Option S.O.O. 6385.

This Page Intentionally Left Blank