FLEET TEAM DIGEST

737MAX-FTD-34-21001

Issue Title : 5G Lower C-band Interference with Radio Altimeter (3.7 - 3.98 GHz)

Airplane Model	ATA	Minor Model(s)
737MAX	3433-00	-7, -8, -8200, -9, -BBJ

Other Model(s)	ECCN
MD-90, MD-11, 737, 747, 767, MD-80, 777, 727, DC-10, 787, 737NG, 757, DC-9, DC-8, 717, 707, MD-10	9E991

Originated Date	Last Revised Date	Created On
04/10/2021	07/09/2026	04/10/2026

Estimated Completion Date	Next Update Date
12/31/2027	09/30/2026

Revision Description

Clerical changes made. Reworked all sections to address Lower C-band only. Upper C-band and future spectrum developments to be addressed in a new Upper C-band FTD targeted for publication in September 2026. Milestones updated. Attachments updated as follows:

- Attachment 2 - New information available
- Attachment 4 - Improved format
- Attachment 6 - Improved format, minor changes to wording
- Attachment 9 - Improved format, new information available
- Attachment 12 - New information available
- Attachment 13 - Improved format, minor edits to wording
- Attachment 15 - Improved format, minor edits to wording

Applicability

All Boeing airplanes equipped with low-range radio altimeter (LRRA)

Description

Worldwide spectrum regulators have allocated frequencies in the 3.4 - 4.2 GHz range for 5G cellular use. Note that in accordance with terminology used by the Federal Aviation Administration (FAA), the “Lower C-band” refers to frequencies from 3.4 - 3.98 GHz and the “Upper C-band” refers to frequencies from 3.98-4.2 GHz. This article addresses 5G deployment in the Lower C-band (3.4 -

BOEING PROPRIETARY - The information contained herein is Proprietary to The Boeing Company and shall not be reproduced or disclosed in whole or in part or used for any reason except when such user possesses direct, written authorization from The Boeing Company. Encrypted emails required for forwarding via Email.The document generated on 11/09/2026 by Fleet Team Digest application via MyBoeingFleet. This document is for reference purposes only, visit the application for all the latest and updated revisions of this document.

Copyright ©2026 Boeing. All rights reserved.

EXPORT CONTROLLED -This technology or software is subject to the U.S. Export Administration Regulations (EAR), (15 C.F.R. Parts 730-774). No authorization from the U.S. Department of Commerce is required for export, re-export, in-country transfer, or access EXCEPT to country group E:1 or E:2 countries/persons per Supp.1 to Part 740 of the EAR. ECCN : 9E991

3.98 GHz).

5G cellular equipment operating in the Lower C-band, particularly higher powered equipment operating in in the 3.7 - 3.98 GHz frequency band, has the potential to interfere with airplane radio altimeters which operate in the 4.2 - 4.4 GHz frequency band. Note that radio altimeter (RA) may also be referred to as low-range radio altimeter (LRRA), radar altimeter, RALT, or RADALT. A number of countries have deployed or are planning deployment of Lower C-band frequencies for 5G cellular use (see Attachment 2). Possible sources of harmful 5G emissions include base stations (cell towers) near airport approach paths, user equipment (cell phones, tablets, laptops, etc.) on the ground near approach paths, and user equipment carried onboard airplanes, also known as Portable Electronic Devices (PEDs). Some authorities have issued safety warnings regarding base stations and user equipment operating in the 5G Lower C-band, while others have already issued regulation including the U.S., Australia, Canada, and Brazil.

RA data is used in automatic landing, flight controls, primary displays, crew alerting, surveillance, and other systems, depending on airplane model. Current Boeing Functional Hazard Assessments, Failure Mode and Effects Analyses, and Single and Multiple Failure Analyses indicate that loss of, or erroneous RA height from one or multiple RAs may result in major, hazardous or catastrophic failure effects depending on a number of factors, including flight phase and position above the ground.

On 07-October-2020, the Radio Technical Commission for Aeronautics (RTCA) released RTCA Paper No. 274-20/PMC-2073 documenting their assessment of 5G interference on aircraft RAs. The assessment was limited to the 3.7 - 3.98 GHz 5G band planned for use in the United States. All known types of base stations and user equipment were considered, and fundamental 5G emissions (3.7 - 3.98 GHz) as well as spurious (out of band) 5G emissions in the RA band (4.2 - 4.4 GHz) were evaluated. Nine types of RA equipment were tested. The study concluded, for usage Category 1 (Commercial Air Transport) aircraft:

1. 5G mid-band fundamental transmissions from ground stations exceed the recommended protection criteria for RAs, and will therefore interfere with most RAs, to varying degrees.
2. Emissions from 5G user equipment on the ground are not expected to cause significant operational impacts for commercial airplanes.
3. Fundamental and spurious emissions from 5G user equipment onboard airplanes may exceed the recommended protection criteria for RAs.

Since the RTCA report was published, Boeing RA suppliers performed independent testing and achieved similar results, noting additional variation due to temperature and equipment tolerances. Also, the RTCA report did not address frequencies and base station characteristics applicable to regions outside the United States. Several factors, such as variation in equipment age, 5G waveform, power levels, antenna orientation/height, terrain or structure reflection/multi-path, and some 5G frequencies in the range 3.4 - 4.99 GHz, were also evaluated for RA equipment compatibility.

In December 2020, Boeing initiated an Enterprise Integrated Product Team (IPT) to determine potential impacts on Boeing airplanes, coordinate industry involvement, and communicate 5G and RA compatibility on Boeing airplanes.

Status

To fulfill its objectives, the Boeing 5G RA Interference IPT has conducted the following activities:

- Supporting regulatory and standards agency investigations into 5G effects on commercial aviation
- Participating in the RTCA 5G environment assessment studies which catalog the characteristics of all types of mid-band 5G emissions that are being deployed globally
- Testing of all digital RAs from Honeywell, Collins, and Thales in the 3.7-3.98 GHz band to understand interference susceptibility based on 5G power level emissions, spurious emissions, temperature variation, serial number variation, etc.
- Flight testing of four RA models (LRA-900, ERT-550, ERT-530, and ALA-52B) in close proximity to live 5G C-band towers at different locations in order to validate analyses of the RA systems on Boeing airplanes, and confirm understanding of the 5G environment
- Analyzing and/or testing the airplane level effects of 5G interference (Refer to Attachment 6)
- Coordinating supplier testing and potential upgrade of RAs used on Boeing airplanes for potential effects of 5G interference
- Continue to monitor interim period 5G deployment between the current regulatory requirements and the adoption of the new RA Minimum Operational Performance Standard (MOPS). Determine any interim impacts to RA equipage and required changes to ensure safe airplane operation

BOEING PROPRIETARY - The information contained herein is Proprietary to The Boeing Company and shall not be reproduced or disclosed in whole or in part or used for any reason except when such user possesses direct, written authorization from The Boeing Company. Encrypted emails required for forwarding via Email.The document generated on 11/09/2026 by Fleet Team Digest application via MyBoeingFleet. This document is for reference purposes only, visit the application for all the latest and updated revisions of this document.

Copyright ©2026 Boeing. All rights reserved.

EXPORT CONTROLLED -This technology or software is subject to the U.S. Export Administration Regulations (EAR), (15 C.F.R. Parts 730-774). No authorization from the U.S. Department of Commerce is required for export, re-export, in-country transfer, or access EXCEPT to country group E:1 or E:2 countries/persons per Supp.1 to Part 740 of the EAR. ECCN : 9E991

- Participating in RTCA WG-239 to update the MOPS for DO-155 to protect future radar altimeters from existing and planned in-band and out-of-band interference
- Monitoring Boeing airplanes for 5G interference
  - Low probability that 5G interference was root cause of events investigated
  - Boeing conducted a study of Aircraft Health Management (AHM) data with the intent of detecting occurrence of 5G interference at airports using a tool to analyze faults related to RAs from the 737 MAX/777/787 airplane models and compare rates of faults triggered before and after launch of 5G C-band in the U.S. Boeing has not see any significant change in the fault rates at any specific location

FAA Airworthiness Directive (AD) 2023-10-02, FAA Model-Specific ADs, Operational Guidelines for Boeing Models, and Related Global Regulation

See Attachment 9 for complete information.

The FAA and other global civil aviation authorities (CAAs) have issued regulation containing required limitations and operating procedures to address the hazards of unreliable RA function due to 5G interference. Boeing has issued Flight Crew Operations Manual (FCOM) Bulletins/Multi-Operator Messages (MOMs) for each model fleet to characterize these operational restrictions.

Additionally, Boeing has been completing an assessment of radio altimeter susceptibility to the hazards of unreliable radio altimeter function during operation in global 5G Lower C-band environments. Boeing has issued recommendations pertaining to the current and planned (unmitigated) 5G Lower C-band environments in Australia, Canada, and Brazil.

Interim Action

RA Design Changes

In order to meet the changing 5G Lower C-band environment, suppliers, with Boeing collaboration, have developed design changes to existing RAs:

- Collins released an STC and associated service bulletin that incorporates an internal, passive hardware filter change and internal software modification to the LRA-900 model that results in an LRA-900+ unit. The STC that upgrades to the LRA-900+ unit was released in December 2022.
- Thales released a similar internal, active filter change and internal software modification to the ERT-550 that results in an ERT-550R unit. The ERT-550 STC that upgrades to the ERT-550R unit was released for 777 in November 2022.
- Honeywell is not planning any RA product improvements to the ALA-51A or ALA-52A at this time. Since the ALA-52B is already compliant to Group 4, there are also no changes currently planned for this unit.

Incorporation of upgraded RAs on aircraft will follow existing Aircraft Maintenance Manual (AMM) guidance for removal/installation. For aircraft other than 777, this generally involves shipset removal and replacement of just the RA units themselves (i.e., no impact to existing aircraft wiring or antennas).

Note that when upgrading RAs, along with IPC part numbers, the AMM/FIM/SDS information may also require change. For operators upgrading RAs on their aircraft based on supplier STC, a free-of-charge Customer Originated Change (COC) can be submitted to incorporate the applicable IPC/AMM/FIM/SDS information. Please refer to Attachment 13 for more information.

In addition to the supplier STCs and associated supplier Service Bulletins, Boeing will incorporate the Thales ERT-550 in production and issue Boeing retrofit Service Bulletins (SBs) for Thales ERT-550R on the 737 MAX and 777-F. See Attachment 12 for schedule information.

Due to extensive issues associated with certification including existing LRA-900 Electro-Magnetic Effects (EME) non-compliances and new type certification requirements for High Intensity Radiated Fields (HIRF), issues with component obsolescence, Boeing has determined it is no longer viable to pursue production/retrofit certification of the Collins LRA-900+. Operators that have already retrofitted or plan to retrofit to LRA-900+ should continue to use the Collins STC for approval.

Instead of the LRA-900+, the newer Collins LRA-2100 will now be certified for airplanes currently in production including 737 MAX, 767-F, 767-2C, 777-F and 777X. Boeing retrofit Service Bulletins will also be issued for LRA-2100. See Attachment 12 for schedule information.

BOEING PROPRIETARY - The information contained herein is Proprietary to The Boeing Company and shall not be reproduced or disclosed in whole or in part or used for any reason except when such user possesses direct, written authorization from The Boeing Company. Encrypted emails required for forwarding via Email.The document generated on 11/09/2026 by Fleet Team Digest application via MyBoeingFleet. This document is for reference purposes only, visit the application for all the latest and updated revisions of this document.

Copyright ©2026 Boeing. All rights reserved.

EXPORT CONTROLLED -This technology or software is subject to the U.S. Export Administration Regulations (EAR), (15 C.F.R. Parts 730-774). No authorization from the U.S. Department of Commerce is required for export, re-export, in-country transfer, or access EXCEPT to country group E:1 or E:2 countries/persons per Supp.1 to Part 740 of the EAR. ECCN : 9E991

Other model RAs or aircraft modifications may be considered via supplier STC, however operators would need to inquire with those suppliers for certification details on specific Boeing aircraft.

Illustrated Parts Catalog (IPC), Aircraft Maintenance Manual (AMM), System Description Section (SDS), and Fault Isolation Manual (FIM) Updates to Reflect STC Installation of 5G Lower C-band Interference-Tolerant RAs

See Attachment 13

Final Action

On 01-January-2028, the existing voluntary telecom 5G mitigation agreements with the FAA are scheduled to sunset. After this, 5G deployment may no longer be restricted, meaning that base stations in urban and rural areas could transmit at maximum power, up to 3.98 GHz, and while tilted above the horizon. At this time, it is not confirmed whether mitigations will be in effect in 2028 and how this could impact currently compliant RAs. However, in FAA Notice of Proposed Rulemaking (NPRM) Docket No. FAA-2025-5666, the FAA expressed their intention to ensure that current telecom mitigations are extended until the deployment of Upper C-band frequencies. Boeing continues to monitor the situation and coordinate with the aviation industry and spectrum regulators to advocate for the needs of our operators with respect to the termination of existing 5G mitigation agreements.

Regarding the deployment of Upper C band frequencies for 5G and the new RA Minimum Operational Performance Standard (MOPS), a new Upper C band FTD article is targeted for publication in September 2026.

Milestones

Note: Target dates are based upon currently available status and have risk of future revision.

Initial Supplier Testing (Honeywell, Collins, Thales): June 2021 (complete)

Boeing Initial AMOCs Issued: January 2022 (complete)

FIMs and AMM Updates: 25-March-2022 (complete)

Commencement of 5G Lower C-band Operation in U.S.: 19-January-2022 (complete)

IPC Updates: 20-May-2022 (complete)

Initial AT&T and Verizon Mitigations End : 05-July-2022 (complete)

Group 1-4 schedule established: 17-June-2022 (complete)

Flight Test: May 2022 (complete)

Expanded Supplier Testing: August 2022 (complete)

Thales ERT-550R STC for 777: 23-November-2022 (complete)

Collins LRA-900+ STC for 737 Classic/737NG/737 MAX/747-400/747-8/757/767/777/MD-10/MD-11: 16-December-2022 (complete)

End of Protection for Group 2 Radio Altimeters at Priority Airports: 01-January-2023 (complete)

BOEING PROPRIETARY - The information contained herein is Proprietary to The Boeing Company and shall not be reproduced or disclosed in whole or in part or used for any reason except when such user possesses direct, written authorization from The Boeing Company. Encrypted emails required for forwarding via Email.The document generated on 11/09/2026 by Fleet Team Digest application via MyBoeingFleet. This document is for reference purposes only, visit the application for all the latest and updated revisions of this document.

Copyright ©2026 Boeing. All rights reserved.

EXPORT CONTROLLED -This technology or software is subject to the U.S. Export Administration Regulations (EAR), (15 C.F.R. Parts 730-774). No authorization from the U.S. Department of Commerce is required for export, re-export, in-country transfer, or access EXCEPT to country group E:1 or E:2 countries/persons per Supp.1 to Part 740 of the EAR. ECCN : 9E991

FLEET TEAM DIGEST

Thales ERT-550R STC for 747-400: 23-February-2023 (complete)

End of Protection for Group 3A Radio Altimeters at Priority Airports: 01-March-2023 (complete)

End of Protection for Group 3B Radio Altimeters at Priority Airports: 01-July-2023 (complete)

Thales ERT-550R STC for 737NG/737 MAX: 03-July-2023 (complete)

Radio Altimeter Tolerant Configuration Required for Part 121 Operators for Operation in Contiguous U.S.: 01-February-2024 (complete)

FAA AD Limitations and Operating Procedures Incorporated into AFM: 2Q 2025 (complete)

FAA NPRM Docket No. FAA-2025-5666 (Upper C-band) Publication: 07-January-2026 (complete)

FAA Final Rulemaking (Upper C-band): 3Q 2026 (target)

737 MAX Production Incorporation for Thales ERT-550R (Attachment 12): 4Q 2026 (target)

737 MAX Service Bulletin Availability for Thales ERT-550R (Attachment 12): 4Q 2026 (target)

737 MAX Production Incorporation for Collins LRA-2100 (Attachment 12): 4Q 2026 (target)

737 MAX Service Bulletin Availability for Collins LRA-2100 (Attachment 12): 4Q 2026 (target)

New RA MOPS Publication: 1Q 2027 (target)

End of Voluntary Telecom 5G Mitigation Agreements with FAA: 01-January-2028 (planned)

Operator Action

FAA AD 2023-10-02, FAA Model-Specific ADs, Operational Guidelines for Boeing Models, and Related Global ADs

See Attachment 15 for complete information.

Note: "Radio altimeter tolerant" is defined in FAA AD 2023-10-02. Regarding operation in 5G Lower C-band environments outside the contiguous U.S., Boeing has completed an assessment for Canada, Brazil, and Australia. For the current and planned environments in Canada, Brazil, and Australia, radio altimeter tolerant airplane configurations include airplanes equipped with the Honeywell ALA-52B, the Thales ERT-550R (with 5G filter STC upgrade), the Collins LRA-900+ (with 5G filter STC upgrade), and the Collins LRA-2100 (future).

- Compliance with FAA AD 2023-10-02 and FAA Model-Specific ADs
  - Operators should comply with FAA AD 2023-10-02 and FAA model-specific ADs by inserting a copy of the limitations and operating procedures into their AFM as described
    - For radio altimeter tolerant airplane configurations, certain FAA AD restrictions may be removed from the AFM
  - Operators should review the Compliance Letters and AMOCs applicable to the RA model/part number installed on their aircraft for relief from FAA AD 2023-10-02 and FAA model-specific ADs and may choose to insert a copy of the applicable AMOC that provides AD relief into their AFM
  - Operators should follow the operational guidance provided in the applicable Boeing-published FCOM bulletins/MOMs (Attachment 9)

BOEING PROPRIETARY - The information contained herein is Proprietary to The Boeing Company and shall not be reproduced or disclosed in whole or in part or used for any reason except when such user possesses direct, written authorization from The Boeing Company. Encrypted emails required for forwarding via Email.The document generated on 11/09/2026 by Fleet Team Digest application via MyBoeingFleet. This document is for reference purposes only, visit the application for all the latest and updated revisions of this document.

Copyright ©2026 Boeing. All rights reserved.

EXPORT CONTROLLED -This technology or software is subject to the U.S. Export Administration Regulations (EAR), (15 C.F.R. Parts 730-774). No authorization from the U.S. Department of Commerce is required for export, re-export, in-country transfer, or access EXCEPT to country group E:1 or E:2 countries/persons per Supp.1 to Part 740 of the EAR. ECCN : 9E991

- Part 121 Operators: Required to upgrade to a radio altimeter tolerant airplane configuration to continue to operate in contiguous U.S. after 01-February-2024 (see Attachment 15)
- Part 129 Operators: Per FAA Notice N8900.670, must demonstrate to their principal inspectors that they have radio altimeter tolerant airplane configurations in order to operate unrestricted in the contiguous U.S.
- Non-Part 121/129 Operators: Are not required to upgrade their aircraft to a radio altimeter tolerant airplane configuration, but subject to FAA AD flight restrictions in the contiguous U.S. if not upgraded

Boeing Operational Guidance in Global 5G Lower C-band Environments

Boeing's assessment indicates that non-radio altimeter tolerant airplanes (non-5G Lower C-band interference-tolerant) are susceptible to the hazards of unreliable radio altimeter function during operation in the current/planned 5G Lower C-band environments in Australia, Canada, and Brazil.

- Boeing advises that mitigation of all identified hazards of 5G interference with radio altimeters is essential and regulatory operational guidance should be supplemented by guidance in the Boeing-published FCOM bulletins/MOMs (Attachment 9) to account for all hazards, all airplanes, and all models which may operate into Australian, Canadian, and Brazilian airspace

According to Boeing's assessment, Boeing advises the following during operation in the current/planned 5G Lower C-band environments in Australia, Canada, and Brazil:

- For non-radio altimeter tolerant airplane configurations, Boeing advises that it is essential to implement all operational restrictions outlined in the Boeing-published FCOM Bulletins/MOMs (Attachment 9)

- For radio altimeter tolerant airplane configurations, Boeing advises that operational restrictions are not needed

Interference from 5G User Equipment on the Ground/Airplane

- The RTCA report concluded that emissions from 5G user equipment on the ground are not expected to cause significant operational impacts for commercial airplanes, therefore, at this time, Boeing has no recommended actions for mitigating 5G user equipment on the ground
- Boeing recommends operators follow existing PED guidance and heed warnings and recommended mitigating actions from regulatory agencies for 5G user equipment carried aboard airplanes by crew or passengers

Flight crews and maintenance crews should remain vigilant for 5G interference, especially in lower altitudes around airports. Although 5G cellular signals can directly affect only RAs, interference may manifest as an effect on any of the downstream systems that use radio altimeter data. Please refer to Attachment 6 for the currently known list of airplane level effects. If operators encounter an event in which 5G interference is suspected, they can submit a report to Boeing Communication System (BCS). Please include the following information if available:

1. Time, location (airport/runway), and flight phase
2. Description of event
3. Flight deck effects observed
4. Air crew actions taken, and results of actions
5. Maintenance data and maintenance actions taken
6. QAR, FDR, or CPL data
7. RA part number
8. The reason 5G emissions are suspected

BOEING PROPRIETARY - The information contained herein is Proprietary to The Boeing Company and shall not be reproduced or disclosed in whole or in part or used for any reason except when such user possesses direct, written authorization from The Boeing Company. Encrypted emails required for forwarding via Email.The document generated on 11/09/2026 by Fleet Team Digest application via MyBoeingFleet. This document is for reference purposes only, visit the application for all the latest and updated revisions of this document.

Copyright ©2026 Boeing. All rights reserved.

EXPORT CONTROLLED -This technology or software is subject to the U.S. Export Administration Regulations (EAR), (15 C.F.R. Parts 730-774). No authorization from the U.S. Department of Commerce is required for export, re-export, in-country transfer, or access EXCEPT to country group E:1 or E:2 countries/persons per Supp.1 to Part 740 of the EAR. ECCN : 9E991

FLEET TEAM DIGEST

Boeing will share suspected 5G events with the FAA. If your airline process requires submission to the FAA, reports of radio altimeter disruptions may be submitted using the Radio Altimeter Anomaly Reporting Form (in addition to submitting a report to Boeing) at the following link:

https://www.faa.gov/air_traffic/nas/radalt_reports/

Reference Categories

Reference Type	Reference Number	Revision Number	Reference Date
Airworthiness Directive (AD)	FAA AD 2026-13-02		06/30/2026
Airworthiness Directive (AD)	FAA AD 2026-13-17 - 737 MAX		06/30/2026
Airworthiness Directive (AD)	Transport Canada AD CF-2026-29 - 737 MAX		06/23/2026
Other	EASA SIB 2021-16R1	Revision 1	06/19/2023
Airworthiness Directive (AD)	FAA AD 2023-12-11 - 737 MAX		06/21/2023
Airworthiness Directive (AD)	Brazil ANAC AD 2024-04-01		07/12/2024
Other	UAE GCAA Safety Alert 2021-03	1	01/26/2022
Other	France DGAC Safety Info Leaflet No. 2021/01	Version 1	02/05/2021
Other	India DGCA AIC No. 19/25		12/05/2025
Other	RTCA Paper No. 274-20/ PMC-2073		10/07/2020
Airworthiness Directive (AD)	Transport Canada AD CF-2024-14		05/15/2024
Other	ICAO Letter SP 74/1-21/22		03/25/2021
Service Information Letter (SIL)	D202012001529 (Honeywell)	Revision 2	03/29/2022
Service Information Letter (SIL)	LRA-900-21-2 (Collins Publication # 523-0832807)	Revision 1	05/10/2022
Service Information Letter (SIL)	LRA-2100-21-1 (Collins Publication # 523-0832808)	Revision 1	05/06/2022
Other	FAA SAIB AIR-21-18	3	05/24/2023
Airworthiness Directive (AD)	FAA AD 2023-10-02		05/26/2023
Other	FAA SAFO 21007	Revision 1	10/12/2023
Other	UK CAA SN-2021/017	Version 4	09/03/2024
Service Bulletin (SB)	LRA-900-34-506 (Collins Publication # 523-0834426)	Revision 2	04/05/2023
Service Bulletin (SB)	ERT-550-34-22 (Thales)		12/07/2022
Service Letter (SL)	737-SL-34-269		
Service Letter (SL)	737-SL-34-270		
Other	FAA Policy Statement PS-		07/19/2023

BOEING PROPRIETARY - The information contained herein is Proprietary to The Boeing Company and shall not be reproduced or disclosed in whole or in part or used for any reason except when such user possesses direct, written authorization from The Boeing Company. Encrypted emails required for forwarding via Email.The document generated on 11/09/2026 by Fleet Team Digest application via MyBoeingFleet. This document is for reference purposes only, visit the application for all the latest and updated revisions of this document.

Copyright ©2026 Boeing. All rights reserved.

EXPORT CONTROLLED -This technology or software is subject to the U.S. Export Administration Regulations (EAR), (15 C.F.R. Parts 730-774). No authorization from the U.S. Department of Commerce is required for export, re-export, in-country transfer, or access EXCEPT to country group E:1 or E:2 countries/persons per Supp.1 to Part 740 of the EAR. ECCN : 9E991

	AIR-600-39-01		
Other	FAA Notice N8900.670		08/15/2023
Other	Australia CASA Parts 91 and 121 MOS Amendment 2026		03/10/2026

Parts List

Part Name	Boeing Part Number	Supplier Name	Supplier Number
LRRA	see Attachment 4		

Related Categories

- Flight Operations : Flight Operations
- Regulatory : Issues mandated by airworthiness directive or other regulatory guidance material

Attachments:

a) Attachment 2 - 5G Global Deployment - Jun 2026

b) Attachment 4 - Radio Altimeters on Boeing Airplanes - Mar 2021

c) Attachment 5 - ICAO SP 74/1-21/22 - Mar 2021

d) Attachment 6 - Possible Airplane Level Impact Due to 5G Interference - Jan 2022

e) Attachment 7 - AT&T and Verizon Proposal Letter - Nov 2021

f) Attachment 8 - Aviation Safety Proposal Letter - Dec 2021

g) Attachment 9 - FAA AD 2023-10-02, FAA Model-Spec ADs, Operational Guidelines, Global Regulation - Jul 2026

h) Attachment 10 - USDOT and FAA Letter to AT&T and Verizon - Jan 2022

i) Attachment 12 - Certification Schedule - Jun 2026

j) Attachment 13 - IPC/AMM/SDS/FIM COCs - Feb 2025

k) Attachment 15 - Compliance to FAA AD 2023-10-02 and Model-Specific ADs - Jun 2026

BOEING PROPRIETARY - The information contained herein is Proprietary to The Boeing Company and shall not be reproduced or disclosed in whole or in part or used for any reason except when such user possesses direct, written authorization from The Boeing Company. Encrypted emails required for forwarding via Email.The document generated on 11/09/2026 by Fleet Team Digest application via MyBoeingFleet. This document is for reference purposes only, visit the application for all the latest and updated revisions of this document.

Copyright ©2026 Boeing. All rights reserved.

EXPORT CONTROLLED -This technology or software is subject to the U.S. Export Administration Regulations (EAR), (15 C.F.R. Parts 730-774). No authorization from the U.S. Department of Commerce is required for export, re-export, in-country transfer, or access EXCEPT to country group E:1 or E:2 countries/persons per Supp.1 to Part 740 of the EAR. ECCN : 9E991