Parachute Anchor Line (S.O.O. 6291) – General Data

1. General

Provisions have been made for the installation of a Parachute Anchor Line from station 112.73 to 321.98 in the passenger compartment. This installation requires that the third seat rail standard customer option, Mod S.O.O. 6243, be installed on aircraft.

2. Description

The Parachute Anchor Line installation consists of a cable assembly that runs between two anchor plates; a forward anchor plate at station 112.73 and an aft anchor plate at station 321.98, secured on the right hand and center seat rails, and a tie down for an Emergency Static Line hook-up at station 301.19, located on the left hand seat rail.

The cable assembly is made from a 3/8 inch diameter 7x19 steel cable, with a turnbarrel for adjustments, and the required attachment fittings and hardware. The cable assembly runs down the right hand side of the aircraft between station 112.73 and 321.98.

3. Removal/Installation

A. Removal of Parachute Anchor Line

1) Remove the lockwire from the turnbarrel in the cable assembly.

2) Adjust the turnbarrel to release the tension in the cable assembly.

3) Remove the nuts, washers and bolts that secure the cable to the anchor bracket and remove the cable assembly.

4) Remove the nuts, washers and bolts that secure the forward anchoring plate to the right hand and center seat rail at station 112.73, and remove the anchoring plate.

5) Remove the nuts, washers and bolts that secure the aft anchoring plate to the right hand and center rail at station 321.98, and remove the anchoring plate.

6) Remove the tie down for the Emergency Static Line hook-up from the left hand seat rail at station 301.19.

7) Install the seat track end piece at the front of both the center and right hand seat rails, and secure with screws.

B. Installation of Parachute Anchor Line

1) Remove the screws securing the seat track end piece, and remove the seat track end piece at the front of both the right hand and center seat rails.

2) Install the bolts, washers and nuts to secure the anchoring plate to the right hand and center seat rail at station 112.73.

3) Install the bolts, washers and nuts to secure the anchoring plate to the right hand and center rail at station 321.98.

4) Install the cable assembly, and install the bolts, washers and nuts securing the cable assembly to the anchor brackets.

5) Adjust the turnbarrel to the tension in the cable assembly.

Note Do not over-tighten the turnbarrel. Adjust sufficiently to draw the cable taut.

6) Safety the turnbarrel with lock wire.

7) Install the tie down for the Emergency Static Line hook-up from the left hand seat rail at station 301.19.