Water Separator and Filter (Mod 6/1440) – Maintenance Practices

1. Removal/Installation

A. Remove Filter Element and Drain Screen

1) Gain access to water separator as follows:

a) Through access panel on underside of wing, inboard of wing station 260.00, for a water separator in the wing.

b) Through rear baggage compartment for water separator in the rear fuselage.

2) Cut and remove lockwire from water separator bowl retaining bolt and drain nipple.

3) Unscrew water separator bowl retaining bolt and withdraw water separator bowl.

4) Remove cotter pin and filter retainer from end of retaining bolt and remove filter element.

5) If fitted, remove drain pipe from water separator bowl.

6) Remove drain nipple, drain screen and washer from water separator bowl drain fitting.

B. Install Filter Element and Drain Screen

1) Check drain screen is clean and not damaged.

2) Position washer and drain screen on water separator bowl drain fitting and install drain nipple. Torque drain nipple to a value of 20 to 25 pound–inches.

3) If removed, connect drain pipe to drain nipple.

4) Check that gaskets (O-rings) in head of water separator are not damaged. Sparingly lubricate each O-ring with lubricant FS–1265 (Dow Corning Corp.), or equivalent.

5) Lubricate O-ring seal on filter element with lubricant FS–1265, or equivalent.

6) Install filter element in water separator bowl. Ensure that spring retainer and spring are in position under filter element.

7) Place filter retainer over retaining bolt and install new cotter pin.

8) Press separator bowl firmly into separator head and engage retaining bolt.

CAUTION **ENSURE THAT BOWL IS FULLY SEATED IN HEAD BEFORE TIGHTENING RETAINING BOLT. DO NOT FORCE BOWL INTO HEAD BY TURNING RETAINING BOLT.**

Note If water separator is in wing, position bowl to align drain pipe with grommet in wing access panel.

9) Torque retaining bolt to a value of 9 to 11 pound–inches above drag torque.

10) Lockwire retaining bolt to drain nipple using MS20995C20.

11) Install wing access panel (if removed).

This Page Intentionally Left Blank