Cabin Compartment – Commuter Version (Mod 6/2050) – General Data

1. General

   The cabin compartment equipment/furnishings consist of passenger seats, 14V or 28V outlets, cabin upholstery and draftproof bulkhead.

2. Seating Arrangement

   Refer to 25-20-01, Cabin Compartment – Seating Arrangement – General Data.

   The basic interior layout of the cabin compartment provides for 19 seats, fitted as standard configuration. The 6th row consists of only one single seat, providing a larger entry area at the airstair door.

   Two configurations of commuter seating arrangements are available:

   A. Commuter – Nineteen Seats (Basic)

      The nineteen seat configuration comprises of five double seats and one single seat on the right side of the cabin, five single seats on the left side and three single tip-up type seats mounted across the rear bulkhead, all of which face forward.

   B. Commuter – Fourteen Seats (S.O.O. 6286)

      The customer option fourteen passenger seat configuration comprises of six single seats on the right side of the cabin, five single seats on the left side and three single tip-up type seats mounted across the rear bulkhead, all of which face forward.

3. 28 Volt Power System (Mod S.O.O. 6283)

   Refer to 25-21-00, 28 Volt Power System (Mod S.O.O. 6283) – General Data.

   As a customer option, a 28 volt power outlet may be installed on the forward right hand side of STA 332 bulkhead in the cabin.

4. 14 Volt Power System (Mod S.O.O. 6272, 6281 and 6282)

   Refer to 25-22-00, 14 Volt Power Converter System (Mod S.O.O. 6272, 6281 and 6282) – General Data.

   Three 14 volt power outlet configurations are available to provide power to peripherals: cell phone, laptops, etc.

   A. STA 332 14V Convenience Outlet (Mod S.O.O. 6272)

      As a customers option, a single 14 volt power outlet may be installed on the forward right hand side of STA 332 bulkhead in the cabin.

   B. Aft Cabin 14V Convenience Outlet (Mod S.O.O. 6281)

      As a customer option, three 14 volt power outlets may be installed between STA 220 and 332 bulkhead in the cabin.

   C. Forward Cabin 14V Convenience Outlet (Mod S.O.O. 6282)

      As a customer option, three 14 volt power outlets may be installed between STA 111 and 186 in the cabin.

5. Cabin Upholstery (Mod 6/2013)

   Refer to 25-20-02, Cabin Compartment – Cabin Upholstery (Mod 6/2013) – General Data for Cabin Upholstery specifications.

6. Draftproof Bulkhead

The draftproof bulkhead has a foam sandwich panel with a thermoplastic fascia bonded to both sides and an aluminum channel edging the aisle side. This bulkhead houses the entrance light switch.

7. Cleaning

For cleaning of the cabin floor, interior and upholstery, refer to the procedures in 12-20-05, Cleaning – General Data, Para 4.