Cooling/Demisting Fans (S.O.O. 6322) – General Data

1. General

One or two electrically-driven fans are installed in the flight compartment on the canopy at station 106 (approximately), and may be used to direct air onto the pilot's and co-pilot's windshields, for demisting purposes or for additional cooling.

The fans are 12 Volt DC; each connected to the 28 Volt DC right bus by a 25 ohm series connected resistor.

Each fan is attached to the aircraft canopy by two screws, and is controlled by a switch labeled FLT COMP FANS, located on the upper forward side of the station 111 sloping bulkhead, to the LH side of the bulkhead opening.

28 Volt DC power is provided from the right bus through a 5 amp FLT COMP FANS (B1) circuit breaker on the main circuit breaker panel (refer to 24-00-00, Electrical Power – General Data).

2. Adjustment/Test

A. Operational Test

1) Apply DC power (refer to 12-00-00, Servicing – General Data, Para 2.).

2) Select FLT COMP FANS switch to ON.

3) Observe operation of pilot's and co-pilot's fans.

Note Fan blades and motors should be smooth running without irregular noise, rattling, or vibration.

4) Select FLT COMP FANS switch to OFF.

5) Disconnect DC power (refer to 12-00-00, Servicing – General Data, Para 2.).

This Page Intentionally Left Blank