Engine Control Charts – General Data

1. General

The charts given in this section relate to the various components associated with engine controls.

A. Cable Charts

Table 1 — Power Control (Throttle) – Cable Chart to Table 4 — Control Console – Cable Chart, give the P/N, end terminations, cable size, length, material and cable proof load figures for all power control cables. When using the charts, refer to 91-00-00, Charts – General Data, Cable Charts.

Table 1 Power Control (Throttle) – Cable Chart

CABLE PART NO. & LOCATION	END TERMINATIONS		CABLE SIZE	LENGTH INCHES	MATERIAL & SPEC	PROOF LOAD LBS
	LEFT	RIGHT				
C6CE1243–3 Throttle, left wing. To rear of engine control pulley.	MS21260L2 RH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 58.300 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1244–3 Throttle, left wing. To front of engine control pulley.	MS21260L2 RH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 68.200 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1249–3 Throttle, right wing. To rear of engine control pulley.	MS21260L2 RH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 50.400 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1250–3 Throttle, right wing. To front of engine control pulley.	MS21260L2 RH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 53.200 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1255–1 Throttle, left-hand lever to wing. Lower cable, fuselage.	MS21260L2 LH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 162.000 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1256–1 Throttle, left-hand lever to wing. Upper cable, fuselage.	MS21260L2 LH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 152.870 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1261–1 Throttle, right-hand lever to wing. Lower cable, fuselage.	MS21260L2 LH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 199.120 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1262–1 Throttle, right-hand lever to wing. Upper cable, fuselage.	MS21260L2 LH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 183.000 ± 0.120	Carbon Steel MIL–W–1511	288

Table 2 Power Control (Propeller Pitch) – Cable Chart

CABLE PART NO. & LOCATION	END TERMINATIONS		CABLE SIZE	LENGTH INCHES	MATERIAL & SPEC	PROOF LOAD LBS
	LEFT	RIGHT				
C6CE1245–3 Propeller pitch, left wing. To rear of propeller control pulley.	MS21260L2 RH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 34.300 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1246–3 Propeller pitch, left wing. To front of propeller control pulley.	MS21260L2 RH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 24.600 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1251–3 Propeller pitch, right wing. To rear of propeller control pulley.	MS21260L2 RH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 82.100 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1252–3 Propeller pitch, right wing. To front of propeller control pulley.	MS21260L2 RH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 76.100 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1257–1 Propeller pitch, left-hand lever to wing. Upper cable, fuselage.	MS21260L2 LH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 196.500 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1258–1 Propeller pitch, left-hand lever to wing. Lower cable, fuselage.	MS21260L2 LH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 192.000 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1263 Propeller pitch, right-hand lever to wing. Lower cable, fuselage.	MS21260L2 LH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 166.500 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1264 Propeller pitch, right-hand lever to wing. Upper cable, fuselage.	MS21260L2 LH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 158.000 ± 0.120	Carbon Steel MIL–W–1511	288

Table 3 Power Control, Fuel Shut-off Valve – Cable Chart

CABLE PART NO. & LOCATION	END TERMINATIONS		CABLE SIZE	LENGTH INCHES	MATERIAL & SPEC	PROOF LOAD LBS
	LEFT	RIGHT				
C6CE1253–1 Fuel shut-off, left-hand lever to wing. Upper cable, fuselage.	MS21260L2 LH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 193.500 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1254–1 Fuel shut-off, left-hand lever to wing. Lower cable, fuselage.	MS21260L2 LH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 200.000 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1259–1 Fuel shut-off, right-hand lever to wing. Lower cable, fuselage.	MS21260L2 LH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 162.250 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1260–1 Fuel shut-off, right-hand lever to wing. Upper cable, fuselage.	MS21260L2 LH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 152.750 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1336–1 Fuel shut-off, left wing. To front of control pulley.	MS21260L2 RH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 34.300 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1336–3 Fuel shut-off, left wing. To rear of control pulley.	MS21260L2 RH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 42.750 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1336–5 Fuel shut-off, right wing. To front of control pulley.	MS21260L2 RH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 75.000 ± 0.120	Carbon Steel MIL–W–1511	288
C6CE1336–7 Fuel shut-off, right wing. To rear of control pulley.	MS21260L2 RH (Swaged)	MS20664C2 (Swaged) with fitting CSP–87–11	1/16 inch 7 X 7	A1 to B1 83.000 ± 0.120	Carbon Steel MIL–W–1511	288

Table 4 Control Console – Cable Chart

CABLE PART NO. & LOCATION	END TERMINATIONS		CABLE SIZE	LENGTH INCHES	MATERIAL & SPEC	PROOF LOAD LBS
	LEFT	RIGHT				
C6CE1315–1 Beta release cable (overhead control console)	C6CEM1068–27 eye end (Swaged) Ensure end of cable is visible through inspection holes.	Soft solder last 0.20 to 0.25 in. of cable to prevent fraying.	1/16 inch 7 X 7	6.00 from attachment hole in eye end, to soldered end of cable.	Corrosion resistant steel (non-magnetic) MIL–C–18375	216

Print Date: 2025-09-18

This Page Intentionally Left Blank