Landing Gear – General Data

1. General

The aircraft is normally fitted with a non-retractable landing gear which consists of the left and right main gear assemblies, a steerable nose gear assembly, and a tail bumper. Each of the single main wheels incorporates a hydraulically-operated, disc type wheel brake unit. Refer to 32-10-00, Main Gear – General Data, 32-20-00, Nose Gear – General Data, and 32-50-00, Nose Wheel Steering System – General Data.

When main and nose wheel-skis are fitted (Mod S.O.O. 6001 and Mod 6/2182) the skis can be extended to permit operation on unprepared snow or ice surfaces, or retracted to permit normal wheel operation. Although the wheel-ski installation is removable, certain associated components must remain permanently installed in the aircraft. These include, the hydraulic piping in the fuselage and on the main landing gear legs, which provide hydraulic fluid from the aircraft hydraulic system to operate the skis and the electrical cables to provide ski position indication. At the time of installation, the gear configuration changes and flight limitation placard must be replaced by a flight limitation placard having markings and limitations appropriate to a wheel-skiplane. Refer to 32-11-00, Main Wheel-Skis – General Data, 32-21-00, Nose Wheel-Ski (Mod S.O.O. 6001) and 32-30-00, Extension and Retraction (Wheel-Skis) Mod S.O.O. 6001.

This Page Intentionally Left Blank