
SiamMask++: More accurate object tracking through layer wise aggregation in Visual Object Tracking

Hyunbin Choi^a, Yungseop Lee^b and Changwon Lim^a

a. Department of Applied Statistics, Chung-Ang University

b. Department of Statistics, Dongguk University


2021. 5. 28.

* This research was supported by Next-Generation Information Computing Development Program through the National Research Foundation of Korea(NRF) funded by the Ministry of Science, ICT (No. 2017M3C4A7083281)

CONTENTS


1. Introduction
2. Related work
3. Proposed algorithm
4. Experiments
5. Conclusions

- **Problem.** Track an **arbitrary object** with the sole input of a single bounding box in the first frame of the video
- **Challenge** : we need to be **class-agnostic**




Example of the VOT2019 datasets and tracking results of our model, SiamMask++.

- SiamFC (Bertinetto et al., 2016) : Introducing Siamese Network for the **first time as a VOT** task
- SiamRPN (Li et al., 2018) : To achieve better performance, they apply the **RPN module** used for object detection to SiamFC
- **SiamRPN++** (Li et al., 2019) : Upgraded SiamRPN with the introduction of **Deep Network** and the introduction of **layer-wise aggregation** method
- **SiamMask** (Wang et al., 2019) : MASK module was introduced for more sophisticated object tracking based on SiamRPN, and **mask (segmentation) based tracking** was introduced in VOT




The proposed framework of SiamRPN++. (Li et al., 2019)




Schematic illustration of SiamMask variants. (Wang et al., 2019)

- SiamMask, a mask (segmentation) based tracker that is required in the future, is used as a benchmarking model
- ➡ **Layer-wise aggregation** and application of methodologies introduced in SiamRPN++
- ➡ Can explain the effectiveness of methodologies introduced by ablation experiments



Our proposed framework (SiamMask++). Given target image and search image, the network fusion the outputs from several SiamMask blocks to output dense predictions

- Note that the roles played by each layer in CNN are different
- layer-wise aggregation introduced in SiamRPN++ is applied to SiamMask
- Introducing **multi-RPN module** and **multi-MASK module**



Details of each SiamMask block in SiamMask++.

$$Cls = \sum_{i=3}^5 \alpha_j \times Cls_i$$

$$Reg = \sum_{i=3}^5 \beta_j \times Reg_i$$

$$Mask = \sum_{i=3}^5 \gamma_j \times Mask_i$$

- Features of conv3, conv4, and conv5 are individually supplied as inputs of the multi-RPN module and the multi-MASK module

- In the **RPN module**, we select the loss used by Faster R-CNN (Ren et al., 2015) and SiamRPN
- The **classification** branch adopts the **cross-entropy loss**
- The **regression** branch adopts the **smooth L_1 loss**

$$\alpha[0] = \frac{N_x - n_x}{n_w} \quad \alpha[1] = \frac{N_x - n_y}{n_h} \quad \alpha[2] = \log \frac{N_w}{n_w} \quad \alpha[3] = \log \frac{N_h}{n_h}$$

$$\text{smooth}_{L_1}(x, \omega) = \begin{cases} 0.5\omega^2 x^2 & , \quad |x| < \frac{1}{\omega^2} \\ |x| - \frac{1}{2\omega^2} & , \quad |x| \geq \frac{1}{\omega^2} \end{cases}$$

$$L_{reg} = \sum_{i=0}^3 \text{smooth}_{L_1}(\alpha[i], \omega)$$

- In the **MASK module**, we select the loss used by SiamMask

$$L_{mask} = \sum_n \left(\frac{1 + c_n}{2wh} \sum_{ij} \log \left(1 + e^{-q_n^{ij} m_n^{ij}} \right) \right).$$

- The **final loss** function is as follows:

$$\text{Loss function} = A \times L_{cls} + B \times L_{reg} + C \times L_{mask}$$

- **Training dataset** : ImageNet DET (Russakovsky et al., 2015), ImageNet VID, COCO (Lin et al., 2014) and Youtube VOS (Xu et al., 2018)
- Warm up while increasing the learning rate at a constant rate from 0.001 to 0.005 during the first 5epoch. Then end to end training slowly decreasing from 0.005 to 0.0025 for 15 epochs
- **Test dataset** : VOT2016 (Kristan et al., 2016), VOT2018 (Kristan et al., 2018) and VOT 2019 (Kristan et al., 2019)
- In the VOT challenge, the evaluation methods are accuracy, robustness, and the representative evaluation metric, **EAO**

- In all respects, SiamMask++ is superior to SiamMask
- The in-depth analysis of SiamMask and SiamMask++ is shown in the tables below:

Tracker	VOT2016		
	accuracy	robustness	EAO
SiamMask + mask binary upsapling	0.637	0.280	0.385
<i>OURS</i> + mask binary upsampling (bi_SiamMask++)	0.632	0.266	0.406 (+5.45%)
SiamMask + mask refine module	0.626	0.289	0.403
<i>OURS</i> + mask refine module (re_SiamMask++)	0.653	0.252	0.435(+7.94%)


Tracker	VOT2018		
	accuracy	robustness	EAO
SiamMask + mask binary upsapling	0.612	0.417	0.297
<i>OURS</i> + mask binary upsampling (bi_SiamMask++)	0.603	0.318	0.366(+23.23%)
SiamMask + mask refine module	0.601	0.417	0.321
<i>OURS</i> + mask refine module (re_SiamMask++)	0.626	0.262	0.398(+23.99%)

Tracker	VOT2019		
	accuracy	robustness	EAO
SiamMask + mask binary upsapling	0.593	0.657	0.254
<i>OURS</i> + mask binary upsampling (bi_SiamMask++)	0.593	0.547	0.283(+11.42%)
SiamMask + mask refine module	0.600	0.647	0.262
<i>OURS</i> + mask refine module (re_SiamMask++)	0.618	0.482	0.3(+14.50%)


Year	Trackers	EAO		
		VOT2016	VOT2018	VOT2019
2016	SiamFC (Bertinetto et al., 2016)	0.235	0.188	-----
2018	SA-Siam (He et al., 2018)	0.291	-----	-----
2018	SiamRPN (Li et al., 2018)	0.344	0.244	-----
2018	DaSiamRPN (Zhu et al., 2018)	0.411	0.326	-----
2018	SA-Siam R (He et al., 2018)	-----	0.337	-----
2019	SiamFC+ (Zhang & Peng, 2019)	0.303	0.270	0.242
2019	SiamRPN+ (Zhang & Peng, 2019)	0.376	0.301	-----
2019	SiamRPN++ (Li et al., 2019)	0.464	0.414	0.282
2019	SiamMask	0.403	0.321	0.262
2020	ACSiamRPN (Qin et al., 2020)	0.397	-----	0.240
2020	SiamFC++ (Xu et al., 2020)	0.460	0.385	-----
2021	SE-SiamFC (Sosnovik et al., 2021)	0.360	-----	-----
2021	<i>SiamMask++</i>	<i>0.435</i>	<i>0.398</i>	<i>0.300</i>

- Ranked 3rd in VOT2016 among trackers based on Siamese Network
- Ranked 2nd in VOT2018 among trackers based on Siamese Network
- Ranked 1st in VOT2019 among trackers based on Siamese Network

➡ The **more difficult** the data set becomes, **the better** the performance will be relatively



EAO at VOT2018 of SiamMask++ with ResNet and ResNext as the backbone according to the increase in shift.



EAO at VOT2019 of SiamMask++ with ResNet and ResNext as the backbone according to the increase in shift.

- Shift range performs **best at 64**
- **ResNet-50** performs better than ResNext-50

- **Depth-wise cross correlation** shows better performance than up-channel correlation
- **Pretrained backbone** shows better performance than non-pretrain backbone
- **Using all convolutional blocks** shows better performance than individual blocks or two block
- A table of experiments with various combinations of backbones, layers, and correlations is shown below:

BackBone	conv3	conv4	conv5	Finetune	corr	VOT2016	VOT2018	VOT2019
ResNext-50	✓	✓	✓	✓	DW	0.330	0.276	0.231
ResNet-50	✓	✓	✓		UP	0.349	0.315	0.255
	✓	✓	✓	✓	UP	0.399	0.357	0.268
ResNet-50	✓			✓	DW	0.365	0.298	0.242
		✓		✓	DW	0.403	0.321	0.262
			✓	✓	DW	0.301	0.268	0.223
	✓	✓		✓	DW	0.378	0.329	0.261
	✓		✓	✓	DW	0.366	0.293	0.244
		✓	✓	✓	DW	0.398	0.336	0.268
ResNet-50	✓	✓	✓		DW	0.387	0.368	0.277
	✓	✓	✓	✓	DW	0.435	0.398	0.300

- Applying the method proven in SiamRPN++ to the SiamMask model to propose a new model for tracking mask (segmentation) based objects
- In-depth analysis of factors affecting performance through experiments
- Proven to be superior to SiamMask in all respects using the same dataset
- The proposed algorithm can be used as a base model for not only VOT but also segmentation-based work.
- The proposed algorithm can be applied to various performance enhancement methodologies introduced in the subsequent work of SiamMask, such as SiamMask_E (Chen et al., 2019)

References

- Bertinetto, L., Valmadre, J., Henriques, J. F., Vedaldi, A., & Torr, P. H. (2016, October). Fully-convolutional siamese networks for object tracking. In *European conference on computer vision* (pp. 850-865). Springer, Cham. https://doi.org/10.1007/978-3-319-48881-3_56
- Li, B., Yan, J., Wu, W., Zhu, Z., & Hu, X. (2018). High performance visual tracking with siamese region proposal network. In *Proceedings of the IEEE conference on computer vision and pattern recognition* (pp. 8971-8980). <https://doi.org/10.1109/CVPR.2018.00935>
- Li, B., Wu, W., Wang, Q., Zhang, F., Xing, J., & Yan, J. (2019). Siamrpn++: Evolution of siamese visual tracking with very deep networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition* (pp. 4282-4291). <https://arxiv.org/abs/1812.11703>
- Wang, Q., Zhang, L., Bertinetto, L., Hu, W., & Torr, P. H. (2019). Fast online object tracking and segmentation: A unifying approach. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition* (pp. 1328-1338). <https://doi.org/10.1109/CVPR.2019.00142>
- Chen, B. X., & Tsotsos, J. K. (2019). Fast visual object tracking with rotated bounding boxes. *arXiv preprint arXiv:1907.03892*. <https://arxiv.org/abs/1907.03892>
- Ren, S., He, K., Girshick, R., & Sun, J. (2015). Faster r-cnn: Towards real-time object detection with region proposal networks. *arXiv preprint arXiv:1506.01497*. <https://arxiv.org/abs/1506.01497>
- Russakovsky, O., Deng, J., Su, H., Krause, J., Satheesh, S., Ma, S., ... & Fei-Fei, L. (2015). Imagenet large scale visual recognition challenge. *International journal of computer vision*, 115(3), 211-252. <https://doi.org/10.1007/s11263-015-0816-y>
- Lin, T. Y., Maire, M., Belongie, S., Hays, J., Perona, P., Ramanan, D., ... & Zitnick, C. L. (2014, September). Microsoft coco: Common objects in context. In *European conference on computer vision* (pp. 740-755). Springer, Cham. https://doi.org/10.1007/978-3-319-10602-1_48
- Xu, N., Yang, L., Fan, Y., Yang, J., Yue, D., Liang, Y., ... & Huang, T. (2018). Youtube-vos: Sequence-to-sequence video object segmentation. In *Proceedings of the European Conference on Computer Vision (ECCV)* (pp. 585-601). <https://arxiv.org/abs/1809.00461>
- Kristan, M., Matas, J., Leonardis, A., Felsberg, M., Cehovin, L., Fernández, G., & Vojir, T. (2016). Hager, and et al. The visual object tracking vot2016 challenge results. In *ECCV workshop* (Vol. 2, No. 6, p. 8). http://personal.ee.surrey.ac.uk/Personal/R.Bowden/publications/2016/Lebeda_VOT2016.pdf
- Kristan, M., Leonardis, A., Matas, J., Felsberg, M., Pflugfelder, R., Cehovin Zajc, L., ... & Sun, Y. (2018). The sixth visual object tracking vot2018 challenge results. In *Proceedings of the European Conference on Computer Vision (ECCV) Workshops* (pp. 0-0). https://doi.org/10.1007/978-3-030-11009-3_1
- Kristan, M., Matas, J., Leonardis, A., Felsberg, M., Pflugfelder, R., Kamarainen, J. K., ... & Hak Ki, B. (2019). The seventh visual object tracking vot2019 challenge results. In *Proceedings of the IEEE/CVF International Conference on Computer Vision Workshops* (pp. 0-0). <https://doi.org/10.1109/ICCVW.2019.00276>
- Pinheiro, P. O., Lin, T. Y., Collobert, R., & Dollár, P. (2016, October). Learning to refine object segments. In *European conference on computer vision* (pp. 75-91). Springer, Cham. https://doi.org/10.1007/978-3-319-46448-0_5
- Xu, Y., Wang, Z., Li, Z., Yuan, Y., & Yu, G. (2020, April). Siamfc++: Towards robust and accurate visual tracking with target estimation guidelines. In *Proceedings of the AAAI Conference on Artificial Intelligence* (Vol. 34, No. 07, pp. 12549-12556). <https://doi.org/10.1609/aaai.v34i07.6944>
- He, A., Luo, C., Tian, X., & Zeng, W. (2018). A twofold siamese network for real-time object tracking. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition* (pp. 4834-4843). <https://arxiv.org/abs/1802.08817>

References

- He, A., Luo, C., Tian, X., & Zeng, W. (2018). Towards a better match in siamese network based visual object tracker. In *Proceedings of the European Conference on Computer Vision (ECCV) Workshops* (pp. 0-0). https://doi.org/10.1007/978-3-030-11009-3_7
- Zhu, Z., Wang, Q., Li, B., Wu, W., Yan, J., & Hu, W. (2018). Distractor-aware siamese networks for visual object tracking. In *Proceedings of the European Conference on Computer Vision (ECCV)* (pp. 101-117). <https://arxiv.org/abs/1808.06048>
- Zhang, Z., & Peng, H. (2019). Deeper and wider siamese networks for real-time visual tracking. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition* (pp. 4591-4600). <https://doi.org/10.1109/CVPR.2019.00472>
- Qin, X., Zhang, Y., Chang, H., Lu, H., & Zhang, X. (2020). ACSiamRPN: Adaptive Context Sampling for Visual Object Tracking. *Electronics*, 9(9), 1528. <https://doi.org/10.3390/electronics9091528>
- Sosnovik, I., Moskalev, A., & Smeulders, A. W. (2021). Scale equivariance improves siamese tracking. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision* (pp. 2765-2774). <https://arxiv.org/abs/2007.09115>

Thank you !
