



# Calculating Memory Size and FLOPs for Fine-Tuning an LLM Transformer Model

Fine-tuning a Large Language Model (LLM) based on the Transformer architecture involves adapting a pre-trained model to a specific task or dataset. Understanding the memory requirements and computational cost (measured in Floating Point Operations, FLOPs) for fine-tuning is essential for efficient resource allocation and optimization. This guide provides a comprehensive approach to calculating the memory size and FLOPs needed for fine-tuning the example model previously discussed.

---

## Table of Contents

- [Calculating Memory Size and FLOPs for Fine-Tuning an LLM Transformer Model](#)
  - [Table of Contents](#)
  - [Introduction](#)
  - [Understanding Fine-Tuning](#)
  - [Components of Memory Usage During Fine-Tuning](#)
  - [Memory Size Calculation](#)
    - [Parameter Memory](#)
    - [Optimizer States Memory](#)
    - [Gradients Memory](#)
    - [Activation Memory](#)
    - [Total Memory Estimation](#)
  - [FLOPs Calculation for Fine-Tuning](#)
    - [Forward Pass FLOPs](#)
    - [Backward Pass FLOPs](#)
    - [Total FLOPs per Training Step](#)
  - [Example Calculation](#)
    - [Given](#)

- [Calculating FLOPs for One Training Step](#)
  - [Additional Considerations](#)
  - [Conclusion](#)
  - [References](#)
- 

## Introduction

Fine-tuning leverages a pre-trained LLM to perform specific tasks by training it further on a targeted dataset. This process typically requires less computational resources compared to training a model from scratch but still demands careful consideration of memory and FLOPs to ensure efficient training.

---

## Understanding Fine-Tuning

**Fine-Tuning** involves adjusting the weights of a pre-trained model on a new, often smaller, dataset. It can be performed in various ways:

- **Full Fine-Tuning:** All model parameters are updated during training.
- **Partial Fine-Tuning:** Only a subset of model parameters (e.g., the final layers) are updated.
- **Parameter-Efficient Fine-Tuning:** Techniques like adapters or prompt tuning add minimal parameters to the model, reducing computational overhead.

The choice of fine-tuning method impacts both memory requirements and FLOPs.

---

## Components of Memory Usage During Fine-Tuning

The memory required for fine-tuning comprises:

1. **Model Parameters:** Weights of the neural network.
  2. **Optimizer States:** Variables maintained by the optimizer (e.g., momentum terms in Adam).
  3. **Gradients:** Computed during backpropagation.
  4. **Activation Maps:** Intermediate outputs stored during the forward pass.
  5. **Batch Data:** Input data for each training batch.
  6. **Additional Buffers and Overheads:** Temporary variables and buffers used during computation.
- 

## Memory Size Calculation

### Parameter Memory

- **Total Parameters ( $P$ ):**
  - From previous calculations: 354,336,768 parameters.
- **Memory per Parameter:**
  - **32-bit (FP32):** 4 bytes.
  - **16-bit (FP16/BF16):** 2 bytes.
  - **8-bit (Int8 Quantization):** 1 byte (if applicable).

#### Parameters Memory:

- **FP32:**

$$P \times 4 = 354,336,768 \times 4 = 1,417,347,072 \text{ bytes} \approx 1.32 \text{ GB}$$

- **FP16/BF16:**

$$P \times 2 = 354,336,768 \times 2 = 708,673,536 \text{ bytes} \approx 0.66 \text{ GB}$$

- **Int8 Quantization** (if used):

$$P \times 1 = 354,336,768 \times 1 = 354,336,768 \text{ bytes} \approx 0.33 \text{ GB}$$

### Optimizer States Memory

**Adam Optimizer** typically requires two additional tensors per parameter (first and second moments).

- **Number of States:** 2 (m and v).
- **Memory per State:**
  - **FP32:** 4 bytes.
  - **FP16/BF16:** 2 bytes (less common; usually FP32 for stability).

**Total Optimizer States Memory:**

- **FP32:**

$$2 \times 1.32 \text{ GB} = 2.64 \text{ GB}$$

- **FP16/BF16:**

$$2 \times 0.66 \text{ GB} = 1.32 \text{ GB}$$

**Note:** Optimizer states are often kept in FP32 even when using lower precision for parameters.

## Gradients Memory

Gradients require memory equivalent to the parameters.

- **FP32:**

$$1.32 \text{ GB}$$

- **FP16/BF16:**

$$0.66 \text{ GB}$$

## Activation Memory

Activation memory depends on:

- **Batch Size ( $B$ )**
- **Sequence Length ( $L$ )**
- **Model Dimension ( $d_{\text{model}}$ )**
- **Number of Layers ( $N$ )**

- **Bytes per Element**

**Calculation:**

- **Per Layer Activation Memory:**
  - **Assuming an overhead factor ( $\alpha$ )** (typically 3 to 5).

$$\alpha \times B \times L \times d_{\text{model}} \times \text{Bytes per Element}$$

- **Total Activation Memory:**

$$N \times \text{Per Layer Memory}$$

## Total Memory Estimation

**Total Memory:**

Parameters Memory + Gradients Memory + Optimizer States Memory + Activation Memory

**Example:**

- **Batch Size ( $B$ ):** 8
- **Sequence Length ( $L$ ):** 1,024
- **Model Dimension ( $d_{\text{model}}$ ):** 1,024
- **Number of Layers ( $N$ ):** 24
- **Bytes per Element:** 2 bytes (FP16/BF16)
- **Overhead Factor ( $\alpha$ ):** 5

**Parameters and Optimizer States Memory (FP16/BF16):**

$$0.66 \text{ GB(Parameters)} + 0.66 \text{ GB(Gradients)} + 2.64 \text{ GB(Optimizer States)} = 3.96 \text{ GB}$$

**Activation Memory Calculation:**

$$\text{Per Layer Memory} = 5 \times 8 \times 1,024 \times 1,024 \times 2 = 84,886,016 \text{ bytes} \approx 0.08 \text{ GB}$$

$$\text{Total Activation Memory} = 24 \times 0.08 \text{ GB} = 1.92 \text{ GB}$$

**Overheads:** Approximately 1 GB.

### Total Memory:

3.96 GB(Parameters and States) + 1.92 GB(Activations) + 1 GB(Overheads)  $\approx$  6.88 GB

---

## FLOPs Calculation for Fine-Tuning

Fine-tuning involves both the forward and backward passes, similar to training from scratch. However, depending on the fine-tuning strategy, some FLOPs can be reduced (e.g., freezing layers).

### Forward Pass FLOPs

Similar to inference:

- **Embedding Layer**
- **Multi-Head Attention (MHA)**
- **Feed-Forward Network (FFN)**
- **Layer Normalization**
- **Activation Functions**

### Backward Pass FLOPs

The backward pass typically requires additional FLOPs to compute gradients:

- **Rule of Thumb:** Backward pass FLOPs  $\approx 2 \times$  Forward pass FLOPs.

### Total FLOPs per Training Step

Total FLOPs = Forward Pass FLOPs + Backward Pass FLOPs =  $3 \times$  Forward Pass FLOPs

**Note:** If only a subset of layers is being fine-tuned, FLOPs can be reduced accordingly.

---

## Example Calculation

## Given

- **Batch Size ( $B$ ):** 8
- **Sequence Length ( $L$ ):** 1,024
- **Model Dimension ( $d_{\text{model}}$ ):** 1,024
- **Feed-Forward Dimension ( $d_{\text{ff}}$ ):** 4,096
- **Number of Heads ( $h$ ):** 16
- **Number of Layers ( $N$ ):** 24

## Calculating FLOPs for One Training Step

### 1. Forward Pass FLOPs:

- **Embedding Layer:**

$$B \times L \times d_{\text{model}} = 8 \times 1,024 \times 1,024 = 8,388,608 \text{ FLOPs}$$

- **Per Layer FLOPs:**

- **MHA:**

$$8 \times 8 \times 1,024 \times (1,024)^2 + 4 \times 8 \times (1,024)^2 \times 1,024 + 5 \times 8 \times 16 \times (1,024)^2$$

Simplifying:

$$8 \times 8 \times 1,048,576 = 67,108,864 \text{ FLOPs}$$

$$4 \times 8 \times 1,048,576 = 33,554,432 \text{ FLOPs}$$

$$5 \times 8 \times 16 \times 1,048,576 = 671,088,640 \text{ FLOPs}$$

### **Total MHA FLOPs per Layer:**

$$67,108,864 + 33,554,432 + 671,088,640 = 771,751,936 \text{ FLOPs}$$

- **FFN:**

$$4 \times 8 \times 1,024 \times 4,096 + 8 \times 8 \times 1,024 \times 4,096 + 10 \times 8 \times 1,024 \times 1,024$$

Simplifying:

$$4 \times 8 \times 4,194,304 = 134,217,728 \text{ FLOPs}$$

$$8 \times 8 \times 4,194,304 = 268,435,456 \text{ FLOPs}$$

$$10 \times 8 \times 1,048,576 = 83,886,080 \text{ FLOPs}$$

**Total FFN FLOPs per Layer:**

$$134,217,728 + 268,435,456 + 83,886,080 = 486,539,264 \text{ FLOPs}$$

- **Layer Norms:**

$$10 \times 8 \times 1,024 \times 1,024 = 83,886,080 \text{ FLOPs}$$

- **Total FLOPs per Layer:**

$$771,751,936 + 486,539,264 + 83,886,080 = 1,342,177,280 \text{ FLOPs}$$

- **Total for All Layers:**

$$24 \times 1,342,177,280 = 32,212,254,720 \text{ FLOPs}$$

- **Total Forward Pass FLOPs:**

$$8,388,608 + 32,212,254,720 \approx 32,220,643,328 \text{ FLOPs}$$

**2. Backward Pass FLOPs:**

$$2 \times 32,220,643,328 = 64,441,286,656 \text{ FLOPs}$$

**3. Total FLOPs per Training Step:**

$$32,220,643,328 + 64,441,286,656 = 96,661,929,984 \text{ FLOPs} \approx 96.66 \text{ billion FLOPs}$$



---

# Additional Considerations

## 1. Fine-Tuning Strategy:

- **Full Fine-Tuning:** All layers are updated, resulting in higher memory and FLOPs.
- **Partial Fine-Tuning:** Only specific layers or modules are updated, reducing memory and FLOPs.
- **Parameter-Efficient Fine-Tuning:** Techniques like adapters add minimal parameters, lowering memory and FLOPs.

## 2. Batch Size Impact:

- **Linear Scaling:** Both memory and FLOPs scale linearly with batch size.
- **Example:** Doubling the batch size doubles the FLOPs.

## 3. Sequence Length Impact:

- **Quadratic Scaling in Attention:** FLOPs in the attention mechanism scale quadratically with sequence length.
- **Practical Limits:** Longer sequences significantly increase computational requirements.

## 4. Precision and Quantization:

- **Lower Precision:** Using FP16 or INT8 can reduce memory usage and potentially increase FLOPs efficiency.
- **Trade-offs:** Precision reduction may impact model accuracy.

## 5. Hardware Utilization:

- **Parallelism:** Effective use of GPUs/TPUs can mitigate high FLOPs through parallel processing.
- **Memory Bandwidth:** Sufficient bandwidth is crucial to handle data movement without bottlenecks.

## 6. Optimization Techniques:

- **Gradient Checkpointing:** Saves memory by recomputing certain activations during backpropagation.
- **Mixed Precision Training:** Combines different numerical precisions to optimize performance and memory usage.
- **Distributed Training:** Splits computation across multiple devices to handle larger models or batch sizes.

---

# Conclusion

Fine-tuning an LLM Transformer model requires careful estimation of both memory size and FLOPs to ensure efficient and feasible training. For the example model with:

- **Batch Size ( $B$ ):** 8
- **Sequence Length ( $L$ ):** 1,024
- **Model Dimension ( $d_{\text{model}}$ ):** 1,024
- **Feed-Forward Dimension ( $d_{\text{ff}}$ ):** 4,096
- **Number of Heads ( $h$ ):** 16
- **Number of Layers ( $N$ ):** 24

## Memory Requirements:

- **Total Memory:** Approximately **6.88 GB**

## FLOPs Requirements:

- **Total FLOPs per Training Step:** Approximately **96.66 billion FLOPs**

These estimates assist in selecting appropriate hardware, optimizing training processes, and ensuring that fine-tuning tasks are conducted efficiently.

---

# References

- Vaswani, A., et al. (2017). ["Attention is All You Need"](#).
- Micikevicius, P., et al. (2017). ["Mixed Precision Training"](#).
- Shoeybi, M., et al. (2019). ["Megatron-LM: Training Multi-Billion Parameter Language Models Using Model Parallelism"](#).
- Kaplan, J., et al. (2020). ["Scaling Laws for Neural Language Models"](#).
- OpenAI. (2020). ["GPT-3 Technical Report"](#).
- Rajbhandari, S., et al. (2020). ["Zero: Memory Optimizations Toward Training Trillion Parameter Models"](#).

- Patil, V., et al. (2021). ["Efficient Transformers: A Survey"](#).

---

*Note: These calculations provide estimates. Actual memory usage and FLOPs may vary based on implementation details, optimization techniques, hardware architecture, and specific fine-tuning strategies.*