

CFG Crux

Release Notes

Version: CRUX-19.07L

Revision: 0.0



Copyright © 2019, Intel Corporation. All rights reserved.

Intel and the Intel logo are trademarks of Intel Corporation in the U.S. and other countries.

* Other names and brands may be claimed as the property of others.

This document contains information on products in the design phase of development.

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT, OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS OTHERWISE AGREED IN WRITING BY INTEL, THE INTEL PRODUCTS ARE NOT DESIGNED OR INTENDED FOR ANY APPLICATION IN WHICH THE FAILURE OF THE INTEL PRODUCT COULD CREATE A SITUATION WHERE PERSONAL INJURY OR DEATH MAY OCCUR.

Intel may make changes to specifications and product descriptions at any time, without notice. Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined." Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them. The information here is subject to change without notice. Do not finalize a design with this information.

The products described in this document may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.

Contact your Intel account manager or distributor to obtain the latest specifications and before placing your product order.

Copies of documents that have an order number and are referenced in this document or in other Intel literature can be obtained from your Intel account manager or distributor.



CFG Crux 19.07L Release Notes

About This Document

This document lists the release notes for CFG Crux. Using CFG NocStudio, users can define NoC architectures, describe specifications and requirements, optimize the NoC design and finally generate the NoC IP files such as RTL, testbench, synthesis scripts, NoC IP documentation etc.

Audience

This document is intended for users of NocStudio:

- NoC Architects
- NoC Designers
- SoC Architects

Prerequisite

Before proceeding, you should generally understand:

• Basics of Network on Chip technology

Related Documents

The following documents can be used as a reference to this document.

- CFG NocStudio Crux User Manual
- CFG Crux IP Integration Spec

Customer Support

For technical support about this product and general information, contact CFG Support.



Revision History

Revision	Date	Updates
0.0	Jul 19,2019	Initial Version



Contents

About This Document3			
A	udier	nce	3
P	rereq	ıisite	3
R	elated	l Documents	3
C	uston	ner Support	3
1	Del	iverables	7
2	Inst	tallation	8
	2.1	Licensing	8
	2.2	Deliverables / Tarball set	8
3	Fea	ture Updates	10
	3.1	GUI Enhancements	10
	3.2	Single NocStudio release	10
	3.3	Noc_registers.xml	10
	3.4	Multiple RegBus Support	10
	3.5	Spyglass CDC	10
	3.6	User defined time unit for SDC Contstraints	10
	3.7	Single Poison bit in LLC	11
	3.8	Stamping Enhancement	11
	3.9	MODELING API and PA-Ultra compatibility Enhancement	11
4	ED	A Tool Compatibility	12
5	Erra	nta	13
	5.1	Stamping Restriction	13
6	Cha	anges to Commands and Properties	14
	6.1	Command Changes	14
	6.2	Default Property Changes	14
	6.3	Mesh Property Changes	14



6.4	Bridge Property Changes	14
6.5	Host Property Changes	14
6.6	Interface Property Changes	14
6.7	Link Property Changes	14
6.8	Router Property Changes	14
6.9	VC Property Changes	14



1 Deliverables

- CFG NocStudio Package contains N7 version of the tool supporting 16 layers and 256 bridges.
- NocStudio executable with interactive GUI.
- Verification checkers to be used in the DV environment.
- Sanity Test Bench.
- Documentation
 - a. NocStudio User Manual: The User Guide describes how to set up a system using NocStudio and how to use it to generate CFG IP.
 - b. IP Integration Spec: The Integration Manual describes how to integrate a configured network into a larger subsystem.
 - c. Technical Reference Manual: The Technical Reference Manual describes how the functionality of the various NoC elements, the features and functions available, and how to dynamically change the functions using the programmer's mode.



2 Installation

2.1 LICENSING

NocStudio uses FlexLM based licensing hosted by Intel Central Licensing group using two dedicated license servers: one in Santa Clara and the other is located in Israel.

In addition to LM_PROJECT, a Linux environmental variable *NETSPD_LICENSE_FILE* shall be set as shown below in order to access the licenses. The LM_PROJECT is essential for users not to check out the wrong combination of license features by accident.

setenv NETSPD_LICENSE_FILE 7010@netspeed01p.elic.intel.com:7010@netspeed02p.elic.intel.com

For teams without LM_PROJECT defined, a node-locked license file may be issued. Simply copy over the license file under NocStudio installation directory and renamed it as "license.dat". If the license file resides in a separated folder, user may set environment variable LM_LICENSE_FILE before opening NocStudio.

2.2 Deliverables / Tarball Set

The CFG IPs and their configuration tool NocStudio have been packaged individually for maximum flexibility allowing mix and match. Each release is tagged with <yy><mm> where yy is the last 2 digits of the year and mm is the month in integer. As an example, release in Jan 2019 will be referenced as 1901 release. Un-tar all individual tarballs delivered as part of the tarball set using the command below.

linux% tar zxvf <tarball_name>.tar.gz

Here is a snippet of tarball set in 1907L release: netspeed-<release>.<package>.tar.gz

Tarball name	Description	Category	
1 10007	N. C. P.	D	
netspeed-1907L.tar.gz	NocStudio	Base	
netspeed-1907L.cruxpkg.tar.gz	Crux IP package (non-AMBA)	NSIP IP	
netspeed-1907L.orionpkg.tar.gz	Orion IP package	AMBA IP	
netspeed-1907L.geminipkg.tar.gz	Gemini IP package	AMBA IP	
netspeed-1907L.pegasuspkg.tar.gz	Pegasus IP package	AMBA IP	



netspeed-1907L.ocppkg.tar.gz netspeed-1907L.daupkg.tar.gz	OCP support package Deadlock Avoidance Unit	Connectivity System
netspeed-1907L.syscpkg.tar.gz	SysC (PA) support package	Flow
netspeed-1907L.cpp61pkg.tar.gz	C++ Modeling API support package for gcc 6.1	Flow

Note:

The release makes use of Qt libraries covered under LGPL: $\underline{\text{http://qt-project.org/downloads}}$



3 FEATURE UPDATES

3.1 GUI ENHANCEMENTS

In this release, a few GUI enhancements have been implemented for ease of access, as follows:

- Double-clicking on a layer performs fit-view for that layer. Double-clicking again returns to the default view.
- GUI "File" menu now lists the history of the recent config files sourced by NocStudio.

3.2 SINGLE NOCSTUDIO RELEASE

In this release, CFG has merged traditional NocStudio (Orion, Gemini and Crux) and SCF NocStudio into a single binary. The license key feature "SCF" and NocStudio command "enter_scf_mode" enables the corresponding product features for Intel specific CMS, CRS, SBO, CHA and so on. A separated license "COREKIT" can be enabled to generate Collage compatible corekit collaterals for server SOC project.

3.3 Noc registers.xml

In this release, in addition to standard noc_registers.csv and noc_reference_manual.html, NocStudio also generates the NOC Registers in XML which is easier for RDL conversion.

3.4 MULTIPLE REGBUS SUPPORT

In this release, NocStudio supports multiple RegBus layers in a design. During new_mesh creation, user can specify the number of regbus layers in addition to NOC layers. Use set_node_regbus_layer to specify all nodes to be included in a specific regbus layer.

3.5 SPYGLASS CDC

In this release, a "cdc" folder has been created by NocStudio during "gen_ip" to provide preliminary support for CDC waiver file which allows user to invoke Spyglass flow and get an abstract model.

3.6 User defined time unit for SDC Constraints

Due to library implementation difference, new default property "prop_default sdc_time_unit [ps|ns] is now supported for NocStudio to generate SDC constraints in "ns" or "ps" time unit. For compatibility purpose, the prop defaults to "ns".



3.7 SINGLE POISON BIT IN LLC

The feature allows user to specify 1 poison bit for every 256 bits of data instead 4–bits in prior releases. A new property "*P_LLC_SINGLE_BIT_POISON*" has been added, please refer to NocStudio help manual for details.

3.8 STAMPING ENHANCEMENT

In this release, node-stamping flow has been enhanced to support for low-power and ILDC (In-Link Domain Crosser) based designs with limitations. New naming support for user to specify pipeline stages separately on data link and credit link has been added. Please refer to Technical Reference Manual Stamping Support chapter for details.

3.9 MODELING API AND PA-ULTRA COMPATIBILITY ENHANCEMENT

In this release, the NOC modeling API has been enhanced to support unique AID and QoS override enabled design.



4 EDA TOOL COMPATIBILITY

• Cadence EDA tools were used for verification and synthesis of this product.

> Xcelium 19.03-s003

➤ Design Compiler RTL Synthesis N-2017.09-SP3

➤ HAL Linting tool 15.20.027
 ➤ Conformal 16.20.s240

- Compatibility testing has been done with VCS N-2017.12-SP2-4.
- For Platform Architect, used GCC version is gcc-6.1.0a. (Backward compatible upto gcc-5.2.0-64)
- Please refer to IP Integration specification to enable/disable specific CFG checker in order to resolve or workaround any verification related issues, if any.

Contact your CFG or Synopsys support team for assistance.



5 ERRATA

5.1 STAMPING RESTRICTION

Node-stamping doesn't support user inserted pipeline stages between the regbus layer router and regbus ring slave. Please contact CFG support if your design requires such configuration options.



6 CHANGES TO COMMANDS AND PROPERTIES

6.1 COMMAND CHANGES

None

6.2 Default Property Changes

None

6.3 MESH PROPERTY CHANGES

None

6.4 Bridge Property Changes

None

6.5 HOST PROPERTY CHANGES

None

6.6 INTERFACE PROPERTY CHANGES

None

6.7 LINK PROPERTY CHANGES

None

6.8 ROUTER PROPERTY CHANGES

None

6.9 VC Property Changes

Non



Intel Corporation
2200 Mission College Blvd,
Santa Clara, CA - 95054.