

We are recovering from significant hosting issues. Much of the site is functional, but currently email delivery is not. Please bear with us as we validate site functionality.



Bookmarks

- ▶ [Welcome to the edX Platform](#)
- ▶ [Entrance Survey](#)
- ▶ [Download Python and Get Motivated!](#)
- ▶ [Week 1: Python Basics](#)
- ▶ [Week 2: Simple Programs](#)
- ▶ [Week 3: Structured Types](#)
- ▶ [Week 4: Good Programming Practices](#)
- ▶ [Midterm Exam](#)
- ▶ [Week 5: Object Oriented Programming](#)

Week 6: Algorithmic Complexity &gt; 12. Searching and Sorting Algorithms &gt; Exercise 5

## Exercise 5

Bookmark this page

### Exercise 5

3 points possible (graded)

**ESTIMATED TIME TO COMPLETE: 8 minutes**

Here is the code for selection sort. For simplicity, assume `L` is a list of integers:

```
def selSort(L):
    for i in range(len(L) - 1):
        minIndx = i
        minVal = L[i]
        j = i+1
        while j < len(L):
            if minVal > L[j]:
                minIndx = j
                minVal = L[j]
            j += 1
        if minIndx != i:
            temp = L[i]
            L[i] = L[minIndx]
            L[minIndx] = temp
```

And here is a suggested alternative:


```
def newSort(L):
    for i in range(len(L) - 1):
        j=i+1
        while j < len(L):
            if L[i] > L[j]:
                temp = L[i]
                L[i] = L[j]
                L[j] = temp
            j += 1
```

1. Do these two functions result in the same sorted lists?




▼ **Week 6:**  
**Algorithmic**  
**Complexity**


**11. Computational**  
**Complexity**

[Finger Exercises](#) 

**12. Searching and**  
**Sorting**  
**Algorithms**

[Finger Exercises](#) 

**Problem Set 6**

[Problem Set due Mar](#)  
[9, 2017 15:30 PST](#) 

► **Week 7:**  
**Plotting**

► **Exit Survey**

► **Sandbox**

☐ Yes

☐ No

2. Do these two functions execute the same number of assignments of values into entries of the lists?

☐ Yes. They execute the same number of assignments.

☐ No. `newSort` may use more - but never fewer - inserts than `selSort` .

☐ No. `selSort` may use more - but never fewer - inserts than `newSort` .

☐ No. Either function may use more inserts than the other.

3. Is the worst-case order of growth of these functions the same?

☐ Yes. `newSort` and `selSort` have the same complexity.

☐ No. `newSort` has higher complexity than `selSort` .

☐ No. `selSort` has higher complexity than `newSort` .

Submit

**Exercise 5**

Topic: Lecture 12 / Exercise 5

Show Discussion 



© 2012-2017 edX Inc. All rights reserved except where noted. EdX, Open edX and the edX and Open EdX logos are registered trademarks or trademarks of edX Inc.

