**edX** | **MITx: 6.00.1x Introduction to Computer Science and Programming ...** | **Help**

# Problem 6

🔖 **Bookmarks**

🔖 **Bookmark this page**

- ▸ Welcome to the edX Platform
- ▸ Entrance Survey
- ▸ Download Python and Get Motivated!
- ▸ Week 1: Python Basics
- ▸ Week 2: Simple Programs
- ▸ Week 3: Structured Types
- ▸ Week 4: Good Programming Practices
- ▾ **Midterm Exam**

**Midterm Exam**
Midterm due Feb 14, 2017 15:30 PST ✎

- ▸ Sandbox

## Problem 6

15.0 points possible (graded)
Implement a function that meets the specifications below.

```
def deep_reverse(L):
    """ assumes L is a list of lists whose elements are ints
    Mutates L such that it reverses its elements and also
    reverses the order of the int elements in every element
of L.
    It does not return anything.
    """
    # Your code here
```

For example, if `L = [[1, 2], [3, 4], [5, 6, 7]]` then `deep_reverse(L)` mutates `L` to be `[[7, 6, 5], [4, 3], [2, 1]]`

Paste your entire function, including the definition, in the box below. Do not leave any debugging print statements.

```
1 # Paste your function here
```

Press ESC then TAB or click outside of the code editor to exit

Unanswered ✎

**BEFORE EMAILING THE STAFF:** Please read carefully. The question states that you need to mutate `L`. Your code must work when you do this:

```
L = [[0, 1, 2], [1, 2, 3], [3, 2, 1], [10, -10, 100]]
deep_reverse(L)
print(L)
```

Submit     You have used 0 of 10 attempts

POWERED BY
OPENedX