

We are recovering from significant hosting issues. Much of the site is functional, but currently email delivery is not. Please bear with us as we validate site functionality.



Bookmarks

- ▶ [Welcome to the edX Platform](#)
- ▶ [Entrance Survey](#)
- ▶ [Download Python and Get Motivated!](#)
- ▶ [Week 1: Python Basics](#)
- ▶ [Week 2: Simple Programs](#)
- ▶ [Week 3: Structured Types](#)
- ▶ [Week 4: Good Programming Practices](#)
- ▶ [Midterm Exam](#)
- ▶ [Week 5: Object Oriented Programming](#)

Week 6: Algorithmic Complexity &gt; Problem Set 6 &gt; Problem 5

## Problem 5

Bookmark this page

### Problem 5

1 point possible (graded)

You have 2 attempts for this problem.

Here is code for linear search that uses the fact that a set of elements is sorted in increasing order:

```
def search(L, e):
    for i in range(len(L)):
        if L[i] == e:
            return True
        if L[i] > e:
            return False
    return False
```

Consider the following code, which is an alternative version of `search`.


```
def newsearch(L, e):
    size = len(L)
    for i in range(size):
        if L[size-i-1] == e:
            return True
        if L[i] < e:
            return False
    return False
```

Which of the following statements is correct? You may assume that each function is tested with a list `L` whose elements are sorted in increasing order; for simplicity, assume `L` is a list of positive integers.




▼ **Week 6:**  
**Algorithmic Complexity**


**11. Computational Complexity**

[Finger Exercises](#) 

**12. Searching and Sorting Algorithms**

[Finger Exercises](#) 

**Problem Set 6**

[Problem Set due Mar 9, 2017 15:30 PST](#) 

► **Week 7:**  
**Plotting**

► **Exit Survey**

► **Sandbox**

☐ `search` and `newsearch` return the same answers for all `L` and `e`.

☐ `search` and `newsearch` return the same answers provided `L` is non-empty.

☐ `search` and `newsearch` return the same answers provided `L` is non-empty and `e` is in `L`.

☐ `search` and `newsearch` never return the same answers.

☒ `search` and `newsearch` return the same answers for lists `L` of length 0, 1, or 2.

Submit

You have used 0 of 2 attempts

**Problem 5**

Topic: Problem Set 6 / Problem 5

Show Discussion

© All Rights Reserved



© 2012-2017 edX Inc. All rights reserved except where noted. EdX, Open edX and the edX and Open EdX logos are registered trademarks or trademarks of edX Inc.

POWERED BY  
OPENedX®

