


Chapter 4:
Entity-Relationship (ER) Data Modelling

- Introduction
- ER Definitions
- ER Notation
- Relationships
- ER Examples


Introduction to ER Modelling

- An *Entity-relationship model* (ERM) is an abstract and conceptual representation of data.
- ER modelling is a DB modelling method, used to produce a type of *conceptual schema* of a system.
- Diagrams created by this process are called *ER diagrams*.
- Sequence: *Conceptual data model* (i.e. ER) is, at a later stage (called *logical design*), mapped to a *logical data model*, (e.g. *relational model*); this is mapped to a physical model in *physical design*.
- ER Model used to interpret, specify & document requirements for DBs irrespective of DBMS being used.



ER Definitions

- **Entity (Instance):**
 - An instance of a physical object in the real world.
 - **Entity Class:** Group of objects of the same type.
 - E.g. Entity Class "Student", Entities "John", "Trish" etc
- **Attributes:**
 - Properties of Entities that describe their characteristics.
 - Types:
 - **Simple:** Attribute that is not divisible, e.g. age.
 - **Composite:** Attribute composed of several simple attributes, e.g. address (house number, street, district)
 - **Multiple:** Attribute with a set of possible values for the same entity, e.g. Phone (home, mobile etc.) or email
 - **Key:** Uniquely Ids the Entity e.g. PPSN, Chassis No.
 - **Value Set (or domain):** Each simple attribute associated with a VS that may be assigned to that attribute for each individual entity, e.g. age = integer, range [18,...65]



ER Definitions (cont'd)

Relationships:

1. Are bi-directional (ie can be put 2 ways)

2. Degree:

binary (i.e. involve only two entities),

ternary (i.e. involve three participating entities).

3. Cardinality: Entity types may be linked in more than one way.

4. May have properties (attrs).

5. Can be Recursive.

Lecturer

Student

Lectures

Binary

Lecturer

Course

Recommends

Ternary

Textbook

4.

Price

Bar

Beers

sells

5.

Marries

Person

3.

1:1

Man

1

Marries

1

Woman

1:m

Lecturer

1

Teaches

m

Students

n:m

Student

n

Enrols on

m

Courses

Keys/Key Attributes

Some definitions:

Super Key – Set of attributes uniquely identifying a row

For SP {S#,P#,QTY} or {S#,P#}

Candidate Key – (Irreducible) combination of attributes which is a unique identifier within a table. For SP {S#,P#}

Primary Key - One of the candidate keys. For SP {S#,P#}

Alternate Key - The candidate key(s) (if any) not chosen as the primary key.

Foreign Key - A (combination of) attribute(s) in one relation whose value(s) are required to equal in the primary key of another relation.

PK for S
(FK for SP)

| S# | SName | Status | City |
|----|-------|--------|-------|
| S1 | Smith | 20 | Paris |
| S2 | Jones | 10 | Paris |
| S3 | Blake | 30 | Rome |

PK for P
(FK for SP)

| P# | PName | Colour | Weight | City |
|----|-------|--------|--------|--------|
| P1 | Nut | Red | 12 | London |
| P2 | Bolt | Green | 17 | Paris |
| P3 | Screw | Blue | 27 | Rome |
| P4 | Screw | Red | 14 | London |

SP

| S# | P# | QTY |
|----|----|-----|
| S1 | P1 | 300 |
| S1 | P2 | 200 |
| S1 | P3 | 400 |
| S2 | P1 | 300 |
| S2 | P2 | 400 |
| S3 | P2 | 200 |

PK for SP

ER Example 1: Entity With Attributes

A student has a student number (identifying), a name, an address (with street number, street and district) and several phone numbers

Student

Student Number

Name

Address

Phone

House no.

Street

District

(c) Martin Crane 2011

2

ER Example 2:
Relationship Cardinality Ratios

• Ordinary Notation

Husband

1

Divorces

1

Wife

Student

1

Owns

N

Book

Student

N

Borrows

M

Book

• Crow's Feet Notation

Student

Owns

Book

Student

Borrows

Book

Relationship Cardinality Ratio Questions

Patient

Has GP

Doctor

Doctor

Performs

Operation

Doctor

Specialise In

Disease

Needle

Injected Into

Patient

Recursive Relationship Examples

Person

Marries

Person

Person

Likes

Person

Supervisor

Supervises

Supervisee

Employee

• Note

– Use of roles in recursive relationship "Supervises"

– Cardinality Ratios

(c) Martin Crane 2011

3

More ER Definitions


- The following are not part of core or lowest common denominator notation:

– Weak Entity:



- One which cannot be id'ed by attributes alone
- E.g. book editions; dependent children,

– ID-Dependent Entity:




- Special case of Weak Entity where id includes entity id it depends on
- E.g. Individual apartments in a block
- Block: Identifier BldgName, Apartment: Identifier {BldgName, ApptNo}

– Derived Attribute

- Attribute whose values are generated from other attribute: AcctBalance
- E.g. AcctBalance=TotalCredit – TotalDebit

More ER Definitions (cont'd)

– Total/Partial Participation




- Partial: Entity's Existence doesn't require existence of associated entity in a relationship. E.g. Employee Entity doesn't require Dependents
- Total: Entity's Existence requires that of associated entity
- Note: Doesn't have to be W.E. to require Total Participation e.g. Employee Works on Project is Total on both sides.

• Extended ER Model


– Sub-/Super-types:

- Used to denote "is a" relationship: Employee is either Hourly or Salaried




ER Example 3: A Hospital Case

- "Patients are treated in a single ward by the doctors assigned to them. Usually each patient will be assigned a single doctor, but in rare cases they will have two. Healthcare assistants also attend to the patients, a number of these are associated with each ward."



ER Example 4: Football Club

- “A football club has a name and a ground and is made up of players. A player can play for only one club and a manager, represented by his name manages a club. A footballer has a registration number, name and age. A club manager also buys players. Each club plays against each other club in the league and matches have a date, venue and score.”



ER Example 5: Bus Company

- “A Bus Company owns a number of busses. Each bus is allocated to a particular route, although some routes may have several busses. Each route passes through a number of towns. One or more drivers are allocated to each stage of a route, which corresponds to a journey through some or all of the towns on a route. Some of the towns have a garage where busses are kept and each of the busses are identified by the registration number and can carry different numbers of passengers, since the vehicles vary in size and can be single or double-decked. Each route is identified by a route number and information is available on the average number of passengers carried per day for each route. Drivers have an employee number, name, address, and sometimes a telephone number.”
- Entities (bold face)
 - Bus** - Company owns busses and will hold information about them.
 - Route** - Buses travel on routes and will need described.
 - Town** - Buses pass through towns and need to know about them
 - Driver** - Company employs drivers, personnel will hold their data.
 - Stage** - Routes are made up of stages
 - Garage** - Garage houses busses, and need to know where they are.


ER Example 5: Bus Company (cont'd)

- Entities and their Relationships (Cardinality)
 - A bus is allocated to a route and a route may have several busses.
 - Bus-Route** (m:1) is serviced by
 - A route comprises of one or more stages.
 - Route-Stage** (1:m) comprises
 - One or more drivers are allocated to each stage.
 - Driver-Stage** (m:1) is allocated
 - A stage passes through some or all of the towns on a route.
 - Stage-Town** (m:n) passes-through
 - A route passes through some or all of the towns
 - Route-Town** (m:n) passes-through
 - Some of the towns have a garage
 - Garage-Town** (1:1) is located in
 - A garage keeps busses and each bus has one 'home' garage
 - Garage-Bus** (m:1) is garaged

ER Example 5: Bus Company (cont'd)

- **Attributes (key attributes)**
 - **Bus** (reg-no, make, size, deck, no-pass)
 - **Route** (route-no, avg-pass)
 - **Driver** (emp-no, name, address, tel-no)
 - **Town** (name)
 - **Stage** (stage-no)
 - **Garage** (name, address)

ER Example 5: Bus Company (cont'd)



ER Example 6: University Database

- "A **lecturer**, identified by his or her **number**, name and room number, is responsible for organising a number of course **modules**. Each module has a **unique code** and also a name and each module can involve a number of lecturers who deliver part of it. A module is composed of a series of **lectures** and because of economic constraints and common sense, sometimes **lectures** on a given topic **can be part of** more than one module. A lecture has a **time**, **room** and **date** and is delivered by a lecturer and a lecturer may **deliver** more than one lecture. **Students**, identified by **number** and **name**, can **attend** lectures and a student must be registered for a number of modules. We also store the date on which the student first **registered** for that module. Finally, a lecturer **acts as a tutor** for a number of students and each student has only one tutor."

ER Example 6: University Database (cont'd)

- **Entities and their Attributes (key)**
 - **Lecturer** (Number, Name, Office), **Student** (Number, Name)
 - **Module** (Code, Name), **Lecture** (Room, Date, Time)
- **Entities and their Relationships (Cardinality) *italics***
 - "A lecturer is responsible for organising a number of course modules"
 - **Lecturer-Module** (1:N) *is responsible for*
 - "Each module can involve a number of lecturers who deliver part of it."
 - **Lecturer-Module** (N:M) *lectures*
 - "A Module is composed of a series of Lectures and Lectures on a given topic can be part of more than one Module."
 - **Module-Lecture** (N:M) *is part of*
 - "A Lecture is delivered by a Lecturer and a lecturer may deliver more than one lecture."
 - **Lecturer-Lecture** (1:N) *delivers*
 - "Students, can attend Lectures"
 - **Student-Lecture** (N:M) *attend*
 - "and a Student must be registered for a number of Modules"
 - **Student-Module** (N:M) *registers* (Attribute: Date)
 - "Lecturer acts as a tutor for a number of Students and each Student has only one tutor"
 - **Lecturer-Student** (1:N) *tutors*

ER Example 6: University Database (cont'd)

