



Chapter 6: Formal Relational Query Languages

Database System Concepts, 6th Ed.

©Silberschatz, Korth and Sudarshan

See www.db-book.com for conditions on re-use



Outline

- Relational Algebra
- Tuple Relational Calculus
- Domain Relational Calculus



Relational Algebra

- Procedural language
- Six basic operators
 - select: σ
 - project: Π
 - union: \cup
 - set difference: $-$
 - Cartesian product: \times
 - rename: ρ
- The operators take one or two relations as inputs and produce a new relation as a result.



Select Operation

- Notation: $\sigma_p(r)$
- p is called the **selection predicate**
- Defined as:

$$\sigma_p(r) = \{t \mid t \in r \text{ and } p(t)\}$$

Where p is a formula in propositional calculus consisting of **terms** connected by : \wedge (**and**), \vee (**or**), \neg (**not**)
Each **term** is one of:

$\langle \text{attribute} \rangle \quad op \quad \langle \text{attribute} \rangle \text{ or } \langle \text{constant} \rangle$

where op is one of: $=, \neq, >, \geq, <, \leq$

- Example of selection:

$$\sigma_{dept_name="Physics"}(instructor)$$



Project Operation

- Notation:

$$\Pi_{A_1, A_2, \dots, A_k}(r)$$

where A_1, A_2 are attribute names and r is a relation name.

- The result is defined as the relation of k columns obtained by erasing the columns that are not listed
- Duplicate rows removed from result, since relations are sets
- Example: To eliminate the *dept_name* attribute of *instructor*

$$\Pi_{ID, name, salary}(instructor)$$



Union Operation

- Notation: $r \cup s$
- Defined as:

$$r \cup s = \{t \mid t \in r \text{ or } t \in s\}$$

- For $r \cup s$ to be valid.
 1. r, s must have the **same arity** (same number of attributes)
 2. The attribute domains must be **compatible** (example: 2nd column of r deals with the same type of values as does the 2nd column of s)
- Example: to find all courses taught in the Fall 2009 semester, or in the Spring 2010 semester, or in both

$$\Pi_{course_id}(\sigma_{semester="Fall" \wedge year=2009}(section)) \cup \Pi_{course_id}(\sigma_{semester="Spring" \wedge year=2010}(section))$$



Set Difference Operation

- Notation $r - s$
- Defined as:

$$r - s = \{t \mid t \in r \text{ and } t \notin s\}$$

- Set differences must be taken between **compatible** relations.
 - r and s must have the **same** arity
 - attribute domains of r and s must be compatible
- Example: to find all courses taught in the Fall 2009 semester, but not in the Spring 2010 semester

$$\Pi_{course_id}(\sigma_{semester="Fall" \wedge year=2009}(section)) - \Pi_{course_id}(\sigma_{semester="Spring" \wedge year=2010}(section))$$



Set-Intersection Operation

- Notation: $r \cap s$
- Defined as:
- $r \cap s = \{ t \mid t \in r \textbf{ and } t \in s \}$
- Assume:
 - r, s have the *same arity*
 - attributes of r and s are compatible
- Note: $r \cap s = r - (r - s)$



Cartesian-Product Operation

- Notation $r \times s$
- Defined as:

$$r \times s = \{t \ q \mid t \in r \textbf{ and } q \in s\}$$

- Assume that attributes of $r(R)$ and $s(S)$ are disjoint. (That is, $R \cap S = \emptyset$).
- If attributes of $r(R)$ and $s(S)$ are not disjoint, then renaming must be used.



Rename Operation

- Allows us to name, and therefore to refer to, the results of relational-algebra expressions.
- Allows us to refer to a relation by more than one name.
- Example:

$$\rho_x(E)$$

returns the expression E under the name X

- If a relational-algebra expression E has arity n , then

$$\rho_{x(A_1, A_2, \dots, A_n)}(E)$$

returns the result of expression E under the name X , and with the attributes renamed to A_1, A_2, \dots, A_n .



Formal Definition

- A basic expression in the relational algebra consists of either one of the following:
 - A relation in the database
 - A constant relation
- Let E_1 and E_2 be relational-algebra expressions; the following are all relational-algebra expressions:
 - $E_1 \cup E_2$
 - $E_1 - E_2$
 - $E_1 \times E_2$
 - $\sigma_P(E_1)$, P is a predicate on attributes in E_1
 - $\Pi_S(E_1)$, S is a list consisting of some of the attributes in E_1
 - $\rho_x(E_1)$, x is the new name for the result of E_1



Tuple Relational Calculus



Tuple Relational Calculus

- A nonprocedural query language, where each query is of the form

$$\{t \mid P(t)\}$$

- It is the set of all tuples t such that predicate P is true for t
- t is a *tuple variable*, $t[A]$ denotes the value of tuple t on attribute A
- $t \in r$ denotes that tuple t is in relation r
- P is a *formula* similar to that of the predicate calculus



Predicate Calculus Formula

1. Set of attributes and constants
2. Set of comparison operators: (e.g., $<$, \leq , $=$, \neq , $>$, \geq)
3. Set of connectives: and (\wedge), or (\vee), not (\neg)
4. Implication (\Rightarrow): $x \Rightarrow y$, if x is true, then y is true

$$x \Rightarrow y \equiv \neg x \vee y$$

5. Set of quantifiers:

- ▶ $\exists t \in r(Q(t)) \equiv$ "there exists" a tuple t in relation r such that predicate $Q(t)$ is true
- ▶ $\forall t \in r(Q(t)) \equiv Q$ is true "for all" tuples t in relation r



Example Queries

- Find the *ID*, *name*, *dept_name*, *salary* for instructors whose salary is greater than \$80,000

$$\{t \mid t \in instructor \wedge t[salary] > 80000\}$$

Notice that a relation on schema (*ID*, *name*, *dept_name*, *salary*) is implicitly defined by the query

- As in the previous query, but output only the *ID* attribute value

$$\{t \mid \exists s \in instructor (t[ID] = s[ID] \wedge s[salary] > 80000)\}$$

Notice that a relation on schema (*ID*) is implicitly defined by the query



Example Queries

- Find the names of all instructors whose department is in the Watson building

$$\{t \mid \exists s \in \text{instructor} (t[\text{name}] = s[\text{name}] \wedge \exists u \in \text{department} (u[\text{dept_name}] = s[\text{dept_name}] \wedge u[\text{building}] = \text{"Watson"}))\}$$

- Find the set of all courses taught in the Fall 2009 semester, or in the Spring 2010 semester, or both

$$\{t \mid \exists s \in \text{section} (t[\text{course_id}] = s[\text{course_id}] \wedge s[\text{semester}] = \text{"Fall"} \wedge s[\text{year}] = 2009 \vee \exists u \in \text{section} (t[\text{course_id}] = u[\text{course_id}] \wedge u[\text{semester}] = \text{"Spring"} \wedge u[\text{year}] = 2010))\}$$



Example Queries

- Find the set of all courses taught in the Fall 2009 semester, and in the Spring 2010 semester

$$\{t \mid \exists s \in \text{section} (t[\text{course_id}] = s[\text{course_id}] \wedge s[\text{semester}] = \text{"Fall"} \wedge s[\text{year}] = 2009 \wedge \exists u \in \text{section} (t[\text{course_id}] = u[\text{course_id}] \wedge u[\text{semester}] = \text{"Spring"} \wedge u[\text{year}] = 2010))\}$$

- Find the set of all courses taught in the Fall 2009 semester, but not in the Spring 2010 semester

$$\{t \mid \exists s \in \text{section} (t[\text{course_id}] = s[\text{course_id}] \wedge s[\text{semester}] = \text{"Fall"} \wedge s[\text{year}] = 2009 \wedge \neg \exists u \in \text{section} (t[\text{course_id}] = u[\text{course_id}] \wedge u[\text{semester}] = \text{"Spring"} \wedge u[\text{year}] = 2010))\}$$



Universal Quantification

- Find all students who have taken all courses offered in the Biology department
 - $\{t \mid \exists r \in \text{student} (t[ID] = r[ID]) \wedge$
 $(\forall u \in \text{course} (u[\text{dept_name}] = \text{"Biology"} \Rightarrow$
 $\exists s \in \text{takes} (t[ID] = s[ID] \wedge$
 $s[\text{course_id}] = u[\text{course_id}]))\}$



Safety of Expressions

- It is possible to write tuple calculus expressions that generate infinite relations.
- For example, $\{ t \mid \neg t \in r \}$ results in an infinite relation if the domain of any attribute of relation r is infinite
- To guard against the problem, we restrict the set of allowable expressions to safe expressions.
- An expression $\{ t \mid P(t) \}$ in the tuple relational calculus is *safe* if every component of t appears in one of the relations, tuples, or constants that appear in P
 - NOTE: this is more than just a syntax condition.
 - ▶ E.g. $\{ t \mid t[A] = 5 \vee \mathbf{true} \}$ is not safe --- it defines an infinite set with attribute values that do not appear in any relation or tuples or constants in P .



Safety of Expressions (Cont.)

- Consider again that query to find all students who have taken all courses offered in the Biology department
 - $\{t \mid \exists r \in \text{student} (t[ID] = r[ID]) \wedge$
 $(\forall u \in \text{course} (u[\text{dept_name}] = \text{"Biology"} \Rightarrow$
 $\exists s \in \text{takes} (t[ID] = s[ID] \wedge$
 $s[\text{course_id}] = u[\text{course_id}]))\}$
- Without the existential quantification on student, the above query would be unsafe if the Biology department has not offered any courses.



Domain Relational Calculus



Domain Relational Calculus

- A nonprocedural query language equivalent in power to the tuple relational calculus
- Each query is an expression of the form:

$$\{ \langle x_1, x_2, \dots, x_n \rangle \mid P(x_1, x_2, \dots, x_n) \}$$

- x_1, x_2, \dots, x_n represent domain variables
- P represents a formula similar to that of the predicate calculus



Example Queries

- Find the *ID*, *name*, *dept_name*, *salary* for instructors whose salary is greater than \$80,000
 - $\{ \langle i, n, d, s \rangle \mid \langle i, n, d, s \rangle \in instructor \wedge s > 80000 \}$
- As in the previous query, but output only the *ID* attribute value
 - $\{ \langle i \rangle \mid \langle i, n, d, s \rangle \in instructor \wedge s > 80000 \}$
- Find the names of all instructors whose department is in the Watson building
 - $\{ \langle n \rangle \mid \exists i, d, s (\langle i, n, d, s \rangle \in instructor \wedge \exists b, a (\langle d, b, a \rangle \in department \wedge b = \text{"Watson"})) \}$



Example Queries

- Find the set of all courses taught in the Fall 2009 semester, or in the Spring 2010 semester, or both

$$\{ \langle c \rangle \mid \exists a, s, y, b, r, t (\langle c, a, s, y, b, r, t \rangle \in \text{section} \wedge s = \text{"Fall"} \wedge y = 2009) \vee \exists a, s, y, b, r, t (\langle c, a, s, y, b, r, t \rangle \in \text{section}] \wedge s = \text{"Spring"} \wedge y = 2010)) \}$$

This case can also be written as

$$\{ \langle c \rangle \mid \exists a, s, y, b, r, t (\langle c, a, s, y, b, r, t \rangle \in \text{section} \wedge ((s = \text{"Fall"} \wedge y = 2009) \vee (s = \text{"Spring"} \wedge y = 2010))) \}$$

- Find the set of all courses taught in the Fall 2009 semester, and in the Spring 2010 semester

$$\{ \langle c \rangle \mid \exists a, s, y, b, r, t (\langle c, a, s, y, b, r, t \rangle \in \text{section} \wedge s = \text{"Fall"} \wedge y = 2009) \wedge \exists a, s, y, b, r, t (\langle c, a, s, y, b, r, t \rangle \in \text{section}] \wedge s = \text{"Spring"} \wedge y = 2010)) \}$$



Safety of Expressions

The expression:

$$\{ \langle x_1, x_2, \dots, x_n \rangle \mid P(x_1, x_2, \dots, x_n) \}$$

is safe if all of the following hold:

1. All values that appear in tuples of the expression are values from *dom*(*P*) (that is, the values appear either in *P* or in a tuple of a relation mentioned in *P*).
2. For every “there exists” subformula of the form $\exists x (P_1(x))$, the subformula is true if and only if there is a value of *x* in *dom*(*P*₁) such that *P*₁(*x*) is true.
3. For every “for all” subformula of the form $\forall x (P_1(x))$, the subformula is true if and only if *P*₁(*x*) is true for all values *x* from *dom*(*P*₁).



Universal Quantification

- Find all students who have taken all courses offered in the Biology department
 - $\{ \langle i \rangle \mid \exists n, d, tc (\langle i, n, d, tc \rangle \in student \wedge$
 $(\forall ci, ti, dn, cr (\langle ci, ti, dn, cr \rangle \in course \wedge dn = \text{"Biology"}$
 $\Rightarrow \exists si, se, y, g (\langle i, ci, si, se, y, g \rangle \in takes))) \}$
 - Note that without the existential quantification on student, the above query would be unsafe if the Biology department has not offered any courses.



End of Chapter 6

Database System Concepts, 6th Ed.

©Silberschatz, Korth and Sudarshan

See www.db-book.com for conditions on re-use