



<http://www.lycato.com>



Layout & i18n

Spring Boot

Nguyễn Nghiệm





AGENDA

- ☐ FRAGMENT
- ☐ LAYOUT
- ☐ INTERNATIONALIZATION



<https://www.thymeleaf.org/doc/tutorials/3.0/usingthymeleaf.html>



Fragment



FRAGMENT DIRECTIVES & EXPRESSIONS

page1.html

☐ **th:fragment**

❖ Định nghĩa fragment

☐ **th:replace**

❖ Thay thế thẻ bằng fragment

☐ **th:insert**

❖ Chèn fragment vào nội dung thẻ

☐ **th:remove**

❖ Xóa thẻ

```
<tag th:insert="~{::frag}">...</tag>
```

```
<tag th:replace="~{::frag}">...</tag>
```

```
<tag th:remove="all">
```

```
    <tag th:fragment="frag">...</tag>  
</tag>
```


page2.html

```
<tag th:insert="~{page1::frag}">...</tag>
```

```
<tag th:replace="~{page1::frag}">...</tag>
```




WHAT IS FRAGMENT?






THYMELEAF FRAGMENT





FRAGMENT PARAMETERS





Layout




Header

Dynamic Content

Aside

Footer



Result

Dynamic Content

Template



LAYOUT

layout.html

th:fragment="dynamic(view)"

<header>

th:replace="\${view}"

<aside>

<footer>

th:replace="layout::dynamic(~{::view})"



page1.html

th:replace="layout::dynamic(~{::view})"



page2.html

th:replace="layout::dynamic(~{::view})"



page3.html



```
<html xmlns:th="http://www.thymeleaf.org"
      th:fragment="dynamic(view)">
<head>...</head>
<body>
  <header>...</header>
  <div>
    <article th:replace="${view}"></article>
    <aside>...</aside>
  </div>
  <footer>...</footer>
</body>
</html>
```

layout.html

```
<html xmlns:th="http://www.thymeleaf.org"
      th:replace="~{layout :: dynamic(~{::view})}">
<body>
  <div th:fragment="view">
    <h1>Hotgirl</h1>
    
  </div>
</body>
</html>
```



page.html



Internationalization



INTERNATIONALIZATION CASE STUDY





MessageSource

- Message.properties



Select & Display Message

- LocaleResolver



Change Language

- Locale Change Interceptor



1.1 MESSAGESOURCE

menu.home=Trang chủ *menu_***vi***.properties*
menu.about=Giới thiệu
page.home=Đây là trang chủ
page.about=Đây là trang giới thiệu

menu.home=Home *menu_***en***.properties*
menu.about=About Us
page.home=This is home page
page.about=This is about us page



1.2 MESSAGESOURCE

@Configuration

public class MessageConfig {

@Bean("messageSource")

public **MessageSource** getMessageSource() {

 ReloadableResourceBundleMessageSource *msg*

 = *new* ReloadableResourceBundleMessageSource();

msg.setDefaultEncoding("utf-8");

msg.setBasenames("classpath:messages/menu");

return msg;

}

}



2.1 LOCALERESOLVER

@Configuration

```
public class MessageConfig {
```

```
    @Bean("messageSource")
```

```
    public MessageSource getMessageSource() {...}
```

```
    @Bean("localeResolver")
```

```
    public LocaleResolver getLocaleResolver() {
```

```
        CookieLocaleResolver resolver = new CookieLocaleResolver();
```

```
        resolver.setDefaultLocale(new Locale("vi"));
```

```
        resolver.setCookiePath("/");
```

```
        resolver.setCookieMaxAge(5 * 24 * 60 * 60); //5 days
```

```
        return resolver;
```

```
    }
```

```
}
```



2.2 DISPLAY MESSAGE

```
...  
<a href="/layout/index" th:text="#{menu.home}"></a> :  
<a href="/layout/about" th:text="#{menu.about}"></a> :  
<a href="">Tiếng Việt</a>  
<a href="">English</a>  
...
```

menu.html

```
...  
<h1 th:text="#{menu.home}"></h1>  
...
```

home.html

```
...  
<h1 th:text="#{menu.about}"></h1>  
...
```

about.html



3.1 LOCALECHANGEINTERCEPTOR

@Configuration

public class MessageConfig *implements* **WebMvcConfigurer** {

@Bean("messageSource")

public MessageSource getMessageSource() {...}

@Bean("localeResolver")

public LocaleResolver getLocaleResolver() {...}

@Override

public void **addInterceptors**(InterceptorRegistry registry) {

LocaleChangeInterceptor localeChange = *new* LocaleChangeInterceptor();

localeChange.setParamName(**"lang"**);

registry.addInterceptor(localeChange).addPathPatterns("/**");

}

}

`Tiếng Việt`
`English`



3.2 CHANGE LANGUAGE REQUEST

...

```
<a href="/home/set-lang?lang=vi">Tiếng Việt</a>  
<a href="/home/set-lang?lang=en">English</a>
```

...

```
<script src="https://ajax.googleapis.com/ajax/libs/jquery/3.5.1/jquery.min.js"></script>  
<script>  
$(document).ready(function(){  
    $("a[href*=lang]").click(function(){  
        var url = $(this).attr("href");  
        $.get(url).then(resp => location.reload());  
    });  
})  
</script>
```



✓ Xây dựng Layout

- ✓ th:fragment

- ✓ th:insert

- ✓ th:replace

- ✓ th:remove

✓ I18N

- ✓ Resources

 - ✓ .properties

 - ✓ @Configuration

- ✓ Display

 - ✓ #{key}

 - ✓ LocaleResolver

- ✓ Change language

 - ✓ LocaleChangeInterceptor

 - ✓ @href="?lang=vi"

