

Total Productive Maintenance — Lubrication Schedule

Purpose

This document defines the lubrication schedule and procedures for production equipment at Acme Corporation as part of the Total Productive Maintenance program.

Scope

This document applies to all production equipment requiring regular lubrication across all production lines.

Lubrication Principles

- Clean before lubricating — contamination of lubricant causes bearing failure.
- Use the correct lubricant type — never substitute without QA approval.
- Apply the correct quantity — over-lubrication causes overheating; under-lubrication causes wear.
- Follow the schedule precisely — lubrication is preventive, not corrective.
- Record each lubrication action.

Lubrication Schedule

Equipment	Lubrication Point	Lubricant	Frequency	Method
Conveyor System	Bearing Blocks	NLGI 2 Grease	Weekly	Grease Gun (2 pumps)
Press Machine	Guide Rails	ISO VG 68 Oil	Daily	Oil Can (3 drops)
Press Machine	Linkage Pins	NLGI 2 Grease	Monthly	Grease Gun (3 pumps)
Mixing Tank	Agitator Bearing	ISO VG 220 Oil	Weekly	Oil Bath Check
Packaging Line	Chain Drive	ISO VG 150 Oil	Weekly	Brush Application
Compressor	Oil Reservoir	ISO VG 100 Oil	Monthly	Top-up to Level
CNC Machine	Spindle	ISO VG 10 Oil	Daily	Auto Lubrication Check

Equipment	Lubrication Point	Lubricant	Frequency	Method
CNC Machine	Ball Screws	NLGI 1 Grease	Weekly	Grease Gun (1 pump)
Centrifuge	Main Bearing	NLGI 2 Grease	Monthly	Grease Gun (4 pumps)

Lubrication Procedure

Weekly Lubrication

1. Review the lubrication schedule for the current week.
2. Gather the specified lubricants and tools.
3. Lock out / tag out the equipment before beginning.
4. Clean all lubrication points with a lint-free cloth.
5. Apply the specified lubricant in the specified quantity.
6. Wipe off any excess lubricant.
7. Record the lubrication in the TPM logbook.
8. Remove lock out / tag out and verify equipment operation.

Monthly Lubrication

1. Complete all weekly lubrication steps.
2. Check oil levels in reservoirs and gearboxes.
3. Inspect grease fittings for damage.
4. Check for leaks around seals and gaskets.
5. Report any abnormalities to the maintenance supervisor.

Lubricant Storage

- All lubricants must be stored in a clean, climate-controlled area.
- Containers must be sealed when not in use.
- Each lubricant container must be clearly labeled with product name and grade.
- First-in, first-out (FIFO) rotation must be followed.
- Expired lubricants must be disposed of per environmental guidelines.

Safety

- Wear appropriate PPE (safety glasses, gloves) when handling lubricants.
- Immediately clean up any spills using absorbent material.
- Dispose of used rags and absorbent material in approved containers.
- Refer to SDS for each lubricant before use.

Related Documents

- Equipment-specific maintenance manuals
- Safety Data Sheets for each lubricant

Document Version 1.1 — Last Updated March 2026