

Day 3: Overfitting and Generalization

Summer STEM: Machine Learning

Department of Electrical Engineering
NYU Tandon School of Engineering
Brooklyn, New York

June 23, 2020

Outline

- 1 Review of Day 2
- 2 Polynomial Regression
- 3 Train and Test Error, Overfitting
- 4 Regularization
- 5 Non-Linear Optimization

General Steps to Solve a Machine Learning Problem

- Load and visualize data

General Steps to Solve a Machine Learning Problem

- Load and visualize data
 - $(x_i, y_i), i = 1, \dots, n$

General Steps to Solve a Machine Learning Problem

- Load and visualize data
 - $(x_i, y_i), i = 1, \dots, n$
- Find an appropriate model to fit the data

General Steps to Solve a Machine Learning Problem

- Load and visualize data
 - $(x_i, y_i), i = 1, \dots, n$
- Find an appropriate model to fit the data
 - Eg: Linear model is $\hat{y} = wx + b$

General Steps to Solve a Machine Learning Problem

- Load and visualize data
 - $(x_i, y_i), i = 1, \dots, n$
- Find an appropriate model to fit the data
 - Eg: Linear model is $\hat{y} = wx + b$
- Choose an appropriate error function

General Steps to Solve a Machine Learning Problem

- Load and visualize data
 - $(x_i, y_i), i = 1, \dots, n$
- Find an appropriate model to fit the data
 - Eg: Linear model is $\hat{y} = wx + b$
- Choose an appropriate error function
 - $MSE = \sum_{i=1}^N (y_i - (b + wx_i))^2$

General Steps to Solve a Machine Learning Problem

- Load and visualize data
 - $(x_i, y_i), i = 1, \dots, n$
- Find an appropriate model to fit the data
 - Eg: Linear model is $\hat{y} = wx + b$
- Choose an appropriate error function
 - $MSE = \sum_{i=1}^N (y_i - (b + wx_i))^2$
- Find parameters that minimize the error function

General Steps to Solve a Machine Learning Problem

- Load and visualize data
 - $(x_i, y_i), i = 1, \dots, n$
- Find an appropriate model to fit the data
 - Eg: Linear model is $\hat{y} = wx + b$
- Choose an appropriate error function
 - $MSE = \sum_{i=1}^N (y_i - (b + wx_i))^2$
- Find parameters that minimize the error function
 - Select b, w to minimize the error function

Extending the Model to Multi-variable Data

- Model: $\hat{y} = w_0 \times 1 + w_1 x_1 + w_2 x_2 + \dots + w_D x_D$

- Design Matrix: Let, $X = \begin{bmatrix} 1 & x_{1_1} & \cdots & x_{1_D} \\ 1 & x_{2_1} & \cdots & x_{2_D} \\ \vdots & & \ddots & \\ 1 & x_{N_1} & \cdots & x_{N_D} \end{bmatrix}$

- We say \mathbf{w}^* solves $\mathbf{y} = X\mathbf{w}$ in the least squares sense, where

$$\mathbf{w}^* = X^\dagger \mathbf{y}$$


- This \mathbf{w}^* is the unique set of parameters that minimize the squared error

Outline

- 1 Review of Day 2
- 2 Polynomial Regression
- 3 Train and Test Error, Overfitting
- 4 Regularization
- 5 Non-Linear Optimization

Polynomial Fitting


- We have been using linear model to fit our data. But it doesn't work well every time
- Some data have more complex relation that cannot be fitted well using a straight line
 - Ex: Projectile motion, Coulomb's law, Exponential growth/decay, ...



- Linear model does not look like a good fit for this data
- Can we use some other model to fit this data?

Polynomial Fitting

- Can we use a polynomial to fit our data?
- Polynomial: A sum of different powers of a variable
 - Examples: $y = x^2 + 2$, $y = 5x^3 - 3x^2 + 4$



- Polynomial Model: $y = w_0 + w_1x + w_2x^2 + w_3x^3 + \dots$

Polynomial Fitting

- Polynomial Model: $y = w_0 + w_1x + w_2x^2 + w_3x^3 + \dots$
- The process of fitting a polynomial is similar to linearly fitting multivariate data
- Recall the linear model for multivariable
- $y = w_0 + w_1x_1 + w_2x_2 + w_3x_3 + \dots$
 - Where $x_1, x_2, x_3 \dots$ are different features
- If we treat x^2 as our second feature, x^3 as our third feature, x^4 as our fourth feature.... We can use the same procedure in multivariate regression for linear fit!

Polynomial Fitting

- Design Matrix for Linear:

$$X = \begin{bmatrix} 1 & x_1 \\ 1 & x_2 \\ \vdots & \vdots \\ 1 & x_N \end{bmatrix}$$


- Design Matrix for Polynomial:

$$\Phi(X) = \begin{bmatrix} 1 & x_1 & x_1^2 & \cdots & x_1^D \\ 1 & x_2 & x_2^2 & \cdots & x_2^D \\ \vdots & \vdots & \ddots & \ddots & \vdots \\ 1 & x_N & x_N^2 & \cdots & x_N^D \end{bmatrix}$$

- For the polynomial fitting, we just added columns of features that are powers of the original feature

Demo: Fit a polynomial

- You are given the data set below with x and y values



- Try to fit the data using a polynomial with a certain degree
- Calculate mean square error between the sample y and your predicted y
- Try different polynomial degree and see if you can improve the mse
- Plot your polynomial over the data points


Outline

- 1 Review of Day 2
- 2 Polynomial Regression
- 3 Train and Test Error, Overfitting
- 4 Regularization
- 5 Non-Linear Optimization

Overfitting

- We learned how to fit our data using polynomials of different order
- With a higher model order, we can fit the data with increasing accuracy
- As you increase the model order, at certain point it is possible find a model that fits your data perfectly (ie. zero error)
- What could be the problem?


Overfitting



■ Which of these model do you think is the best? Why?


Overfitting

- The problem is that we are only fitting our model using data that is given
- Data usually contains noise
- When a model becomes too complex, it will start to fit the noise in the data
- What happens if we apply our model to predict some data that the model has never seen before? It will not work well.
- This is called over-fitting



Overfitting


- Split the data set into a train set and a test set
- Train set will be used to train the model
- The test set will not be seen by the model during the training process
- Use test set to evaluate the model when a model is trained



- With the training and test sets shown, which one do you think is the better model now?

Train and Test Error

- Plot of train error and test error for different model order
- Initially both train and test error go down as model order increase
- But at a certain point, test error start to increase because of overfitting



Outline

- 1 Review of Day 2
- 2 Polynomial Regression
- 3 Train and Test Error, Overfitting
- 4 Regularization**
- 5 Non-Linear Optimization

How can we prevent overfitting without knowing the model order before-hand?

- **Regularization:** methods to prevent overfitting

How can we prevent overfitting without knowing the model order before-hand?

- **Regularization:** methods to prevent overfitting
 - We just covered regularization by model order selection

How can we prevent overfitting without knowing the model order before-hand?


- **Regularization:** methods to prevent overfitting
 - We just covered regularization by model order selection
- Is there another way? Talk among your classmates.

How can we prevent overfitting without knowing the model order before-hand?

- **Regularization:** methods to prevent overfitting
 - We just covered regularization by model order selection
- Is there another way? Talk among your classmates.
 - Solution: We can change our cost function.


Weight Based Regularization

- Looking back at the polynomial overfitting



Weight Based Regularization

- Looking back at the polynomial overfitting
- Notice that weight-size increases with overfitting



New Cost Function

$$J = \sum_{i=1}^N (y_i - y_{i_{pred}})^2$$

New Cost Function

$$J = \sum_{i=1}^N (y_i - y_{i_{pred}})^2 + \lambda \sum_{j=1}^D (w_j)^2$$

New Cost Function

$$J = \sum_{i=1}^N (y_i - y_{i_{pred}})^2 + \lambda \sum_{j=1}^D (w_j)^2$$

- Penalize complexity by simultaneously minimizing weight values.

New Cost Function

$$J = \sum_{i=1}^N (y_i - y_{i_{pred}})^2 + \lambda \sum_{j=1}^D (w_j)^2$$

- Penalize complexity by simultaneously minimizing weight values.
- We call λ a **hyperparameter**

New Cost Function

$$J = \sum_{i=1}^N (y_i - y_{i_{pred}})^2 + \lambda \sum_{j=1}^D (w_j)^2$$

- Penalize complexity by simultaneously minimizing weight values.
- We call λ a **hyperparameter**
 - λ determines relative importance

New Cost Function

$$J = \sum_{i=1}^N (y_i - y_{i_{pred}})^2 + \lambda \sum_{j=1}^D (w_j)^2$$

- Penalize complexity by simultaneously minimizing weight values.
- We call λ a **hyperparameter**
 - λ determines relative importance

New Cost Function

$$J = \sum_{i=1}^N (y_i - y_{i_{pred}})^2 + \lambda \sum_{j=1}^D (w_j)^2$$

- Penalize complexity by simultaneously minimizing weight values.
- We call λ a **hyperparameter**
 - λ determines relative importance

Table 1.2 Table of the coefficients w^* for $M = 9$ polynomials with various values for the regularization parameter λ . Note that $\ln \lambda = -\infty$ corresponds to a model with no regularization, i.e., to the graph at the bottom right in Figure 1.4. We see that, as the value of λ increases, the typical magnitude of the coefficients gets smaller.

	$\ln \lambda = -\infty$	$\ln \lambda = -1.8$	$\ln \lambda = 0$
w_0^*	0.35	0.35	0.13
w_1^*	232.37	4.74	-0.05
w_2^*	-5321.83	-0.77	-0.06
w_3^*	48568.31	-31.97	-0.05
w_4^*	-231639.30	-3.89	-0.03
w_5^*	640042.26	55.28	-0.02
w_6^*	-1061800.52	41.32	-0.01
w_7^*	1042400.18	-45.95	-0.00
w_8^*	-557682.99	-91.53	0.00
w_9^*	125201.43	72.68	0.01

Tuning Hyper-parameters

- Motivation: never determine a hyper-parameter based on training data

Tuning Hyper-parameters

- Motivation: never determine a hyper-parameter based on training data
- **Hyper-Parameter:** a parameter of the algorithm that is not a model-parameter solved for in optimization.

Tuning Hyper-parameters

- Motivation: never determine a hyper-parameter based on training data
- **Hyper-Parameter:** a parameter of the algorithm that is not a model-parameter solved for in optimization.
 - Ex: λ weight regularization value vs. model weights (\mathbf{w})

Tuning Hyper-parameters

- Motivation: never determine a hyper-parameter based on training data
- **Hyper-Parameter:** a parameter of the algorithm that is not a model-parameter solved for in optimization.
 - Ex: λ weight regularization value vs. model weights (\mathbf{w})
- Solution: split dataset into three

Tuning Hyper-parameters

- Motivation: never determine a hyper-parameter based on training data
- **Hyper-Parameter**: a parameter of the algorithm that is not a model-parameter solved for in optimization.
 - Ex: λ weight regularization value vs. model weights (\mathbf{w})
- Solution: split dataset into three
 - **Training set**: to compute the model-parameters (\mathbf{w})

Tuning Hyper-parameters

- Motivation: never determine a hyper-parameter based on training data
- **Hyper-Parameter**: a parameter of the algorithm that is not a model-parameter solved for in optimization.
 - Ex: λ weight regularization value vs. model weights (\mathbf{w})
- Solution: split dataset into three
 - **Training set**: to compute the model-parameters (\mathbf{w})
 - **Validation set**: to tune hyper-parameters (λ)

Tuning Hyper-parameters

- Motivation: never determine a hyper-parameter based on training data
- **Hyper-Parameter**: a parameter of the algorithm that is not a model-parameter solved for in optimization.
 - Ex: λ weight regularization value vs. model weights (\mathbf{w})
- Solution: split dataset into three
 - **Training set**: to compute the model-parameters (\mathbf{w})
 - **Validation set**: to tune hyper-parameters (λ)
 - **Test set**: to compute the performance of the algorithm (MSE)

Outline

- 1 Review of Day 2
- 2 Polynomial Regression
- 3 Train and Test Error, Overfitting
- 4 Regularization
- 5 Non-Linear Optimization**

Motivation

- Cannot rely on closed form solutions

Motivation

- Cannot rely on closed form solutions
 - Computation efficiency: operations like inverting a matrix is not efficient

Motivation

- Cannot rely on closed form solutions
 - Computation efficiency: operations like inverting a matrix is not efficient
 - For more complex problems, like neural network, a closed form solution is not always available

Motivation

- Cannot rely on closed form solutions
 - Computation efficiency: operations like inverting a matrix is not efficient
 - For more complex problems, like neural network, a closed form solution is not always available
- Need an optimization technique to find an optimal solution

Motivation

- Cannot rely on closed form solutions
 - Computation efficiency: operations like inverting a matrix is not efficient
 - For more complex problems, like neural network, a closed form solution is not always available
- Need an optimization technique to find an optimal solution
 - Machine learning practitioners use gradient based methods

Understanding Optimization

- *Recap* $\hat{y} = w_0 + w_1x$
- *Loss*, $J = \sum_{i=1}^N (y_i - \hat{y}_i)^2 \implies J = \sum_{i=1}^N (y_i - w_0 - w_1x_i)^2$
- Want to find w_0 and w_1 that minimizes J

