

Jan 27 (Wed), 2021 Harry Li

CMPE240 Welcome to 240 Section 2

Email: hua.li@sjtu.edu

Office Hours: M.W. 4:30-5:30 pm.
Zoom Based

Greensheet [github/hualili](https://github.com/hualili)
CMPE240/2018F

References:

1. Greensheet on github
(650)400-1116 Text message
Pre-requisite Requirements (80D)

Advanced Microprocessor Systems

Smart phones & RISC Architecture

5G, Edge AI → IoT, AI → GPU

Prototype System

Fully Functional Microprocessor
System

Action Items:

1° [github/hualili/cmpe240](https://github.com/hualili/cmpe240)

2° Pre-requisite Requirements, 180D

3° LPC1769 CPU module

digkey.com OR mouser.com

Handson: multiple projects, 3 miles Stones

4° CPU Datasheet

CMPE240 Feb: (Mon) 1/
Today's Topics: 1° System Level
Architecture — LPC1769
Ref: [github/hualili/cmpe240](https://github.com/hualili/cmpe240)

2018F-102 2° CPU Data-
Sheet

Example:

1° CPU Module @ center of the
System Layout Design

NXP1769

Prototype
digkey.com
mouser

2° Wirewrapping Board

Dimension: 6" x 4"

with Through-holes,
Architectural and one side of Board
Aspects whose through-holes

with metal plating; **But**
not the entire Board (just
the through-holes)

3° PWR CKT: J1 Connector

Right Angle Connector;

S/W Toggle Switch; IC



Regulator 7805, 1117

Red LED 4~10mA

Resistor, Cap.(LPF)

NXP.com Note: Debug/Development

No External Power CKT



Ref: CPU module Design.pdf
github, Rev.D. or higher

From the Datasheet, Two tables
on Each Side of the CPU module
First, Left Side, the outer table
is for mbed, Not interested.

Naming Convention:

- ① CPU pin is named identical as the name appeared in the CPU Datasheet;
- ② The physical connection Label(s) are given on the SCH to match up the physical Board

Question: Find the pin for GND

From SCH,

Connectivity Table

Functional Pin	Physical Pin	Note
GND	J2-1	
VIN	J2-2	4.5~5.5VDC

Enumeration of the pin(s)
CPU pin (1st pin) starts as
"P";

CPU Datasheet 2018S-3-

UM10360

CPU Architecture, PP, q




Fig.2.

CPU
Peripheral Controllers (SCH, Data sheet)

Feb 3. CMPE240 Harry Li

Note: 1° Have your video when participating the Class; 2° Honest Pledge Form / Sign CANVAS submission By Sat. 11:59 pm;

Today's Topics: 1° CPU Architecture / CPU Datasheet

SCH ; 2° Homework Design of prototype Board


Peripheral Controller

Ref: ① CPU Datasheet, pp.9.
 ② SCH

Example: From SCH.

→ SPI Serial Peripheral Interface
 Note: RESET pin has to be included in
 Our Prototype Design

MOSI: Master Output Slave Input



MISO: Master Input Slave Output

SCK: Serial Clock (0)

SSEL: Enable SPI Controller (ON
 the Slave Side, Active Low)

Note: MOSIx, MISOx, SCKx,
 SSELx, where x stands for the
 xth of SPI Controller

Question: Find Number of SPI I/F
 for this LPC1769 CPU?

Two SPI I/F SPI0, SPI1

2^o UART (Serial I/F), Note RS232 for G.E (2D, 3D)

{ TX (Transmitter)
 Rx (Receiver)

3rd pin has to be a part of it : GND

TxD, RxD

Multiplexing, TX/SDA

Init & Config for Special
 Purpose Registers will define
 which function the pin will
 I/O assume.

Action 1: Homework —

Read SCH, generate a
 table for all Peripheral
 Controllers

Table: CPU Datasheet, pp.9

Table 2: SCH to find subset
 of the I/O controller.

Advanced Feature:

G.E. Graphics Engine

Example: Broadcom

Pie3D, 4 → GE

NVDA: GPU (Graphics

Processing Unit)

NAND 128 GPU,

TX2, 6 CPU +

256 GPU

"3+1"
 pins

{ MOSI/MISO/SCK
 SSEL(Enable)

Software Implementation


for G.E (2D, 3D)

Basic Concepts.

1^o RISC (Reduced Instruction

Set Computer) { ARM
 MIPS }

32 Bit



Memory : $2^{32} = 2^{10} \cdot 2^{10} \cdot 2^{10} \cdot 2^2 = 4 \text{ GB}$

Note : 10 Byte Addressable
 Smallest memory with unique address is a Single Byte

CMPE240 Feb 8 (Mon), Harry LI

Today's Topics :

1° Bill of Material (github)

2° CPU Architecture

3° Preparation to Bring up your
 CPU, MCU Expresso



Two Step Process to Prepare for Prototype
 Board,

Step 1: CPU module LPC1769


Wirewrapping (Prototype Board)
 "Glue" Logic Resistors, Caps,

PWR Regulation IC
 (7805), Red LED, Stand-offs


CMOS CPU ARM
 V_{out} 3.3VDC, 10~30mA
 Estimate 3.3V / 10mA, 3.3V / 30mA
 3.3×10^2 , 1.1 × 10²
 Amps.



To Cmp to Realize CPUF.



$$V_{CC} \left(1 - e^{-\frac{t}{RC}}\right) \dots (1)$$



2nd part for caps : 7805

Datasheet for 7805, Caps are those with Polarity "↑" ↓"


Bill of the Material to Build

G.E.

SPI I/F Based Color LCD

Device. a SPI (Not I2C)


b Module - Connector



2-3 Weeks

CPU Architecture Discussion

1° memory map




$$2^{32} = 4 \text{ GB}$$

3° Memory Bank: 8

$$4 \text{ G} / 8 = 2^{10} \cdot 2^{10} \cdot 2^{10} \cdot 2^2 / 2^3$$

$$= 2^9 \cdot 2^{10} \cdot 2^{10} = 512 \text{ M}$$

Question: How many Bits from the Addr. Bus do we need to uniquely define each memory Through-Hole Bank? 3 Bits



What is the Starting Address of the 2nd Bank:

$a_{31} a_{30} a_{29}, a_{28}$

0 0 1 : 0

0 X 2000_0000 ; — 2nd Bank

0 X 4000_0000 ; — 3rd Bank

Cmpe240 Feb 10 (Wed)

Ref: github/hinalili/Cmpe240

... 2018F-107-LecGPP

Homework 1. Form 4-Person Team

First, Last Name, Last 4 Digits SID

E-mail Address → Submission

2° Byte Addressable Machine
~ Whose Smallest mem. cell
With unique address is a
Single Byte

Via Email & Canvas By Thursday

11:59 Subject Title → Team Coordinator
Document Name First-Last-CmpE240 in Zip format

8-mail submission.

Homework 2: (1 pt)

Requirements ① Build a prototype Board, ② Write a first program

Turn On/Off LED "Hello, the World"

Note: Use Prototype Board to Build GPP I/O To Drive LED On/Off

③ Build I/O Testing Circuit, the CKT input is from GPP (GPIO)




Fig 1.

CPU → prototype CKT₁: For Output

Testing "1" to Turn on LED

"0" to Turn off LED

CKT₂: For Input Testing

Input "1", Toggle switch to connect GPP

Input to V_{CC} (via a Resistor)

Input "0", Toggle the switch to GND
(via Resistor)

Submission:

1° Project Exported

Document Name First-Last-CmpE240 in Zip format

2° White paper, Report

3° Video Clip (upto 5~7
Seconds) Short please.

Example: From PPT on GPP I/F.

Identify CPU GPP Pin

P0.3 J2-22 Input

P0.21 J2-23 Output

Consider the Output Testing CKT,




Fig. 2

$$V_{CC} = IR + V_{LED} \quad \dots (1)$$

$$V_{CC} = 3.3 \text{ VDC}$$

$$I \approx 10 \text{ mA}, V_{LED} = 1.2 \text{ VDC}$$


$$3.3 = (0 \times 10^{-3}) R + 1.2$$

$$R = (3.3 - 1.2) / 10^{-2} = 210 \Omega$$

Now, Let's Design CKT₂

④ Write One page Report (IEEE paper format) white paper Due ON CANVAS

Due 2 weeks from Today, Feb 24.



System Level & Software Design


1. CPU Architecture → mem.
Peripheral Controllers map
GPP Controller BANK of

a Power Address 1st Address Background:

0X0000_0000 CPU when powered up

It will fetch the 1st Executable Instruction at this location

Fig 1



Feb 15 Monday


Today's Topic: GPP I/O Testing

CPU Architecture & Special Purpose Registers.

Power-up Addr: Addr.
when CPU is powered, it will fetch the 1st instruction to execute at this memory location.

Firmware → A program which has been burned into Rom/Flash

Question: How do you write C program to perform GPIO init & config? So that I/O I/F can be established?



Special Purpose Registers
32 bits:
Their function:

- a Control function: Init & Config
- b Data Exchange Function: Pull up/Down

CMPE240

Naming convention:

Prefix + Root + Postscript

3 3 (3)
GPx CON

General purpose GPxCON




Fig 4.

Prototype
Board

GPxCON[0] = 1

Action 1 : LTC1769 patch.zip

Import it as a project

into your IDE

Test run blenky Program

To modify the GPP
= 0 So P0,2 & F0,3

Can be employed for
I/O Testing

Note: 1° Project Panel on the

top left of your IDE GUI

→ Select "Blenky" By
highlighting it.

CMPE240 Feb 17 (W)

Ref: 1° [github/finalisti11/CMPE240/2018S-11-GPIOD2015-1-30.zip](https://github.com/finalisti11/CMPE240/2018S-11-GPIOD2015-1-30.zip)

Question: How many Control function
can one Control Register define?

$$2^{32} = 4 \text{ G}$$

Now, GPxDAT, 0x4000_0204

LSB (Little Endian) 2018-10-LCD-



GPxDAT[0] Fig 3.

drawLine.zip

3° ~ /2018F/2018F-107-~
(For GPP)

4° ~ /2018F/2018F-109
(For SPI LCD)

5° ~ /cmpe240/2018S-10-~
DrawLine.zip
(For 2D GE-Line Plot)

Topics: 1° SPRs for SPI LCD I/F; 2° SPRs for GPP.

Init & Config of Peripheral Controller(s)

GPP

SPI (Serial Peripheral Interface)

Note: External Connector → CPU GPP. 2018S-8-SPI (photo Board)

J2-X

Pf.2, etc.

Example:

SPI Interface for Color
LCD Display.


Hardware Design

Software Design

Consider Hardware Design Block Diagram

Step 1

SPI Host



Pin Connectivity "3+1"

CPU	SPI(S)	Note
MOSI Pf.9/J2-5	SI	CPU(0)
MISO Pf.8/J2-6	SO	CPU(I)
SCK Pf.7/J2-7	CLK	CPU(0)
SSEL Pf.6/J2-8	CS (nCS) Active Low	CPU(0)

Table 1: Connectivity Table

2018S-8-SPI (photo Board)

Note: Connectivity Table for CPU to SPI LCD Display Device.

Action 1: Solder up the SPI LCD Device;


Software Design

Background:

(0,0)

X-Y Coordinate
Origin(0,0)

Upper Left
Corner




Resolution: $M \times N$


M : No. of Pixels per Row

N : No. of Rows per Frame

Example: 160×120



2^o $I(x,y)$ Image plane(s)



r: red;

g: green;


b: blue.

Fig. 1

$$I(x,y) = (r(x,y), g(x,y), b(x,y)) \quad 3^o \text{ Ref: 2021S-10b-homework}$$

... (1)

Feb 22 (Monday)



① GPP I/O Testing
CPU

Architecture

CPU Block Diagram

② SPR

Init & Config.

Memory map

Peripherals


Peripheral Controller

GPP + SPI

③ Implementation

A Scanning (Image Formation)

Start at $(0,0)$ \rightarrow L2R one pixel at a time, \rightarrow T2B one row at a time.




4^o Report Template
2018-10 ~

Discussion on Graphics

1^o Graphics $\left\{ \begin{array}{l} \text{Pixel Graphics } I(x,y) \\ \text{Vector Graphics} \end{array} \right.$

2^o Display Device $\left\{ \begin{array}{l} \text{2D \& 3D G.E.} \\ \text{OX} \\ \text{Y} \end{array} \right.$



$M \times N$

b) Timing Calculation


b) Frame Rate FPS (Frame Per Second)

30 FPS

$$f_F = 30 \text{ Hz};$$

$$T_F = \frac{1}{f_F} = 33.3 \times 10^{-3} \text{ sec.} \quad \dots (1)$$

Note: GPP PPT 2018F-107



b) Horizontal Timing (Clock)

Given Graphics/Image with $M \times N$

$$f_H(\text{Sync}_H) = N f_F(\text{Sync}_F) \quad \dots (2)$$

b) Pixel Timing (clock, Data Clock)

$$f_D(\text{Sync}_D) = M f_H(\text{Sync}_H) \quad \dots (3)$$

Example: Given Graphics $I(x, y)$

with 1024×768 , And find


Timing for pixel $I(10b, 278)$

$$\text{Sol: } \text{Sync}_F = 30 \text{ Hz} (\equiv f_F)$$

$$\text{Sync}_H = N \cdot \text{Sync}_F = 768 \text{ Sync}_F$$

$$\text{Sync}_D = M \text{ Sync}_H$$

$$= 1024 \text{ Sync}_H$$




Scan 10b pixels to Reach to $(10b, 278)$, Hence $10b \frac{1}{\text{Sync}_D}$

Therefore,

$$T = T_{\Sigma H} + T_{\Sigma D}$$

$$= 278 \frac{1}{\text{Sync}_H} + 10b \frac{1}{\text{Sync}_D}$$

3rd Timing in terms of Graphics Display Controller Design.



Display module (A+B)

Design of the Display Controller

Timing Scheme

TFT Display

Complete Build
Drawline.
OKRun
Debug


Probs Loading.

Error:

migration is
failed ...


Cancel the Session

Sync H

Software Aspects of SPI
Implementation

Flow of the Discussion

C Implementation → Graphics → SPI → C-Code
 Drawline.zip
 (Project)
 MCUXpresso



Example: Import/Build/Debug Drawline.zip

Execute

Note:


1° MCUXpresso Version, 11.3.0 ✓

IDE :

SDK i (LPC1769)

SDK j ≈ No SDK for LPC1769

b LPC1769 Pre-Built for IDE

Control Signal:
 1° nGS (\bar{CS})

No SDK for LPC1769

NXP
OpenMCUCheck LPC1769
Pre-installed

Import

LPC1769 Patch.

Complete Build

Import DrawLine.zip

github

Controller Enable


2° Data/Command

D/C, or

C/D

Controller to LCD Display.

Part II:



2D Graphics


Action 1. LCD Wirewrapped
on the Prototype Board

Action 2. Test Drawline Project

Note:

1° mathematical Formulation


Vectors $\vec{P}(x, y) = \vec{P} = (x, y)$




$$\vec{P}(4, 5) = (4, 5)$$

2° Generate A Screen Saver
Based on G.E. (Vector Graphics)

Given a Set of Vectors
(Vertex)



Note: $\vec{P}_0, \vec{P}_1, \dots, \vec{P}_3$ are
arranged in the Counter
Clockwise Direction C.C.W.



3° Vector Representation of
Line a fix pt. and a direction




Fig.4

Define Direction Vector

$$\vec{d}(x, y) = \vec{P}_{i+1}(x_{i+1}, y_{i+1}) - \vec{P}_i(x_i, y_i) = \vec{P}_{i+1} - \vec{P}_i$$

... (1)

Example: Given $\vec{P}_i(3,4)$, $\vec{P}_{i+1}(1.5, -1.1)$

Find Direction Vector?

$$\text{Sol: } \vec{d}(x,y) \triangleq \vec{P}_{i+1}(1.5, -1.1) - \vec{P}_i(3,4)$$

$$= (1.5, -1.1) - (3, 4) = (-1.5, -5.5)$$

↳ Define A Line Starting pt \vec{P}_i

Ending (end) pt \vec{P}_{i+1} ,

$$\vec{P}(x,y) = \vec{P}_i(x_i, y_i) + \lambda \vec{d}(x, y) \quad \dots (1)$$

↑ ↓ ↓
Arbitrary pt. on the Line Scaling factor Direction Vector

$$\vec{P}(x,y) = \vec{P}_i(x_i, y_i) + \lambda (\vec{P}_{i+1}(x_{i+1}, y_{i+1}) - \vec{P}_i(x_i, y_i)) \quad \dots (1b)$$

From Eqn(1)

$$\lambda = 0, \vec{P}(x,y) = \vec{P}_i(x_i, y_i)$$

$$\lambda = 1, \vec{P}(x,y) = \vec{P}_{i+1}(x_{i+1}, y_{i+1})$$

$0 < \lambda < 1$, Pt Between \vec{P}_i and \vec{P}_{i+1}

↳ See Fig 3, PP. 13

From Eqn(1b)

$$P(x,y) = P_i(x_i, y_i) + \lambda (P_{i+1}(x_{i+1}, y_{i+1}) - P_i(x_i, y_i)) \quad \dots (2)$$

for $i = 0, 1, 2, 3$

Introducing Super Script to Eqn(1b) for the level of iterations
 initially, SuperScript Starts at ϕ . One Level higher.

$$\vec{P}_i^{\phi}(x, y) = \vec{P}_i^{\phi}(x_i^{\phi}, y_i^{\phi}) + \lambda \left(\vec{P}_{i+1}^{\phi}(x_{i+1}^{\phi}, y_{i+1}^{\phi}) - \vec{P}_i^{\phi}(x_i^{\phi}, y_i^{\phi}) \right) \quad (3)$$

\uparrow pt i @ next level, e.g. One Level higher

Generalize it,

$$\vec{P}_i^{j+1} = \vec{P}_i^j + \lambda (\vec{P}_{i+1}^j - \vec{P}_i^j) \quad (4)$$

$$\vec{P}_i^{j+1}(x_i^{j+1}, y_i^{j+1}) = \vec{P}_i^j(x_i^j, y_i^j) + \lambda \left(\vec{P}_{i+1}^j(x_{i+1}^j, y_{i+1}^j) - \vec{P}_i^j(x_i^j, y_i^j) \right) \dots \quad (4-1b)$$

$$\left\{ \begin{array}{l} x_i^{j+1} = x_i^j + \lambda (x_{i+1}^j - x_i^j) \\ y_i^{j+1} = y_i^j + \lambda (y_{i+1}^j - y_i^j) \end{array} \right. \dots \quad (5a)$$

$$\left\{ \begin{array}{l} x_i^{j+1} = x_i^j + \lambda (x_{i+1}^j - x_i^j) \\ y_i^{j+1} = y_i^j + \lambda (y_{i+1}^j - y_i^j) \end{array} \right. \dots \quad (5b)$$

March 3rd.

Example: Let Design A Square

By giving initial set of \vec{P}


Vertices (Vertices)

$\{ \vec{P}_0, \vec{P}_1, \vec{P}_2, \vec{P}_3 \}$

$$\vec{P}_0(x_0, y_0) = (60, 60),$$

$$\vec{P}_1(x_1, y_1) = (10, 60),$$

$$\vec{P}_2(x_2, y_2) = (10, 10), \quad \vec{P}_3(x_3, y_3) = (60, 10)$$



Step 2. Equation(s) for all the Boundary Line

Line 1: By \vec{P}_0, \vec{P}_1

Line 2: .. \vec{P}_1, \vec{P}_2

Line 3: .. \vec{P}_2, \vec{P}_3

Line 4: \vec{P}_3, \vec{P}_0

$\text{mod}(3) \rightarrow$ Note for C/C++ code

$$\overrightarrow{P} = \overrightarrow{P}_i + \lambda (\overrightarrow{P}_{i+1} - \overrightarrow{P}_i)$$

for line 1, 2, ..., 3.

Note: Based Line 1, 2, ..., 3

Generate New Set of Points

to form a set of Lines,

Line 1 @ One Level Higher

Line 2

Line 3

Line 4


Therefore, Eqn (1) now becomes

$$\overrightarrow{P}_{i+1}^j = \overrightarrow{P}_i^j + \lambda (\overrightarrow{P}_{i+1}^j - \overrightarrow{P}_i^j)$$

for $j=0$.

Note!

for $i=0$



$$\overrightarrow{P}_0^j = \overrightarrow{P}_0 + \lambda (\overrightarrow{P}_1 - \overrightarrow{P}_0) \Big|_{\lambda=0.2}$$

Due to the Design Consider Part II.
in Fig 3, PP.13

Build A Tree \rightarrow Forest

From the given Condition

$$\overrightarrow{P}_0 = (60, 60), \overrightarrow{P}_1 = (10, 60)$$

Note $\overrightarrow{P}_0(60, 60), \overrightarrow{P}_1(10, 60)$

$$\begin{aligned} \dots (1) \quad (x_0^j, y_0^j) &= (60, 60) + 0.2((10, 60) \\ &\quad - (60, 60)) \\ &= (60, 60) + 0.2(-50, 0) \end{aligned}$$

From Eqn (5-b)

$$x_0^j = 60 + \lambda * (-50)$$

$$y_0^j = 60 + \lambda * 0$$

$$\begin{cases} x_0^j = 60 + 0.2 * (-50) \\ y_0^j = 60 + 0.2 * (0) \end{cases}$$

$$\begin{cases} x_0^j = 60 + 0.2 * (-50) \\ y_0^j = 60 + 0.2 * (0) \end{cases}$$

Project 1. Due 2nd
Midterm March
24 (W)


CMPE240 March 8.

Project 1. 2D Screen
Saver Due 2 weeks
from today, 2nd.
(CANVAS)

Midterm ON March 24
(Wed)

2D Vector Transformation

Example: Give a set of Vertices

 $P_i(x_i, y_i)$ Before $P_i'(x'_i, y'_i)$ After


$$\begin{matrix} x'_i \\ y'_i \end{matrix} \stackrel{?}{=} \begin{matrix} x_i \\ y_i \end{matrix} + \begin{matrix} \Delta x \\ \Delta y \end{matrix} \dots (1)$$

After Before


$$y'_i = y_i + \Delta y \dots (2)$$

$$\begin{pmatrix} x'_i \\ y'_i \\ 1 \end{pmatrix} = \begin{pmatrix} 1 & 0 & \Delta x \\ 0 & 1 & \Delta y \\ 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} x_i \\ y_i \\ 1 \end{pmatrix} \dots (2*)$$

Dummy Dimension

 $\vec{P}_i(x_i, y_i)$ 

Note: $\alpha < 0$ for Clockwise Rotation
 $\alpha > 0$ for Counter Clockwise



$$\begin{pmatrix} x'_i \\ y'_i \\ 1 \end{pmatrix} = \begin{pmatrix} \cos\alpha & -\sin\alpha & 0 \\ \sin\alpha & \cos\alpha & 0 \\ 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} x_i \\ y_i \\ 1 \end{pmatrix}$$


After ... (3) Before

$$x'_i = r \cos(\alpha + \beta)$$

$$= r \cos\alpha \cos\beta - r \sin\alpha \sin\beta$$

$$= x_i \underline{\cos\alpha} - y_i \underline{\sin\alpha}$$

Scaling

 S_{3x3}

$$\begin{pmatrix} x'_i \\ y'_i \\ 1 \end{pmatrix} = \begin{pmatrix} s_x & 0 & 0 \\ 0 & s_y & 0 \\ 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} x_i \\ y_i \\ 1 \end{pmatrix}$$

$$\begin{aligned} x'_i &= s_x x_i + 0 \cdot y_i + 0 \cdot 1 \\ &= s_x x_i \end{aligned} \dots (4)$$

Project 1 (10pts), Part II. Build A

Tree

Step 1. Design | Select 2 Vertices (pts) \vec{P}_0, \vec{P}_1




Fig.4




Fig.5

$$\vec{P}_0(10,10), \vec{P}_1(10,30)$$




Fig.4b

Pre-process \rightarrow Rotation \rightarrow Post Processing
 (move \sim to match Eqn (3) (move it
 (0,0) — Origin) Back)

$$T_{3 \times 3}$$

$$R_{3 \times 3}$$

$$T_{3 \times 3}^{-1}$$

Step 2. Find New Vector @ Same Direction as the 1st One

$$\vec{P} = \vec{P}_0 + \lambda(\vec{P}_1 - \vec{P}_0) \dots (5)$$

Let $\lambda = 0.8$

$$\begin{pmatrix} x_i \\ y_i \\ 1 \end{pmatrix}_{\text{After}}^? = T_{3 \times 3}^{-1} R_{3 \times 3} T_{3 \times 3} \begin{pmatrix} x_i \\ y_i \\ 1 \end{pmatrix}_{\text{Before}} \dots (6)$$

ORDER!




Fig.5

$$T_{3 \times 3}(\Delta X, \Delta Y), \Delta X = -10, \Delta Y = -30$$

$$R_{3 \times 3}(\alpha), \alpha = \frac{\pi}{6}$$

Step 3. Rotation by $\alpha = \frac{\pi}{6}$
 in Both Directions

$$T_{3 \times 3}^{-1}(\Delta' X, \Delta' Y), \Delta' X = 10, \Delta' Y = 30$$



$$x_p = x_v + \frac{m}{2} \dots (7)$$

{
 ≈ Direction
 } Offset

Level > 7 Required;


No Recursive Calls Because it takes too much memory,
For-Loop, while-Loop

$$y_p = -y_v + \frac{N}{2} \dots (8)$$

(Half of the No. of Rows)

$$x_p = x_v + \frac{m}{2} \dots (7)$$

$$y_p = -y_v + \frac{N}{2} \dots (8)$$



SPI LCD ==

Physical


Design of
Virtual
Display

→ Mapping
→ Physical
Display

(x_v, y_v) for Virtual ~
 (x_p, y_p) for Physical ~

Mapping Function Example: Given 2 Vertices

(Vertices) $\vec{P}_0(10, 5), \vec{P}_1(10, 15)$



Find (1): $\vec{P}_1 = ?$ (2) Rotation
 $P_L^T, \vec{P}_{1L} = ?$

Sol: (1) Assume $\lambda = 0.8$

(Reduction of Tree Trunk By
80%)

$$\vec{P} = \vec{P}_0 + \lambda (\vec{P}_1 - \vec{P}_0)$$

Hence

$$\vec{P}'_1 = \vec{P}_0 + 1.8 (\vec{P}_1 - \vec{P}_0)$$

$$= (10, 5) + 1.8 ((10, 15) - (10, 5))$$

$$= (10, 5) + 1.8 (0, 10)$$

$$\therefore \vec{P}'_1 = (x'_1, y'_1) = (10, 5 + 18) = (10, 23)$$

(2) Rotation,

$$T_{\Sigma} = T^{-1} R T$$

where $T = \begin{pmatrix} 1 & 0 & \Delta X \\ 0 & 1 & \Delta Y \\ 0 & 0 & 1 \end{pmatrix}$ | $\Delta X = -10$
 $\Delta Y = -15$

And $R = \begin{pmatrix} \cos \alpha & -\sin \alpha & 0 \\ \sin \alpha & \cos \alpha & 0 \\ 0 & 0 & 1 \end{pmatrix}$ $\alpha = 30^\circ$

then $T^{-1} = \begin{pmatrix} 1 & 0 & -\Delta X \\ 0 & 1 & -\Delta Y \\ 0 & 0 & 1 \end{pmatrix}$ | $-\Delta X = 10$
 $-\Delta Y = 15$

$$T^{-1} R T$$

$$\begin{pmatrix} \cos \alpha & -\sin \alpha & 0 \\ \sin \alpha & \cos \alpha & 0 \\ 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} 1 & 0 & \Delta X \\ 0 & 1 & \Delta Y \\ 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} 1 & 0 & -\Delta X \\ 0 & 1 & -\Delta Y \\ 0 & 0 & 1 \end{pmatrix}$$

Reference pt \vec{P}_1
Starting. \vec{P}_1

$$\begin{pmatrix} \cos \alpha & -\sin \alpha & \Delta X \cdot \cos \alpha \\ \sin \alpha & \cos \alpha & \Delta Y \cdot \cos \alpha \\ 0 & 0 & 1 \end{pmatrix}$$

$$\begin{pmatrix} \cos \alpha & -\sin \alpha & \Delta X(\cos \alpha - \Delta Y \sin \alpha) \\ \sin \alpha & \cos \alpha & \Delta Y \sin \alpha + \Delta X \cos \alpha \\ 0 & 0 & 1 \end{pmatrix}$$

$$T^{-1} = \begin{pmatrix} 1 & 0 & -\Delta X \\ 0 & 1 & -\Delta Y \\ 0 & 0 & 1 \end{pmatrix}$$

$$= \begin{pmatrix} C & -S & \Delta X(C - \Delta Y S - \Delta X) \\ S & C & \Delta X S + \Delta Y C - \Delta Y \\ 0 & 0 & 1 \end{pmatrix}$$

M_{Σ}

Ch 8 P24

$$\begin{pmatrix} x'_i \\ y'_i \\ 1 \end{pmatrix} = M \Sigma \begin{pmatrix} x_i \\ y_i \\ 1 \end{pmatrix}$$

Before
After

$$\begin{pmatrix} x'_{i_L} \\ y'_{i_L} \\ 1 \end{pmatrix} = M \Sigma \begin{pmatrix} x'_i \\ y'_i \\ 1 \end{pmatrix}$$

21

Compute the mapping to find
(x'_i, y'_i) location on a physical
display device.

Sol: From eqn(7) & (8) on PP. 19,

$$\begin{cases} x_p = x_v + \frac{m}{2} \\ y_p = -y_v + \frac{n}{2} \end{cases} \dots (7)$$

$$\dots (8)$$

$$M = 1024, N = 768$$

Hence

$$\begin{cases} x_p = x_v + \frac{m}{2} \\ y_p = -y_v + \frac{n}{2} \end{cases} \quad m = 1024$$

$$= x_v + 512$$

$$x_{i_L} = \cos \theta x[i] - \sin \theta y[i]$$

$$+ \Delta x \cos \theta - \Delta y \sin \theta - \Delta x$$

Similarly for y'_{i_L} ,

$$y_{i_L} = \sin \theta x[i] + \cos \theta y[i]$$

$$+ \Delta x \sin \theta + \Delta y \cos \theta - \Delta y$$

Note: Work on
Virtual to physical
mapping

$$y_p = -y_v + \frac{768}{2}$$

$$\text{Similarly, } y_v = 235$$

$$y_p = -235 + \frac{768}{2}$$

Project 1 (10 pts)

Implementation of Part I.

2D Rotating Pattern

Example: Suppose we have a display
Device with Resolution
 1024×768 .

Suppose In our algorithm design
we have a pixel location
 $(x_i, y_i) = (127, 235)$


- a A set of Squares Rotation
with One Same Color
b Change location/Color/size

C

Keep the patterns, please
don't remove them!

Part II Once Part I is Done
Switch to Part I.


- a Breadth first




- b L>> C Create A patch of Forest
Changing Location/Size

Note: Please Don't freeze the
Drawing Till All the trees
are constructed.

Note: Report Writing.



{ GPP SPRs,
SPI SPRs. Solid Obj.
ITL, HS, Removal



March 15 (Monday)


Note: 1st midterm A week from
this Wednesday (March
24th)

2nd Smartphone (Cam Capability)
A piece of Paper to the
Class, Test the Environment

Ref: github : 2018F-114-
3D Graphics

Virtual Camera Location

1°



Right-Hand System,


2° Virtual Camera

a Virtual Enclosure


b Optic Lens (Pin Hole)

$\phi_d \approx b$ Very Small diameter

c Projection plane, the plane to form projected Image when light passing through the lens and reaches the projection plane.



3. Denote $E(x_e, y_e, z_e)$ as



Projection of $E(x_e, y_e, z_e)$ On to $X_w - Y_w$ Plane in the $X_w - Y_w - Z_w$ World Coordinate System

4. Viewer Coordinate System

Viewer ~ Virtual Camera

$X_e - Y_e - Z_e$ Viewer Coordinate System.

"Eye"

a $E(x_e, y_e, z_e)$ As the origin.


b Left-Hand System.

c Z_e -axis points to the origin.

5. Perspective Projection

Complex

24



3D Object formed on 2D plane

7. Transformation Pipeline


To Display 3D object(s) on to 2D LCD Display Screen,

W2V (World-2-Viewer)
Transform
Perspective Projection.

6. Perspective Projection \rightarrow @ the Virtual Camera in X_w - Y_w - Z_w , in X_e - Y_e - Z_e .

Objects in X_w - Y_w - $Z_w \rightarrow$ Viewer Coordinate System X_e - Y_e - Z_e

Projection Plane
form Perspective
Projection



3 parameters:

\hat{a} theta θ Angle

\hat{b} Vector E to D ,

"rho", Distance

Mathematical Formulation

1. Formula: Transformation $\stackrel{\text{def}}{=} \text{World-to-Viewer}$ Pipeline $\stackrel{\text{def}}{=}$ Transform

\hookrightarrow 2^o Foundation

\hookrightarrow a Translation

\hookrightarrow Rotations $\left\{ \begin{array}{l} \text{wrt } X_w \text{ and} \\ \dots \text{ w.r.t. } Y_w \\ \dots \text{ w.r.t. } Z_w \end{array} \right.$ wrt Arbitrary Axis

$\stackrel{\text{def}}{=} \text{Perspective Projection} \stackrel{\text{def}}{=} \text{Angle } \theta_w \text{ and } \phi_e \dots (1)$

World_2_Visitor

Competitivo

25

Transform, Map P_i from the World-coordinate to Viewer Coordinate.

$$\begin{pmatrix} x'_i \\ y'_i \\ z'_i \end{pmatrix} = T \begin{pmatrix} x_i \\ y_i \\ z_i \\ 1 \end{pmatrix}$$

After
 $x_w - y_w - z_w$

Before
 $x_w - y_w - z_w$

World to Viewer Transform.

March 17 (wed)
Topics : 1° Hardware Architecture 2° Software SPRs Init & Config.

Example: 2D & 3D F.T.
SPI I/F LCD Display to work with LPC1769.

GPIO(GPP) SPI
A set of b_n'

Per. Cont.
System Configuration PWR
CLK
Configuration of the Peripheral Cont. Multi-plexing

$$\begin{pmatrix} \sin\theta & \cos\theta & 0 & 0 \\ \cos\theta & \sin\theta & " & " \\ 0 & 0 & " & " \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

Part I.
"θ"

Conjunto to Rotation Matrix

$$\begin{pmatrix} \cos\theta & -\sin\theta & 0 \\ \sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

$$\begin{pmatrix} 0 & 0 & 0 & 0 \\ \cos\phi & \cos\phi & \sin\phi & " \\ \sin\phi & \sin\phi & -\cos\phi & " \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

Part II
"φ"

RTOS
Peripheral Controller { GPP
SPI }

SPI's SPR.

1. Naming Convention

LPC_SC → PCONP


2. Power Up the Selected Peripheral Controller By Setting the Corresponding.

$$\begin{pmatrix} - & - & - & P \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

roh

CmpE240

26



Tech Spec.

1° 8 bit Transfer,

$$CR\phi[3:\phi] = 0111 = 0x7$$

$$\& = \sim(3 \ll 20)$$

"AND" "11" "Negation, OD"

2° SPI

$$CR\phi[5:4] = 00 \text{ (SPI)}$$

3° Clock f_{SPI}

$$\cong CR\phi[15:8]$$

$$8 \text{ bits} \quad 255 = 2^8$$

Clear
2 Bits



Set 2 bits
as "01"

$$f = \frac{\text{PCLK}}{\text{SPI } (SCR+1) \text{ CPSDVSR}} \dots (1)$$

$$[0, 255]$$

Much harder.

Today's Topics :

1° Midterm Review

2° SPRs CR ϕ , CR λ
for SPI I/F

Ref:

1° CPU Datasheet.

PP431-433.

Note: $\begin{cases} CR\phi \\ CR\lambda \end{cases}$ LPC_SSP1 \rightarrow CR ϕ
Control Register

Tables 57 |



CR ϕ


2° Sample code

SPI_init(Draw a
Line)

Example: SSPC Source Code

Walk-Through: 15/-208

Line 162-165 PINSEL0



$$f_{\text{SPI}} = \frac{1 \times 10^6}{(7+1) * \text{DVR}}$$

To find f_{SPI} .

$$2^8 = 256, \text{ SCR } [0, 255]$$

PP. 433, CPSDVSR & [2, 254]

Midterm Review.

1° Video On, Mandatory.

a Submission to CANVAS
15 min. File Uploading

No Late Submission

After the Deadline

Paper will be disqualifed

b If CANVAS Disrupted,

then E-mail Submission

= file in "zip"

Line 173

$\text{CR} = 0x0707 \rightarrow$ Tech

(\rightarrow Spec.)

... ;0000;0111 ;0000;0111

fb upper
Bits all
zeros.

$\text{CR}[5:8]$ SCR $\text{CR}[5:4] = 00$ SPI
 Clock

$$f_{\text{SPI}} = \frac{\text{PCLK}}{(\text{SCR} + 1) * \text{DVR}}$$

$\text{CR}[5:8] = 0 \times 7$

FirstName + 4 Digits + CmPE240
SID mid.zip

2° 3 Questions ±

Hardware { CPU Block Diagram
Memory Map


SPRs.

CIC, SCH Design

$\text{CR1}[2] = 0$, Software: Coding
for "Master"

CmpE240

SPR → Binary Pattern
 Coding → for Init & Config
 Debugging Purpose
 Algorithm:
 2D Vector Graphics.
 G.F.
 Tech Spec.



= b Virtual v.s. physical
 = Display Transform.

$$\vec{P} = \vec{P}_i + \lambda (\vec{P}_{i+1} - \vec{P}_i)$$

Screen Saver. } i. Rotation!
 " " 2D Transforms
 " " w/o Rotation matrix

Composition of 2D Transform.

$$\begin{cases} R_{3 \times 3} \\ T_{3 \times 3} \end{cases} \rightarrow \text{Tree.}$$

Preprocess + $R_{3 \times 3}$ + Post ~

28

Formula: One Page Formula Sheet is allowed,
 However, No Example, or Verbal explanation is Not allowed,
 Submission of the formula page is required with your mid-term paper.
 No multiple choice question.

SCH: Requires All the pins needed in the design to have Label;

Wire: "Arrow" to indicate direction.

Block Diagram: wire(s), label(s) direction (Arrow)

CPU Datasheet will be provided

C Code program will be provided for Answering questions, or for Redesign.

Calculator is allowed ;