

CARNEGIE MELLON UNIVERSITY
COMPUTER SCIENCE DEPARTMENT
15-445/645 – DATABASE SYSTEMS (FALL 2021)
PROF. LIN MA

Homework #5 (by Preetansh Goyal and Joseph Koshakow)

Due: **Thursday Dec 2, 2021 @ 11:59pm**

IMPORTANT:

- **Upload this PDF** with your answers to **Gradescope by 11:59pm on Thursday Dec 2, 2021.**
- **Plagiarism:** Homework may be discussed with other students, but all homework is to be completed **individually**.
- **You have to use this PDF for all of your answers.**

For your information:

- Graded out of **120** points; **4** questions total

Revision : 2021/11/26 16:04

Question	Points	Score
Write-Ahead Logging	35	35
Replication	33	33
Two-Phase Commit	40	30
Miscellaneous	12	12
Total:	120	110

Question 1: Write-Ahead Logging.....[35 points]

Consider a DBMS using write-ahead logging with physical log records with the STEAL and NO-FORCE buffer pool management policy. Assume the DBMS executes a non-fuzzy checkpoint where all dirty pages are written to disk.

Its transaction recovery log contains log records of the following form:

<txnId, objectId, beforeValue, afterValue>

The log also contains checkpoint, transaction begin, and transaction commit records.

The database contains three objects (i.e., A, B, and C).

The DBMS sees records as in Figure 1 in the WAL on disk after a crash.

Assume the DBMS uses ARIES as described in class to recover from failures.

LSN	WAL Record
1	<T1 BEGIN>
2	<T1, A, 6, 7>
3	<T1, B, 42, 43>
4	<T2 BEGIN>
5	<T2, C, 33, 71>
6	<T1 COMMIT>
7	<T2, B, 43, 100>
8	<T3 BEGIN>
9	<T3, A, 7, 20>
10	<T2, B, 100, 67>
11	<CHECKPOINT>
12	<T3, A, 20, 42>
13	<T2, C, 71, 13>
14	<T2 COMMIT>
15	<T3, A, 42, 66>

Figure 1: WAL

(a) **[10 points]** What are the values of A, B, and C in the database stored on disk before the DBMS recovers the state of the database?

- ☐ A=6, B=100, C=71
- ☐ A=66, B=67, C=13
- ☐ A=7, B:Not possible to determine, C=43
- ☐ A=42, B=42, C=71
- ☐ A=20, B:43, C=Not possible to determine
- ☐ A=20, B:Not possible to determine, C=43
- ☐ A=20, B,C:Not possible to determine
- ☐ A:Not possible to determine, B=42 C=71
- ☒ A:Not possible to determine, B=67, C:Not possible to determine
- ☐ A,B,C:Not possible to determine

- (b) **[5 points]** What should be the correct action on T1 when recovering the database from WAL?
- ☒ do nothing to T1
 - ☐ redo all of T1's changes
 - ☐ undo all of T1's changes
- (c) **[5 points]** What should be the correct action on T2 when recovering the database from WAL?
- ☐ do nothing to T2
 - ☒ redo all of T2's changes
 - ☐ undo all of T2's changes
- (d) **[5 points]** What should be the correct action on T3 when recovering the database from WAL?
- ☐ do nothing to T3
 - ☐ redo all of T3's changes
 - ☒ undo all of T3's changes
- (e) **[10 points]** Assume that the DBMS flushes all dirty pages when the recovery process finishes. What are the values of A, B, and C after the DBMS recovers the state of the database from the WAL in Figure 1?
- ☐ A=6, B=42, C=33
 - ☐ A=66, B=67, C=13
 - ☐ A=6, B=100, C=13
 - ☒ A=7, B=67, C=13
 - ☐ A=20, B=42, C=71
 - ☐ A=42, B=100, C=33
 - ☐ A=7, B=100, C=71
 - ☐ A=42, B=67, C=13
 - ☐ A=20, B=43, C=33
 - ☐ A=66, B=43, C=71
 - ☐ A=42, B=42, C=13
 - ☐ Not possible to determine

Question 2: Replication.....[33 points]

Consider a DBMS using active-passive, master-replica replication with multi-versioned concurrency control. All read-write transactions go to the master node (NODE A), while read-only transactions are routed to the replica (NODE B). You can assume that the DBMS has “instant” fail-over and master elections. That is, there is no time gap between when the master goes down and when the replica gets promoted as the new master. For example, if NODE A goes down at timestamp ① then NODE B will be elected the new master at ②.

The database has a single table `foo(id, val)` with the following tuples:

id	val
1	x
2	y
3	z

Table 1: `foo(id, val)`

For each questions listed below, assume that the following transactions shown in Figure 2 are executing in the DBMS: (1) Transaction #1 on NODE A and (2) Transaction #2 on NODE B. You can assume that the timestamps for each operation is the real physical time of when it was invoked at the DBMS and that the clocks on both nodes are perfectly synchronized.

time	operation	time	operation
①	BEGIN;	②	BEGIN READ ONLY;
②	UPDATE foo SET val = 'xx';	③	SELECT val FROM foo WHERE id = 3;
③	UPDATE foo SET val = 'yyy' WHERE id = 3;	④	SELECT val FROM foo WHERE id = 1;
④	UPDATE foo SET val = 'zz' WHERE id = 1;	⑤	SELECT val FROM foo WHERE id = 1;
⑤	COMMIT;	⑥	COMMIT;

(a) Transaction #1 – NODE A

(b) Transaction #2 – NODE B

Figure 2: Transactions executing in the DBMS.

- (a) Assume that the DBMS is using *asynchronous* replication with *continuous* log streaming (i.e., the master node sends log records to the replica in the background after the transaction executes them). Suppose that NODE A crashes at timestamp ⑤ before it executes the COMMIT operation.

- i. **[10 points]** If Transaction #2 is running under READ COMMITTED, what is the return result of the `val` attribute for its SELECT query at timestamp ⑤? Select all that are possible.
- ☐ zz
 - ☒ x
 - ☐ y
 - ☐ yyy
 - ☐ z

- ☐ xx
☐ None of the above
- ii. **[10 points]** If Transaction #2 is running under the READ UNCOMMITTED isolation level, what is the return result of the val attribute for its SELECT query at timestamp ⑤? Select all that are possible.
- ☒ zz
☒ x
☐ y
☐ yyy
☐ z
☒ xx
☐ None of the above
- (b) **[13 points]** Assume that the DBMS is using *synchronous* replication with *on commit* propagation. Suppose that both NODE A and NODE B crash at exactly the same time at timestamp ⑥ after executing Transaction #1's COMMIT operation. You can assume that the application was notified that the Transaction #1 was committed successfully.
- After the crash, you find that NODE A had a major hardware failure and cannot boot. NODE B is able to recover and is elected the new master.
- What are the values of the tuples in the database when the system comes back online? Select all that are possible.
- ☐ { (1,x), (2,y), (3,z) }
☐ { (1,xx), (2,xx), (3,xx) }
☐ { (1,xx), (2,xx), (3,yyy) }
☒ { (1,zz), (2,xx), (3,yyy) }
☐ { (1,x), (2,xx), (3,z) }
☐ { (1,x), (2,xx), (3,xx) }
☐ None of the above

Question 3: Two-Phase Commit.....[40 points]

Consider a distributed transaction T operating under the two-phase commit protocol. Let N_0 be the *coordinator* node, and N_1, N_2, N_3 be the *participant* nodes.

The following messages have been sent:

time	message
1	N_0 to N_1 : “Phase1:PREPARE”
2	N_1 to N_0 : “OK”
3	N_0 to N_2 : “Phase1:PREPARE”
4	N_0 to N_3 : “Phase1:PREPARE”

Figure 3: Two-Phase Commit messages for transaction T

- (a) [10 points] Who should send a message next at time 5 in Figure 3? Select *all* the possible answers.

- ☐ N_0
☐ N_1
☒ N_2
☒ N_3
☐ It is not possible to determine

- (b) [10 points] To whom? Again, select *all* the possible answers.

- ☒ N_0
☐ N_1
☐ N_2
☐ N_3
☐ It is not possible to determine

- (c) [10 points] Suppose that N_0 received the “ABORT” response from N_2 at time 5 in Figure 3. What should happen under the two-phase commit protocol in this scenario?

- ☐ N_0 resends “Phase1:PREPARE” to N_2
☐ N_2 resends “OK” to N_0
☐ N_0 sends “Phase2:COMMIT” all of the participant nodes
☒ N_0 sends “ABORT” all of the participant nodes
☐ N_0 resends “Phase1:PREPARE” to all of the participant nodes
☐ It is not possible to determine

- (d) [10 points] Suppose that N_0 successfully receives all of the “OK” messages from the participants from the first phase. It then sends the “Phase2:COMMIT” message to all of the participants but N_1 and N_3 crash before they receives this message. What is the status of the transaction T when N_1 comes back on-line?

☐ T 's status is *aborted*



T 's status is *committed*



☒ It is not possible to determine

Question 4: Miscellaneous [12 points]

- (a) **[4 points]** With consistent hashing, if a node fails then all keys must be reshuffled among the remaining nodes.
- ☐ True
- ☒ False
- (b) **[4 points]** For a DBMS that uses ARIES, all updated pages must be flushed to disk for a transaction to commit.
- ☐ True
- ☒ False
- (c) **[4 points]** During the undo phase of ARIES, all transactions that committed after the last checkpoint are undone.
- ☐ True
- ☒ False