# Demo: SMART: Screen-based Gesture Recognition on Commodity Mobile Devices

Zimo Liao<sup>1</sup>, Zhicheng Luo<sup>2</sup>, Qianyi Huang<sup>2,5</sup>, Linfeng Zhang<sup>3</sup>, Fan Wu<sup>1</sup>, Qian Zhang<sup>4</sup>, Yi Wang<sup>2,5</sup>, Guihai Chen<sup>1</sup>

<sup>1</sup>Shanghai Jiao Tong University

<sup>2</sup>Southern University of Science and Technology <sup>3</sup>Tsinghua University <sup>4</sup>Hong Kong University of Science and Technology <sup>5</sup>Peng Cheng Laboratory

{zimo\_liao, wu-fan}@sjtu.edu.cn, zhichluo.chn@gmail.com, huangqy@sustech.edu.cn,

zhang-lf19@mails.tsinghua.edu.cn, qianzh@cse.ust.hk, wy@ieee.org, gchen@cs.sjtu.edu.cn

### **ABSTRACT**

In-air gesture control extends a touch screen and enables contactless interaction, thus has become a popular research direction in the past few years. Prior work has implemented this functionality based on cameras, acoustic signals, and Wi-Fi via existing hardware on commercial devices. However, these methods have low user acceptance. Solutions based on cameras and acoustic signals raise privacy concerns, while WiFi-based solutions are vulnerable to background noise. As a result, these methods are not commercialized and recent flagship smartphones have implemented in-air gesture recognition by adding extra hardware on-board, such as mmWave radar and depth camera. The question is, can we support inair gesture control on legacy devices without any hardware modifications?

In this demo, we design and implement *SMART*, an inair gesture recognition system leveraging the screen and ambient light sensor (ALS), which are ordinary modalities on mobile devices. We implement *SMART* on a tablet. Results show that *SMART* can recognize 9 types of frequently used in-air gestures with an average accuracy of 96.1%.

### **CCS CONCEPTS**

## - Human-centered computing $\rightarrow$ Human computer interaction (HCI); Gestural input.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

ACM MobiCom '21, January 31–February 4, 2022, New Orleans, LA, USA © 2022 Association for Computing Machinery. ACM ISBN 978-1-4503-8342-4/22/01...\$15.00 https://doi.org/10.1145/3447993.3511174




Figure 1: "Screen-Hand-ALS" light path. Light from screen is reflected by the hovering hand, and the ALS can sense the intensity of the reflected light. We analyze the received light signal and recognize different gesture.

#### **KEYWORDS**

Gesture recognition; visible light sensing; device-free;nonintrusive visible communication

### 1 INTRODUCTION

Gesture control is a natural and user-friendly way to interact with devices. It extends the traditional keyboard/touch screen and provides users with great freedom. In home scenarios, smart TV can be directly controlled with gestures, instead of using a remote controller; when driving, the driver can adjust the volume of music using simple gestures, which is less distracting than using touch screens or buttons. Besides, gesture control prevents our hands from physically touching any devices which may carry harmful viruses. This is of vital importance for devices in public areas.