

Serverless Machine Learning on Modern Hardware

IBM Research

#Res6SAIS


Serverless Computing



- No need to setup/manage a cluster
- Automatic, dynamic and fine-grained scaling
- Sub-second billing
- AWS Lambda, Google Cloud Functions, Azure Functions, Databricks Serverless


Challenge: Performance

Example:
Sorting 100GB



Challenge: Performance

Example:
Sorting 100GB




Challenge: Performance (2)

- **Scheduler:** when to best add/remove resources?
- **Container startup:** may have to dynamically spin up containers per function
- **Storage:** input data needs to be fetched from remote storage (e.g., S3)
 - As opposed to compute-local storage, e.g., HDFS
- **Data sharing:** intermediate needs to be temporarily stored on remote storage (S3, Redis)
 - Affects operations like shuffle, broadcast, etc.,

Challenge: Performance (2)

- **Scheduler:** when to best add/remove resources?
- **Container startup:** may have to dynamically spin up containers per function
- **Storage:** input data needs to be fetched from remote storage (e.g., S3)
 - As opposed to compute-local storage, e.g., HDFS
- **Data sharing:** intermediate needs to be temporarily stored on remote storage (S3, Redis)
 - Affects operations like shuffle, broadcast, etc.,

Example: MapReduce (Cluster)




data is mostly
written and
read locally

Serverless MapReduce

Dynamically
growing/shrinking
compute cloud



Map
Stage



Shuffle



Reduce
Stage




Storage Service
(e.g, S3, Redis)

data is
exclusively
written and
read remotely


I/O Overhead

Example:
Sorting 100GB




What about other workloads?

Example: SQL, Query 77 / TPC-DS benchmark



What about other workloads?


Example: SQL, Query 77 / TPC-DS benchmark



What about other workloads?

Example: Iterative ML (e.g., linear regression)


could be co-located
with worker nodes



What about other workloads?

Example: Iterative ML (e.g., linear regression)

could be co-located
with worker nodes




What about other workloads?

Example: Iterative ML (e.g., linear regression)

~~could be co-located
with worker nodes~~

Needs to be
remote



Can we..

- ..use Spark to run such workloads in a serverless fashion?
 - Dynamic scaling of compute nodes as jobs are running
 - No cluster configuration
 - No startup time
- ..reduce the performance overheads to a minimum?

Design Options

- **Scheduling:**

- Use serverless framework to schedule executors
- Use serverless framework to schedule tasks
- Enable Spark to dynamically scale up and down executors

- **Intermediate data:**

- Executors cooperate with scheduler to flush data remotely
- Consequently store all intermediate state remotely

Design Options

- **Scheduling:**

- Use serverless framework to schedule executors
- Use serverless framework to schedule tasks
- Enable Spark to dynamically scale up and down executors

High startup
Latency!

- **Intermediate data:**

- Executors cooperate with scheduler to flush data remotely
- Consequently store all intermediate state remotely

Design Options

- **Scheduling:**

- Use serverless framework to schedule executors
- Use serverless framework to schedule tasks
- Enable Spark to dynamically scale up and down executors



High startup
Latency!



Slow!

- **Intermediate data:**

- Executors cooperate with scheduler to flush data remotely
- Consequently store all intermediate state remotely

Design Options

- **Scheduling:**

- Use serverless framework to schedule executors
- Use serverless framework to schedule tasks
- Enable Spark to dynamically scale up and down executors

High startup
Latency!

Slow!

- **Intermediate data:**

- Executors cooperate with scheduler to flush data remotely
- Consequently store all intermediate state remotely

Design Options

- **Scheduling:**

- Use serverless framework to schedule executors
- Use serverless framework to schedule tasks

High startup
Latency!

Slow!

- Enable Spark to dynamically scale up and down executors

- **Intermediate data:**

- Executors cooperate with scheduler to flush data remotely
- Consequently store all intermediate state remotely

Complex!

Design Options

- **Scheduling:**

- Use serverless framework to schedule executors
- Use serverless framework to schedule tasks

High startup
Latency!

Slow!

- Enable Spark to dynamically scale up and down executors


- **Intermediate data:**

- Executors cooperate with scheduler to flush data remotely


Complex!

- Consequently store all intermediate state remotely


Architecture Overview




Architecture Overview




Architecture Overview




Architecture Overview




HCL Scheduler




HCL Scheduler




HCL Scheduler



HCL Scheduler



Example using ML and SQL



What about Performance?

- Workloads:
 - Deep learning (digit recognition) using Spark/Tensorflow, MNIST data set
 - SQL: TPC-DS
- Clusters:
 - 8 node cluster, 10Gb/s Ethernet
 - 8 node cluster, 100Gb/s RoCE
- Software
 - Spark2.3, Tensorflow 1.2

Conclusion

- Offering serverless to a wide range of workloads is challenging
 - Requires maintenance of state
 - Requires efficient decoupling of storage and compute
- Efficient scheduling and fast remote storage enable Spark to run in a serverless fashion
 -

Backup

Workloads and Frameworks

	Microservices	Workflows	MapReduce	SQL	ML
AWS λ, Google CF, Azure F					
AWS λ + AWS StepFunction					
PyWren					
Databricks Serverless					

Serverless frameworks not designed to run arbitrary workloads