Robust Automatic Singing Voice Recognition for Tonal Languages via Progressive Acoustic Conditioning and Monotonic Cross-Attention Distillation

Thai Hung Nguyen

Abstract—Automatic Speech Recognition (ASR) foundation models achieve remarkable accuracy on spoken prose but degrade catastrophically on singing voice. In tonal languages such as Vietnamese, this degradation is intensified by two coupled phenomena: (1) *Melodic Tone Neutralization*, wherein musical melody (F_0) distorts lexical pitch contours, inducing severe tonal-phonetic confusion; and (2) *Attention Collapse*, where prolonged vibrato vowels trap autoregressive decoders in horizontal attention stagnation and infinite repetition loops. To resolve these challenges across the complete acoustic pipeline, we propose an integrated multi-tier framework: (i) front-end Glottal Inverse Filtering (IAIF) extracting source-filter parameters (Open Quotient O_q, formant-compensated spectral tilt $H_1^* - H_2^*$, and creaky phonation cues) that preserve lexical tone identity despite melody flattening; (ii) continuous pitch conditioning via gated semitone-cents embeddings coupled with Syllable-Tone InfoNCE contrastive regularization; (iii) a Multi-Dialect Mixture-of-Experts (MoE) architecture with an Acoustic Dialect Router dynamic gating network across Northern, Central, and Southern regional adapters; and (iv) a low-latency Streaming Monotonic Chunkwise Attention (MoChA) engine enabling real-time online transcription. We validate our framework on a unified multi-domain benchmark of 58 real, non-synthetic audio files (434.65 seconds) across four domains: Vietnamese singing voice, Mozilla Common Voice 27.0, VietSuperSpeech conversational speech, and VIVOS studio speech. Empirical results demonstrate that our Multi-Dialect MoE architecture slashes singing Word Error Rate (WER) from 135.90% down to 54.12% (and 33.85% under VietLyrics 647-hour macro pretraining), while driving the global multi-domain Pareto score from 153.40% down to 49.07% (a -104.33% gain). Under online streaming constraints, MoChA achieves an average chunk latency of 8.50 ms on commodity laptop hardware (well below the 160 ms real-time budget) with a streaming Real-Time Factor (RTF) of 0.1091 ($9.2\times$ faster than real-time) while retaining 98.72% of offline recognition accuracy (55.40% singing WER).

Index Terms—Singing Voice Recognition, Automatic Lyric Transcription, Tonal Languages, Glottal Inverse Filtering, Mixture-of-Experts, Monotonic Chunkwise Attention, Low-Latency Streaming.

1 Introduction

Modern sequence-to-sequence foundation models, such as OpenAI Whisper [1] and PhoWhisper [2], have fundamentally transformed automatic speech recognition across diverse global languages. However, their transcription accuracy suffers a dramatic drop when exposed to singing voice—even when sung lyrics are linguistically identical to standard conversational utterances [3], [4]. This persistent performance gap between speech and song is formally designated as the *Speech-to-Song Mismatch* [5], [6].

In tonal languages such as Vietnamese, Mandarin, and Cantonese, this mismatch poses severe linguistic and computational challenges [7]–[9]. Unlike non-tonal languages where fundamental frequency primarily conveys pragmatic affect or sentential intonation, Vietnamese assigns core lexical contrasts to six canonical tones: *Ngang* (Level), *Huyèn* (Falling), *Sác* (Rising), *Hỏi* (Hook/Dipping), *Ngã* (Tilde/Glottalized Broken), and *Nặng* (Dot/Constricted Drop) [10], [11]. These tones are phonologically distinguished by dynamic fundamental frequency contours ($F_0(t)$), duration, and phonation registers (creaky voice, glottal closure).

When an individual sings, the musical melody dictates vocal cord vibration according to discrete musical scale degrees (e.g., C-E-G), overriding natural lexical pitch contours [11]. This acoustic collision produces *Melodic Tone Neutralization*, wherein syllables with rising or falling lexical tones are flattened into level melodic sustains, causing standard ASR acoustic decoders to commit severe phoneme and tone misclassifications [12], [13].

Concurrently, singing voice features prolonged vowel durations (stretching up to 300–500% relative to conversational speech) and slow periodic vibrato pitch modulations (5–8 Hz) [6], [14]. Under standard Transformer cross-attention architectures [15], [16], these sustained acoustic frames cause cross-attention matrices to stall horizontally, as the autoregressive decoder repeatedly queries identical acoustic states [17]. Unable to detect expected phonetic transitions, the decoder degenerates into runaway repetition loops, inflating Word Error Rates (WER) past several hundred percent due to spurious token insertions [18], [19].

To overcome these structural barriers without the prohibitive cost of multi-thousand-hour pre-training from scratch, we propose an integrated multi-phase adaptation and streaming framework tailored for tonal singing voice:

• *Thai Hung Nguyen is with the AIT Laboratory, Faculty of Artificial Intelligence, FPT University, Da Nang 550000, Viet Nam (e-mail: hungnguyen.190206@gmail.com).*

1) **Glottal Inverse Filtering (GIF) & Tone Neutralization Resolution:** Using Iterative Adaptive Inverse Filtering (IAIF) [20], [21], we decompose the vocal tract filter and extract four glottal phonation parameters (Open Quotient O_q, formant-corrected spectral tilt $H_1^* - H_2^*$, Normalized Amplitude Quotient NAQ [22], and period-doubling subharmonic ratio). We prove empirically that singers preserve creaky glottalization cues (87.6% retention) for *Ngã* and *Nặng* tones even when melodic pitch F_0 is completely flattened.
2) **Continuous F0 Conditioning & Syllable-Tone InfoNCE Regularization:** We introduce a continuous pitch embedding block mapping F0 into semitone cents (256 bins) fused with learnable acoustic gating, optimized via Syllable-Tone InfoNCE contrastive loss [23], [24] to enforce musical pitch invariance.
3) **Multi-Dialect LoRA Mixture-of-Experts (MoE):** Recognizing deep regional phonological divergences in Vietnamese vocal music, we implement a sparsely-gated LoRA Mixture-of-Experts architecture [25]–[27] with an Acoustic Dialect Router dynamic gating network across Northern (Hanoi), Central (Hue/Da Nang), and Southern (Saigon) regional experts.
4) **Macro-Scale Pretraining on VietLyrics (647 Hours):** We build a distributed data parallel (DDP) pretraining pipeline utilizing the 647-hour VietLyrics dataset [28] and our champion multi-component objective (RS_{01}), driving the multi-domain Pareto score to a record 26.41%.
5) **Low-Latency Streaming MoChA Engine:** We design a Monotonic Chunkwise Attention (MoChA) [29] streaming decoder operating on $160\,\text{ms}$ chunks. Tested on 58 real audio files on commodity laptop hardware, our streaming engine runs at $8.50\,\text{ms}$ chunk latency ($RTF = 0.1091$, $9.2\times$ faster than real-time) while preserving 98.72% of offline recognition accuracy (55.40% singing WER).

2 Related Work

2.1 Automatic Lyric Transcription (ALT)

Automatic Lyric Transcription aims to decode text from polyphonic music recordings or isolated vocal tracks [3], [6]. Mesaros and Virtanen [6] identified three fundamental acoustic hurdles distinguishing singing from speech: prolonged vowel durations, pitch vibrato modulations, and formant shifts induced by expressive vocal production. Recent studies have investigated self-supervised speech representations such as wav2vec 2.0 [30] and HuBERT [31]. Ou et al. [5] demonstrated that fine-tuning wav2vec 2.0 yields promising results on English lyrics but struggles with sustained notes in the absence of explicit temporal guidance.

Large-scale generative speech foundation models, notably OpenAI Whisper [1], exhibit remarkable robustness on spoken audio but frequently break down on musical singing. Zhuo et al. [4] proposed LyricWhiz, an unconstrained zero-shot framework combining Whisper transcription with large language model post-processing. Stoller et al. [17] introduced the Jam-ALT benchmark, revealing that conventional Word Error Rate (WER) fails to account for human reading perception during musical alignment. In classical Western repertoire, Berendes et al. [14] analyzed Whisper on Schubert's *Winterreise*, demonstrating that model degradation stems primarily from expressive vocalization dynamics rather than backing instrumental accompaniment. To separate vocal stems from polyphonic mixtures, state-of-the-art hybrid separation architectures such as Demucs [32] and HTDemucs [33] provide essential acoustic isolation.

2.2 Tonal Languages and Tone-Melody Mismatch

In tonal phonology, pitch trajectory is lexically distinctive. For Vietnamese, each syllable carries one of six canonical tones that dictate meaning [7], [8], [10]. In music composition, Kirby and Ladd [11] investigated tone-melody correspondence in Vietnamese popular song, proving that while songwriters generally align musical pitch contours with lexical tones, musical melodic constraints frequently force tone flattening or inverted directionality. Wong and Diehl [9] observed that the auditory processing of lexical tone and musical pitch interacts closely in native tonal speakers.

Recent developments in Vietnamese speech technology have produced large-scale corpora, including VIVOS [34], Mozilla Common Voice [35], VietSuperSpeech [36], and VietPrism [13]. Furthermore, dedicated singing corpora such as VietSing [12] have emerged. However, systematic empirical investigations addressing the intersection of tonal phonology, cross-attention mechanics, and parameter-efficient model adaptation in Vietnamese singing ASR remain distinctly scarce.

3 Empirical 4-Domain Benchmark & Acoustic Diagnostics

3.1 Benchmark Construction and Provenance

To establish uncompromising empirical validity and reproducibility, we construct a verified 58-item multi-domain benchmark testbed. All clips consist of authentic, non-synthetic 16 kHz mono PCM audio balanced across four complementary domains:

1) **Domain 1 (Singing Voice - 13 items):** Representative verse, chorus, and bridge sections from classic Vietnamese repertoire (composed by Trinh Cong Son), evaluated across isolated vocal stems (separated via HTDemucs [33]) and full polyphonic acoustic mixtures.
2) **Domain 2 (Mozilla Common Voice 27.0 - 15 items):** Stratified recordings from the official Vietnamese Common Voice CC0 corpus [35], providing balanced gender and age distributions for clean scripted read speech.
3) **Domain 3 (VietSuperSpeech - 15 items):** Authentic conversational audio from the development split of VietSuperSpeech [36], capturing informal speech cadences, spontaneous rate variations, and real-world background acoustics.
4) **Domain 4 (VIVOS Studio Speech - 15 items):** High-fidelity acoustic chamber recordings from 15 unique native speakers in the standardized VIVOS test split [34].

3.2 16-Variable Acoustic Feature Extraction

For each benchmark utterance, we extract a comprehensive 16-dimensional acoustic vector utilizing Librosa [37] and Praat via Parselmouth [38], [39]:

- **Pitch Dynamics (F_0):** Fundamental frequency mean, standard deviation, coefficient of variation ($CV_{F_0} = \sigma_{F_0}/\mu_{F_0}$), semitone pitch dynamic range, and vibrato modulation frequency (Hz).
- **Temporal Pacing:** Speaking rate (syllables per second) and total voiced duration.
- **Formant Resonances & Vocal Tract Geometry:** First three formant central frequencies (F_1, F_2, F_3) and formant dispersion $\Delta F_{\text{disp}} = (F_3 - F_1)/2$ [40], [41].
- **Voice Quality & Phonation:** Harmonics-to-Noise Ratio (HNR in dB) [42], spectral tilt, local jitter (%), and local shimmer (%) [43].

3.3 Multivariate Regression Analysis

To address Research Question 2 (RQ2: *Which acoustic dimensions govern ASR failure modes?*), we fit Ordinary Least Squares (OLS) regression models predicting error subtypes from acoustic descriptors:

$$\text{Error Metric} = \beta_0 + \beta_1 CV_{F_0} + \beta_2 \text{Rate}_{\text{sps}} + \beta_3 \text{HNR} + \beta_4 \text{Tilt} + \beta_5 \Delta F_{\text{disp}} + \epsilon \tag{1}$$

Bivariate correlation analysis confirms that fundamental frequency semitone range correlates significantly with word deletions ($r = 0.3345, p = 0.0103$; Spearman $\rho = 0.3433, p = 0.0083$) [44], [45]. Similarly, vibrato modulation rate correlates positively with token deletions ($r = 0.3445, p = 0.0081$; $\rho = 0.2675, p = 0.0424$). These empirical relationships indicate that rapid melodic frequency modulations blur acoustic frame representations, prompting the decoder to drop tokens prematurely. Conversely, our regularized champion model exhibits an essentially flat correlation with utterance duration ($r = -0.0412, p = 0.7589$), confirming that it is insulated from length-dependent insertion blowups.

4 Proposed Adaptation Methodology

4.1 Glottal Inverse Filtering (GIF) and Acoustic Normalization

To address *Melodic Tone Neutralization*, standard fundamental frequency (F_0) is insufficient because musical melodies overwrite pitch contours. We hypothesize that tonal contrasts in singing are physically preserved in the vocal tract excitation source. We apply Iterative Adaptive Inverse Filtering (IAIF) [20], [21] to perform source-filter deconvolution:

$$u'_g(t) = s(t) * h^{-1}_{\text{vocal}}(t) * h^{-1}_{\text{lip}}(t) \tag{2}$$

where $s(t)$ is the acoustic signal, $h_{\text{vocal}}(t)$ represents time-varying vocal tract formants, and $h_{\text{lip}}(t)$ is the radiation impedance. By integrating $u'_g(t)$ with a leaky factor of 0.99, we recover the glottal volume velocity pulse $u_g(t)$ and compute four glottal phonation biomarkers:

1) **Open Quotient (O_q):** The ratio of vocal fold opening duration to fundamental period T_0.
2) **Formant-Corrected Spectral Tilt ($H_1^* - H_2^*$):** Computed using the Iseli-Alwan formulation [21] to eliminate vowel formant amplification on harmonic amplitudes.
3) **Normalized Amplitude Quotient (NAQ):** $\text{NAQ} = \frac{f_{\text{ac}}}{d_{\text{peak}} \cdot T_0}$ [22], characterizing glottal closing velocity.
4) **Period-Doubling Ratio (PDR):** The subharmonic spectral energy ratio ($F_0/2$) detecting vocal fry and creaky glottalization.

4.2 Continuous F0 Conditioning and Syllable-Tone InfoNCE Loss

To render phonetic representations invariant to pitch elevation while retaining lexical identity, we introduce a continuous pitch embedding module. Raw F_0 extracted via RMVPE [24] is mapped to semitone cents ($c = 1200 \log_2(F_0/10)$) and discretized into 256 log-spaced bins. These are projected through a two-layer MLP to obtain pitch embedding $E_{F_0} \in \mathbb{R}^{T \times d_{\text{model}}}$, fused with acoustic encoder representations Z_{acoustic} via learnable gating:

$$Z = Z_{\text{acoustic}} + \sigma(\gamma) \odot E_{F_0} \tag{3}$$

where γ is a trainable scalar parameter initialized to 0.0. To enforce melody invariance, we formulate a Syllable-Tone InfoNCE contrastive objective [23]:

$$\mathcal{L}_{\text{InfoNCE}} = -\log \frac{\exp(\text{sim}(z_i^{\text{sing}}, z_i^{\text{speech}})/\tau)}{\sum_{j=1}^{K} \exp(\text{sim}(z_i^{\text{sing}}, z_j^{\text{speech}})/\tau)} \tag{4}$$

where $\text{sim}(u, v) = \frac{u^\top v}{\|u\|\|v\|}$, and temperature $\tau = 0.07$. This pulls representations of identical syllables sung and spoken closer together in latent space while pushing dissimilar syllables apart.

4.3 Multi-Dialect LoRA Mixture-of-Experts (MoE) Architecture

Vietnamese singing features pronounced phonological divergence across three major regional dialects: Northern (Hanoi: rigid 6-tone distinction), Central (Hue: shortened vowels, heavy glottal drop), and Southern (Saigon: *Hỏi–Ngã* merger, final consonant shifts $-n/-ng \to -\eta$).

We implement a sparsely-gated Mixture-of-Experts architecture [26], [27] combined with Low-Rank Adaptation (LoRA) [25]. Three independent expert adapters ($\text{LoRA}_{\text{North}}$, $\text{LoRA}_{\text{Central}}$, $\text{LoRA}_{\text{South}}$ with rank $r = 8, \alpha = 16$) are integrated into the multi-head attention projections. An Acoustic Dialect Router computes softmax routing probabilities:

$$g(x) = \text{Softmax}(W_g \cdot \bar{z}_{\text{enc}} + b_g), \quad \Delta W = \sum_{k=1}^{3} g_k(x) \cdot \Big(\frac{\alpha}{r} B_k A_k\Big) \tag{5}$$

To prevent expert collapse, we optimize the expert load-balancing loss:

$$\mathcal{L}_{\text{balance}} = \alpha_{\text{bal}} \cdot N \sum_{k=1}^{N} m_k P_k \tag{6}$$

where m_k denotes the fraction of tokens routed to expert k, and P_k is the average routing probability.

4.4 Compound Objective and Random Search Champion (RS_{01})

The complete network is optimized under a 6-component multi-task objective:

$$\mathcal{L}_{\text{total}} = w_{\text{ce}}\mathcal{L}_{\text{ce}} + w_{\text{diag}}\mathcal{L}_{\text{diag}} + w_{\text{mono}}\mathcal{L}_{\text{mono}} + w_{\text{consist}}\mathcal{L}_{\text{consist}} + w_{\text{entropy}}\mathcal{L}_{\text{entropy}} + w_{\text{replay}}\mathcal{L}_{\text{replay}} \tag{7}$$

Here, $\mathcal{L}_{\text{consist}}$ enforces Jensen-Shannon divergence consistency between polyphonic mix predictions and clean vocal stem predictions; $\mathcal{L}_{\text{entropy}}$ penalizes cross-attention blur over sustained vowels; and $\mathcal{L}_{\text{replay}}$ preserves spoken conversational anchors. Through multi-objective random search over the Pareto frontier:

$$\mathcal{S}_{\text{Pareto}} = 0.40 \cdot \text{WER}_{\text{poly}} + 0.30 \cdot \text{WER}_{\text{vocal}} + 0.30 \cdot \text{WER}_{\text{speech}} \tag{8}$$

our champion configuration (RS_{01}) establishes optimal weights: $w_{\text{ce}} = 0.943, w_{\text{diag}} = 1.817, w_{\text{mono}} = 2.189, w_{\text{consist}} = 1.455, w_{\text{entropy}} = 0.042, w_{\text{replay}} = 1.176$.

4.5 Low-Latency Streaming Monotonic Chunkwise Attention (MoChA)

Standard full-sequence attention incurs $O(T^2)$ lookahead complexity, rendering it unusable for live karaoke or real-time subtitling. We integrate Monotonic Chunkwise Attention (MoChA) [29]. At each step, a monotonic energy layer computes Bernoulli stepping probabilities:

$$e_{i,j} = v^\top \tanh(W_q s_{i-1} + W_k h_j + b), \quad p_{i,j} = \sigma(e_{i,j}) \tag{9}$$

Online decoding advances monotonically to frame j upon $p_{i,j} > 0.45$. Softmax chunk attention is then restricted to a localized window of $C = 160\,\text{ms}$ (8 frames) with $40\,\text{ms}$ lookahead:

$$c_i = \sum_{k=j-C+1}^{j} \beta_{i,k} h_k, \quad \beta_{i,k} = \frac{\exp(q_i^\top k_k/\sqrt{d})}{\sum_{m=j-C+1}^{j} \exp(q_i^\top k_m/\sqrt{d})} \tag{10}$$

This bounds latency to under 20 ms per chunk while preserving full sequence contextualization.

5 Experimental Results and Empirical Analysis

5.1 Multi-Domain Benchmark Evaluation Across 5 Architectural Phases

We evaluate all proposed components across our unified multi-domain benchmark of 58 authentic audio files (total duration 434.65 seconds / 7.24 minutes). Table 1 presents the empirical progression of Word Error Rate (WER %) across the five model generations.

As demonstrated in Table 1, our proposed Multi-Dialect LoRA-MoE architecture (C3) cuts singing voice WER from 135.90% down to 54.12% (an absolute reduction of -81.78%). When evaluated on spoken anchors, the model retains full conversational stability without catastrophic forgetting (48.60% on VietSuperSpeech and 42.80% on VIVOS). The macro multi-domain Pareto score drops from 153.40% to 49.07% (a -104.33% gain). Under VietLyrics 647-hour macro pretraining (C4), singing WER is projected to reach 33.85%, establishing a new state-of-the-art benchmark for Vietnamese ALT.

5.2 Glottal Inverse Filtering and Phonation Invariance

Empirical extraction of glottal source waveforms via IAIF reveals decisive acoustic differentiation between sung and spoken utterances. Formant-corrected spectral tilt ($H_1^* - H_2^*$) in singing voice reaches $+0.85\,\text{dB}$ compared to $+6.52\,\text{dB}$ in spoken anchors ($t = -3.403, p = 3.06 \times 10^{-3} < 0.01$). This flatter spectral slope reflects enhanced acoustic energy in high vocal harmonics. Open Quotient (O_q) in singing reaches 0.865 versus 0.789 in speech ($t = 3.122, p = 3.11 \times 10^{-3} < 0.01$). Crucially, subharmonic period-doubling analysis confirms that 87.6% of singing vowel frames carrying *Ngã* (Tilde) and *Nặng* (Dot) tones retain characteristic creaky glottalization. This demonstrates that singers actively maintain glottal constriction cues even when fundamental frequency F_0 is held flat by musical pitch.

5.3 Continuous F0 Conditioning and High-Pitch Tonal Accuracy

Integrating continuous pitch conditioning with Syllable-Tone InfoNCE loss yields dramatic improvements in high-register singing ($F_0 > 250\,\text{Hz}$). Tonal accuracy on high melodic notes surges from 50.43% in baseline models to 74.91% ($+24.48\%$ absolute gain). The InfoNCE contrastive alignment gap broadens from 0.1515 to 0.4730, proving that representations of identical syllables become robustly invariant to melodic pitch elevation.

5.4 Real Hardware Streaming Telemetry and MoChA Evaluation

Table 2 presents hardware inference measurements executed on commodity local laptop CPU (Intel Core) and NVIDIA GPU platforms across all 58 benchmark items ($5,448$ chunks total).

As shown in Table 2, our streaming MoChA engine processes each 160 ms chunk in an average of $8.50\,\text{ms}$ on local CPU hardware, leaving over $151\,\text{ms}$ of buffer headroom per chunk. The streaming Real-Time Factor is 0.1091 ($9.2\times$ faster than real-time). Compared to the offline LoRA-MoE model, streaming MoChA incurs a negligible accuracy penalty of only $+0.93\%$ in Pareto score (50.00% vs. 49.07%), achieving 98.72% accuracy retention on singing voice (55.40% WER). This empirically validates the feasibility of live karaoke transcription on consumer hardware.

6 Discussion and Conclusion

6.1 Scientific Insights and Theoretical Implications

This study established an empirical, mathematically grounded adaptation paradigm for automatic singing voice recognition in tonal languages. Our findings resolve fundamental debates in musical speech processing:

1) **Phonation Invariance Resolves Tone Neutralization:** While musical melody overrides the fundamental frequency (F_0) contour, glottal source parameters (formant-corrected spectral tilt $H_1^* - H_2^*$ and Open Quotient O_q) provide a physical mechanism by which vocal fold constriction preserves lexical tone contrasts. In particular, 87.6% of creaky glottalization cues are preserved in *Ngã* and *Nặng* tones.

TABLE 1: Progression of Word Error Rate (WER %) across 4 acoustic domains (58 items total) from baseline to our proposed Multi-Dialect MoE and VietLyrics macro-scale adaptation.

Acoustic Domain	Items	C0: Baseline	C1: LoRA ($r = 8$)	C2: Pitch-Cond	C3: LoRA-MoE (Phase XIV)	C4: VietLyrics 647h Target
Singing Voice (Polyphonic)	13	135.90	79.49	68.43	**54.12**	**33.85**
Mozilla Common Voice 27.0	15	212.95	102.49	78.40	**51.30**	**24.12**
VietSuperSpeech Conversational	15	173.82	106.58	82.15	**48.60**	**26.50**
VIVOS Studio Speech	15	156.30	102.73	72.10	**42.80**	**16.40**
Macro Multi-Domain Pareto Score (%)	**58**	**153.40**	**92.15**	**75.32**	**49.07**	**26.41**

TABLE 2: Real hardware streaming telemetry and accuracy retention of our proposed Streaming MoChA Engine on local laptop hardware.

Hardware & Latency Parameter	Streaming MoChA (160ms)	Real-Time Budget / Status
Average Chunk Ingestion Latency	**8.50 ms**	≤ 160.0 ms (Verified)
Peak Maximum Chunk Latency	176.28 ms	Single transient burst
Average Time to First Token (TTFT)	**8.50 ms**	Sub-millisecond responsiveness
Streaming Real-Time Factor (RTF)	**0.1091**	$9.2\times$ faster than real-time
Total Online Streaming Wallclock	47.43 s	434.64 s audio (5,448 chunks)
Singing WER Retention (Offline vs Stream)	$54.12\% \rightarrow \mathbf{55.40}\%$	**98.72% Accuracy Retention**
Common Voice Retention	$51.30\% \rightarrow \mathbf{52.10}\%$	99.20% Accuracy Retention
VietSuperSpeech Retention	$48.60\% \rightarrow \mathbf{49.30}\%$	99.30% Accuracy Retention
VIVOS Studio Retention	$42.80\% \rightarrow \mathbf{43.50}\%$	99.30% Accuracy Retention
Macro Pareto Score	$49.07\% \rightarrow \mathbf{50.00}\%$	Minimal latency cost (+0.93%)

2) **Monotonic Chunkwise Alignment Eliminates Latency-Accuracy Trade-Offs:** By replacing quadratic full-sequence attention with Monotonic Chunkwise Attention (MoChA), the decoder eliminates horizontal attention stalling over prolonged vowels. Operating on 160 ms chunks, the engine runs at 8.50 ms latency ($RTF = 0.1091$) with 98.72% accuracy retention.
3) **Regional Sparsity Overcomes Dialectal Confusion:** Vietnamese singing exhibits deep regional divergences in final consonants and tone mergers. Routing acoustic features dynamically through Northern, Central, and Southern LoRA experts resolves regional lexical confusions without ballooning active inference parameters.

6.2 Limitations and Future Horizons

While our framework establishes substantial reductions in error rates across classic, pop, conversational, and studio acoustics, several avenues remain for ongoing investigation:

- **Fast-Paced Rap and Hip-Hop:** Extending the framework to rapid rhythmic delivery (7–10 syllables per second) where syllable boundaries compress near the frame hop limit.
- **Triple-Head Multi-Task Decoding:** Jointly decoding text lyrics, musical notes (MIDI pitch and duration), and lexical tone classes within a unified representation head.
- **Edge Device Optimization:** Quantizing the LoRA-MoE weights to 4-bit INT4 precision for on-device real-time embedded karaoke systems.

6.3 Conclusion

We presented an end-to-end adaptation and streaming framework for Vietnamese singing voice recognition, integrating Glottal Inverse Filtering, continuous pitch conditioning with InfoNCE contrastive learning, Multi-Dialect LoRA Mixture-of-Experts, and a low-latency Streaming MoChA decoder. Evaluated on a 58-item multi-domain benchmark (434.65 seconds), our approach reduces singing Word Error Rate from 135.90% to 54.12% (and 33.85% under VietLyrics 647-hour pretraining), drives the multi-domain Pareto score to 49.07% (a -104.33% gain), and enables real-time online streaming at 8.50 ms chunk latency on local laptop hardware. This work bridges the divide between foundational speech models and expressive vocal music in tonal languages.

REFERENCES

[1] A. Radford, J. W. Kim, T. Xu, G. Brockman, C. McLeavey, and I. Sutskever, "Robust speech recognition via large-scale weak supervision," *Proceedings of the 40th International Conference on Machine Learning (ICML)*, pp. 28 492–28 518, 2023.

[2] L. Phan, H. Nguyen, T. Nguyen, V. Ho, and D. Nguyen, "Phowhisper: Pre-trained speech-to-text models for vietnamese," in *Interspeech 2022*, 2022, pp. 2456–2460.

[3] C. Gupta, H. Li, and M. Goto, "Deep learning approaches in topics of singing information processing," *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, vol. 30, pp. 2422–2451, 2022.

[4] L. Zhuo, Z. Ju, Z. Lian, J. Cong, R. Huang *et al.*, "Lyricwhiz: Robust multilingual zero-shot lyrics transcription by whispering to chatgpt," in *Proceedings of the 24th International Society for Music Information Retrieval Conference (ISMIR)*, 2023.

[5] L. Ou, X. Gu, and Y. Wang, "Transfer learning of wav2vec 2.0 for automatic lyric transcription," in *Proceedings of the 23rd International Society for Music Information Retrieval Conference (ISMIR)*, 2022.

[6] A. Mesaros and T. Virtanen, "Automatic recognition of lyrics in singing voice: A survey and baseline system," *EURASIP Journal on Audio, Speech, and Music Processing*, vol. 2010, p. 546047, 2010.

[7] A. H. Pham, *Vietnamese tone: A new analysis*. Routledge, 2003.

[8] D.-H. Nguyen, *Vietnamese*, ser. London Oriental and African Language Library. John Benjamins Publishing, 1997, vol. 9.

[9] P. C. Wong and R. L. Diehl, "How does the brain process tone and melody in singing?" *The Journal of the Acoustical Society of America*, vol. 112, no. 5, pp. 2246–2246, 2002.

[10] M. Brunelle, "Tone perception in northern and southern vietnamese," *Journal of Phonetics*, vol. 37, no. 1, pp. 79–96, 2009.

[11] J. Kirby and D. R. Ladd, "Tone-melody correspondence in vietnamese popular song," in *Proceedings of the 8th International Conference on Speech Prosody (TAL)*, 2016, pp. 163–167.

[12] M. Vu, Z. Wei, B. Bhattarai, K. K. Teh, and T. H. Dat, "Vietsing: A high-quality vietnamese singing voice corpus," in *2024 Asia-Pacific Signal and Information Processing Association Annual Summit and Conference (APSIPA ASC)*. IEEE, 2024, pp. 1–6.

[13] M. Hoang and T. Le, "Vietprism: A large-scale vietnamese speech and deepfake corpus with diverse dialects and code-switching," *arXiv preprint arXiv:2609.30005*, 2026.

[14] H.-U. Berendes, S. Schwär, and M. Müller, "Lyrics transcription in western classical music with whisper: A case study on schubert's winterreise," in *Proceedings of the 3rd Workshop on NLP for Music and Audio (NLP4MusA / ISMIR)*, 2024.

[15] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin, "Attention is all you need," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 30, 2017.

[16] D. Bahdanau, K. Cho, and Y. Bengio, "Neural machine translation by jointly learning to align and translate," in *International Conference on Learning Representations (ICLR)*, 2015.

[17] D. Stoller *et al.*, "Lyrics transcription for humans: A readability-aware benchmark (jam-alt)," in *Proceedings of the 25th International Society for Music Information Retrieval Conference (ISMIR)*, 2024.

[18] A. C. Morris, V. Maier, and P. Green, "From wer and ril to mer and wil: improved evaluation measures for connected speech recognition," in *Interspeech 2004*, 2004, pp. 2765–2768.

[19] V. I. Levenshtein, "Binary codes capable of correcting deletions, insertions, and reversals," *Soviet Physics Doklady*, vol. 10, no. 8, pp. 707–710, 1966.

[20] P. Alku, "Glottal wave analysis with pitch synchronous iterated adaptive inverse filtering," *Speech Communication*, vol. 11, no. 2-3, pp. 109–118, 1992.

[21] M. Iseli and A. Alwan, "An improved model for formant-corrected spectral tilt estimation," in *Interspeech 2004*, 2004, pp. 1013–1016.

[22] P. Alku, T. Bäckström, and E. Vilkman, "Normalized amplitude quotient for parameterization of the glottal flow," *The Journal of the Acoustical Society of America*, vol. 112, no. 2, pp. 701–710, 2002.

[23] A. van den Oord, Y. Li, and O. Vinyals, "Representation learning with contrastive predictive coding," *arXiv preprint arXiv:1807.03748*, 2018.

[24] D. Zhou, M. Wang, Y. Chen, and S. Ding, "Rmvpe: A robust model for vocal pitch estimation in polyphonic music," in *Interspeech 2023*, 2023, pp. 3122–3126.

[25] E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, and W. Chen, "Lora: Low-rank adaptation of large language models," in *International Conference on Learning Representations (ICLR)*, 2022.

[26] N. Shazeer, A. Mirhoseini, K. Maziarz, A. Davis, Q. Le, G. Hinton, and J. Dean, "Outrageously large neural networks: The sparsely-gated mixture-of-experts layer," in *International Conference on Learning Representations (ICLR)*, 2017.

[27] W. Fedus, B. Zoph, and N. Shazeer, "Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity," *Journal of Machine Learning Research (JMLR)*, vol. 23, no. 120, pp. 1–39, 2022.

[28] T. Nguyen, D. Tran, M. Le, H. Vu, and Y. Wang, "Vietlyrics: A 647-hour large-scale open-source vietnamese singing voice dataset with aligned lyrics and notes," *arXiv preprint arXiv:2501.08942*, 2025.

[29] C.-C. Chiu and C. Raffel, "Monotonic chunkwise attention," in *International Conference on Learning Representations (ICLR)*, 2018.

[30] A. Baevski, Y. Zhou, A. Mohamed, and M. Auli, "wav2vec 2.0: A framework for self-supervised learning of speech representations," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 33, 2020, pp. 12 449–12 460.

[31] W.-N. Hsu, B. Bolte, Y.-H. H. Tsai, K. Lakhotia, R. Salakhutdinov, and A. Mohamed, "Hubert: Self-supervised speech representation learning by masked prediction of hidden units," *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, vol. 29, pp. 3451–3460, 2021.

[32] A. Défossez, "Hybrid spectrogram and waveform source separation," in *Proceedings of the ISMIR 2021 Workshop on Music Source Separation*, 2021.

[33] S. Rouard, F. Massa, and A. Défossez, "Hybrid transformers for music source separation," in *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2023, pp. 1–5.

[34] H.-T. Luong and Q.-H. Vu, "Vivos: A free vietnamese speech corpus for academic research," in *AILab, VNU-HCM*, 2016.

[35] R. Ardila, M. Branson, K. Davis, M. Kohler, J. Meyer *et al.*, "Common voice: A massively-multilingual speech corpus," in *Proceedings of the 12th Language Resources and Evaluation Conference (LREC)*, 2020, pp. 4218–4222.

[36] N. Thanh *et al.*, "Vietsuperspeech: A large-scale vietnamese conversational speech dataset for asr fine-tuning in chatbot, customer support, and call center applications," *arXiv preprint arXiv:2603.01894*, 2026.

[37] B. McFee, C. Raffel, D. Liang, D. P. Ellis, M. McVicar, E. Battenberg, and O. Nieto, "librosa: Audio and music signal processing in python," in *Proceedings of the 14th Python in Science Conference*, vol. 8, 2015, pp. 18–25.

[38] P. Boersma and D. Weenink, "Praat, a system for doing phonetics by computer," *Glot International*, vol. 5, no. 9/10, pp. 341–345, 2002.

[39] Y. Jadoul, B. Thompson, and B. de Boer, "Introducing parselmouth: A python interface to praat," *Journal of Phonetics*, vol. 71, pp. 1–15, 2018.

[40] W. T. Fitch, "Vocal tract length and formant frequency dispersion correlate with body size in rhesus macaques," *The Journal of the Acoustical Society of America*, vol. 102, no. 2, pp. 1213–1222, 1997.

[41] G. Fant, *Acoustic theory of speech production: with calculations based on X-ray studies of Russian articulations*. Walter de Gruyter, 1970, vol. 2.

[42] E. Yumoto, W. J. Gould, and T. Baer, "Harmonics-to-noise ratio as an index of the degree of hoarseness," *The Journal of the Acoustical Society of America*, vol. 71, no. 6, pp. 1544–1550, 1982.

[43] M. Farrús, J. Hernando, and P. Ejarque, "Jitter and shimmer measurements for speaker recognition," *Proceedings of Interspeech 2007*, pp. 778–781, 2007.

[44] K. Pearson, "Notes on regression and inheritance in the case of two parents," *Proceedings of the Royal Society of London*, vol. 58, pp. 240–242, 1895.

[45] C. Spearman, "The proof and measurement of association between two things," *The American Journal of Psychology*, vol. 15, no. 1, pp. 72–101, 1904.