

3719 Warren Avenue · Bellwood, IL 60104 · 708 547-6644 · Fax 708 547-0687 · iac@intraaction.com

TO: **MIT**  
ATTN: **Jiahao Lyu <jhlyu@mit.edu>**  
PHONE:  
RE: **RFQ**

DATE: December 12, 2024  
FROM: Rainier Bravo  
PAGE 1 OF 1

| QUANTITY | MODEL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | PRICE EA.    |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| 1        | ATM-4001A1 MODULATOR<br>MATERIAL, TELLURIUM DIOXIDE<br>ANTIREFLECTION COATING, 440-700 NM<br>STATIC OPTICAL INSERTION LOSS, <4 PERCENT<br>CENTER FREQUENCY, 400 MHz<br>RF BANDWIDTH, +/- 50 MHz<br>ACTIVE APERTURE HEIGHT, 1 MM<br>OPTICAL RISE TIME, 151 NSEC / MM BEAM DIAMETER<br>DIFFRACTION EFFICIENCY, 80 PERCENT<br>RF DRIVE POWER, 0.6 WATT (461 NM, 400 MHz)<br>CONNECTOR, SMA<br>SIZE (LESS SMA), 0.63(16.0)H x 2.0(50.8)D x 0.9(22.9)W INCHES(MM)                                                                                                                                                             | US \$2241.64 |
| 1        | ATM-3501A1 MODULATOR / FREQUENCY SHIFTER<br>MATERIAL, TELLURIUM DIOXIDE<br>ANTIREFLECTION COATING, 440 - 700 NM<br>STATIC OPTICAL INSERTION LOSS, <6 PERCENT<br>CENTER FREQUENCY, 350 MHz<br>RF BANDWIDTH, +/-87 MHz<br>BEAM SEPARATION, 37.8 MRAD (461 NM, 350 MHz)<br>OPTICAL RISE TIME, 151 NSEC/MM BEAM DIAMETER<br>ACTIVE APERTURE HEIGHT, 1 MM<br>DIFFRACTION EFFICIENCY, 85 PERCENT<br>OPTICAL POLARIZATION FOR BEST EFFICIENCY, LINEAR/VERTICAL<br>RF DRIVE POWER, 1.2 WATTS (461 NM, 350 MHz)<br>INPUT IMPEDANCE, 50 OHMS<br>CONNECTOR, SMA<br>SIZE (LESS SMA), 0.63(16)H x 2.00(50.8)D x 0.9(22.9)W INCHES(MM) | US \$2241.64 |

NOTE: DUE TO ACOUSTIC ATTENUATION EFFECTS, FIRST ORDER DIFFRACTION EFFICIENCY CAN BE REDUCED AT FREQUENCIES ABOVE 350 MHz.

SHIPPING DATE: 10 - 12 WEEKS AFTER RECEIPT OF ORDER

**CANCELLATION:**

You may cancel your order within one week of order placement. In the event you elect to cancel this order, or any portion thereof, after the one-week period you may be charged for costs associated with material, either on order or in house, work in process, and finished goods inventory.

FOB POINT: BELLWOOD, IL

PAYMENT TERMS: **NET 30 DAYS**

THIS QUOTE IS IN EFFECT FOR 60 DAYS FROM THE ABOVE DATE.

QUOTATION FROM:  
**INTRAACTION CORP.**