

Map/Reduce Java Example

```
public class WordCount {

    public static class Map extends MapReduceBase implements
        Mapper<LongWritable, Text, Text, IntWritable> {
        private final static IntWritable one = new IntWritable(1);
        private Text word = new Text();

        public void map(LongWritable key, Text value, OutputCollector<Text, IntWritable>
            output, Reporter reporter) throws IOException {
            String line = value.toString();
            StringTokenizer tokenizer = new StringTokenizer(line);
            while (tokenizer.hasMoreTokens()) {
                word.set(tokenizer.nextToken());
                output.collect(word, one);
            }
        }
    }
}
```

```
public static class Reduce extends MapReduceBase implements
    Reducer<Text, IntWritable, Text, IntWritable> {
    public void reduce(Text key, Iterator<IntWritable> values, OutputCollector<Text,
        IntWritable> output, Reporter reporter) throws IOException {

        int sum = 0;
        while (values.hasNext()) { sum += values.next().get(); }
        output.collect(key, new IntWritable(sum));
    }
}
```

```
public static void main(String[] args) throws Exception {
    JobConf conf = new JobConf(WordCount.class);
    conf.setJobName("wordcount");
    conf.setOutputKeyClass(Text.class);
    conf.setOutputValueClass(IntWritable.class);
    conf.setMapperClass(Map.class);
    conf.setCombinerClass(Reduce.class);
    conf.setReducerClass(Reduce.class);
    conf.setInputFormat(TextInputFormat.class);
    conf.setOutputFormat(TextOutputFormat.class);
    FileInputFormat.setInputPaths(conf, new Path(args[0]));
    FileOutputFormat.setOutputPath(conf, new Path(args[1]));

    JobClient.runJob(conf);
}
```

How it looks like in Java

```
File Edit Options Buffers Tools Java Help
public class WordCount {
    public static class Map extends MapReduceBase implements
        Mapper<LongWritable, Text, Text, IntWritable> {
        private final static IntWritable one = new IntWritable(1);
        private Text word = new Text();

        public void map(LongWritable key, Text value, OutputCollector<Text, IntWritable>
            output, Reporter reporter) throws IOException {
            String line = value.toString();
            StringTokenizer tokenizer = new StringTokenizer(line);
            while (tokenizer.hasMoreTokens()) {
                word.set(tokenizer.nextToken());
                output.collect(word, one);
            }
        }

        public static class Reduce extends MapReduceBase implements
            Reducer<Text, IntWritable, Text, IntWritable> {
            public void reduce(Text key, Iterator<IntWritable> values, OutputCollector<Text,
                IntWritable> output, Reporter reporter) throws IOException {
                int sum = 0;
                while (values.hasNext()) { sum += values.next().get(); }
                output.collect(key, new IntWritable(sum));
            }
        }

        public static void main(String[] args) throws Exception {
            JobConf conf = new JobConf(WordCount.class);
            conf.setJobName("wordcount");
            conf.setOutputKeyClass(Text.class);
            conf.setOutputValueClass(IntWritable.class);
            conf.setMapperClass(Map.class);
            conf.setCombinerClass(Reduce.class);
            conf.setReducerClass(Reduce.class);
            conf.setInputFormat(TextInputFormat.class);
            conf.setOutputFormat(TextOutputFormat.class);
            FileInputFormat.setInputPaths(conf, new Path(args[0]));
            FileOutputFormat.setOutputPath(conf, new Path(args[1]));

            JobClient.runJob(conf);
        }
    }
}
```

Provide implementation for
Hadoop's Mapper abstract class

Map function

Provide implementation for
Hadoop's Reducer abstract class

Reduce function

Job configuration