

# Descriptive Statistics of the NRW80+ Dataset

Prof. Dr. Stephan Huber<sup>1,2</sup>

<sup>1</sup> Fresenius University of Applied Science

<sup>2</sup> Charlotte Fresenius University

## Abstract

In this paper, I illustrate the process of importing NRW80+ data (see Zank, Woopen, Wagner, Rietz, & Kaspar, 2022) into R. Additionally, I present descriptive statistics and graphical visualizations to gain insights into Likert-scaled surveys. The paper adheres to the APA style, implementing the R template provided by the ‘papaja’ package (Aust & Barth, 2023).

*Keywords:* papaja, NRW80+, descriptive statistics

Word count: 905

## Contents

<b>1</b>	<b>Technical Note</b>	<b>2</b>
<b>2</b>	<b>Import Data</b>	<b>4</b>
<b>3</b>	<b>How to Use the NRW80+ Data</b>	<b>5</b>
3.1	Load and Subset Data . . . . .	5
3.2	Get an Overview by Counting . . . . .	6
3.2.1	<code>table()</code> of R base . . . . .	6
3.2.2	<code>tabyl()</code> of <code>janitor</code> . . . . .	10
3.2.3	<code>frq()</code> of <code>sjmisc</code> . . . . .	12
3.3	First Summary Statistics . . . . .	16
3.3.1	Using <code>summary()</code> and <code>get_summary_stats()</code> . . . . .	16
3.3.2	Using <code>psych::describe()</code> . . . . .	18
3.3.3	Using <code>summarize()</code> and the <code>tidyverse</code> . . . . .	19

---

All files related to that paper are hosted on github. see: [https://github.com/hubchev/courses/tree/main/rmd/rmd\\_desc](https://github.com/hubchev/courses/tree/main/rmd/rmd_desc).

Correspondence concerning this article should be addressed to Prof. Dr. Stephan Huber, Im Mediapark 4e. E-mail: [stephan.huber@hs-fresenius.de](mailto:stephan.huber@hs-fresenius.de)

3.4	Make APA Tables using <code>apa_table()</code> . . . . .	19
3.5	Use the Likert Scale using <code>gglikert()</code> . . . . .	21
4	Cross-Referencing in R Markdown	26
	References	27

## 1 Technical Note

In the following, I load (and install) packages that I use later on and I show information about my R session with `sessionInfo()`.

```
# (Install and) load pacman package
if (!require(pacman)) install.packages("pacman")

# load packages that are already installed and install packages that are not
# installed yet and then load them:
pacman::p_load(tinylab,
               haven,
               labelled,
               janitor,
               skimr,
               rstatix,
               HH,
               likert,
               expss,
               tidyr,
               ggstats,
               psych,
               sjlabelled,
               sjmisc,
               tidyverse)

sessionInfo()
```

```
## R version 4.2.2 Patched (2022-11-10 r83330)
## Platform: x86_64-pc-linux-gnu (64-bit)
## Running under: Debian GNU/Linux 12 (bookworm)
##
## Matrix products: default
## BLAS:   /usr/lib/x86_64-linux-gnu/openblas-pthread/libblas.so.3
## LAPACK: /usr/lib/x86_64-linux-gnu/openblas-pthread/libopenblas-r0.3.21.so
##
## locale:
##  [1] LC_CTYPE=en_US.UTF-8      LC_NUMERIC=C
```

```
## [3] LC_TIME=en_US.UTF-8      LC_COLLATE=en_US.UTF-8
## [5] LC_MONETARY=en_US.UTF-8  LC_MESSAGES=en_US.UTF-8
## [7] LC_PAPER=en_US.UTF-8     LC_NAME=C
## [9] LC_ADDRESS=C             LC_TELEPHONE=C
## [11] LC_MEASUREMENT=en_US.UTF-8 LC_IDENTIFICATION=C
##
## attached base packages:
## [1] stats      graphics  grDevices  utils      datasets  methods   base
##
## other attached packages:
## [1] lubridate_1.9.3      forcats_1.0.0      stringr_1.5.1
## [4] dplyr_1.1.4          purrr_1.0.2        readr_2.1.4
## [7] tidbale_3.2.1        tidyverse_2.0.0    sjmisc_2.8.9
## [10] sjlabelled_1.2.0     psych_2.3.9        ggstats_0.5.1
## [13] tidyr_1.3.0          expss_0.11.6       maditr_0.8.3
## [16] likert_1.3.5         xtable_1.8-4       ggplot2_3.4.4
## [19] rstatix_0.7.2        skimr_2.1.5        janitor_2.2.0
## [22] labelled_2.12.0      haven_2.5.3        pacman_0.5.1
## [25] papaja_0.1.2         tinylabels_0.2.4   koRpus.lang.en_0.1-4
## [28] koRpus_0.13-8        sylly_0.1-6
##
## loaded via a namespace (and not attached):
## [1] nlme_3.1-163          matrixStats_1.1.0
## [3] insight_0.19.6        repr_1.1.6
## [5] tools_4.2.2           backports_1.4.1
## [7] utf8_1.2.4            R6_2.5.1
## [9] colorspace_2.1-0      withr_2.5.2
## [11] tidyselct_1.2.0       gridExtra_2.3
## [13] mnormt_2.1.1          emmeans_1.8.9
## [15] compiler_4.2.2        cli_3.6.1
## [17] htmlTable_2.4.1       sandwich_3.0-2
## [19] bookdown_0.36         bayestestR_0.13.1
## [21] scales_1.2.1          checkmate_2.3.0
## [23] mvtnorm_1.2-3         digest_0.6.33
## [25] rmarkdown_2.25        base64enc_0.1-3
## [27] pkgconfig_2.0.3       htmltools_0.5.7
## [29] fastmap_1.1.1         htmlwidgets_1.6.1
## [31] rlang_1.1.2           rstudioapi_0.15.0
## [33] generics_0.1.3        zoo_1.8-12
## [35] jsonlite_1.8.7        car_3.1-1
## [37] magrittr_2.0.3        parameters_0.21.3
## [39] Matrix_1.6-3          Rcpp_1.0.11
## [41] munsell_0.5.0         fansi_1.0.5
## [43] abind_1.4-5           lifecycle_1.0.4
## [45] stringi_1.8.2         multcomp_1.4-25
```

```
## [47] yaml_2.3.7                snakecase_0.11.1
## [49] carData_3.0-5             MASS_7.3-60
## [51] plyr_1.8.9                grid_4.2.2
## [53] parallel_4.2.2            lattice_0.22-5
## [55] splines_4.2.2             hms_1.1.3
## [57] knitr_1.45                pillar_1.9.0
## [59] estimability_1.4.1        effectsize_0.8.6
## [61] reshape2_1.4.4            codetools_0.2-19
## [63] glue_1.6.2                evaluate_0.23
## [65] data.table_1.14.8         tzdb_0.4.0
## [67] vctrs_0.6.4               gtable_0.3.4
## [69] datawizard_0.9.0          xfun_0.41
## [71] syllly.en_0.1-3           broom_1.0.5
## [73] coda_0.19-4               survival_3.5-7
## [75] wordcountaddin_0.3.0.9000 timechange_0.2.0
## [77] TH.data_1.1-2
```

## 2 Import Data

I host a R script on my GitHub account (see [https://raw.githubusercontent.com/hubchev/courses/main/scr/readin\\_GESIS.R](https://raw.githubusercontent.com/hubchev/courses/main/scr/readin_GESIS.R)) that explains how to import the NRW80+ data. You find the content of the script below. I have manually saved the data, `gesis.RData`, in a subfolder named `gesis.RData`.

```
# set working directory
setwd("/home/sthu/Dropbox/hsf/23-ws/ewa/")

# clear the environment
rm(list = ls())

# load packages
# install.packages("haven")
# install.packages("tidyverse")
library("haven")
library("tidyverse")

# Data manually downloaded from:
# Zank, Susanne, Wopen, Christiane, Wagner, Michael, Rietz, Christian, &
# Kaspar, Roman (2022). Quality of Life and Well-being of Very Old People in
# NRW (Representative Survey NRW80+) Cross-Section Wave 1. GESIS, Cologne.
# ZA7558 Data file Version 2.0.0, https://doi.org/10.4232/1.13978.

# All source data and information to the data can be found in the subfolder
# "source".
```

```
# unzip the ZA7558_v2-0-0.dta.zip and save it in data
unzip("source/ZA7558_v2-0-0.dta.zip", exdir = "data/.")

# read in the data
dfdta <- read_dta("data/ZA7558_v2-0-0.dta")
dfsav <- read_sav("source/ZA7558_v2-0-0.sav")

# check if both formats provide the same data
all.equal(dfdta, dfsav)

# --> this is NOT the case. The labels and missings are treated differently.

# save the environment
save.image(file="data/gesis.RData")
```

### 3 How to Use the NRW80+ Data

#### 3.1 Load and Subset Data

I load the data and select some variables that are of particular interest to me.

```
getwd()

## [1] "/home/sthu/Dropbox/hsf/23-ws/ewa/rmd_desc"

load("data/gesis.RData")

df <- dfdta |>
  select(starts_with("alter"),
         ALT_agegroup,
         ALT_sex,
         famst1, famst7,
         demtectcorr,
         kogstat,
         final,
         geschlecht)

# Remove the common prefix from all variables
df <- df |>
  mutate_all(~ set_label(., gsub("^Alternserleben: ", "", get_label(.))))
```

For simplification, let us focus on the questions that refer to the “Experience of Ageing” and create a new dataset `df_alter1` that contains only those questions:

```
df_alter1 <- df |>
  select(alter11,
         alter12,
         alter13,
         alter14,
         alter15,
         alter16,
         alter17,
         alter18,
         alter19,
         alter110) |>
  drop_unused_labels()

# to remove unused labels you can use drop_unused_labels():
df_alter1_un <- df_alter1 |>
  drop_unused_labels()

summary(df_alter1)
```

```
##      alter11      alter12      alter13      alter14
## Min.   :-2.000  Min.   :-2.000  Min.   :-2.000  Min.   :-2.000
## 1st Qu.: 1.000   1st Qu.: 2.000   1st Qu.: 1.000   1st Qu.: 2.000
## Median : 3.000   Median : 4.000   Median : 2.000   Median : 3.000
## Mean   : 2.656   Mean    : 3.282   Mean    : 2.349   Mean    : 2.763
## 3rd Qu.: 4.000   3rd Qu.: 4.000   3rd Qu.: 3.000   3rd Qu.: 4.000
## Max.    : 5.000   Max.    : 5.000   Max.    : 5.000   Max.    : 5.000
##      alter15      alter16      alter17      alter18
## Min.   :-2.00    Min.   :-2.000  Min.   :-2.000  Min.   :-2.000
## 1st Qu.: 2.00     1st Qu.: 2.000   1st Qu.: 2.000   1st Qu.: 1.000
## Median : 3.00     Median : 4.000   Median : 3.000   Median : 3.000
## Mean   : 2.99     Mean    : 3.405   Mean    : 3.237   Mean    : 2.712
## 3rd Qu.: 4.00     3rd Qu.: 5.000   3rd Qu.: 4.000   3rd Qu.: 4.000
## Max.    : 5.00     Max.    : 5.000   Max.    : 5.000   Max.    : 5.000
##      alter19      alter110
## Min.   :-2.000   Min.   :-2.000
## 1st Qu.: 2.000   1st Qu.: 1.000
## Median : 3.000   Median : 2.000
## Mean   : 2.969   Mean    : 2.305
## 3rd Qu.: 4.000   3rd Qu.: 3.000
## Max.    : 5.000   Max.    : 5.000
```

### 3.2 Get an Overview by Counting

**3.2.1 table() of R base.** With the `table()` function, you can count how many observations of each unique value a variable contains:

```
table(df_alter1$alter11)
```

```
##
## Weiß nicht Verweigert Gar nicht Ein wenig Mäßig Stark Sehr stark
##      80          6      390      266      451      511      159
```

To do that for each variable of a dataset is easy using `~`, the pipe operator, and `map()` of the package `purrr` (Wickham & Henry, 2023):

```
df_alter1 |>
  map(~ table(.))
```

```
## $alter11
## .
## Weiß nicht Verweigert Gar nicht Ein wenig Mäßig Stark Sehr stark
##      80          6      390      266      451      511      159
##
## $alter12
## .
## Weiß nicht Verweigert Gar nicht Ein wenig Mäßig Stark Sehr stark
##      36          4      196      245      379      648      355
##
## $alter13
## .
## Weiß nicht Verweigert Gar nicht Ein wenig Mäßig Stark Sehr stark
##      20          3      500      577      403      244      116
##
## $alter14
## .
## Weiß nicht Verweigert Gar nicht Ein wenig Mäßig Stark Sehr stark
##     122          8      222      260      527      543      181
##
## $alter15
## .
## Weiß nicht Verweigert Gar nicht Ein wenig Mäßig Stark Sehr stark
##     101          4      199      211      452      680      216
##
## $alter16
## .
## Weiß nicht Verweigert Gar nicht Ein wenig Mäßig Stark Sehr stark
##      19          3      149      324      358      537      473
##
## $alter17
```

```
## .
## Weiß nicht Verweigert Gar nicht Ein wenig Mäßig Stark Sehr stark
##      20          2        145        362        471        525        338
##
## $alterl8
## .
## Weiß nicht Verweigert Gar nicht Ein wenig Mäßig Stark Sehr stark
##      20          3        516        350        325        340        309
##
## $alterl9
## .
## Weiß nicht Verweigert Gar nicht Ein wenig Mäßig Stark Sehr stark
##      83          10       261        228        425        564        292
##
## $alterl10
## .
## Weiß nicht Verweigert Gar nicht Ein wenig Mäßig Stark Sehr stark
##      44          7       537        433        486        251        105
```

Using `proportions()` returns the conditional proportions:

```
df_alterl |>
  map(~ proportions(table(.)))
```

```
## $alterl1
## .
## Weiß nicht Verweigert Gar nicht Ein wenig Mäßig Stark
## 0.042941492 0.003220612 0.209339775 0.142780462 0.242082662 0.274288782
## Sehr stark
## 0.085346216
##
## $alterl2
## .
## Weiß nicht Verweigert Gar nicht Ein wenig Mäßig Stark
## 0.019323671 0.002147075 0.105206656 0.131508320 0.203435319 0.347826087
## Sehr stark
## 0.190552872
##
## $alterl3
## .
## Weiß nicht Verweigert Gar nicht Ein wenig Mäßig Stark
## 0.010735373 0.001610306 0.268384326 0.309715513 0.216317767 0.130971551
## Sehr stark
## 0.062265164
```



```

##
## $alterl4
## .
##   Weiß nicht   Verweigert   Gar nicht   Ein wenig   Mäßig   Stark
## 0.065485776 0.004294149 0.119162641 0.139559850 0.282877080 0.291465378
##   Sehr stark
## 0.097155126
##
## $alterl5
## .
##   Weiß nicht   Verweigert   Gar nicht   Ein wenig   Mäßig   Stark
## 0.054213634 0.002147075 0.106816962 0.113258186 0.242619431 0.365002684
##   Sehr stark
## 0.115942029
##
## $alterl6
## .
##   Weiß nicht   Verweigert   Gar nicht   Ein wenig   Mäßig   Stark
## 0.010198604 0.001610306 0.079978529 0.173913043 0.192163178 0.288244767
##   Sehr stark
## 0.253891573
##
## $alterl7
## .
##   Weiß nicht   Verweigert   Gar nicht   Ein wenig   Mäßig   Stark
## 0.010735373 0.001073537 0.077831455 0.194310252 0.252818035 0.281803543
##   Sehr stark
## 0.181427805
##
## $alterl8
## .
##   Weiß nicht   Verweigert   Gar nicht   Ein wenig   Mäßig   Stark
## 0.010735373 0.001610306 0.276972625 0.187869028 0.174449812 0.182501342
##   Sehr stark
## 0.165861514
##
## $alterl9
## .
##   Weiß nicht   Verweigert   Gar nicht   Ein wenig   Mäßig   Stark
## 0.044551798 0.005367687 0.140096618 0.122383253 0.228126677 0.302737520
##   Sehr stark
## 0.156736447
##
## $alterl10
## .

```

```
## Weiß nicht Verweigert Gar nicht Ein wenig Mäßig Stark
## 0.023617821 0.003757381 0.288244767 0.232420827 0.260869565 0.134728932
## Sehr stark
## 0.056360709
```

**3.2.2 tabyl() of janitor.** With `tabyl()` which is part of `janitor` (Firke, 2023), we can get both nicely:

```
df_alterl1 |>
  tabyl(alterl1)
```

```
## alterl1    n    percent
##      -2   80 0.042941492
##      -1    6 0.003220612
##       1  390 0.209339775
##       2  266 0.142780462
##       3  451 0.242082662
##       4  511 0.274288782
##       5  159 0.085346216
```

```
df_alterl1 |>
  map(~ tabyl(.))
```

```
## $alterl1
## .      n    percent
## -2   80 0.042941492
## -1    6 0.003220612
##  1  390 0.209339775
##  2  266 0.142780462
##  3  451 0.242082662
##  4  511 0.274288782
##  5  159 0.085346216
##
## $alterl2
## .      n    percent
## -2   36 0.019323671
## -1    4 0.002147075
##  1  196 0.105206656
##  2  245 0.131508320
##  3  379 0.203435319
##  4  648 0.347826087
##  5  355 0.190552872
##
```

```

## $alterl3
##   .   n   percent
##  -2  20 0.010735373
##  -1   3 0.001610306
##   1 500 0.268384326
##   2 577 0.309715513
##   3 403 0.216317767
##   4 244 0.130971551
##   5 116 0.062265164
##
## $alterl4
##   .   n   percent
##  -2 122 0.065485776
##  -1   8 0.004294149
##   1 222 0.119162641
##   2 260 0.139559850
##   3 527 0.282877080
##   4 543 0.291465378
##   5 181 0.097155126
##
## $alterl5
##   .   n   percent
##  -2 101 0.054213634
##  -1   4 0.002147075
##   1 199 0.106816962
##   2 211 0.113258186
##   3 452 0.242619431
##   4 680 0.365002684
##   5 216 0.115942029
##
## $alterl6
##   .   n   percent
##  -2  19 0.010198604
##  -1   3 0.001610306
##   1 149 0.079978529
##   2 324 0.173913043
##   3 358 0.192163178
##   4 537 0.288244767
##   5 473 0.253891573
##
## $alterl7
##   .   n   percent
##  -2  20 0.010735373
##  -1   2 0.001073537
##   1 145 0.077831455

```

```
## 2 362 0.194310252
## 3 471 0.252818035
## 4 525 0.281803543
## 5 338 0.181427805
##
## $alterl8
## . n percent
## -2 20 0.010735373
## -1 3 0.001610306
## 1 516 0.276972625
## 2 350 0.187869028
## 3 325 0.174449812
## 4 340 0.182501342
## 5 309 0.165861514
##
## $alterl9
## . n percent
## -2 83 0.044551798
## -1 10 0.005367687
## 1 261 0.140096618
## 2 228 0.122383253
## 3 425 0.228126677
## 4 564 0.302737520
## 5 292 0.156736447
##
## $alterl10
## . n percent
## -2 44 0.023617821
## -1 7 0.003757381
## 1 537 0.288244767
## 2 433 0.232420827
## 3 486 0.260869565
## 4 251 0.134728932
## 5 105 0.056360709
```

**3.2.3 frq() of sjmisc.** As the variables `df_alterl1` are factors. Thus, we can use the `sjmisc` package, see Lüdtke (2018) and the cheatsheet of `sjmisc` <http://strengjacke.de/sjmisc-cheatsheet.pdf>. Also worth a reading is `browseVignettes("sjmisc")`.

For example, we can use `frq()` for nice frequency tables:

```
df_alterl1 |>
  map(~ frq(. , show.na = T))
```

```
## $alterl1
```

```
## Beziehungen und andere Menschen mehr schätzen (x) <numeric>
```

```
## # total N=1863 valid N=1863 mean=2.66 sd=1.61
```

```
##
```

Value	Label	N	Raw %	Valid %	Cum. %
-2	Weiß nicht	0	0.00	0.00	0.00
-1	Verweigert	0	0.00	0.00	0.00
1	Gar nicht	80	4.29	4.29	4.29
2	Ein wenig	6	0.32	0.32	4.62
3	Mäßig	390	20.93	20.93	25.55
4	Stark	266	14.28	14.28	39.83
5	Sehr stark	451	24.21	24.21	64.04
6	<NA>	511	27.43	27.43	91.47
7	<NA>	159	8.53	8.53	100.00
<NA>	<NA>	0	0.00	<NA>	<NA>

```
##
```

```
## $alterl2
```

```
## Gesundheit mehr Aufmerksamkeit widmen (x) <numeric>
```

```
## # total N=1863 valid N=1863 mean=3.28 sd=1.45
```

```
##
```

Value	Label	N	Raw %	Valid %	Cum. %
-2	Weiß nicht	0	0.00	0.00	0.00
-1	Verweigert	0	0.00	0.00	0.00
1	Gar nicht	36	1.93	1.93	1.93
2	Ein wenig	4	0.21	0.21	2.15
3	Mäßig	196	10.52	10.52	12.67
4	Stark	245	13.15	13.15	25.82
5	Sehr stark	379	20.34	20.34	46.16
6	<NA>	648	34.78	34.78	80.94
7	<NA>	355	19.06	19.06	100.00
<NA>	<NA>	0	0.00	<NA>	<NA>

```
##
```

```
## $alterl3
```

```
## geistige Leistungsfähigkeit nimmt ab (x) <numeric>
```

```
## # total N=1863 valid N=1863 mean=2.35 sd=1.28
```

```
##
```

Value	Label	N	Raw %	Valid %	Cum. %
-2	Weiß nicht	0	0.00	0.00	0.00
-1	Verweigert	0	0.00	0.00	0.00
1	Gar nicht	20	1.07	1.07	1.07
2	Ein wenig	3	0.16	0.16	1.23
3	Mäßig	500	26.84	26.84	28.07
4	Stark	577	30.97	30.97	59.04

```

##      5 | Sehr stark | 403 | 21.63 | 21.63 | 80.68
##      6 |      <NA> | 244 | 13.10 | 13.10 | 93.77
##      7 |      <NA> | 116 | 6.23 | 6.23 | 100.00
## <NA> |      <NA> | 0 | 0.00 | <NA> | <NA>
##
## $alterl4
## mehr Erfahrung, um Dinge und Menschen einzuschätzen (x) <numeric>
## # total N=1863 valid N=1863 mean=2.76 sd=1.72
##
## Value |      Label |    N | Raw % | Valid % | Cum. %
## -----
##    -2 | Weiß nicht |    0 | 0.00 | 0.00 | 0.00
##    -1 | Verweigert |    0 | 0.00 | 0.00 | 0.00
##     1 | Gar nicht |  122 | 6.55 | 6.55 | 6.55
##     2 | Ein wenig |    8 | 0.43 | 0.43 | 6.98
##     3 |      Mäßig |  222 | 11.92 | 11.92 | 18.89
##     4 |      Stark |  260 | 13.96 | 13.96 | 32.85
##     5 | Sehr stark |  527 | 28.29 | 28.29 | 61.14
##     6 |      <NA> |  543 | 29.15 | 29.15 | 90.28
##     7 |      <NA> |  181 | 9.72 | 9.72 | 100.00
## <NA> |      <NA> |    0 | 0.00 | <NA> | <NA>
##
## $alterl5
## besseres Gefühl, was wichtig ist (x) <numeric>
## # total N=1863 valid N=1863 mean=2.99 sd=1.66
##
## Value |      Label |    N | Raw % | Valid % | Cum. %
## -----
##    -2 | Weiß nicht |    0 | 0.00 | 0.00 | 0.00
##    -1 | Verweigert |    0 | 0.00 | 0.00 | 0.00
##     1 | Gar nicht |  101 | 5.42 | 5.42 | 5.42
##     2 | Ein wenig |    4 | 0.21 | 0.21 | 5.64
##     3 |      Mäßig |  199 | 10.68 | 10.68 | 16.32
##     4 |      Stark |  211 | 11.33 | 11.33 | 27.64
##     5 | Sehr stark |  452 | 24.26 | 24.26 | 51.91
##     6 |      <NA> |  680 | 36.50 | 36.50 | 88.41
##     7 |      <NA> |  216 | 11.59 | 11.59 | 100.00
## <NA> |      <NA> |    0 | 0.00 | <NA> | <NA>
##
## $alterl6
## Einschränkung der Aktivitäten (x) <numeric>
## # total N=1863 valid N=1863 mean=3.40 sd=1.38
##
## Value |      Label |    N | Raw % | Valid % | Cum. %
## -----

```

```

##      -2 | Weiß nicht |    0 | 0.00 |    0.00 |    0.00
##      -1 | Verweigert |    0 | 0.00 |    0.00 |    0.00
##       1 | Gar nicht |   19 | 1.02 |    1.02 |    1.02
##       2 | Ein wenig |    3 | 0.16 |    0.16 |    1.18
##       3 |      Mäßig |  149 | 8.00 |    8.00 |   9.18
##       4 |      Stark |  324 | 17.39 |   17.39 |  26.57
##       5 | Sehr stark |  358 | 19.22 |   19.22 |  45.79
##       6 |      <NA> |  537 | 28.82 |   28.82 |  74.61
##       7 |      <NA> |  473 | 25.39 |   25.39 | 100.00
## <NA> |      <NA> |    0 | 0.00 |    <NA> |    <NA>
##
## $alterl7
## weniger Energie (x) <numeric>
## # total N=1863 valid N=1863 mean=3.24 sd=1.32
##
## Value |      Label |    N | Raw % | Valid % | Cum. %
## -----
##      -2 | Weiß nicht |    0 | 0.00 |    0.00 |    0.00
##      -1 | Verweigert |    0 | 0.00 |    0.00 |    0.00
##       1 | Gar nicht |   20 | 1.07 |    1.07 |    1.07
##       2 | Ein wenig |    2 | 0.11 |    0.11 |    1.18
##       3 |      Mäßig |  145 | 7.78 |    7.78 |    8.96
##       4 |      Stark |  362 | 19.43 |   19.43 |   28.40
##       5 | Sehr stark |  471 | 25.28 |   25.28 |   53.68
##       6 |      <NA> |  525 | 28.18 |   28.18 |   81.86
##       7 |      <NA> |  338 | 18.14 |   18.14 |  100.00
## <NA> |      <NA> |    0 | 0.00 |    <NA> |    <NA>
##
## $alterl8
## Abhängigkeit von der Hilfe Anderer (x) <numeric>
## # total N=1863 valid N=1863 mean=2.71 sd=1.53
##
## Value |      Label |    N | Raw % | Valid % | Cum. %
## -----
##      -2 | Weiß nicht |    0 | 0.00 |    0.00 |    0.00
##      -1 | Verweigert |    0 | 0.00 |    0.00 |    0.00
##       1 | Gar nicht |   20 | 1.07 |    1.07 |    1.07
##       2 | Ein wenig |    3 | 0.16 |    0.16 |    1.23
##       3 |      Mäßig |  516 | 27.70 |   27.70 |   28.93
##       4 |      Stark |  350 | 18.79 |   18.79 |   47.72
##       5 | Sehr stark |  325 | 17.44 |   17.44 |   65.16
##       6 |      <NA> |  340 | 18.25 |   18.25 |   83.41
##       7 |      <NA> |  309 | 16.59 |   16.59 |  100.00
## <NA> |      <NA> |    0 | 0.00 |    <NA> |    <NA>
##

```

```
## $alterl9
## Freiheit, Tage nach eigenem Willen zu verleben (x) <numeric>
## # total N=1863 valid N=1863 mean=2.97 sd=1.68
##
## Value |      Label |   N | Raw % | Valid % | Cum. %
## -----
##    -2 | Weiß nicht |   0 |  0.00 |   0.00 |   0.00
##    -1 | Verweigert |   0 |  0.00 |   0.00 |   0.00
##     1 | Gar nicht  |  83 |  4.46 |   4.46 |   4.46
##     2 | Ein wenig  |  10 |  0.54 |   0.54 |   4.99
##     3 | Mäßig     | 261 | 14.01 |  14.01 |  19.00
##     4 | Stark     | 228 | 12.24 |  12.24 |  31.24
##     5 | Sehr stark | 425 | 22.81 |  22.81 |  54.05
##     6 |      <NA> | 564 | 30.27 |  30.27 |  84.33
##     7 |      <NA> | 292 | 15.67 |  15.67 | 100.00
##    <NA> |      <NA> |   0 |  0.00 |   <NA> |   <NA>
##
## $alterl10
## Motivation fällt schwerer (x) <numeric>
## # total N=1863 valid N=1863 mean=2.31 sd=1.38
##
## Value |      Label |   N | Raw % | Valid % | Cum. %
## -----
##    -2 | Weiß nicht |   0 |  0.00 |   0.00 |   0.00
##    -1 | Verweigert |   0 |  0.00 |   0.00 |   0.00
##     1 | Gar nicht  |  44 |  2.36 |   2.36 |   2.36
##     2 | Ein wenig  |   7 |  0.38 |   0.38 |   2.74
##     3 | Mäßig     | 537 | 28.82 |  28.82 |  31.56
##     4 | Stark     | 433 | 23.24 |  23.24 |  54.80
##     5 | Sehr stark | 486 | 26.09 |  26.09 |  80.89
##     6 |      <NA> | 251 | 13.47 |  13.47 |  94.36
##     7 |      <NA> | 105 |  5.64 |   5.64 | 100.00
##    <NA> |      <NA> |   0 |  0.00 |   <NA> |   <NA>
```

### 3.3 First Summary Statistics

**3.3.1 Using `summary()` and `get_summary_stats()`.** First, I am interested in the class of the data and some very basic summary statistics.

```
summary(df)
```

```
##      alterl1      alterl2      alterl3      alterl4
## Min.    :-2.000  Min.    :-2.000  Min.    :-2.000  Min.    :-2.000
## 1st Qu.: 1.000   1st Qu.: 2.000   1st Qu.: 1.000   1st Qu.: 2.000
```



```

## Median : 3.000 Median : 4.000 Median : 2.000 Median : 3.000
## Mean : 2.656 Mean : 3.282 Mean : 2.349 Mean : 2.763
## 3rd Qu.: 4.000 3rd Qu.: 4.000 3rd Qu.: 3.000 3rd Qu.: 4.000
## Max. : 5.000 Max. : 5.000 Max. : 5.000 Max. : 5.000
##
## alterl5 alterl6 alterl7 alterl8
## Min. : -2.00 Min. : -2.000 Min. : -2.000 Min. : -2.000
## 1st Qu.: 2.00 1st Qu.: 2.000 1st Qu.: 2.000 1st Qu.: 1.000
## Median : 3.00 Median : 4.000 Median : 3.000 Median : 3.000
## Mean : 2.99 Mean : 3.405 Mean : 3.237 Mean : 2.712
## 3rd Qu.: 4.00 3rd Qu.: 5.000 3rd Qu.: 4.000 3rd Qu.: 4.000
## Max. : 5.00 Max. : 5.000 Max. : 5.000 Max. : 5.000
##
## alterl9 alterl10 alter_int alter_cont
## Min. : -2.000 Min. : -2.000 Min. : 80.00 Min. : 80.11
## 1st Qu.: 2.000 1st Qu.: 1.000 1st Qu.: 82.00 1st Qu.: 82.99
## Median : 3.000 Median : 2.000 Median : 86.00 Median : 86.59
## Mean : 2.969 Mean : 2.305 Mean : 86.48 Mean : 86.98
## 3rd Qu.: 4.000 3rd Qu.: 3.000 3rd Qu.: 90.00 3rd Qu.: 90.56
## Max. : 5.000 Max. : 5.000 Max. : 102.00 Max. : 102.92
## NA's :6 NA's :6
## alterl_m1 alterl_m2 alterp ALT_agegroup
## Min. : 1.000 Min. : 1.000 Min. : -4.000 Min. : 1.000
## 1st Qu.: 2.600 1st Qu.: 2.200 1st Qu.: -4.000 1st Qu.: 1.000
## Median : 3.200 Median : 2.800 Median : -4.000 Median : 2.000
## Mean : 3.168 Mean : 2.877 Mean : 2.632 Mean : 1.883
## 3rd Qu.: 3.800 3rd Qu.: 3.600 3rd Qu.: -4.000 3rd Qu.: 3.000
## Max. : 5.000 Max. : 5.000 Max. : 99.000 Max. : 3.000
## NA's : 16 NA's : 14
## ALT_sex famst1 famst7 demtectcorr
## Min. : 1.000 Min. : -1.000 Min. : -3.000 Min. : -11.000
## 1st Qu.: 1.000 1st Qu.: 1.000 1st Qu.: -3.000 1st Qu.: -1.000
## Median : 2.000 Median : 4.000 Median : 0.000 Median : 0.000
## Mean : 1.502 Mean : 2.765 Mean : -1.179 Mean : -1.742
## 3rd Qu.: 2.000 3rd Qu.: 4.000 3rd Qu.: 0.000 3rd Qu.: 0.000
## Max. : 2.000 Max. : 5.000 Max. : 1.000 Max. : 2.000
##
## kogstat final geschlecht
## Min. : -4.00 Min. : 81.00 Min. : 1.000
## 1st Qu.: -4.00 1st Qu.: 81.00 1st Qu.: 1.000
## Median : -4.00 Median : 81.00 Median : 2.000
## Mean : -3.21 Mean : 81.09 Mean : 1.502
## 3rd Qu.: -4.00 3rd Qu.: 81.00 3rd Qu.: 2.000
## Max. : 7.00 Max. : 82.00 Max. : 2.000
##

```

```
sumstat_alter <- df |>
  get_summary_stats(
    alterl1,
    alterl2,
    alterl3,
    alterl4,
    alterl5,
    alterl6,
    alterl7,
    alterl8,
    alterl9,
    alterl10,
    type = "five_number")

sumstat_alter
```

```
## # A tibble: 10 x 7
##   variable      n  min  max   q1 median   q3
##   <fct>    <dbl> <dbl> <dbl> <dbl>  <dbl> <dbl>
## 1 alterl1  1863   -2    5     1     3     4
## 2 alterl2  1863   -2    5     2     4     4
## 3 alterl3  1863   -2    5     1     2     3
## 4 alterl4  1863   -2    5     2     3     4
## 5 alterl5  1863   -2    5     2     3     4
## 6 alterl6  1863   -2    5     2     4     5
## 7 alterl7  1863   -2    5     2     3     4
## 8 alterl8  1863   -2    5     1     3     4
## 9 alterl9  1863   -2    5     2     3     4
## 10 alterl10 1863   -2    5     1     2     3
```

**3.3.2 Using `psych::describe()`.** A powerful alternative for descriptive summary statistics is provided by the function `describe()` of the `psych` package (William Revelle, 2023).

```
sumstat_alter_psych <- df |>
  select(starts_with("alterl")) |>
  psych::describe() |>
  as_tibble(rownames="Question") |>
  select(-skew, -kurtosis, -range, -vars)

sumstat_alter_psych
```

```
## # A tibble: 12 x 10
```

```
##      Question      n mean    sd median trimmed  mad   min   max    se
##      <chr>      <dbl> <dbl> <dbl>  <dbl>  <dbl> <dbl> <dbl> <dbl> <dbl>
##  1 alterl1     1863  2.66 1.61    3      2.76 1.48   -2    5 0.0374
##  2 alterl2     1863  3.28 1.45    4      3.43 1.48   -2    5 0.0336
##  3 alterl3     1863  2.35 1.28    2      2.28 1.48   -2    5 0.0296
##  4 alterl4     1863  2.76 1.72    3      2.96 1.48   -2    5 0.0398
##  5 alterl5     1863  2.99 1.66    3      3.20 1.48   -2    5 0.0385
##  6 alterl6     1863  3.40 1.38    4      3.54 1.48   -2    5 0.0321
##  7 alterl7     1863  3.24 1.32    3      3.33 1.48   -2    5 0.0306
##  8 alterl8     1863  2.71 1.53    3      2.68 1.48   -2    5 0.0355
##  9 alterl9     1863  2.97 1.68    3      3.14 1.48   -2    5 0.0389
## 10 alterl10    1863  2.31 1.38    2      2.28 1.48   -2    5 0.0321
## 11 alterl_m1   1847  3.17 0.829   3.2    3.21 0.890    1    5 0.0193
## 12 alterl_m2   1849  2.88 0.958   2.8    2.86 1.04    1    5 0.0223
```

**3.3.3 Using `summarize()` and the `tidyverse`.** As you may be aware, the `tidyverse` package provides powerful and flexible functions such as `filter`, `select`, `group_by`, and `summarize`. Here is an example demonstrating how these functions can be utilized to create descriptive statistic tables:

```
descriptives <- dfdata |>
  # filter(alterl1 > 0) |>
  group_by(geschlecht) |>
  summarize(
    Mean = mean(alterl1)
    , Count = n()
    , SD = sd(alterl1)
    , Min = min(alterl1)
    , Max = max(alterl1)
  )

descriptives
```

```
## # A tibble: 2 x 6
##   geschlecht   Mean Count    SD Min      Max
##   <dbl+lbl>   <dbl> <int> <dbl> <dbl+lbl> <dbl+lbl>
## 1 1 [Männlich]  2.71   927  1.50 -2 [Weiß nicht] 5 [Sehr stark]
## 2 2 [Weiblich]  2.60   936  1.72 -2 [Weiß nicht] 5 [Sehr stark]
```

### 3.4 Make APA Tables using `apa_table()`

The R output shown above might not meet publishable standards as it requires proper formatting, including a table with a caption and adherence to APA rules. To achieve this, the `apa_table()` function is recommended, and further details can be found in Aust and Barth (2020, sec. 4.2).

Table 1

*Summary Statistics: Experience of Ageing.*

variable	n	min	max	q1	median	q3
alterl1	1,863.00	-2.00	5.00	1.00	3.00	4.00
alterl2	1,863.00	-2.00	5.00	2.00	4.00	4.00
alterl3	1,863.00	-2.00	5.00	1.00	2.00	3.00
alterl4	1,863.00	-2.00	5.00	2.00	3.00	4.00
alterl5	1,863.00	-2.00	5.00	2.00	3.00	4.00
alterl6	1,863.00	-2.00	5.00	2.00	4.00	5.00
alterl7	1,863.00	-2.00	5.00	2.00	3.00	4.00
alterl8	1,863.00	-2.00	5.00	1.00	3.00	4.00
alterl9	1,863.00	-2.00	5.00	2.00	3.00	4.00
alterl10	1,863.00	-2.00	5.00	1.00	2.00	3.00

*Note.* This table contains all variables of ‘alterl\*’.

```
apa_table(
  sumstat_alter
  , caption = "Summary Statistics: Experience of Ageing."
  , note = "This table contains all variables of `alterl*`."
  , escape = TRUE
)
```

```
apa_table(
  sumstat_alter_psych
  , caption = "Summary Statistics: Experience of Ageing (psych)"
  , note = "This table contains all variables of `alterl*`."
  , escape = TRUE
)
```

```
apa_table(
  descriptives
  , caption = "Experience of Ageing: Valuing Relationships and Other People
  More (By Gender)"
  , escape = TRUE
)
```

Table 1 was created with the function `get_summary_stats()` of the `rstatix` package (Kassambara, 2023), Tables 2 and 4 were created with the function `describe()` of the `psych` package (William Revelle, 2023), and Table 3 was created with the function `summarize()` of the `dplyr` package (Wickham, François, Henry, Müller, & Vaughan, 2023).

Table 2

*Summary Statistics: Experience of Ageing (psych)*

Question	n	mean	sd	median	trimmed	mad	min	max	se
alterl1	1,863.00	2.66	1.61	3.00	2.76	1.48	-2.00	5.00	0.04
alterl2	1,863.00	3.28	1.45	4.00	3.43	1.48	-2.00	5.00	0.03
alterl3	1,863.00	2.35	1.28	2.00	2.28	1.48	-2.00	5.00	0.03
alterl4	1,863.00	2.76	1.72	3.00	2.96	1.48	-2.00	5.00	0.04
alterl5	1,863.00	2.99	1.66	3.00	3.20	1.48	-2.00	5.00	0.04
alterl6	1,863.00	3.40	1.38	4.00	3.54	1.48	-2.00	5.00	0.03
alterl7	1,863.00	3.24	1.32	3.00	3.33	1.48	-2.00	5.00	0.03
alterl8	1,863.00	2.71	1.53	3.00	2.68	1.48	-2.00	5.00	0.04
alterl9	1,863.00	2.97	1.68	3.00	3.14	1.48	-2.00	5.00	0.04
alterl10	1,863.00	2.31	1.38	2.00	2.28	1.48	-2.00	5.00	0.03
alterl_m1	1,847.00	3.17	0.83	3.20	3.21	0.89	1.00	5.00	0.02
alterl_m2	1,849.00	2.88	0.96	2.80	2.86	1.04	1.00	5.00	0.02

*Note.* This table contains all variables of ‘alterl\*’.

Table 3

*Experience of Ageing: Valuing Relationships and Other People More (By Gender)*

geschlecht	Mean	Count	SD	Min	Max
1	2.71	927	1.50	-2	5
2	2.60	936	1.72	-2	5

### 3.5 Use the Likert Scale using `gglikert()`

We have seen that the data contain not only the five different (Likert scaled) answers. Thus, let us remove all values that have, in one or multiple questions, no answer of the Likert scale. The cleaned dataset is named `df_alterl_balance`.

```
df_alterl_balance <- df_alterl %>%
  rowwise() %>%
  mutate(has_negative = ifelse(any(c(across(alterl1:alterl10)) < 0), 1, 0)) |>
  filter(has_negative == 0) |>
  select(starts_with("alter")) |>
  as_tibble()
```

Using the `gglikert()` of the `ggstats` package (Larmarange, 2023) allows us to draw nice graphs. I highly recommend reading the vignette of the package in the R documentation which you get with `vignette("gglikert")`.

Figures 1 and 3 shows the proportions of answers using `df_alterl` data and Figures 2

and 4 does so using the `df_alter1_balance` data whereby the latter to show the proportions stacked. Do you see any difference and can you explain the differences?

```
gglikert(df_alter1,
  exclude_fill_values = c("Weiß nicht", "Verweigert"),
  sort = "ascending"
)
```




Figure 1. Experience of Ageing: Proportions of Answers (`df_alter1`)

```
gglikert(df_alter1_balance,
  sort = "ascending"
)
```

```
gglikert_stacked(df_alter1,
  sort = "ascending",
  sort_method = "mean"
)
```




Figure 2. Experience of Ageing: Proportions of Answers (df\_alter1\_balance)




Figure 3. Experience of Ageing: Proportions of Answers - Stacked (df\_alter)

```
gglikert_stacked(df_alterl_balance,
  sort = "ascending",
  sort_method = "mean"
)
```




Figure 4. Experience of Ageing: Proportions of Answers - Stacked (df\_alterl\_balance)

As we are interested in the differences of the two samples, it makes sense to look at the summary statistics for the `df_alter_balance` sample. This is shown in Table 4.

```
sumstat_alter_psych_bal <- df_alterl_balance |>
  psych::describe() |>
  as_tibble(rownames="Question") |>
  select(-skew, -kurtosis, -range, -vars)

apa_table(
  sumstat_alter_psych_bal
  , caption = "Summary Statistics: Experience of Ageing - balanced (psych)"
  , note = "This table contains all variables of `alterl*` and only observations where all"
  , escape = TRUE
)
```



Table 4

*Summary Statistics: Experience of Ageing - balanced (psych)*

Question	n	mean	sd	median	trimmed	mad	min	max	se
alterl1	1,596.00	2.89	1.28	3.00	2.87	1.48	1.00	5.00	0.03
alterl2	1,596.00	3.44	1.22	4.00	3.55	1.48	1.00	5.00	0.03
alterl3	1,596.00	2.33	1.15	2.00	2.23	1.48	1.00	5.00	0.03
alterl4	1,596.00	3.16	1.16	3.00	3.20	1.48	1.00	5.00	0.03
alterl5	1,596.00	3.32	1.15	4.00	3.40	1.48	1.00	5.00	0.03
alterl6	1,596.00	3.38	1.26	4.00	3.46	1.48	1.00	5.00	0.03
alterl7	1,596.00	3.21	1.19	3.00	3.24	1.48	1.00	5.00	0.03
alterl8	1,596.00	2.66	1.43	2.00	2.57	1.48	1.00	5.00	0.04
alterl9	1,596.00	3.27	1.27	3.00	3.34	1.48	1.00	5.00	0.03
alterl10	1,596.00	2.35	1.17	2.00	2.26	1.48	1.00	5.00	0.03

*Note.* This table contains all variables of ‘alterl\*’ and only observations where all questions had been answered.

#### 4 Cross-Referencing in R Markdown

In adherence to the APA style guidelines (Association et al., 2022), it is imperative to reference all figures and tables by their respective numbers within the text. Avoid using generic phrases like “the table above” or “the figure below.” Additionally, refrain from hard-coding the numbers for a more dynamic and standardized approach. Xie, Dervieux, and Riederer (2023) explains concisely how to do that with R Markdown, see: <https://bookdown.org/yihui/rmarkdown-cookbook/cross-ref.html>.

For example, I can refer to Table 1 with `\@ref(tab:tabrstatix)` because I have specified the corresponding label in the R code-chunk, see:

```
```{r tabrstatix, echo=TRUE}
apa_table(
  sumstat_alter
  , caption = "Summary Statistics: Experience of Ageing."
  , note = "This table contains all variables of `alterl*`."
  , escape = TRUE
)
```
```

`\clearpage`

# Exercises

1. With `'knitr::purl("desc_NRW80.Rmd")'` you can extract the whole R code from the R Markdown file.
2. The dataset `'gesis.RData'` comes with two different tibbles: `'dfsav'` and `'dfdta'`. Is there a difference in the variables?
3. Check possible differences in the `'gglikert'` plots when using `'df_alterl_un'` instead of `'df_alterl'`.
4. The stats above show that dealing with missing or non-standard answers is a crucial thing when working with survey data.
5. The labels of the variables `'alterl1:alterl10'` have "Alternserleben: " at the beginning.

```
```r
# Remove the common prefix from all variables
df <- df |>
  mutate_all(~ set_label(., gsub("^Alternserleben: ", "", get_label(.))))
```

### References

- Association, A. P. et al. (2022). *Publication manual of the american psychological association*. : American Psychological Association.
- Aust, F., & Barth, M. (2020). *Papaja: Reproducible APA manuscripts with r markdown*. Retrieved from [https://frederikaust.com/papaja\\_man/](https://frederikaust.com/papaja_man/)
- Aust, F., & Barth, M. (2023). *papaja: Prepare reproducible APA journal articles with R Markdown*. Retrieved from <https://github.com/crsh/papaja>
- Firke, S. (2023). *Janitor: Simple tools for examining and cleaning dirty data*. Retrieved from <https://CRAN.R-project.org/package=janitor>
- Kassambara, A. (2023). *Rstatix: Pipe-friendly framework for basic statistical tests*. Retrieved from <https://CRAN.R-project.org/package=rstatix>
- Larmarange, J. (2023). *Ggstats: Extension to 'ggplot2' for plotting stats*. Retrieved from <https://CRAN.R-project.org/package=ggstats>
- Lüdtke, D. (2018). Sjmisc: Data and variable transformation functions. *Journal of Open Source Software*, 3(26), 754. <https://doi.org/10.21105/joss.00754>
- Wickham, H., François, R., Henry, L., Müller, K., & Vaughan, D. (2023). *Dplyr: A grammar of data manipulation*. Retrieved from <https://CRAN.R-project.org/package=dplyr>
- Wickham, H., & Henry, L. (2023). *Purrr: Functional programming tools*. Retrieved from <https://CRAN.R-project.org/package=purrr>
- William Revelle. (2023). *Psych: Procedures for psychological, psychometric, and personality research*. Evanston, Illinois: Northwestern University. Retrieved from <https://CRAN.R-project.org/package=psych>
- Xie, Y., Dervieux, C., & Riederer, E. (2023). *R markdown cookbook*. online. Retrieved from <https://bookdown.org/yihui/rmarkdown-cookbook/>
- Zank, S., Woopen, C., Wagner, M., Rietz, C., & Kaspar, R. (2022). *Quality of life and well-being of very old people in NRW (representative survey NRW80+) - cross-section wave 1*. GESIS, Cologne. ZA7558 Data file Version 2.0.0. <https://doi.org/10.4232/1.13978>