Academia Journal AcadXXXXXXXX

Research Article

Importance-Balanced Interleaved Feature Projection for Quantum-Inspired Variational Classifiers: A Controlled Study of Feature Allocation and Interaction Topology in Breast Cancer Diagnosis

Daksh Kaila[1,*], Monika Aggarwal[2], Samya Muhuri[1]

1 Thapar Institute of Engineering and Technology, Patiala, Punjab, India

2 Indian Institute of Technology Delhi, New Delhi, Delhi, India

* Correspondence: [dkaila_be25@thapar.edu]

Received: [Day Month Year] | Accepted: [Day Month Year] | Published: [Day Month Year]

Abstract

Introduction: Quantum-inspired variational classifiers must compress many continuous features into a small number of simulated qubit registers. How features are allocated across registers, and how the registers interact, are rarely examined under controlled conditions, so it is unclear which design choices actually drive performance.

Materials and methods: We study an Importance-Balanced Interleaved Projection (IBIP) strategy that ranks features on training data with XGBoost permutation importance and distributes them cyclically across qubits. A quantum-inspired variational classifier (classical non-linear projection followed by exact statevector simulation) was evaluated on the Wisconsin Diagnostic Breast Cancer (WDBC) dataset with five two-qubit and seven three-qubit interaction topologies, each under IBIP and sequential allocation, using matched seeds, five-fold cross-validation and paired statistics. The primary comparison was replicated over 20 seeds. A four-way ablation compared sequential, random, importance-blocked and IBIP allocation; six classical baselines and two external datasets (Parkinson's disease, Cleveland heart disease) provided context.

Results: On WDBC, sequential allocation, which places the mean, standard-error and worst-value descriptors on separate qubits, outperformed IBIP for the three-qubit CNOT-Star model (97.68% ± 1.15% vs. 96.62% ± 1.69% accuracy over 20 seeds; paired difference −1.05 points, 95% CI [−1.86, −0.25], $p = 0.013$), while ROC-AUC did not differ (0.9935 vs. 0.9922, $p = 0.455$). IBIP was more accurate than importance-blocked allocation on all three datasets (+1.03 to +8.20 points; significant for heart disease, $p = 0.009$). Under IBIP, no entangling topology outperformed the uncoupled circuit, whereas the cyclic CNOT-Ring reduced accuracy by about 14 points. After correcting an implementation error, iSWAP performed comparably to the other exchange gates (95.96%). The best quantum-inspired configuration (97.72%) matched, but did not exceed, an RBF-kernel SVM (97.72%).

Conclusions: In the tested two- and three-qubit configurations, feature allocation affected accuracy more than interaction topology; topology comparisons used five seeds and are exploratory. Concentrating top-ranked features in one register should be avoided. A semantically meaningful grouping that already

spreads informative features across registers, as in WDBC, performed best; interleaving is a reasonable default otherwise. Quantum-inspired models did not surpass classical baselines on these tabular tasks.

Keywords: Quantum-Inspired Machine Learning; Variational Quantum Classifier; Feature Allocation; Circuit Topology; Breast Cancer Diagnosis; Statistical Validation

1. Introduction

Breast cancer remains one of the leading causes of cancer-related mortality among women worldwide, and early, accurate diagnosis is essential for timely clinical intervention. Machine learning has been applied extensively to this problem, and classical models such as Support Vector Machines (SVMs) [1], Random Forests [5] and gradient boosting [6] achieve high accuracy on benchmark data such as the Wisconsin Diagnostic Breast Cancer (WDBC) dataset [24]. Understanding how alternative learning paradigms represent and process such features remains an active area of research.

Recent advances in quantum machine learning (QML) [2,3,7] have introduced variational quantum classifiers (VQCs) and quantum-inspired architectures built from parameterized rotations, interaction gates and expectation-value measurements [8–11]. On near-term processors and in classical simulation, these models use only a few qubits, so a high-dimensional feature vector must be compressed into a small number of registers. This creates a **feature allocation problem**: deciding which features feed which qubit. Many implementations assign features in their original column order, which can concentrate the most informative features in a single register, and the effect of this choice is rarely tested. Likewise, interaction topologies are usually chosen ad hoc rather than compared under matched conditions.

This work studies both questions under controlled conditions. We examine an Importance-Balanced Interleaved Projection (IBIP) strategy, which ranks features on training data using permutation importance [5,6,23] and distributes them cyclically across qubits, and compare it against sequential, random and importance-blocked allocation. We also compare five two-qubit and seven three-qubit interaction topologies, each under two allocations, using identical seeds and data splits.

Preliminary experiments suggested that IBIP improved accuracy over sequential allocation on WDBC. Under matched seeds, paired tests and a 20-seed replication, that result did not hold: sequential allocation was better on WDBC. We report this directly and examine why. The primary contributions are:

- A controlled, paired comparison of IBIP and sequential allocation on WDBC across 5 seeds, five-fold cross-validation and a 20-seed replication.
- A four-way allocation ablation that identifies when interleaving helps (relative to concentrating top features) and when it does not (relative to a meaningful feature grouping).
- A matched comparison of twelve interaction topologies, showing that, in the tested configurations, allocation matters more than topology and entanglement offers no consistent benefit.
- A transparent comparison against six classical baselines, an operating-threshold analysis, and a secondary evaluation on two external biomedical datasets.

1.1 Related Work

Foundational studies established how parameterized quantum circuits can act as trainable models [7–10], and circuit-centric VQCs have become one of the most widely studied architectures [11]. Breast cancer

diagnosis is a common QML benchmark because of the availability and clinical relevance of WDBC. Premanand et al. compared quantum machine learning models with conventional classifiers [12], Pagadala et al. proposed a quantum convolutional neural network with Boruta and genetic-algorithm feature selection [13], and Xiang et al. developed a hybrid quantum-classical convolutional network [14].

Feature encoding [15] and projection strategies are central to these models because classical information must be compressed into a few quantum states [16,17]. Existing approaches typically use fixed partitions, sequential grouping or dimensionality reduction before encoding; how the distribution of feature importance across qubits affects learning has received little attention. Separately, gate choice and circuit connectivity influence expressibility, entanglement and trainability [18–21], and barren plateaus constrain deeper circuits [4]. Quantum-inspired optimizers such as Superpositional Gradient Descent (SuperGD) [22] modulate gradient updates with sinusoidal interference terms. The present work differs from prior breast cancer QML studies by focusing not on maximizing accuracy but on controlled measurement of how allocation and topology shape performance, with classical baselines reported under the same protocol.

2. Materials and methods

The overall workflow is illustrated in Figure 1.




Figure 1. Overview of the quantum-inspired classification framework and evaluation pipeline.

2.1 Dataset and Preprocessing

Experiments used the WDBC dataset from the UCI Machine Learning Repository [24]: 569 fine-needle aspiration samples, each described by 30 real-valued nuclear morphology features. The features are ten measurements (radius, texture, perimeter, area, smoothness, compactness, concavity, concave points, symmetry, fractal dimension), each summarized as a mean (features 1–10), standard error (11–20) and

worst value (21–30). Of the 569 samples, 212 (37.3%) are malignant and 357 benign. Malignant is treated as the positive class for sensitivity, specificity, precision and F1-score.

Data were split 80:20 with stratification, giving 114 test samples (42 malignant, 72 benign) per split. Features were z-score standardized using the mean and standard deviation of the training partition only. Feature ranking was likewise computed on the training partition of each split or fold, so test samples were never used for standardization, ranking or parameter fitting.

2.2 Feature Ranking via Permutation Importance

Feature importance was estimated with permutation importance [23] on an XGBoost classifier [6] fitted to the training data: each feature is shuffled and the resulting loss in performance, averaged over 10 repetitions, is recorded. Permutation importance was chosen because it measures relevance directly with respect to predictive performance and avoids the biases of impurity-based measures. Because shuffling is random, rankings can vary slightly between runs; we return to this in Section 3.2.

2.3 Feature Allocation Strategies

Let $n \in \{2, 3\}$ be the number of qubits and D the number of features. Four allocation strategies were compared (Table 1):

- **Sequential:** contiguous blocks in original column order. For WDBC with three qubits, Q_0 receives the mean descriptors, Q_1 the standard errors and Q_2 the worst values.
- **Random:** features randomly partitioned into equal groups.
- **Importance-Blocked:** features ranked by importance and assigned in contiguous blocks, so Q_0 receives the top-ranked third.
- **IBIP:** ranked features distributed round-robin, so that qubit q receives ranks q+1, q+1+n, q+1+2n, … (Figure 2).

When D is not divisible by n, the first registers receive one extra feature. IBIP is designed to give every register a comparable share of informative features before the interaction layer.




Figure 2. Illustration of Importance-Balanced Interleaved Projection (IBIP). Ranked features are distributed cyclically across qubits.

Strategy	Q0	Q1	Q2
Sequential	Mean descriptors (1–10)	Standard errors (11–20)	Worst values (21–30)
Random	10 random features	10 random features	10 random features
Importance-Blocked	Ranks 1–10	Ranks 11–20	Ranks 21–30
IBIP	Ranks 1, 4, 7, ..., 28	Ranks 2, 5, 8, ..., 29	Ranks 3, 6, 9, ..., 30

Table 1. Feature allocation strategies for the three-qubit (10–10–10) WDBC configuration. Two-qubit models use 15–15 splits by the same rules.

2.4 Quantum-Inspired Variational Classifier

For each qubit q, the assigned feature subvector $x_q \in \mathbb{R}^{dq}$ is mapped to a rotation angle by a trainable classical projection:

$$\varphi_q = \pi \cdot \tanh(W_q^T x_q / \sqrt{d_q})$$

The hyperbolic tangent bounds the angle to (−π, π), and the $1/\sqrt{d_q}$ factor prevents saturation. This projection is a classical layer. The circuit is then simulated exactly as a complex statevector in $(\mathbb{C}^2)^{\otimes n}$, starting from $|0\ldots0\rangle$: each qubit receives an encoding rotation $R_y(\varphi_q)R_z(e_q)$, the interaction gates of the chosen topology are applied, and each qubit receives a variational rotation $R_y(v_q)R_z(v_q)$. Pauli-Z expectation values $z_q = \langle\psi|Z_q|\psi\rangle$ are combined linearly and passed through a sigmoid:

$$\hat{y} = \sigma(\Sigma_q \beta_q z_q + b)$$

The output ŷ is the predicted probability of the benign class, and the malignancy score is 1 − ŷ. The final R rotation commutes with the Z measurement and therefore does not affect the output. The three-qubit model has 40 trainable parameters (30 projection weights, 3 encoding angles, 3 variational angles, 3 readout weights and 1 bias); the two-qubit model has 37. At this scale the entire model is a small, classically computable function, and no quantum computational advantage is implied: the term quantum-inspired refers to its circuit structure.

2.5 Interaction Topologies

Two-qubit models (15–15 allocation) used one of five interaction layers: **SWAP** (full state exchange), **√SWAP** (partial exchange), **iSWAP** (exchange with an i phase on $|01\rangle$ and $|10\rangle$), **CNOT** ($Q_0 \rightarrow Q_1$), or **Independent** (no interaction).

Three-qubit models (10–10–10 allocation) used one of seven interaction graphs: **CNOT-Star** ($Q_0 \rightarrow Q_1$, $Q_0 \rightarrow Q_2$), **CNOT-Chain** ($Q_0 \rightarrow Q_1 \rightarrow Q_2$), **CNOT-Ring** ($Q_0 \rightarrow Q_1 \rightarrow Q_2 \rightarrow Q_0$), **Full-Mesh** (CNOTs on all three pairs), **SWAP-Star**, **SWAP-Chain**, and **Independent**. SWAP gates permute qubit states without creating entanglement. Because every qubit has its own trainable rotations and readout weight, SWAP-based circuits represent the same family of functions as the Independent circuit up to relabeling; any difference between them reflects optimization rather than expressive capacity.

2.6 Hybrid Optimization Framework

Training minimized Binary Cross-Entropy loss with per-sample updates over 50 epochs:

$$L = -[\, y \cdot \log(\hat{y}) + (1 - y) \cdot \log(1 - \hat{y}) \,]$$

Gradients for the encoding and variational angles were estimated with a parameter-shift-style rule, evaluating the model at θ ± π/2. This shift rule is exact for the expectation value of a single-occurrence

rotation; because it is applied here to the sigmoid output, and because v_q appears in two gates, it serves as a gradient estimate rather than an exact gradient. Gradients for the projection weights were obtained by applying the same shift to φ_q and the chain rule through the tanh projection. Parameters were updated with Superpositional Gradient Descent [22]:

$$p \leftarrow p - \eta \cdot g \cdot (1 + \lambda \cdot \sin(\pi p))$$

where η is the learning rate and λ the interference strength. Hyperparameters were held constant for all models (Table 2).

Parameter	Value
Learning rate (η)	0.01
Interference strength (λ)	0.5
Epochs	50
BCE stability constant	10^{-7}
Train–test split	80:20, stratified
Seeds	0, 42, 123, 777, 2025 (20-seed replication: 0–19)

Table 2. Experimental hyperparameters.

2.7 Classical Baselines

Six classical models were evaluated under the same splits and preprocessing: SVM with RBF kernel (C = 1.0) [1], SVM with linear kernel (C = 1.0), logistic regression (C = 1.0, L2), XGBoost (100 trees, depth 3, learning rate 0.1) [6], Random Forest (100 trees, depth 5) [5], and Ridge classifier (α = 1.0).

2.8 External Datasets

To check whether allocation effects observed on WDBC also appear in data with different feature structures, two additional UCI datasets were evaluated with the three-qubit CNOT-Star model under all four allocations and 5 seeds:

- **Parkinson's disease** [25]: 195 voice recordings (147 patients, 48 controls), 22 acoustic features, allocated 8–7–7. In column order, sequential allocation places fundamental-frequency and jitter measures on Q_0, shimmer and noise-to-harmonic measures on Q_1, and the harmonics-to-noise ratio together with the non-linear dynamical measures (RPDE, DFA, spread1, spread2, D2, PPE) on Q_2.
- **Cleveland heart disease** [26]: 303 patients, 13 clinical features, allocated 5–4–4. Sequential allocation places age, sex, chest-pain type, resting blood pressure and cholesterol on Q_0; fasting blood sugar, resting ECG, maximum heart rate and exercise angina on Q_1; and ST depression, ST slope, number of major vessels and thalassemia on Q_2.

For both datasets, IBIP and importance-blocked allocation used rankings computed on each training partition, exactly as for WDBC.

2.9 Evaluation Protocol and Statistics

Every two- and three-qubit configuration was trained under both IBIP and sequential allocation with the same five seeds, and separately evaluated with five-fold stratified cross-validation. The primary comparison (three-qubit CNOT-Star, IBIP vs. sequential) was replicated over 20 seeds (0–19). Reported

metrics are accuracy, sensitivity (malignant recall), specificity, precision, F1-score and ROC-AUC, as mean ± standard deviation. Allocation comparisons are paired by seed or fold and use the paired *t*-test, the Wilcoxon signed-rank test, Cohen's d_z and the 95% confidence interval of the paired difference. Because five paired runs provide limited power, five-seed comparisons are treated as exploratory, and conclusions about the primary comparison rest on the 20-seed replication. Each seed determines both the stratified train–test split and the parameter initialization, so variation across seeds reflects data-split as well as initialization variability; five-fold stratified cross-validation (shuffled, random state 42) provides a second resampling scheme. Hyperparameters were fixed in advance for all quantum-inspired and classical models, and no model was tuned on test data. Per-seed and per-fold results, including all paired differences, are released with the code. Finally, the effect of the decision threshold on sensitivity was examined by classifying a sample as malignant when its malignancy score exceeded $\tau \in \{0.5, 0.4, 0.3, 0.2\}$.

AI use statement: The AI tool Claude (Anthropic) was used to assist with manuscript preparation: reviewing the draft for internal consistency with the result files, reformatting the manuscript into the journal's required template, and converting the reference list to the specified citation style. All experimental design, data analysis, modeling, and scientific conclusions reported in this manuscript reflect the authors' own work and judgment.

3. Results

3.1 Primary Comparison on WDBC: IBIP vs. Sequential Allocation

Table 3 compares IBIP and sequential allocation for the three-qubit CNOT-Star model under three protocols. Sequential allocation achieved higher accuracy in all three. In the 20-seed replication the paired difference was −1.05 points (95% CI [−1.86, −0.25]; $t(19) = -2.73$, $p = 0.013$; Wilcoxon $p = 0.010$; $d_z = -0.61$). The difference in ROC-AUC was not significant (−0.0013, $p = 0.455$), indicating that the two allocations rank cases similarly and differ mainly near the decision threshold. Across the 20 matched seeds, IBIP was less accurate in 13, equal in 6 and more accurate in 1, with per-seed differences ranging from −6.14 to +2.63 points. Sequential allocation also showed lower variability across seeds (SD 1.15 vs. 1.69 points).

Protocol	Allocation	Accuracy (%)	Sensitivity (%)	Specificity (%)	ROC-AUC
5 seeds	IBIP	95.26 ± 2.02	91.43 ± 5.22	97.50 ± 2.06	0.9853 ± 0.0127
	Sequential	97.37 ± 2.24	95.24 ± 6.94	98.61 ± 1.70	0.9929 ± 0.0097
5-fold CV	IBIP	96.14 ± 2.28	94.36 ± 5.87	97.21 ± 2.60	0.9926 ± 0.0067
	Sequential	97.54 ± 1.69	95.77 ± 5.06	98.60 ± 1.40	0.9891 ± 0.0144
20 seeds	IBIP	96.62 ± 1.69	94.64 ± 3.53	97.78 ± 1.45	0.9922 ± 0.0067
	Sequential	97.68 ± 1.15	96.19 ± 2.72	98.54 ± 1.23	0.9935 ± 0.0069
Paired difference (20 seeds)		−1.05 [−1.86, −0.25]; p = 0.013			−0.0013; p = 0.455

Table 3. Three-qubit CNOT-Star on WDBC under IBIP and sequential allocation (mean ± SD). Paired difference = IBIP − Sequential, with 95% CI.

The advantage of sequential allocation on WDBC is consistent with the dataset's structure: column order already groups the features into three semantically coherent families (mean, standard error, worst value), and sequential allocation assigns one family to each qubit. IBIP instead mixes families within every register.

3.2 Four-Way Allocation Ablation

To isolate the role of interleaving, the CNOT-Star model was trained under all four allocations with the same five seeds (Table 4, Figure 3). IBIP was more accurate than importance-blocked allocation (+2.46 points, $d_z = 0.92$), although with five seeds this difference was not significant ($p = 0.108$). IBIP and random allocation were statistically indistinguishable (+0.53, $p = 0.374$), and sequential allocation was the most accurate.

Allocation	Accuracy (%)	Sensitivity (%)	ROC-AUC	IBIP − strategy [95% CI]	p (paired t)
Sequential	97.37 ± 2.24	95.24 ± 6.94	0.9929	−2.11 [−3.76, −0.45]	0.024
Random	94.74 ± 2.24	91.43 ± 3.19	0.9896	+0.53 [−0.93, +1.99]	0.374
Importance-Blocked	92.81 ± 2.51	89.52 ± 5.48	0.9793	+2.46 [−0.85, +5.76]	0.108
IBIP	95.26 ± 2.95	93.33 ± 4.58	0.9909	—	—

Table 4. Four-way allocation ablation on WDBC (three-qubit CNOT-Star, 5 matched seeds).




Figure 3. Test accuracy of the four allocation strategies on WDBC (CNOT-Star, 5 seeds). Bars show means with 95% CIs; dots show individual seeds.

Importance-blocking places the ten highest-ranked features on Q_0 and the ten weakest on Q_2, leaving one register with little discriminative signal. Interleaving avoids this imbalance. The ablation recomputed feature rankings independently of the topology suite; because permutation importance is stochastic, per-seed IBIP accuracies differ between the two experiments even though their means coincide (95.26%). Sequential allocation, which does not depend on a ranking, is unaffected by this source of variance.

3.3 Two-Qubit Interaction Suite

Table 5 reports the five two-qubit interaction layers. Differences between gates were small (95.96%–96.84% under IBIP; 94.56%–97.02% under sequential allocation). The iSWAP accuracy of 58.80% observed in preliminary experiments (and reported in the original submission) was the result of an implementation error. The original prototype code was not preserved, so we tested candidate errors with a diagnostic script (released with the code). Discarding the imaginary part of the statevector did not degrade accuracy; storing the iSWAP matrix with a real data type, which zeroes its i entries and makes the gate non-unitary, was the only tested error that produced a comparable collapse (72.8% accuracy, ROC-AUC 0.78), and we regard it as the most likely cause. With exact complex simulation, iSWAP achieved 95.96% ± 2.20%,

comparable to the other gates. SWAP and Independent reached the same mean accuracy under IBIP (96.84%), consistent with their equivalence as function classes.

Interaction	IBIP accuracy (%)	IBIP ROC-AUC	Sequential accuracy (%)	Sequential ROC-AUC
SWAP	96.84 ± 2.29	0.9919	95.44 ± 1.57	0.9897
√SWAP	96.84 ± 2.20	0.9921	96.49 ± 1.75	0.9930
iSWAP	95.96 ± 2.20	0.9900	94.56 ± 1.44	0.9884
CNOT (Q0 → Q1)	96.14 ± 2.02	0.9914	97.02 ± 1.00	0.9943
Independent	96.84 ± 2.11	0.9907	94.56 ± 1.44	0.9871

Table 5. Two-qubit interaction layers on WDBC (15–15 allocation, 5 seeds, mean ± SD).

3.4 Three-Qubit Topology Suite

Table 6 and Figure 4 report the seven three-qubit topologies. Two patterns emerge. First, under IBIP, no entangling topology outperformed the uncoupled Independent circuit (95.44%); paired differences against Independent ranged from −1.23 to −0.18 points (all $p \geq 0.089$). Under sequential allocation, CNOT-based topologies were 1.6–2.1 points more accurate than Independent (CNOT-Chain +2.11, $p = 0.051$; CNOT-Star +1.75, $p = 0.142$), a suggestive but not significant trend with five seeds. Second, the cyclic CNOT-Ring markedly degraded performance under both allocations (−14.91 points vs. Independent under sequential allocation, $p = 0.002$), with sensitivity falling to 62%–65%.

Topology	IBIP accuracy (%)	Sequential accuracy (%)	IBIP ROC-AUC	Sequential ROC-AUC	5-fold CV IBIP / Seq. (%)
CNOT-Star	95.26 ± 2.02	97.37 ± 2.24	0.9853	0.9929	96.14 / 97.54
CNOT-Chain	94.21 ± 2.20	97.72 ± 1.33	0.9831	0.9931	95.25 / 97.72
Full-Mesh	94.39 ± 2.53	97.19 ± 1.69	0.9834	0.9921	94.55 / 97.37
SWAP-Star	95.09 ± 3.70	96.14 ± 2.11	0.9877	0.9872	96.14 / 96.49
SWAP-Chain	94.56 ± 2.73	94.74 ± 3.56	0.9880	0.9858	96.49 / 97.19
Independent	95.44 ± 3.13	95.61 ± 1.64	0.9892	0.9869	96.14 / 96.84
CNOT-Ring	81.75 ± 7.11	80.70 ± 4.34	0.8616	0.8575	83.67 / 83.49

Table 6. Three-qubit topologies on WDBC (10–10–10 allocation, 5 seeds, mean ± SD; final column: five-fold cross-validation means).




Figure 4. Three-qubit topologies on WDBC under IBIP and sequential allocation (5 seeds; error bars show 95% CIs).

To examine the CNOT-Star and CNOT-Chain geometries more closely, we computed graph path lengths, single-qubit von Neumann entanglement entropies on the test set and gradient norms during training, for one training run (seed 42, IBIP allocation). The star topology has a shorter mean path (1.33 vs. 1.67) and a more entangled hub qubit (0.498 vs. 0.310 bits), but the mean single-qubit entropy was slightly higher for the chain (0.409 vs. 0.393 bits) and gradient norms were similar (1.73 vs. 1.81). Since the ordering of these two topologies reverses with allocation (Table 6), and since the unentangled circuit performs as well under IBIP, these quantities do not explain accuracy differences and are reported descriptively.

3.5 Sensitivity to the Ranking Criterion

IBIP was repeated with four ranking criteria over 10 seeds: XGBoost permutation importance (96.23% ± 2.30%), Random Forest permutation importance (95.88% ± 2.07%), mutual information (96.40% ± 1.13%) and ANOVA F-statistic (96.32% ± 2.14%). ROC-AUC exceeded 0.990 in every case. IBIP performance is therefore insensitive to the choice of ranker.

3.6 Comparison with Classical Baselines

Table 7 compares the classical baselines with the best quantum-inspired configurations under identical splits. The RBF-kernel SVM and logistic regression were the strongest models. The best quantum-inspired configuration, sequential CNOT-Chain, matched the SVM's mean accuracy (97.72%) with slightly lower ROC-AUC, while CNOT-Star under IBIP was 2.5 points less accurate. Logistic regression reached comparable accuracy with 31 parameters, fewer than the 40 of the three-qubit model.

Model	Accuracy (%)	Sensitivity (%)	Specificity (%)	Precision (%)	F1 (%)	ROC-AUC	5-fold CV accuracy (%)
SVM (RBF)	97.72 ± 1.59	95.24 ± 4.12	99.17 ± 1.24	98.57	96.82	0.9944	97.72 ± 1.82
Logistic Regression	97.54 ± 1.69	94.76 ± 3.91	99.17 ± 0.76	98.51	96.57	0.9939	97.37 ± 1.86
SVM (Linear)	97.02 ± 2.37	93.81 ± 6.43	98.89 ± 1.52	98.09	95.78	0.9928	97.37 ± 2.48
XGBoost	96.49 ± 1.39	94.76 ± 1.99	97.50 ± 2.06	95.78	95.23	0.9919	95.26 ± 2.02
Random Forest	94.91 ± 2.27	92.38 ± 3.91	96.39 ± 1.58	93.71	93.03	0.9872	95.08 ± 1.32
Ridge Classifier	94.74 ± 2.06	86.67 ± 5.98	99.44 ± 0.76	98.96	92.30	0.9933	95.61 ± 1.86
QIVC CNOT-Chain (Seq.)	97.72 ± 1.33	96.19 ± 4.33	98.61 ± 1.70	97.71	96.86	0.9931	97.72 ± 1.71
QIVC CNOT-Star (Seq.)	97.37 ± 2.24	95.24 ± 6.94	98.61 ± 1.70	97.71	96.29	0.9929	97.54 ± 1.69
QIVC CNOT-Star (IBIP)	95.26 ± 2.02	91.43 ± 5.22	97.50 ± 2.06	95.64	93.39	0.9853	96.14 ± 2.28

Table 7. Classical baselines and quantum-inspired variational classifiers (QIVC) on WDBC (5 seeds; accuracy, sensitivity, specificity and CV accuracy as mean ± SD, other metrics as means).

Table 8 gives the confusion matrices pooled over the five test splits (570 test cases: 210 malignant, 360 benign). The RBF-SVM and sequential CNOT-Star missed the same number of malignant cases (10), while CNOT-Star under IBIP missed 18.

Model	TP	FN	FP	TN
SVM (RBF)	200	10	3	357
Logistic Regression	199	11	3	357
QIVC CNOT-Chain (Seq.)	202	8	5	355
QIVC CNOT-Star (Seq.)	200	10	5	355
QIVC CNOT-Star (IBIP)	192	18	9	351

Table 8. Confusion matrices on WDBC pooled over five test splits (malignant = positive class; TP/FN = malignant cases detected/missed, FP/TN = benign cases misclassified/correctly classified).

3.7 Operating Threshold and Clinical Metrics

In diagnosis, a missed malignancy is more costly than a false alarm. Table 9 shows how lowering the threshold τ on the malignancy score trades specificity for sensitivity. At $\tau = 0.5$, sequential CNOT-Star missed on average 2.0 of 42 malignant cases per test split; at $\tau = 0.3$ this fell to 1.4, with specificity of 96.4%. The quantum-inspired models and the SVM followed nearly identical trade-off curves.

Model	$\tau = 0.5$	$\tau = 0.4$	$\tau = 0.3$	$\tau = 0.2$
QIVC CNOT-Star (Seq.)	95.24 / 98.61 (2.0)	96.19 / 98.33 (1.6)	96.67 / 96.39 (1.4)	97.14 / 95.56 (1.2)
QIVC CNOT-Chain (Seq.)	96.19 / 98.61 (1.6)	96.67 / 98.33 (1.4)	97.14 / 96.94 (1.2)	97.14 / 95.00 (1.2)
SVM (RBF)	95.71 / 98.33 (1.8)	96.19 / 96.67 (1.6)	96.67 / 94.72 (1.4)	97.14 / 93.89 (1.2)

Table 9. Sensitivity / specificity (%) and mean missed malignant cases per split (in parentheses) at decreasing thresholds τ on the malignancy score (WDBC, 5 seeds, 42 malignant test cases per split). For the SVM, thresholds are applied to Platt-scaled probabilities, so values at $\tau = 0.5$ differ slightly from Table 7.

3.8 Secondary Evaluation on External Datasets

Table 10 and Figure 5 report the two external datasets. On both, IBIP was more accurate than importance-blocked allocation, significantly so for heart disease (+8.20 points, 95% CI [3.42, 12.97], $p = 0.009$). Relative to sequential allocation, the outcome depended on the dataset. On Parkinson's disease, IBIP was 5.64 points more accurate, a trend that did not reach significance ($p = 0.063$). Although the columns are grouped by acoustic family, the sequential layout places the harmonics-to-noise ratio and all non-linear dynamical measures, the combination that best separated patients from controls in the original study [25], on a single qubit. On heart disease, sequential allocation, whose column order already spreads strong predictors (chest-pain type, maximum heart rate, vessel count, thalassemia) across all three registers, was marginally better (−0.98 points, $p = 0.070$). IBIP and random allocation were again indistinguishable, and the RBF-SVM remained the most accurate model on both datasets.

Dataset	Allocation	Accuracy (%)	ROC-AUC	IBIP − strategy [95% CI]	p (paired t)
Parkinson's disease	IBIP	84.10 ± 5.85	0.8524	—	—
(195 × 22)	Importance-Blocked	83.08 ± 2.92	0.8731	+1.03 [−8.15, +10.20]	0.772
	Random	84.10 ± 4.93	0.9007	0.00 [−3.18, +3.18]	1.000
	Sequential	78.46 ± 1.40	0.8717	+5.64 [−0.48, +11.77]	0.063
	SVM (RBF)	88.21 ± 3.44	0.9152	—	—
Heart disease	IBIP	80.66 ± 4.24	0.8695	—	—
(303 × 13)	Importance-Blocked	72.46 ± 4.55	0.8173	+8.20 [+3.42, +12.97]	0.009
	Random	80.66 ± 2.14	0.8842	0.00 [−3.22, +3.22]	1.000
	Sequential	81.64 ± 3.36	0.8944	−0.98 [−2.10, +0.13]	0.070
	SVM (RBF)	85.25 ± 2.32	0.9193	—	—

Table 10. Allocation strategies on two external datasets (three-qubit CNOT-Star, 5 seeds, mean ± SD).




Figure 5. Allocation strategies on the external datasets (CNOT-Star, 5 seeds; error bars show 95% CIs). Dashed lines mark RBF-SVM accuracy.

4. Discussion

4.1 Feature Allocation Matters More than Topology

Across all experiments, changing the allocation moved accuracy by 5–9 points between the best and worst strategy, whereas entangling topologies other than CNOT-Ring stayed within about two points of the uncoupled circuit. In low-qubit quantum-inspired classifiers, the decision of which features share a register is therefore the more consequential design choice.

The ablation clarifies what interleaving does. Its benefit is relative to concentration: when the most informative features are packed into one register, the remaining registers carry little signal, and accuracy drops (by 2.5 points on WDBC, not significant with five seeds, and by 8.2 points on heart disease). IBIP prevents this by construction. It does not, however, outperform an allocation that follows a meaningful feature grouping. On WDBC, assigning the mean, standard-error and worst-value families to separate qubits was the best strategy, and the 20-seed replication confirms that this advantage is robust, though small (about one point) and confined to accuracy rather than ROC-AUC. What matters is whether each register receives informative features. When column order already spreads them, as in WDBC and heart disease, sequential allocation performs well; when it concentrates them, as in Parkinson's disease, IBIP is a reasonable default. IBIP also inherits variance from the stochastic ranking step, which sequential allocation avoids.

4.2 Topology and Entanglement

Under IBIP, entangling topologies offered no advantage over independent registers, and SWAP-based circuits are equivalent to the Independent circuit as function classes. Under sequential allocation, CNOT-based coupling showed a modest, non-significant advantage, suggesting that interaction may be more useful when each register encodes a distinct, coherent feature family that benefits from being combined. The failure of CNOT-Ring is the clearest topology effect: closing the loop with a CNOT from Q_2 back to Q_0 consistently degraded learning under this optimizer and readout. Entanglement entropy and path length did not track accuracy, so we refrain from attributing performance differences to entanglement.

4.3 Relation to Classical Models

Classical baselines matched or exceeded every quantum-inspired configuration, on WDBC and, by wider margins, on the external datasets. Logistic regression achieved comparable accuracy with fewer parameters, so parameter efficiency does not favor the quantum-inspired model either. The contribution of this study is thus not a better diagnostic model but a controlled account of which design decisions matter in this model class. Because the circuit structure mirrors that of hardware VQCs, these findings on allocation are relevant to future hardware studies, although this study does not test hardware execution.

Prior breast cancer QML studies [12–14] used different encodings, qubit counts, feature-selection or dimensionality-reduction steps and evaluation protocols. Their reported accuracies are therefore not directly comparable with ours, and we do not rank them; the common lesson is that reporting matched classical baselines and repeated, paired evaluation is necessary before claiming an advantage.

4.4 Scalability

The number of parameters grows as $O(D + n)$, since each projection vector absorbs its register's share of the features. Exact statevector simulation requires $O(2^n)$ memory and $O(N \cdot n \cdot 2^n)$ time per epoch, which limits classical simulation to roughly 25–30 qubits. On hardware, each expectation value would be estimated from repeated measurements; a standard error below 0.02 requires on the order of 1,000–

2,500 shots per value. As *n* grows, each register receives fewer features, and whether allocation remains as influential at larger scale is an open question.

4.5 Limitations

Five-seed comparisons in the topology suites and on the external datasets have limited statistical power and should be read as exploratory; only the primary WDBC comparison was replicated over 20 seeds. The topology suite was run on WDBC only, and the external datasets were evaluated with a single topology. A third dataset, Breast Cancer Coimbra (116 samples, 9 serum biomarkers), was also evaluated; all quantum-inspired configurations remained close to chance level (55.8%–65.8% accuracy, vs. 78.3% for the RBF-SVM), indicating that this model class is poorly suited to very small, low-dimensional data. These results are included in the released code. Finally, all experiments used noiseless simulation, a single optimizer and fixed hyperparameters, and the threshold analysis was performed for sequential allocation only.

5. Conclusions

This study examined feature allocation and interaction topology in quantum-inspired variational classifiers for breast cancer diagnosis under matched, statistically paired conditions. Feature allocation influenced performance more than interaction topology. Interleaving ranked features across qubits (IBIP) was more accurate than concentrating the top-ranked features in one register on all three datasets (significantly on heart disease), and it tended to outperform sequential allocation where column order placed the most informative features on a single qubit (Parkinson's disease). On WDBC, however, where column order separates the mean, standard-error and worst-value descriptors, sequential allocation was more accurate than IBIP over 20 seeds (97.68% vs. 96.62%, $p = 0.013$), with equivalent ROC-AUC.

Entangling topologies did not improve on independent registers under IBIP, the cyclic CNOT-Ring consistently degraded performance, and iSWAP, once correctly simulated, behaved like the other exchange gates. The best quantum-inspired configuration matched but did not exceed an RBF-kernel SVM. For practitioners, the recommendation is to group features by meaning where a natural grouping already spreads informative features across registers, to interleave ranked features otherwise, and never to concentrate the most informative features in a single register. Future work will extend the topology analysis to further datasets, larger registers and hardware noise models.

Artificial Intelligence (AI) Use

The author(s) acknowledge the use of the AI tool Claude (Anthropic) for language editing, as well as for manuscript reformatting and reference management as declared in the Materials and methods section. The tool was applied to enhance clarity and scholarly tone and to assist in restructuring the manuscript to the journal's required format, and all edits were carefully reviewed and validated by the author(s) to ensure accuracy, compliance with academic standards, and research integrity. The author(s) fully support Academia.edu Journals' adherence to COPE guidelines on AI in publication ethics and confirm that this use has been managed responsibly and ethically.

Funding

This research received no external funding.

Author Contributions

Conceptualization, D.K.; methodology, D.K.; software, D.K.; validation, D.K.; formal analysis, D.K.; investigation, D.K.; resources, M.A. and S.M.; data curation, D.K.; writing—original draft preparation, D.K.; writing—review and editing, M.A. and S.M.; supervision, M.A. and S.M. All authors have read and agreed to the published version of the manuscript.

Conflict of Interest

The authors declare that they have no competing interests.

Data Availability Statement

The WDBC [24], Parkinson's disease [25], Cleveland heart disease [26] and Breast Cancer Coimbra datasets are publicly available from the UCI Machine Learning Repository. The complete source code, fixed seeds, per-seed and per-fold result tables, and scripts that generate every table and figure are available at https://github.com/hubdk17/Breast_Cancer_QML-Wisconsin-.

Institutional Review Board Statement

Not applicable. This study did not involve human or animal participants; it used publicly available, de-identified datasets.

Informed Consent Statement

Not applicable.

Supplementary Materials

No supplementary materials are associated with this manuscript. [Edit if applicable.]

Publisher's Note

Academia.edu Journals stays neutral regarding jurisdictional claims in published maps and institutional affiliations. All claims expressed in this article are solely those of the authors and do not necessarily represent those of their affiliated organizations, or those of the publisher, the editors, and the reviewers.

References

1. Cortes C, Vapnik V. Support-vector networks. Mach Learn. 1995;20(3):273-297.

2. Feynman RP. Simulating physics with computers. Int J Theor Phys. 1982;21(6):467-488.

3. Nielsen MA, Chuang IL. Quantum Computation and Quantum Information. Cambridge, UK: Cambridge University Press; 2010.

4. McClean JR, Boixo S, Smelyanskiy VN, Babbush R, Neven H. Barren plateaus in quantum neural network training landscapes. Nat Commun. 2018;9:4812.

5. Breiman L. Random forests. Mach Learn. 2001;45(1):5-32.

6. Chen T, Guestrin C. XGBoost: a scalable tree boosting system. In: Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining; 2016. p. 785-794.

7. Biamonte J, Wittek P, Pancotti N, Rebentrost P, Wiebe N, Lloyd S. Quantum machine learning. Nature. 2017;549:195-202.

8. Mitarai K, Negoro M, Kitagawa M, Fujii K. Quantum circuit learning. Phys Rev A. 2018;98(3):032309.

9. Havlíček V, Córcoles AD, Temme K, Harrow AW, Kandala A, Chow JM, et al. Supervised learning with quantum-enhanced feature spaces. Nature. 2019;567:209-212.

10. Cerezo M, Arrasmith A, Babbush R, Benjamin SC, Endo S, Fujii K, et al. Variational quantum algorithms. Nat Rev Phys. 2021;3:625-644.

11. Schuld M, Bocharov A, Svore KM, Wiebe N. Circuit-centric quantum classifiers. Phys Rev A. 2020;101(3):032308.

12. Premanand V, Sai MS, Srinivas S, Reddy S. Quantum machine learning for breast cancer detection: a comparative study with conventional machine learning methods. Indian J Nat Sci. 2023;14(78):57728-57736.

13. Pagadala V, Venkatesh B, Boinapalli S, Dhulipalla RK, Annapoorna S. A quantum convolutional neural network for breast cancer classification using Boruta and GA-based feature selection with quantum feature maps. J Electron Electromed Eng Med Inform. 2025;7(3).

14. Xiang Q, Li D, Hu Z, Yuan Y, Sun Y, Zhu Y, et al. Quantum classical hybrid convolutional neural networks for breast cancer diagnosis. Sci Rep. 2024;14:24699.

15. Pérez-Salinas A, Cervera-Lierta A, Gil-Fuster E, Latorre JI. Data re-uploading for a universal quantum classifier. Quantum. 2020;4:226.

16. Yano H, Suzuki Y, Itoh KM, Raymond R, Yamamoto N. Efficient discrete feature encoding for variational quantum classifier. IEEE Trans Quantum Eng. 2021;2. doi:10.1109/TQE.2021.3103050.

17. Thumwanit N, Lortaraprasert C, Yano H, Raymond R. Trainable discrete feature embeddings for variational quantum classifier. arXiv:2106.09415. 2021.

18. Sim S, Johnson PD, Aspuru-Guzik A. Expressibility and entangling capability of parameterized quantum circuits for hybrid quantum-classical algorithms. Adv Quantum Technol. 2019;2(12):1900070.

19. Du Y, Huang T, You S, Hsieh MH, Tao D. Quantum circuit architecture search for variational quantum algorithms. npj Quantum Inf. 2022;8:62.

20. Nakhl AC, Quella T, Usman M. Calibrating the role of entanglement in variational quantum circuits. Phys Rev A. 2024;109(3):032413.

21. Ballarin M, Mangini S, Montangero S, Macchiavello C, Mengoni R. Entanglement entropy production in quantum neural networks. Quantum. 2023;7:1023.

22. Pamuk AE, Ozdemir EK, Kocabay ST. Superpositional gradient descent: harnessing quantum principles for model training. In: IEEE International Conference on Quantum Artificial Intelligence; 2025.

23. Altmann A, Toloşi L, Sander O, Lengauer T. Permutation importance: a corrected feature importance measure. Bioinformatics. 2010;26(10):1340-1347.

24. Wolberg WH, Street WN, Mangasarian OL. Breast Cancer Wisconsin (Diagnostic) Data Set. UCI Machine Learning Repository; 1995.

25. Little MA, McSharry PE, Hunter EJ, Spielman J, Ramig LO. Suitability of dysphonia measurements for telemonitoring of Parkinson's disease. IEEE Trans Biomed Eng. 2009;56(4):1015-1022.

26. Detrano R, Janosi A, Steinbrunn W, Pfisterer M, Schmid JJ, Sandhu S, et al. International application of a new probability algorithm for the diagnosis of coronary artery disease. Am J Cardiol. 1989;64(5):304-310.