

- Home
- About
- Free eBook
- Archives
- · Best of the Blog
- Contact

10 Practical Linux Cut Command Examples to Select File Columns

by Balakrishnan Mariyappan on June 6, 2013

Tweet

Linux command cut is used for text processing. You can use this command to extract portion of text from a file by selecting columns.

This tutorial provides few practical examples of cut command that you can use in your day to day command line activities.

For most of the example, we'll be using the following test file.

```
$ cat test.txt
cat command for file oriented operations.
cp command for copy files or directories.
ls command to list out files and directories with its attributes.
```

1. Select Column of Characters

To extract only a desired column from a file use -c option. The following example displays 2nd character from each line of a file test.txt

```
$ cut -c2 test.txt
a
p
s
```

As seen above, the characters a, p, s are the second character from each line of the test.txt file.

2. Select Column of Characters using Range

Range of characters can also be extracted from a file by specifying start and end position delimited with -. The following example extracts first 3 characters of each line from a file called test.txt

```
$ cut -c1-3 test.txt
cat
cp
ls
```

3. Select Column of Characters using either Start or End Position

Either start position or end position can be passed to cut command with -c option.

The following specifies only the start position before the '-'. This example extracts from 3rd character to end of each line from test.txt file.

```
$ cut -c3- test.txt
t command for file oriented operations.
command for copy files or directories.
command to list out files and directories with its attributes.
```

The following specifies only the end position after the '-'. This example extracts 8 characters from the beginning of each line from test.txt file.

```
$ cut -c-8 test.txt
cat comm
cp comma
ls comma
```

The entire line would get printed when you don't specify a number before or after the '-' as shown below.

```
$ cut -c- test.txt
cat command for file oriented operations.
cp command for copy files or directories.
ls command to list out files and directories with its attributes.
```

4. Select a Specific Field from a File

Instead of selecting x number of characters, if you like to extract a whole field, you can combine option -f and -d. The option -f specifies which field you want to extract, and the option -d specifies what is the field delimiter that is used in the input file.

1 of 5 06/25/2013 09:20 PM

The following example displays only first field of each lines from /etc/passwd file using the field delimiter: (colon). In this case, the 1st field is the username. The file

```
$ cut -d':' -f1 /etc/passwd
root
daemon
bin
sys
sync
games
bala
```

5. Select Multiple Fields from a File

You can also extract more than one fields from a file or stdout. Below example displays username and home directory of users who has the login shell as "/bin/bash".

```
$ grep "/bin/bash" /etc/passwd | cut -d':' -f1,6
root:/root
bala:/home/bala
```

To display the range of fields specify start field and end field as shown below. In this example, we are selecting field 1 through 4, 6 and 7

```
$ grep "/bin/bash" /etc/passwd | cut -d':' -f1-4,6,7
root:x:0:0:/root:/bin/bash
bala:x:1000:1000:/home/bala:/bin/bash
```

6. Select Fields Only When a Line Contains the Delimiter

In our /etc/passwd example, if you pass a different delimiter other than: (colon), cut will just display the whole line.

In the following example, we've specified the delimiter as | (pipe), and cut command simply displays the whole line, even when it doesn't find any line that has | (pipe) as delimiter.

```
$ grep "/bin/bash" /etc/passwd | cut -d'|' -f1
root:x:0:0:root:/root:/bin/bash
bala:x:1000:1000:bala,,,:/home/bala:/bin/bash
```

But, it is possible to filter and display only the lines that contains the specified delimiter using -s option.

The following example doesn't display any output, as the cut command didn't find any lines that has | (pipe) as delimiter in the /etc/passwd file.

```
prop "/bin/bash" /etc/passwd | cut -d'|' -s -f1
```

7. Select All Fields Except the Specified Fields

In order to complement the selection field list use option -complement.

The following example displays all the fields from /etc/passwd file except field 7

```
\ grep\ "/bin/bash"\ /etc/passwd\ |\ cut\ -d':'\ --complement\ -s\ -f7\ root:x:0:0:root:/root\ bala:x:1000:1000:bala,,,:/home/bala
```

8. Change Output Delimiter for Display

By default the output delimiter is same as input delimiter that we specify in the cut -d option.

To change the output delimiter use the option -output-delimiter as shown below. In this example, the input delimiter is: (colon), but the output delimiter is # (hash).

```
\ grep\ "/bin/bash"\ /etc/passwd\ |\ cut\ -d':'\ -s\ -f1,6,7\ --output-delimiter='#'root#/root#/bin/bash bala#/home/bala#/bin/bash
```

9. Change Output Delimiter to Newline

In this example, each and every field of the cut command output is displayed in a separate line. We still used -output-delimiter, but the value is \$'\n' which indicates that we should add a newline as the output delimiter.

```
$ grep bala /etc/passwd | cut -d':' -f1,6,7 --output-delimiter=$'\n'
bala
/home/bala
/bin/bash
```

10. Combine Cut with Other Unix Command Output

The power of cut command can be realized when you combine it with the stdout of some other Unix command.

Once you master the basic usage of cut command that we've explained above, you can wisely use cut command to solve lot of your text manipulation requirements.

The following example indicates how you can extract only useful information from the <u>ps command</u> output. We also showed how we've filtered the output of ps command using grep and sed before the final output was given to cut command. Here, we've used cut option -d and -f which we've explained in the above examples.

- \$ ps axu | grep python | sed 's/\s\+/ /g' | cut -d' ' -f2,11-2231 /usr/bin/python /usr/lib/unity-lens-video/unity-lens-video 2311 /usr/bin/python /usr/lib/unity-scope-video-remote/unity-scope-video-remote 2414 /usr/bin/python /usr/lib/ubuntuone-client/ubuntuone-syncdaemon 2463 /usr/bin/python /usr/lib/system-service/system-service-d 3274 grep --color=auto python
- <u>Tweet</u> > Add your comment



Linux provides several powerful administrative tools and utilities which will help you to manage your systems effectively. If you don't know what these tools are and how to use them, you could be spending lot of time trying to perform even the basic administrative tasks. The focus of this course is to help you understand system administration tools, which will help you to become an effective Linux system administrator.

Get the Linux Sysadmin Course Now!


If you enjoyed this article, you might also like..


- 1. 50 Linux Sysadmin Tutorials
- 2. 50 Most Frequently Used Linux Commands (With Examples)
- Top 25 Best Linux Performance Monitoring and Debugging Tools
 Mommy, I found it! 15 Practical Linux Find Command Examples
- 5. Linux 101 Hacks 2nd Edition eBook Free

- Awk Introduction 7 Awk Print Examples
- Advanced Sed Substitution Examples
- 8 Essential Vim Editor Navigation Fundamentals
- 25 Most Frequently Used Linux IPTables Rules Examples
- Turbocharge PuTTY with 12 Powerful Add-Ons









Tags: Bash Cut Command, Cut Command Line, Cut Delimiter, Cut Delimiter Space, Cut Fields, Shell Cut Command, Unix Cut Command

{ 6 comments... read them below or add one }

1 Jalal Hajigholamali June 6, 2013 at 8:48 am

simple and very nice and useful article

2 Bob June 6, 2013 at 9:41 am

Great article.

3 Srinivas Jupudi June 7, 2013 at 12:22 am

Nice Article

4 niraj June 7, 2013 at 12:28 am

Nice artical

5 Erlo June 7, 2013 at 1:07 pm

Linux/Unix has lots of nice little utilities 🕲) I was not aware of cut, I have always used awk for these things. awk combined with sed is a kind of swiss pocket knife.

6 xlob June 7, 2013 at 8:01 pm

Thanks for article.

@Erlo For substitution awk can use gsub internal command instead of pipe into sed?

Leave a Comment

Louvo a common	
	Name
	E-mail
	Websit

3 of 5 06/25/2013 09:20 PM

Notify me of followup comments via e-mail Submit Previous post: Buffer Overflow Attack Explained with a C Program Example Next post: How to Force Install a Perl Module using CPAN

Search >Email >RSS >Twitter >Facebook

COURSE

o Linux Sysadmin CentOS 6 Course - Master the Tools, Configure it Right, and be Lazy

EBOOKS

- Free <u>Linux 101 Hacks 2nd Edition eBook</u> Practical Examples to Build a Strong Foundation in Linux
 <u>Bash 101 Hacks eBook</u> Take Control of Your Bash Command Line and Shell Scripting

- Sed and Awk 101 Hacks eBook Enhance Your UNIX / Linux Life with Sed and Awk
 Vim 101 Hacks eBook Practical Examples for Becoming Fast and Productive in Vim Editor
 Nagios Core 3 eBook Monitor Everything, Be Proactive, and Sleep Well

• POPULAR POSTS

- o 12 Amazing and Essential Linux Books To Enrich Your Brain and Library
- o 50 UNIX / Linux Sysadmin Tutorials
- 50 Most Frequently Used UNIX / Linux Commands (With Examples)
 How To Be Productive and Get Things Done Using GTD
 30 Things To Do When you are Bored and have a Computer

- o Linux Directory Structure (File System Structure) Explained with Examples
- Linux Crontab: 15 Awesome Cron Job Examples
- o Get a Grip on the Grep! 15 Practical Grep Command Examples
- Unix LS Command: 15 Practical Examples
 15 Examples To Master Linux Command Line History
- Top 10 Open Source Bug Tracking System
- Vi and Vim Macro Tutorial: How To Record and Play
- o Mommy, I found it! -- 15 Practical Linux Find Command Examples
- 15 Awesome Gmail Tips and Tricks
- 15 Awesome Google Search Tips and Tricks
 RAID 0, RAID 1, RAID 5, RAID 10 Explained with Diagrams
- Can You Top This? 15 Practical Linux Top Command Examples
- Top 5 Best System Monitoring Tools
- Top 5 Best Linux OS Distributions
- How To Monitor Remote Linux Host using Nagios 3.0
 Awk Introduction Tutorial 7 Awk Print Examples
- How to Backup Linux? 15 rsync Command Examples
- The Ultimate Wget Download Guide With 15 Awesome Examples
- Top 5 Best Linux Text Editors
- Packet Analyzer: 15 TCPDUMP Command Examples
 The Ultimate Bash Array Tutorial with 15 Examples
- o 3 Steps to Perform SSH Login Without Password Using ssh-keygen & ssh-copy-id
- Unix Sed Tutorial: Advanced Sed Substitution Examples
- o UNIX / Linux: 10 Netstat Command Examples
- The Ultimate Guide for Creating Strong Passwords
- o 6 Steps to Secure Your Home Wireless Network
- Turbocharge PuTTY with 12 Powerful Add-Ons

CATEGORIES

- o Linux
- o Vim
- Sed
- o Awk
- o Bash
- o Nagios o OpenSSH
- IPTables
- Apache
- o MySQL

- GoogleUbuntu
- PostgreSQL
- Hello World
- <u>C Programming</u>
- <u>C++ Programming</u>
- o DELL
- o <u>Oracle</u>
- <u>VMware</u>

About The Geek Stuff

My name is **Ramesh Natarajan**. I will be posting instruction guides, how-to, troubleshooting tips and tricks on Linux, database, hardware, security and web. My focus is to write articles that will either teach you or help you resolve a problem. Read more about <u>Ramesh</u> Natarajan and the blog.

Support Us

Support this blog by purchasing one of my ebooks.

Bash 101 Hacks eBook

Sed and Awk 101 Hacks eBook

Vim 101 Hacks eBook

Nagios Core 3 eBook

Contact Us

Email Me: Use this Contact Form to get in touch me with your comments, questions or suggestions about this site. You can also simply drop me a line to say hello!.

Follow us on Twitter

Become a fan on Facebook

Copyright © 2008-2013 Ramesh Natarajan. All rights reserved | Terms of Service | Advertise

5 of 5