

ROUTER
ROUTER#
ROUTER#disable
ROUTER>
ROUTER>
ROUTER>
ROUTER>
ROUTER>enable
ROUTER#
ROUTER#
ROUTER#conf t
Enter configuration commands, one per line. End with CNTL/Z.
ROUTER(config)#interface ethernet 0/0
ROUTER(config-if)#ip address 50.0.0.1 255.0.0.0
ROUTER(config-if)#no shutdown
ROUTER(config-if)#
ROUTER(config-if)#
ROUTER(config-if)#exit
ROUTER(config)#exit
ROUTER#
*Aug 18 17:50:56.396: %SYS-5-CONFIG_I: Configured from console by console
ROUTER#show ip int brief

Interface	IP-Address	OK?	Method	Status	Prot
Ethernet0/0	50.0.0.1	YES	manual	up	up
Ethernet0/1	unassigned	YES	TFTP	down	down

Router(config)#

ROUTER

```
ROUTER(config-if)#ip address 50.0.0.1 255.0.0.0
ROUTER(config-if)#no shutdown
ROUTER(config-if)#
ROUTER(config-if)#
ROUTER(config-if)#exit
ROUTER(config)#exit
ROUTER#
*Aug 18 17:50:56.396: %SYS-5-CONFIG_I: Configured from console by console
ROUTER#show ip int brief
Interface                IP-Address      OK? Method Status      Prot
ocol
Ethernet0/0              50.0.0.1        YES manual up          up
Ethernet0/1              unassigned      YES TFTP  down        down
Ethernet0/2              unassigned      YES TFTP  down        down
Ethernet0/3              unassigned      YES TFTP  down        down

ROUTER#
ROUTER#
ROUTER#conf t
Enter configuration commands, one per line. End with CNTL/Z.
ROUTER(config)#
ROUTER(config)#
ROUTER(config)#
ROUTER(config)#username isfaq password isfaq
ROUTER(config)#line console 0
ROUTER(config-line)#password console
ROUTER(config-line)#exit
ROUTER#
```


ROUTER

Ethernet0/2	unassigned	YES TFTP	down	down
Ethernet0/3	unassigned	YES TFTP	down	down

ROUTER#

ROUTER#

ROUTER#conf t

Enter configuration commands, one per line. End with CNTL/Z.

ROUTER(config)#

ROUTER(config)#

ROUTER(config)#

ROUTER(config)#username isfaq password isfaq

ROUTER(config)#line console 0

ROUTER(config-line)#password console

ROUTER(config-line)#login local

ROUTER(config-line)#

ROUTER(config-line)#

ROUTER(config-line)#exit

ROUTER(config)#exit

ROUTER#

*Aug 18 17:53:37.782: %SYS-5-CONFIG_I: Configured from console by console

ROUTER#exit

Router(config)#

ROUTER

Press RETURN to get started.

User Access Verification

Username: isfaq

Password:

ROUTER>

ROUTER>

ROUTER>enable

ROUTER#conf t

Enter configuration commands, one per line. End with CNTL/Z.

ROUTER(config)#

ROUTER(config)#

ROUTER(config)#enable secret enable

ROUTER(config)#

ROUTER(config)#exit

ROUTER#e

*Aug 18 17:54:35.322: %SYS-5-CONFIG_I: Configured from console by isfaq on console

ROUTER#exit

Router(config)# exit
Router(config)#

ROUTER

User Access Verification

Username: isfaq

Password:

ROUTER>

ROUTER>enable

Password:

ROUTER#

ROUTER#

ROUTER#conf t

Enter configuration commands, one per line. End with CNTL/Z.

ROUTER(config)#

ROUTER(config)#

ROUTER(config)#

ROUTER(config)#

ROUTER(config)#

ROUTER(config)#

ROUTER(config)#

ROUTER(config)#

ROUTER(config)#

ROUTER(config)#line vty 0 4

ROUTER(config-line)#transport input telnet

ROUTER(config-line)#password telnet

ROUTER(config-line)#login

ROUTER(config-line)#exit

ROUTER(config)#

ROUTER(config)#

ROUTER(config)#

ROUTER(config-line)#exit

Router(config)#

Create enable secret password

QEMU (Win)

S0.0.0.1 - PuTTY

User Access Verification

Password:

ROUTER>enable

Password:

ROUTER#

ROUTER#

ROUTER#conf t

Enter configuration commands, one per line. End with CNTL/Z.

ROUTER(config)#