dune-rover executive brief

Executive brief: predicting slip and traversability of wheeled robots on Arabian dunes

Huda Mueen, `hudasol/dune-rover`, 2026-10-20. Generated by `scripts/build_report.py`; every number comes from a result file or an evidence row in `research/evidence.csv`. **This is a proposal and a research summary. No agreement, partnership or endorsement exists with any institution, and none is implied.** Heat and dust limits are the subject of the separate repository `hudasol/dhill`. No cost is given.

Labels: **PUBLISHED** (read in a retrieved source), **SIMULATED BY ME** (output of this repository's code; simulation only, never field evidence), **PLANNED** (not run).

1. Question and Gulf relevance

How much does a small wheeled robot slip on a dune slope, can it be predicted, and how fine must a terrain map be to plan on Gulf dunes? No published slip against slope dataset exists for a wheeled robot on Arabian dune sand; the only Arabian field item is a qualitative report of a rover stuck in loose sand in Oman (FLD-042). Open elevation data for the region are about 30 m.

2. What is published (PUBLISHED; 494 verified rows from 174 sources)

- **Earth dune slope curve.** At Dumont Dunes, California, a 340 kg test rover went from below 50 % slip at 12.5 degrees to about 90 % at 20 degrees, without soil parameters (FLD-HV13-1, FLD-HV13-2).
- **Field slip is large and patchy:** Spirit 15 to 20 % at 19 degrees and 95 % at 16 degrees on look alike terrain (FLD-011, FLD-012); Perseverance above 94 % at about 20 degrees (FLD-025).
- **Arabian sand:** grain size, sorting, mineralogy and density of UAE, Qatari, Saudi and Omani dune sands are published (SND rows); no friction angle or slip face angle measured on UAE dunes was found.

3. What was tested (SIMULATED BY ME; every main test pre registered in `docs/PREDICTIONS.md`, post hoc analyses labelled)

- **Slip models against published curves.** 4 model families, calibrated on other studies, predicted a held out study with median slip errors of 0.20 to 0.24; none met the bar of 0.15 fixed beforehand, and an empirical curve did as well as the physics.
- **Independent simulator.** Project Chrono with published soils gives 0.21 slip at 12.5 degrees for a Scarecrow sized wheel, against about 0.49 on the Dumont curve.
- **Terrain map against real lidar.** On three North American dune fields (USGS one metre lidar), 25.6 % to 28.6 % of the cells a 30 m three class map called TRAVERSABLE contained steep slip faces (1.8 % to 3.6 % at 10 m).
- **Planning.** On 30 m maps no policy was safer than naive planning against lidar truth; with 10 m maps a conservative policy failed less often than naive at two of three sites on the pairs it could route (post hoc comparison).

- **Arabian maps.** With slip parameters calibrated on published curves, UNKNOWN at 30 m is 62.8 % (Liwa), 44.3 % and 46.0 % (Rub' al Khali), against 8.6 %, 10.9 % and 2.5 % under the original assumed ranges (25.1 %, 30.9 % and 4.2 % if draws that cannot move on level ground are rejected, post hoc).

4. Negative results

- No slip model transfers between vehicles and soils with useful accuracy; two implementations of the same Bekker and Janosi laws disagree by more than field scatter.
- A 30 m map labels 36 % to 73 % of the cells that contain a steep face as TRAVERSABLE (7 % to 20 % at 10 m); the slip face detector works much better at 10 m than at 30 m.
- The planned pass or fail rule accepts a model that collapses above 20 degrees in 53 % of synthetic replicates; stricter options reject a correct model more than half the time.

5. Error rate of the evidence table

Every row was re checked against its full text by a separate agent. Of the 323 rows added on 2026-10-20, 30 had a material error before correction (9.3 %, Wilson 95 % interval 6.6 to 12.9 %); every material error is corrected, and minor errors where the verifier gave a corrected value. A blinded human spot check of 20 rows is prepared.

6. The first field experiment (PLANNED)

A slope ladder with one small four wheel rover (5 to 25 kg) on one dune stoss slope (bins 0 to 20 degrees, denser between 10 and 20), a 12 run pilot, RTK or drone slope, soil tests at every station, calibration up to 10 degrees and predictions committed before steeper runs, plus a drone survey of the dune at 10 m or finer to test the map on Arabian terrain (`docs/FIELD_VALIDATION_PLAN.md`).

7. The ask

A supervised dune site, a small wheeled rover, RTK GNSS or a drone survey, soil tests and recovery support; work packages and fallbacks are in `docs/PROPOSAL_ROBOTICS.md` and `docs/PROPOSAL_EDGE.md`. Success means a complete dataset and an honest comparison with the committed predictions, even if the model fails.